MILITARY STANDARD

AUTOMATED ENGINEERING

DOCUMENT PREPARATION SYSTEM

COUNTERS, RECIPROCATING AND ROTATING

TO ALL HOLDERS OF MIL-STD-35-106(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-106(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
5-23	3 September 1976	5-23	24 November 1975
5-24	24 November 1975	(REPRINTED WITHOUT CHANGE)	
5-67	3 September 1976	5-67	24 November 1975
5-68	24 November 1975	(REPRINTED WITHOUT CHANGE)	

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of MIL-STD-35-106(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages as a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Custodians:
Army-MI

Review Activities:
Army-AT
Army-AV
Army-EL
Army-ME
Army-MR
Army-SG
Army-WC

User Activity:
Army-MU

Preparing Activity:
Army-MI

Project EDS-A199

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

Code 1990 is the 1006 requirement code (5.4).

Code 1992 is the 1006 except requirement code (5.4).

The counting coil and reset coil resistances will be specified by the use of Codes 1810 and 1811 previously discussed in Section 5.10.1. Do not use Code 1990 or Code 1992 if either Code 1810 or 1811 is used.

Code 1994 and an "X", entered on the SRS, will specify the requirements shall be as specified herein. Use Code 1994 with Codes 1810 and 1811.

5.16 Determination of Actuation Force

Code 1920 is the 1006 test code (5.4).

Code 1921 is the 1066 except test code (5.4).

Code 1922 and an "X", entered on the SRS, will specify to test in accordance with GG-C-00620.

Code 1930 is the 1006 requirement code (5.4).

Code 1931 is the 1006 except requirement code (5.4).

To detail requirements, there are two codes available. These codes and information concerning them are as follows:

Code 1933 and a value, entered on the SRS, will specify the maximum actuating force in pounds.

Code 1934 and a value, entered on the SRS, will specify the maximum actuating force in newtons.

5.17 Dielectric Withstanding Voltage at Reduced Barometric Pressure

Code 4883 is the 1006 test code (5.4).

Code 4884 is the 1006 except test code (5.4).

To detail a dielectric withstanding voltage test at reduced barometric pressure, Codes 6300 and 4886, and either Code 4849 or 4885, are mandatory. Other codes are optional. Information concerning them is as follows:

Code 6300 and an "X", entered on the SRS, will specify the dielectric withstanding voltage test in accordance with Method 301 of MIL-STD-202 shall be performed at reduced barometric pressure.

Supersedes page 5-23 of 24 November 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

Code 4886 and a letter, entered on the SRS, will specify the altitude shall be specified in test condition letter Method 105 of MIL-STD-202.

Code 4885 and a value, entered on the SRS, will specify dc test voltage. Do not use Code 4885 with Code 4849.

Code 4849 and a value, entered on the SRS, will specify ac test voltage. Do not use Code 4849 with Code 4885.

Code 6311 and an "X", entered on the SRS, will specify the test voltage shall be applied between terminations tied together and mounting hardware.

Code 6312 and an "X", entered on the SRS, will specify the test voltage shall be applied between terminations tied together and case.

Code 4859 and a document designation, entered on the SRS, will specify special preparations in accordance with the document (5.7).

Code 4891 and a value, entered on the SRS, will specify duration in seconds of voltage application. This code is used only if duration required is other than 60 seconds.

Code 6280 and a document designation, entered on the SRS, will specify mounting in accordance with the document (5.7).

Code 4907 is the 1006 requirment code (5.4).

Code 4908 is the 1006 except requirement code (5.4).

To detail requirements, Code 4906 is mandatory and others are optional. Infomration concerning them is as follows:

Code 4906 and an "X", entered on the SRS, will specify there shall be no evidence of flashover, mechanical damage, arcing, or insulation breakdown after test.

Code 4901 and an "X", entered on the SRS, will specify the device shall remain within specified tolerance after test.

Code 4894 and a value, entered on the SRS, will specify maximum leakage current in milliampers.

5.18 Dielectric Withstanding Voltage at Sea Level

Code 4860 is the 1006 test code (5.4).

Code 4861 is the 1006 except test code (5.4).

Reprinted without change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.14 (Cont)	Count Life (Cont)	
	Requirement(s) as follows:	
	Minimum counts required without failure (no.)	1964
	*Counting agreement required between master counter and test counter (± counts)	1965
	Maximum difference between counter under test and control counter readings (± pct)	1967
5.15	DC Resistance	
	(Select one test method)	
	Test per 1006 document.	1980
	Test per 1006 document except ____	1982
	Test per MIL-STD-202 Method 302.	1984
	Test voltage (V)	1985
	(Select one requirement)	
	Requirement(s) per 1006 document.	1990
	Requirement(s) per 1006 document except ___	1992
	Requirement(s) as follows:	
	As specified herein (see 5.10.1)	1994

Supersedes page 5-67 of 24 November 1975.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION REQUIREMENTS LIST (SRL)

REF PARA	CHARACTERISTIC NAME	CODE
5.16	Determination of Acutation Force	
	(Select one test method)	
	Test per 1006 document.	1920
	Test per 1006 document except ____	1921
	Test per GG-C-00620.	1922
	(Select one requirement)	
	Requirement(s) per 1006 document.	1930
	Requirement(s) per 1006 document except ____	1931
	Requirement(s) as follows:	
	Maximum actuating force	
	(lbs)	1933
	(N)	1934
5.17	Dielectric Withstanding Voltage at Reduced Barometric Pressure	
	(Select one test method)	
	Test per 1006 document.	4883
	Test per 1006 document except ____	4884

Reprinted without change.

☆U.S. GOVERNMENT PRINTING OFFICE: 1976-603-766/6583

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.