

FED SUP CLASS
5935





Design standard for use with MIL-C-28748/10

© Entire standard revised

APPROVED 20 Dec 1965 REVISED (A) 29 Jul 1968 (B) 20 May 1970 (C) 8 July 1976

User activities: Army ME, AV, WC; Navy MC; Air Force

Reviewer activities: Army MI, MU, AT; Navy AS, SH, OS; Air Force 11, 80; DSA - ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

P A Navy - EC Other Cust AF - 85 Army - EL	International interest	TITLE INSERT (INSULATOR), RECTANGULAR CONNECTOR POLARIZED CENTER SCREW-LOCK, ELECTRICAL, 10 (SIZE 16 CRIMP REMOVABLE) SOCKET CONTACTS	MILITARY STANDARD MS 18156
Procurement Specification MIL-C-28748		SUPERSEDES	SHEET 1 OF 3

DD FORM 1 SEP 63 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5935-2004-6

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:15Z
Check the source to verify that this is the current version before use.

TYPE
SEE TABLE I




TABLE I		
TYPE	A	B
1	90°	135°
2	85°	137°30'

TABLE II		
MS PART NUMBER	POLARIZATION *	JACKSCREW
MS 18156-1N	N (TYPE 1)	SUPPLIED WITH CONNECTOR
MS 18156-1V	V (TYPE 1)	
MS 18156-1W	W (TYPE 1)	
MS 18156-1X	X (TYPE 2)	
MS 18156-1Y	Y (TYPE 2)	
MS 18156-1Z	Z (TYPE 2)	
MS 18156-2N	N (TYPE 1)	NOT SUPPLIED WITH CONNECTOR POLARIZING BOSS THREADED INTERNALLY 138-32 UNC-2B
MS 18156-2V	V (TYPE 1)	
MS 18156-2W	W (TYPE 1)	
MS 18156-2X	X (TYPE 2)	
MS 18156-2Y	Y (TYPE 2)	
MS 18156-2Z	Z (TYPE 2)	

TABLE III		
MS PART NUMBER	POLARIZATION *	GUIDE PIN
MS 18156-3N	N (TYPE 1)	SUPPLIED WITH CONNECTOR
MS 18156-3V	V (TYPE 1)	
MS 18156-3W	W (TYPE 1)	
MS 18156-3X	X (TYPE 2)	
MS 18156-3Y	Y (TYPE 2)	
MS 18156-3Z	Z (TYPE 2)	
MS 18156-4N	N (TYPE 1)	NOT SUPPLIED WITH CONNECTOR POLARIZING BOSS WITH .144 ± .002 I D TO ACCEPT GUIDE PIN
MS 18156-4V	V (TYPE 1)	
MS 18156-4W	W (TYPE 1)	
MS 18156-4X	X (TYPE 2)	
MS 18156-4Y	Y (TYPE 2)	
MS 18156-4Z	Z (TYPE 2)	

* LARGE OPENING IN POLARIZATION BOSS MUST BE ADJACENT TO POLARIZATION LETTER ON CONNECTOR BODY

APPROVED 20 Dec 1965 REVISED © For changes see sheets 1, 2 and 3

User activities: Army ME, AV, WC; Navy MC; Air Force
Reviewer activities: Army MI, MU, AT; Navy AS, SH, OS; Air Force 11, 80; DSA - ES
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use is still to be taken from this document.

P A Navy - EC	International interest	TITLE INSERT (INSULATOR), RECTANGULAR CONNECTOR POLARIZED CENTER SCREW-LOCK, ELECTRICAL, 10 (SIZE 16 CRIMP REMOVABLE) SOCKET CONTACTS	MILITARY STANDARD
Other Cust: AF - 85, Army - EL			MS 18156
Procurement Specification: MIL-C-28748		SUPERSEDES	SHEET 2 OF 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:15Z
Check the source to verify that this is the current version before use.

INCHES	MM	INCHES	MM
.001	03	.285	7 24
002	05	287	7 29
005	13	300	7 62
006	15	312	7 93
.010	25	340	8 64
.057	1 45	.375	9 53
094	2 39	470	11 94
130	3.30	570	14.48
.138	3.51	590	14.99
149	3 78	838	21 29
156	3.96	923	23 44
.218	5.54	956	24 28
.225	5 72	1 300	33 02
250	6 35	1 420	36 07
		1 520	38 61
		1 675	42 55

NOTES:
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is ±.015 (.38 mm).
3. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
4. Tolerance between any two adjacent contact centers shall be ±.004 (.10 mm). Tolerance between any two contact centers, other than adjacent contacts, shall be ±.006 (.15 mm).
5. Contact hole details shall be in accordance with MIL-C-28748.
6. For mating connector see MS18155 (pin body)
7. Dimensions symmetrical about centerlines.
8. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
9. Reference documents shall be of the issue in effect on date of invitation for bid.
10. Insert material shall be in accordance with MIL-C-28748.
11. Flatness, squareness and parallelism shall be within dimensional tolerances.
12. Center polarizing hardware may be rotated by removing retaining ring and spacer or removing cap (left hand thread) at rear of insert.
13. Maximum insertion and withdrawal force (connector assembly) shall be 9 pounds.
14. Maximum torque required at jackscrew to properly engage or disengage connector shall be 1.5 inch pounds.
15. Jackscrew wrench size 3/32 hex

APPROVED 20 Dec 1965 REVISED © For changes see sheets 1, 2 and 3

User activities: Army ME, AV, WC; Navy MC; Air Force
Reviewer activities: Army MI, MU, AT; Navy AS, SH, OS; Air Force 11, 80; DSA - ES

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use will be made from this document.

P A Navy - EC Other Cus. AF - 85 Army - EL	International interest	TITLE INSERT (INSULATOR), RECTANGULAR CONNECTOR POLARIZED CENTER SCREW-LOCK, ELECTRICAL, 10 (SIZE 16 CRIMP REMOVABLE) SOCKET CONTACTS	MILITARY STANDARD MS18156
Procurement Specification MIL-C-28748		SUPERSEDES	SHEET 3 OF 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:15Z
Check the source to verify that this is the current version before use.