FED. SUP CLASS
2640

MS PART NUMBER	FIIN	MARKING CODE ①	NUMBER OF PLIES TO EACH PATCH	TIRE TO BE REPAIRED: INJURY SIZE MAX (INCHES)	TIRE TO BE REPAIRED: PLY RATING	TIRE TO BE REPAIRED: FOR UNIT NO.	SIZE EACH PLY: PLY NUMBERS	SIZE EACH PLY: DIMENSIONS	MAXIMUM OVER-ALL PATCH DIM. (INCHES)
MS 51312-1	684-5135	②③ 2-0-A	2	NAIL	ALL	1	1 & 2	3/4 X 2-1/2	3
MS 51312-2	684-5136	2-1/2-4/6	2	1/2	4/6	1	1 & 2	2-1/2 X 5	6
MS 51312-3	684-5137	2-1-4/6	2	1	4/6	1	1 & 2	3 X 7	8
MS 51312-4	684-5138	2-2-4	2	2	4	1	1 & 2	4 X 8	9
MS 51312-5	684-5139	4-3-4/6	4	3	4/6	1	1 & 2 3 & 4	5 X 7 6 X 9	10
MS 51312-6	684-5140	4-4-4/6	4	4	4/6	1	1 & 2 3 & 4	6 X 8 7 X 10	11
MS 51312-7	684-5141	4-2-8/10	4	2	8/10	1	1 & 2 3 & 4	4 X 8 5 X 10	11
MS 51312-8	684-5142	6-4-8/12	6	4	8/12	1	1 & 2 3 & 4 5 & 6	6 X 10 7 X 12 8 X 14	15
MS 51312-9	684-5143	8-4-12/16	8	4	12/16	1	1 & 2 3 & 4 5 & 6 7 & 8	6 X 10 7 X 12 8 X 14 9 X 16	17
MS 51312-10	684-5144	8-6-12/14	8	6	12/14	1	1 & 2 3 & 4 5 & 6 7 & 8	8 X 12 9 X 14 10 X 16 11 X 18	19
MS 51312-11	684-5145	10-6-14/18	10	6	14/18	1	1 & 2 3 & 4 5 & 6	8 X 12 9 X 14 10 X 16	21
						2	7 & 8 9 & 10	11 X 18 13 X 20	

NOTES:

1. IDENTIFICATION MARKING TO BE APPLIED TO EACH PATCH. THE CODE DENOTES THE NUMBER OF PLIES IN THE PATCH, THE MAXIMUM INJURY SIZE IN INCHES AND THE PLY RATING OF THE TIRE FOR WHICH THE PATCH IS INTENDED. EXAMPLE: 4-2-8/10 INDICATES 4 PLIES TO THE PATCH, 2-INCH MAXIMUM TIRE-INJURY SIZE AND PATCH SUITABLE FOR 8 AND 10 PLY TIRES.
2. "O" INDICATES NAIL HOLE.
3. "A" INDICATES USE WITH ALL PLY RATINGS.

APPROVED 16 JULY 1959 REVISED

CUSTODIANS	OTHER INT.
P.A.-Ord	A-CE
Navy-Docks	N-NOrd, MC
AF-USAF	AF-

PROCUREMENT SPECIFICATION: ZZ-T-446

MILITARY STANDARD

PATCH, PNEUMATIC TIRE REPAIR: UNCURED

SUPERSEDES:

MS51312

SHEET 1 OF 2

DD FORM 1 OCT 52 672-1

THIS MILITARY STANDARD IS APPROVED BY THE DEPARTMENT OF DEFENSE AND IS MANDATORY ON ALL ACTIVITIES. SELECTION FOR ALL NEW ENGINEERING AND DESIGN APPLICATIONS AND FOR REPETITIVE USE SHALL BE MADE FROM THIS DOCUMENT.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil - Downloaded: 2026-04-28T17:59Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS 2640

MS PART NUMBER	FIIN	MARKING CODE (1)	NUMBER OF PLIES TO EACH PATCH	TIRE TO BE REPAIRED		SIZE EACH PLY			MAX OVER-ALL PATCH DIM (INCHES)
				INJURY SIZE MAX (INCHES)	PLY RATING	FOR UNIT NO.	PLY NUMBERS	DIMENSIONS (INCHES)	
MS 51312-12	684-5146	12-7-14/20	12	7	14/20	1	1 & 2 3 & 4 5 & 6	9 X 14 10 X 16 11 X 18	25
						2	7 & 8 9 & 10 11 & 12	12 X 20 13 X 22 15 X 24	
MS 51312-13	684-5147	14-7-18/24	14	7	18/24	1	1 & 2 3 & 4 5 & 6	8 X 12-1/2 9 X 14 10 X 15-1/2	24
						2	7 & 8 9 & 10	11 X 17 13 X 18-1/2	
						3	11 & 12 13 & 14	13 X 20 15 X 21	
MS 51312-14	684-5148	14-9-20/24	14	9	20/24	1	1 & 2 3 & 4 5 & 6	10 X 15-1/2 11 X 17 12 X 18-1/2	25-1/2
						2	7 & 8 9 & 10	13 X 20 14 X 21-1/2	
						3	11 & 12 13 & 14	15 X 23 16 X 24-1/2	
MS 51312-15	684-5149	16-7-18/28	16	7	18/28	1	1 & 2 3 & 4 5 & 6	8 X 12-1/2 9 X 14 10 X 15-1/2	24
						2	7 & 8 9 & 10 11 & 12	11 X 17 12 X 18-1/2 13 X 20	
						3	13 & 14 15 & 16	15 X 21-1/2 16 X 23	
MS 51312-16	684-5150	16-12-20/24	16	12	20/24	1	1 & 2 3 & 4 5 & 6	13 X 18-1/2 14 X 20 15 X 21-1/2	30
						2	7 & 8 9 & 10 11 & 12	16 X 23 17 X 24-1/2 18 X 26	
						3	13 & 14 15 & 16	19 X 27-1/2 20 X 29	

NOTES:

1. IDENTIFICATION MARKING TO BE APPLIED TO EACH PATCH. THE CODE DENOTES THE NUMBER OF PLIES IN THE PATCH, THE MAXIMUM INJURY SIZE IN INCHES AND THE PLY RATING OF THE TIRE FOR WHICH THE PATCH IS INTENDED. EXAMPLE: 4-2-8/10 INDICATES 4 PLIES TO THE PATCH, 2-INCH MAXIMUM TIRE-INJURY SIZE AND PATCH SUITABLE FOR 8 AND 10 PLY TIRES.

GENERAL:

2. CORD MATERIAL FOR ALL SIZES OF PATCHES SHALL BE NYLON.
3. PATCHES SHALL CONFORM TO SPECIFICATION ZZ-T-486.
4. REFERENCED DOCUMENTS SHALL BE THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

APPROVED 16 JULY 1959 REVISED

CUSTODIANS: P.A.—Ord; Navy—Ships; AF—USAF

OTHER INT.: A—CE; N—NAVAIR, NSC; D—

MILITARY STANDARD

PATCH, PNEUMATIC TIRE REPAIR: UNCURED

MS51312

PROCUREMENT SPECIFICATION: ZZ-T-486

SUPERSEDES:

SHEET 2 OF 2

DD FORM 1 OCT 61 672-1

THIS MILITARY STANDARD IS APPROVED BY THE DEPARTMENT OF DEFENSE AND IS MANDATORY ON ALL ACTIVITIES. SELECTION FOR ALL NEW ENGINEERING AND DESIGN APPLICATIONS AND FOR REPETITIVE USE SHALL BE MADE FROM THIS DOCUMENT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:59Z
Check the source to verify that this is the current version before use.

Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.