
User activities: Army WC, SL, MU
Navy AS, MC, SH, OS
Air Force 19

Reviewer activities: Army MI, SL
Navy
Air Force 11, 17, 80
DSA-ES



RATINGS	
Style	LT10
Grade	1
Class	A
Temperature rise	15°C
Ambient temperature	90°C
Operating temperature	-55° to +105°C
Dielectric withstanding Voltage (sea level)	700 volts rms for a minimum of 60 sec
Dielectric withstanding Voltage (reduced barometric pressure)	180 volts rms for a minimum of 60 sec
Terminal pull	5 pounds
Altitude	70, 000 feet
Weight	1 5 grams max Ⓐ

Ltr	Dimensions in inches with metric equivalents (mm) in parentheses.	
	Minimum	Maximum
A	205 (5.21)	.225 (5.72)
B	550 (13 97)	.570 (14.48)
C	1.250 (31.75)	1.625 (41.28)
D	026 (66)	030 (76)

ELECTRICAL CHARACTERISTICS (INITIAL)

Dash no 1/	Type designation	Inductance at 25°C	Q min	Test frequency	Self-resonant frequency, min	DC resistance maximum	Rated DC Current
		µH		MHz	MHz	ohms	mA
-01	LT10K037	1100	60	25	2.8	21 0	78
-02	LT10K038	1200	60	25	2 7	22 0	76
-03	LT10K039	1300	60	25	2 6	23 0	75
-04	LT10K040	1500	65	25	2.4	25.0	72
-05	LT10K041	1600	65	25	2.3	26 0	70
-06	LT10K042	1800	65	25	2 2	28.0	68
-07	LT10K043	2000	65	25	2.1	29 0	67
-08	LT10K044	2200	70	25	2 0	30 0	66
-09	LT10K045	2400	70	25	1 9	31.0	64
-10	LT10K046	2700	70	25	1 8	33.0	62
-11	LT10K047	3000	70	25	1 7	35 0	61
-12	LT10K048	3300	70	25	1.6	38 0	58
-13	LT10K049	3600	70	25	1 5	40 0	57

1/ The dash number added to the MS military standard number constitutes the MS part number, example, MS90540-01.

Ⓐ denotes changes

APPROVED 15 Jun 65 REVISED Ⓐ 7 Jun 73

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

PA ARMY-EL	International interest	TITLE Ⓐ COILS, RADIO FREQUENCY, MOLDED, FIXED, SUBMINIATURE (IRON CORE) TYPES LT10K037 TO LT10K049 INCL	MILITARY STANDARD
Other Cust AF-80 NAVY-EC			MS90540
Procurement Specification MIL-C-15305		SUPERSEDES	PAGE 1 OF 2

DD FORM 1 SEP 63 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5950-0454-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

FED SUP CLASS
5950

Electrical Characteristics (Final) Ⓐ				
Inspection Group	Allowable variation from initial measurement		Allowable % from specified minimum value in Electrical Characteristics (initial) table	
	Inductance Percent	DC resistance	Self-resonant frequency	Q
Qualification Inspection				
Group II	±2	--	--	-10
Group III	±5	±(3% + 001 ohm)	- 8	-10
Group IV	±5	±(2% + .001 ohm)	-10	-15
Quality Conformance Inspection				
Group C				
Subgroup I	±2	--	--	-10
Subgroup II	±5	±(2% + 001 ohm)	-10	-15
Subgroup III	±5	±(3% + 001 ohm)	- 8	-10

Ⓐ NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. These coils are intended to be mounted by their leads.
4. The polarizing voltage during the moisture-resistance test is applied with the positive lead connected to the coil terminals tied together, and the negative lead connected to the metal strap
5. Tinned, solid copper wire, AWG #21.
6. Barometric pressure test (test condition C) is applicable.
7. Shock, specified pulse, method 213, test condition I, is applicable.
8. Referenced document shall be the issue in effect on date of invitation for bid.
9. This standard takes precedence over the procurement specification referenced herein.

APPROVED 15 Jun 65 REVISED Ⓐ For changes see pages 1 and 2.

User activities: Army WC, SL, MU; Navy AS, MC, SH, OS; Air Force 19
Reviewer activities: Army MI, SL; Navy; Air Force 11, 17, 80
DSA-ES

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

PA Army-EL Other Cust AF-80 Navy-EC	International Interest	TITLE Ⓐ COILS, RADIO FREQUENCY, MOLDED, FIXED, SUBMINIATURE (IRON CORE) TYPES LT10K037 TO LT10K049 INCL	MILITARY STANDARD MS90540
Procurement Specification MIL-C-15305		SUPERSEDES	PAGE 2 OF 2

DD FORM 1 SEP 63 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

5950-0454-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated Fold on lines on reverse side, staple in corner, and send to preparing activity Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements

SPECIFICATION MS90510 COILS, RADIO FREQUENCY, MOLDED, FIXED, SUBMINIATURE (IRON CORE) TYPES LT10K07 TO LT10K[illegible] INCL

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

ESC-FM 1068-68

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN: AMSEL-RD-ED
Fort Monmouth, New Jersey 07703

To detach this form, cut along this line

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:38Z
Check the source to verify that this is the current version before use.