MILITARY STANDARD

ENVIRONMENTAL TEST METHODS

TO ALL HOLDERS OF MIL-STD-810B

1. The following pages of MIL-STD-810B have been revised and supersede the pages listed:

New page	Date	Superseded page	Date
iii	21 Sep 70	iii	15 June 1967
iv	21 Sep 70	iv	15 June 1967
v thru vii	21 Sep 70	v	15 June 1967

2. Make the following pen and ink changes:

a. Page ii, paragraph 3, and DD Form 1426: Change address to:

"Commander, Aeronautical Systems Division
Attn: ASNPS-20
Wright-Patterson AFB, Ohio 45433".

b. Page 8: Add the following new section and paragraph after 5.1:

"6. NOTES

6.1 International interest. Certain provisions of this standard are the subject of international standardization agreements (STANAG 3518 AE). When amendment, revision, or cancellation of this standard is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels, including departmental standardization offices, if required."

c. Page 8: Below reviewer activities listing add "International interest (see 6.1)".

d. Page 502-1, paragraph 4(b): Delete and substitute:

"(b) Storage temperature and duration (step 2)."

e. Page 504-3, paragraph 3.2, Procedure I, Step 7, line 4: Delete "step 1" and substitute "step 7".

FSC MISC

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:57Z
Check the source to verify that this is the current version before use.

f. Page 504-7, Figure 504-1, NOTE 2: Delete "PEQUIREMENTS" and substitute "REQUIREMENTS".

g. Page 506-1, paragraph 3.1, Procedure I, sixth sentence: Delete and substitute "The wind source shall be maintained at this velocity for 15 minutes afterwhich the wind source shall be turned off."

h. Page 507-5, step 7, line 1: Delete "4 through 6" and substitute "2, 4, 5, and 6".

i. Page 508-3, paragraph 3.7 Criteria for passing test: Delete "3.7" and substitute "3.1.7".

j. Page 510-1, paragraph 2.1, last sentence: Delete "Fenton Foundry Supply Company, Dayton, Ohio and".

3. The following is a cumulative list of earlier changes:

a. Superseded methods

New method	Date	Superseded method	Date
513.1	20 October 1969	513	15 June 1967
514.1	20 October 1969	514	15 June 1967
515.1	20 October 1969	515	15 June 1967
516.1	20 October 1969	516	15 June 1967
517.1	20 October 1969	517	15 June 1967
519.1	18 September 1970	T519	29 Sept 1969

b. New method

Method		Date
T519	Gunfire Vibration, Aircraft	29 September 1969.

4. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

5. Holders of MIL-STD-810B will verify that pen and ink changes and page changes have been entered and will destroy the previous notices (notice pages only). This notice will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:57Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - AS
Air Force - 11

Review activities:
Army - EL, MI, MU, ME, AV, GL
Navy - AS, SH, OS, YD
Air Force - 11

Preparing activity:
Air Force- 11

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:57Z
Check the source to verify that this is the current version before use.

CONTENTS

Section		Page
1.	Scope	1
1.1	Purpose	1
1.2	Application of test methods	1
1.3	Numbering system	1
1.4	Revision of standard	1
1.5	Revision of test methods	1
1.6	Method of reference	1
2.	Referenced documents	1
3.	General requirements	2
3.1	Test conditions	2
3.1.1	Measurements of test conditions	3
3.1.2	Tolerance of test conditions	3
3.1.3	Accuracy of test apparatus	3
3.1.4	Stabilization of test temperature	3
3.1.5	Reference conditions	4
3.2	Performance of test	4
3.2.1	Pretest performance record	4
3.2.2	Installation of test item in test facility	4
3.2.3	Performance check during test	4
3.2.4	Visual inspection and failure criteria.	4
3.3	Test facilities apparatus	4
3.3.1	Test chamber.	4
3.3.1.1	Volume of test chamber.	4
3.3.1.2	Heat source	4
3.3.1.3	Location of temperature sensors	4
3.4	Test data	5
4.	Test sequence	5
5.	Test methods	8
6.	Notes	8
6.1	International interest	8

TEST METHODS

Method No.		
500	Altitude	500-1-500-2
501	High temperature	501-1-501-2
502	Low temperature	502-1-502-1
503	Temperature shock	503-1-503-1
504	Temperature - altitude	504-1-504-10
505	Sunshine	505-1-505-2
506	Rain	506-1-506-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:57Z
Check the source to verify that this is the current version before use.

CONTENTS

TEST METHODS (Continued)

Method No.		Page
507	Humidity	507-1-507-5
508	Fungus	508-1-508-3
509	Salt fog	509-1-509-4
510	Dust test	510-1-510-2
511	Explosive atmosphere	511-1-511-5
512	Leakage (immersion)	512-1-512-2
513.1	Acceleration	513.1-1-513.1-6
514.1	Vibration	514.1-1-514.1-30
515.1	Acoustical noise	515.1-1-515.1-6
516.1	Shock	516.1-1-516.1-10
517.1	Space simulation	517.1-1-517.1-11
518	Temperature-humidity-altitude	518-1-518-3
519.1	Gunfire vibration, aircraft	519.1-519.1-17

TABLES

Table I	Recommended test sequence	6-7
Table 504-I	Temperature range for various equipment classes	504-5
Table 504-II	Test chamber conditions for temperature-altitude tests	504-6
Table 513.1-I	G levels for structural test (Procedure I)	513.1-3
Table 513.1-II	G levels for operational test (Procedure II)	513.1-4
Table 514.1-I	Test procedure and time schedule chart for equipment installed in airplanes and helicopters - equipment category (a)	514.1-14
Table 514.1-II	Test procedure and time schedule chart for equipment installed in airplanes - equipment category (b)	514.1-16
Table 514.1-III	Test procedure and time schedule chart for equipment installed in helicopters - equipment category (c)	514.1-18
Table 514.1-IV	Test procedure and time schedule chart for equipment installed in air launched missiles - equipment category (d)	514.1-20
Table 514.1-V	Test procedure and time schedule chart for equipment installed in ground launched missiles - equipment category (e)	514.1-22
Table 514.1-VI	Test procedure and time schedule chart for equipment installed in ground vehicles - equipment category (f)	514.1-24

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:57Z
Check the source to verify that this is the current version before use.

CONTENTS

TABLES (Continued)

Page

Table 514.1-VII Test procedure and time schedule chart for equipment transported by common carrier, land or air - equipment category (g) 514.1-26
Table 514.1-IX Linear cycling rates 514.1-28
Table 515.1-I Acoustical noise test category 515.1-2
Table 516.1-I Transit drop test (Procedure II) 516.1-3
Table 517.1-I Pressure levels for effects simulation 517.1-2
Table 517.1-II Average radiation characteristics of planets. 517.1-3
Table 517.1-III Solar simulator classification 517.1-3
Table 517.1-IV Solar electromagnetic energy distribution. 517.1-4
Table 517.1-V Solar simulator - instrumentation performance requirements 517.1-6
Table 517.1-VI Significant parameters for solar simulation 517.1-7
Table 519.1-I Ballistic table. 519.1-15
Table 519.1-II Random vibration test time 519.1-17

FIGURES

Figure 504-1 Operational requirements for class 1, 1A, and 1B aerospace equipment. Temperature vs. altitude. 504-7
Figure 504-2 Operational requirements for class 2 aerospace equipment. Temperature vs. altitude. 504-8
Figure 504-3 Operational requirements for class 3 aerospace equipment. Temperature vs. altitude. 504-9
Figure 504-4 Operational requirements for class 4 aerospace equipment. Temperature vs. altitude. 504-10
Figure 505-1 Simulated solar radiation cycle - Procedure II 505-3
Figure 507-1 Humidity cycle for procedure I 507-6
Figure 507-2 Humidity cycle - Procedures II and III 507-7
Figure 507-3 Humidity cycle - Procedure IV 507-8
Figure 509-1 Variations of specific gravity of salt (NaCl) solution with temperature 509-5
Figure 509-2 Salt solution filter. 509-5

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:57Z
Check the source to verify that this is the current version before use.

CONTENTS

FIGURES (Continued)

		Page
Figure 509-3	Location of salt solution filter	509-6
Figure 511-1	Weight of air (lbs)	511-6
Figure 511-2	Temperature of fuel (^{o}F)	511-7
Figure 511-3	Correction of factor	511-8
Figure 513.1-1	Direction of vehicle acceleration	513.1-6
Figure 514.1-1	Vibration test curves for equipment installed in airplanes and helicopters - equipment category (a)	514.1-15
Figure 514.1-2	Vibration test curves for equipment installed in airplanes, excluding helicopters - equipment category (b)	514.1-17
Figure 514.1-3	Vibration test curves for equipment installed in helicopters - equipment category (c)	514.1-19
Figure 514.1-4	Vibration test curves for equipment installed in air launched missiles - equipment category (d)	514.1-21
Figure 514.1-5	Vibration test curves for equipment installed in ground launched missiles - equipment category (e)	514.1-23
Figure 514.1-6	Vibration test curves for equipment installed in ground vehicles - equipment category (f)	514.1-25
Figure 514.1-7	Vibration test curves for equipment transported by common carrier, land or air - equipment category (g)	514.1-27
Figure 514.1-9	Cut-off frequency vs. weight, equipment shipped by aircraft	514.1-29
Figure 514.1-10	Logarithmic sweep	514.1-30
Figure 515.1-1	Octave band spectrum for acoustical noise test	515.1-5
Figure 515.1-2	Octave band spectrum for acoustical noise test	515.1-6
Figure 516.1-1	Terminal-peak sawtooth shock pulse configuration and its tolerance limits	516.1-8
Figure 516.1-2	Half sine shock pulse configuration and its tolerance limits	516.1-9
Figure 516.1-3	System frequency response	516.1-10
Figure 518-1	Temperature-humidity-altitude cycle (Procedure I)	518-3
Figure 519.1-1	$G_o/n_o r_o$ vs. D	519.1-7

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:57Z
Check the source to verify that this is the current version before use.

CONTENTS

FIGURES (Continued)

Page

Figure 519.1-2 Reduction factor for mass loading 519.1-8
Figure 519.1-3 Determination of the D vector 519.1-9
Figure 519.1-4 Origin of the D vector for multigun, staggered array 519.1-10
Figure 519.1-5 Random vibration test curve 519.1-11
Figure 519.1-6 Peripherally mounted item 519.1-12
Figure 519.1-7 Swept random vibration test curve 519.1-13
Figure 519.1-8 Reduction of G_{max} vs. distance parameter h/c 519.1-14

☆ U. S. GOVERNMENT PRINTING OFFICE: 1972 -714-163/5244

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T22:57Z
Check the source to verify that this is the current version before use.