
FED. SUP CLASS
2H05

REVIEW ACTIVITY : DCSC, CO
USER ACTIVITY : YD.



Ⓓ CANCELED AFTER 24 JUNE 1982
NO SUPERSEDING STANDARD

NOTE.

1. ...E. NO. 49
...1008 OR 1010

2. PL ... ...E I.D. (6% MIN. TIN) TO A THICKNESS .001 NOMINAL. FLASH-TIN PLATE ALL OVER AFTER ...N PLATE.

3. IN 2.. ... DIA. INSPECTION BLOCK WITH ONE PARTING LINE FACE AGAINST A STOP AT HORIZONTAL CENTER LINE OF BLOCK AND A PRESSURE OF 1335 LBS. ON OTHER P.L. FACE. HEIGHT WILL BE 1.09475-1.09575 ON SIDE OPPOSITE STOP.

4. REMOVE ALL BURRS.

5. MS PART NUMBER AND PART MANFUFACTURER'S IDENTIFICATION TO BE CLEARLY MARKED WITHOUT INTERFERING WITH THE FUNCTION OF THE PART.

6. TOLERANCES: UNLESS OTHERWISE SPECIFIED, LINEAR MACHINED DIMENSIONS ±.010: ANGULAR MACHINED DIMENSIONS ±30'. DO NOT SCALE DRAWING.

7. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

8. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

9. ALL DIMENSIONS IN INCHES.

Ⓒ ENTIRE STANDARD REVISED

APPROVED 19 JUNE 1952 REVISED Ⓐ 27 NOVEMBER 1953 Ⓑ 24 OCTOBER 1955 Ⓒ 8 July 1966 Ⓓ 24 JUNE 1982

This Military Standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. Army - MO(ERDL) Other Cust A.F. - 69 NAVY - YD	TITLE BEARING, SLEEVE: ENGINE, PLAIN, 2-1/16" X 1-1/16"	PART NO. MS 13994-1 MILITARY STANDARD MS 13994
PROCUREMENT SPECIFICATION MIL-E-11275	SUPERSEDES	SHEET 1 OF 1

Source: https://assist.dla.mil -- Downloaded: 202640-23T13:31Z
Check the source to verify that this is the current version before use.