FED. SUP CLASS
2805



DASH NUMBER	A					
-1	.506					.230 .250
-2				.354 .374		.245 .265
				.416 .436	.348	.315 .335
-5	.201 .206		.221 .236			.200 .220

© CANCELED AFTER 24 JUNE 1982
NO SUPERSEDING STANDARD.

NOTES:

1. EDGES MUST BE [illegible] BURRS MUST BE TUMBLED.
2. MATERIAL: STEEL, S. .00
   HEAT TREA. RH-C-60 MIN.
3. TOLERANCES: UNLESS OTHERWISE SPECIFIED, LINEAR MACHINED DIMENSIONS ± .010: ANGULAR MACHINED DIMENSIONS ± 30'. DO NOT SCALE DRAWING.
4. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
5. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
6. ALL DIMENSIONS IN INCHES.
7. THE "MS" PART NUMBER CONSISTS OF THE MS NUMBER, PLUS THE DASH NUMBER
   EXAMPLE: MS 13997-1

REVIEW ACTIVITY : DCSC, S.
USER ACTIVITY : TD.

This Military Standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 19 JUNE 1952 REVISED (A) 24 OCTOBER 1955 (B) 8 July 1966 (C) 24 JUNE 1982

(B) ENTIRE STANDARD REVISED

P.A. Army - MO(ERDL)	TITLE	MILITARY STANDARD
Other Cust A.F. - 69 NAVY - YD	LOCK, VALVE SPRING RETAINER: ENGINE	MS 13997
PROCUREMENT SPECIFICATION MIL-E-11275	SUPERSEDES:	SHEET 1 OF 1

DD FORM SEP 67 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T13:31Z
Check the source to verify that this is the current version before use.