INCH-POUND

MIL-M-28787/278A(SH)
AMENDMENT 1
19 March 1992

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DRIVER, LAMP/RELAY, DIGITAL, KEY CODE FQD

This amendment forms a part of Military Specification MIL-M-28787/278A(EC), dated 3 May 1984, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions C1-C12, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions H1-H8, -55°C (Class II), Max column: Delete "1,100" and substitute "1,110".

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through Q shall be performed in any order with the following exceptions. Test conditions A2-A4, B, and C are stress tests and shall be performed only at 25 ± 5°C. If test conditions A2-A4, B, and C are part of a sequence of tests, the order of testing shall be as follows: A2-A4, B, and C where applicable, followed by the remaining tests in the sequence."

4.5.1, fifth line: Delete "C through P" and substitute "A1, D through M, and P".

4.5.3, third line: Delete "C through P" and substitute "A1, D through M, and P".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:21Z
Check the source to verify that this is the current version before use.

MIL-M-28787/278A(SH)
AMENDMENT 1

PAGE 6

4.5.3, sixth line: Delete "C through Q" and substitute "A1, D through M, and P".

Preparing activity:
Navy – SH

(Project 5963–N784)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:21Z
Check the source to verify that this is the current version before use.