MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

RELAY, ANALOG, KEY CODE RRF

This amendment forms a part of Military Specification MIL-M-28787/279(EC), dated 23 August 1979, and is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2, second line: Delete "100°C" and substitute "85°C".

PAGE 4

TABLE I, column heading: Delete "100°C ±5°C" and substitute "85°C ±5°C".

PAGE 5

4.3, delete and substitute the following:

"4.3 Test equipment. Test equipment specified on figures and in tables with a type designator shall be as specified in MIL-STD-1665. Other equipment and components shall be as specified on the figures. All resistors shall be metal film and all capacitors shall be ceramic unless otherwise specified."

4.4.2, add the following sentence at the end of the paragraph:

"If test condition A is performed at any time during quality assurance inspecting testing, it shall be followed by performance of at least all 100 percent tests."

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N631)

FSC 5963

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:22Z
Check the source to verify that this is the current version before use.