INCH-POUND

MIL-M-28787/287A
AMENDMENT 3
28 April 1993
SUPERSEDING
AMENDMENT 2
9 July 1985

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

BUFFER, BIDIRECTIONAL, DIGITAL, KEY CODE HRL

This amendment forms a part of Military Specification MIL-M-28787/287A(EC), dated 29 April 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

*TABLE I, Test conditions C1-C16, C17-C32, and D1-D38, Test type column: Delete "X" (three places) and substitute "S" (three places).

*TABLE I, Test conditions D1-D38, Min columns: Delete "0.0" (five places) and substitute "-0.4" (five places).

*TABLE I, Test conditions E1-E48, Min columns: Delete "0.0" (five places) and substitute "-10" (five places).

*TABLE I, Test conditions E49-E96 and F1-F16, Min columns: Delete "0" (ten places) and substitute "-6" (ten places).

PAGE 5

*TABLE I, Test conditions L1-L4, L5, L6, Min column: Delete "-10" (ten places) and substitute "0" (ten places).

PAGE 6

TABLE I, Test conditions AA33-AA36, Max columns: Delete "15" (five places) and substitute "20" (five places).

PAGE 7

*4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through AA shall be performed in any order with the following exceptions. Test conditions A, B, C, and D are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, or D are part of a sequence of tests, the order of testing shall be as follows: A, B, C, and D where applicable, followed by the remaining tests in the sequence."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:23Z
Check the source to verify that this is the current version before use.

*4.5.1, fifth line: Delete "C through V" and substitute "E through X".

*4.5.3, third line: Delete "C through V" and substitute "E through X".

*4.5.3, sixth line: Delete "C through AA" and substitute "E through AA".

PAGES 19 AND 20

*TABLE VI, Test conditions D1-D21 and D22-D38, Min column: Delete "0.0" (two places) and substitute "-0.4" (two places).

PAGES 22, 23, AND 24

*TABLE VII, Test conditions E1-E20, E21-E40, E41-E48, and E50-E61, Min column: Delete "0" (three places) and substitute "-10" (three places).

PAGE 24

*TABLE VII, Test condition E49, Min column: Delete """ and substitute "-6".

PAGES 25 AND 26

*TABLE VII, Test conditions E62-E82, Min column: Delete "0" (two places) and substitute "-6" (two places).

PAGE 27

*TABLE VIII, Test conditions F1-F16, Min column: Delete "0" and substitute "-6".

PAGE 46

*TABLE XIII, Test conditions L1-L6, Min column: Delete "-10" and substitute "0".

PAGE 85

TABLE XXVII, Test condition AA33, Max limit column: Delete "15" and substitute "20".

PAGE 86

*FIGURE 26, ITEM C01 box: Delete "C01" and substitute "C06".

*FIGURE 26, NOTE 3, first line: Delete "(C01)" and substitute "(C06)".

*FIGURE 26, NOTE 3, second line: Delete "Frequency = 120 Hz." and substitute "Frequency = 1 KHz."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:23Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - SH
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0227)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:23Z
Check the source to verify that this is the current version before use.