MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DECODER, DIGITAL, KEY CODE AFA

This specification is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document establishes the requirements and test procedures for the acquisition of an electronic decoder module.

1.2 Classification. This specification covers two classes of modules.

Class I and class II as specified in MIL-STD-1389.

2. APPLICABLE DOCUMENTS

* 2.1 Government specifications and standards. Unless otherwise specified, the following specifications and standards, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-28787 - Modules, Standard Electronic, General Specification for.

STANDARDS

MILITARY

MIL-STD-1389 - Design Requirements for Standard Electronic Modules.

MIL-STD-1665 - Test Equipment for the Standard Electronic Modules Program.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 General requirements. The module shall comply with the requirements of MIL-M-28787 except as modified herein.

3.2 Correlation requirements. Before any production modules are tested, all testers and test equipment shall be correlated in accordance with MIL-M-28787.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Electronic Systems Command, ATTN: ELEX 8111, Department of the Navy, Washington, DC 20363, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

3.3 Failure rate requirements. All modules acquired to this specification shall have a predicted failure rate no greater than 0.104 failures per million operating hours for class I or 0.208 failures per million operating hours for class II, when predicted in accordance with MIL-STD-1389. When a class II module is used in a class I environment, failure rate for class I shall be used for reliability prediction (see 6.3).

3.4 Performance requirements. The module shall conform to the electrical requirements specified in table I. Class I modules shall conform to the electrical requirements of class I only, and class II modules shall conform to the electrical requirements of class I and class II (see 6.3).

3.5 Module configuration requirements. The module configuration requirements shall be in accordance with MIL-STD-1389 and as specified herein.

3.5.1 Key code. The module key code shall be AFA.

3.5.2 Size. The module size shall be 1A.

3.5.3 Weight. The module shall have a maximum weight of 35 grams.

3.5.4 Contact pins. The module shall have 40 contact pins positioned A1 through A40.

3.5.5 Fin position. The module shall have an insertion and extraction and heat dissipation fin on increment A.

3.5.6 Depth. The module shall have no additional depth requirements.

3.5.7 Holddown holes. The module shall have no additional requirements for location or quantity of holddown holes.

3.5.8 Marking Marking shall be as specified in MIL-STD-1389, and the module shall be marked with the military part number M28787/291-1 for class I and M28787/291-2 for class II, except no marking shall interfere with heat dissipation from the fin (for example, affixing a label which may be a heat barrier).

3.6 Circuit pin configuration. The function diagram and pin assignments shall conform to figure 1.

3.7 Acceptance tests. All production modules shall be tested in accordance with footnotes 1 and 2 of table I.

3.8 End-of-life limits. Modules which have been plugged into an operating system, or exceed 2 years from date of manufacture and are to be tested, shall be capable of conforming to the 25°C end-of-life limits of table I (see 6.2).

3.9 Power supply voltage. The module shall be capable of conforming to the requirements of table I for a power supply voltage (V_{CC}) of 5.0 ±0.5 V dc, except that the limits for output short circuit current apply only for a power supply voltage of 5.5 V dc ±1 percent.

3.10 Functional test. All modules shall be subjected to functional tests which conform to the requirements stated in 3.10.1, 3.10.2, and 3.10.3.

3.10.1 Test patterns. A set of unique input patterns shall be generated capable of detecting all nonredundant failures in the module logic network. The test patterns shall be generated by assuming "stuck at H state" and "stuck at L state" failures in each of the basic logic functions and applying input patterns to detect these failures. The unique test patterns necessary to satisfy these requirements shall be submitted with the qualification samples. If the tests of tables I and XIX satisfy or exceed these unique test patterns, no additional tests shall be added; otherwise, the needed tests shall be added to table XIX. "Stuck at H state" indicates a failure resulting in a steady high-level output. "Stuck at L state" indicates a failure resulting in a steady low-level output. Prior to any change in module design which would necessitate a different set of test patterns to detect a "stuck at H state" or a "stuck at L state", the vendor shall be required to submit to

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

the contracting activity and the Standard Electronic Modules Program Quality Assurance Activity (SEMP-QAA) the proposed new set of test patterns for approval.

3.10.2 Input requirements. The following input voltage levels shall be used for test patterns:

Low level - Input voltage shall be 0.7 V ±1%.
High level - Input voltage shall be 2.0 V ±1%.

3.10.3 Output requirements. The output requirements for the test patterns shall be as follows:

Low level - Output voltage shall be 0 V minimum, 0.4 V maximum.
High level - Output voltage shall be 2.5 V minimum, V_{CC} maximum.

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance. The quality assurance provisions of MIL-M-28787 shall apply.

4.2 Acceptance tests. Acceptance tests of all modules shall be in accordance with procedures and equipment specified in MIL-M-28787.

4.3 Test equipment. Test equipment specified on figures and in tables with a type designator shall be as specified in MIL-STD-1665. Other equipment and components shall be as specified on the figures. All resistors shall be metal film and all capacitors shall be ceramic unless otherwise specified.

4.4 Test procedures. The module shall be tested as specified in table I.

4.4.1 Alternate test methods. Alternate test methods may be employed if approved by the SEMP-QAA and they conform to the requirements of MIL-M-28787.

4.4.2 Order of testing. Test conditions A through W shall be performed in any order with the following exceptions. If test conditions A, B, C, D, or E are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E where applicable, followed by the remaining tests in the sequence.

4.5 Qualification testing. Initial qualification tests and periodic-check tests shall be performed in accordance with the test plan specified in MIL-M-28787 with the following modifications or additions.


4.5.1 Operating temperature tests. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through W in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25° ±5°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions D through T, U, and W shall be performed in the order specified in 4.4.2 using the initial limits for applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2.

4.5.1.1 Component temperature test. The component temperature test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 3.

4.5.2 Vibration tests. The vibration tests shall be conducted in accordance with MIL-M-28787. During the vibration tests, the module shall be operated in the test circuit shown on figure 4. Following the vibration tests, the electrical tests of table I which are marked with an "X" in the test type column, and test condition U, shall be performed using the initial limits at 25° ±5°C ambient.

4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests D through T, U, and W shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements of table I. Following the return of the module to 25°C, electrical tests D through W shall be performed in the order specified in 4.4.2 using the 25° ±5°C ambient end-of-life requirements of table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTES:
1. G1, G2 = Enable inputs.
2. SEL A, B, C = Select inputs.
3. Y0-Y7 = Outputs.
4. GND = 0 V_{REF}.
5. V_{CC} = 5.0 V dc ±10%.

FIGURE 1. AFA module function diagram, decoder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE I. Module electrical requirements.

Test condition	Parameter	Ref test table	Test type 1/-3/	25° ±5°C 4/		Class I 4/				Class II 4/				Unit
						0° ±5°C		60° ±5°C		-55° ±5°C		85° ±5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
A	Isolation													
	Initial	III	S	10	∞	10	∞	10	∞	10	∞	10	∞	MΩ
	End-of-life	III	S	1	∞	1	∞	1	∞	1	∞	1	∞	MΩ
B1-B24	V_{OUT} (low loaded)	IV	S	10	800	10	800	10	800	10	800	10	800	mV
C1,C6,C11	Input breakdown current	V	S	0	200	0	200	0	200	0	200	0	200	µA
C2-C5, C7-C10, C12-C14	Input breakdown current	V	S	0	100	0	100	0	100	0	100	0	100	µA
D1-D24	Output short circuit current	VI	X	-6	-100	-6	-100	-6	-100	-6	-100	-6	-100	mA
E1-E24	Output leakage current	VII	X	0	1	0	1	0	1	0	1	0	1	mA
F1-F14	Input clamp diode voltage	VIII	X	-0.4	-1.5	-0.4	-1.5	-0.4	-1.5	-0.4	-1.5	-0.4	-1.5	V
G1-G24	Output voltage, low level	IX	X	0	400	0	400	0	400	0	400	0	400	mV
H1-H24	Output voltage, high level	X	X	2.5	4.5	2.5	4.5	2.5	4.5	2.5	4.5	2.5	4.5	V
J1,J6,J11	Input current, high level	XI	X	0	40	0	40	0	40	0	40	0	40	µA
J2-J5, J7-J10, J12-J14	Input current, high level	XI	X	0	20	0	20	0	20	0	20	0	20	µA
K1,K6,K11	Input current, low level	XII	X	-0.01	-0.86	-0.01	-0.86	-0.01	-0.86	-0.01	-0.86	-0.01	-0.86	mA
K2-K5, K7-K10, K12-K14	Input current, low level	XII	X	-0.01	-0.43	-0.01	-0.43	-0.01	-0.43	-0.01	-0.43	-0.01	-0.43	mA
L	Power supply current	XIII	X	0.1	30.0	0.1	30.0	0.1	30.0	0.1	30.0	0.1	30.0	mA
M1-M24	Transition time (t_{TLH}), C_L = 50 pF	XIV	S	5	50	5	55	5	55	5	60	5	58	ns

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE I. Module electrical requirements - Continued.

Test condition	Parameter	Ref test table	Test type 1/-3/	25° ±5°C 4/		Class I 4/				Class II 4/				Unit
						0° ±5°C		60° ±5°C		-55° ±5°C		85° ±5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
M25-M48	Transition time (t_{TLH}), C_L = 150 pF	XIV	Q	10	80	10	90	10	90	10	100	10	95	ns
N1-N24	Transition time (t_{THL}), C_L = 50 pF	XIV	S	3	18	3	20	3	20	3	22	3	21	ns
N25-N48	Transition time (t_{THL}), C_L = 150 pF	XIV	Q	6	40	6	42	6	42	6	44	6	43	ns
P1-P16	Propagation delay time (t_{PLH}), C_L = 50 pF	XIV	S	2	30	2	32	2	32	2	34	2	33	ns
P17-P32	Propagation delay time (t_{PLH}), C_L = 150 pF	XIV	Q	5	40	5	42	5	42	5	44	5	43	ns
P33-P56	Propagation delay time (t_{PLH}), C_L = 50 pF	XIV	S	2	22	2	24	2	24	2	26	2	25	ns
P57-P80	Propagation delay time (t_{PLH}), C_L = 150 pF	XIV	Q	4	32	4	34	4	34	4	36	4	35	ns
P81-P84, P89-P92, P97-P100, P105-P108, P113-P116, P121-P124, P129-P132, P137-P140, P145-P148	Propagation delay time (t_{PLH}), C_L = 50 pF	XIV	S	2	24	2	26	2	26	2	28	2	27	ns
P85-P88, P93-P96, P101-P104, P109-P112, P117-P120, P125-P128, P133-P136, P141-P144, P149-P152	Propagation delay time (t_{PLH}), C_L = 50 pF	XIV	S	2	31	2	33	2	33	2	35	2	34	ns

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE I. Module electrical requirements - Continued.

Test condition	Parameter	Ref test table	Test type 1/-3/	25° ±5°C 4/		Class I 4/				Class II 4/				Unit
						0° ±5°C		60° ±5°C		-55° ±5°C		85° ±5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
P153-P156, P161-P164, P169-P172, P177-P180, P185-P188, P193-P196, P201-P204, P209-P212, P217-P220	Propagation delay time (t_{PLH}), C_L = 150 pF	XIV	Q	3	34	3	36	3	36	3	38	3	37	ns
P157-P160, P165-P168, P173-P176, P181-P184, P189-P192, P197-P200, P205-P208, P213-P216, P221-P224	Propagation delay time (t_{PLH}), C_L = 150 pF	XIV	Q	4	41	4	43	4	43	4	45	4	44	ns
Q1-Q16	Propagation delay time (t_{PHL}), C_L = 50 pF	XIV	S	2	42	2	44	2	44	2	46	2	45	ns
Q17-Q32	Propagation delay time (t_{PHL}), C_L = 150 pF	XIV	Q	5	52	5	54	5	54	5	56	5	55	ns
Q33-Q56	Propagation delay time (t_{PHL}), C_L = 50 pF	XIV	S	2	36	2	38	2	38	2	40	2	39	ns
Q57-Q80	Propagation delay time (t_{PHL}), C_L = 150 pF	XIV	Q	5	46	5	48	5	48	5	50	5	49	ns

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE I. Module electrical requirements - Continued.

Test condition	Parameter	Ref test table	Test type 1/-3/	25° ±5°C 4/		Class I 4/				Class II 4/				Unit
						0° ±5°C		60° ±5°C		-55° ±5°C		85° ±5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
Q81-Q84, Q89-Q92, Q97-Q100, Q105-Q108, Q113-Q116, Q121-Q124, Q129-Q132, Q137-Q140, Q145-Q148	Propagation delay time (t_{PHL}), C_L = 50 pF	XIV	S	2	45	2	47	2	47	2	49	2	48	ns
Q85-Q88, Q93-Q96, Q101-Q104, Q109-Q112, Q117-Q120, Q125-Q128, Q133-Q136, Q141-Q144, Q149-Q152	Propagation delay time (t_{PHL}), C_L = 50 pF	XIV	S	2	43	2	45	2	45	2	47	2	46	ns
Q153-Q156, Q161-Q164, Q169-Q172, Q177-Q180, Q185-Q188, Q193-Q196, Q201-Q204, Q209-Q212, Q217-Q220	Propagation delay time (t_{PHL}), C_L = 150 pF	XIV	Q	5	55	5	57	5	57	5	59	5	58	ns
Q157-Q160, Q165-Q168, Q173-Q176, Q181-Q184, Q189-Q192, Q197-Q200, Q205-Q208, Q213-Q216, Q221-Q224	Propagation delay time (t_{PHL}), C_L = 150 pF	XIV	Q	5	53	5	55	5	55	5	57	5	56	ns

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20 11:24Z
Check the source to verify that this is the current version before use.

*TABLE I. Module electrical requirements - Continued.

Test condition	Parameter	Ref test table	Test type 1/-3/	25° ±5°C 4/		Class I 4/				Class II 4/				Unit
						0° ±5°C		60° ±5°C		-55° ±5°C		85° ±5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
R1-R24	Output crosstalk, low level	XV	Q	0	500	0	500	0	500	0	500	0	500	mV
S1-S24	Output crosstalk, high level	XV	Q	0	400	0	400	0	400	0	400	0	400	mV
T	Power supply transient amplitude	XVI	Q	0	400	0	400	0	400	0	400	0	400	mV
U	Power supply filter capacitance	XVII	S	1.6	3.0	1.6	3.0	1.6	3.0	1.6	3.0	1.6	3.0	µF
V1,V6,V11	Input capacitance	XVIII	Q	5	30	5	30	5	30	5	30	5	30	pF
V2-V5, V7-V10, V12-V14	Input capacitance	XVIII	Q	5	15	5	15	5	15	5	15	5	15	pF
W1-W40	Functional	XIX	X	← Test vectors must produce output vectors as specified in table XIX. →										

1/ "X" parameters shall be 100 percent tested during module acceptance tests.
2/ "S" parameters shall be sample acceptance tested (1 percent or two modules from each inspection lot, whichever is greater) at 25°C.
3/ "Q" parameters shall be tested during qualification testing only.
4/ Unless otherwise specified, limits are for initial and end-of-life.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-28787.

6. NOTES

6.1 Definitions. Definitions are as specified in MIL-STD-1331.

6.2 End-of-life. When any individual module circuit parameter fails to conform to the end-of-life requirements of table I, the module is considered to have completed its useful life (see 3.8).

6.3 Substitutability. Class II modules are substitutable for class I modules. When class II modules are used in a class I environment, the failure rate for class I shall be used for reliability prediction (see 3.3 and 3.4).

* 6.4 Module description. The following electrical parameters reflect the 0° to 60°C and -55° to 85°C end-of-life limits from table I.

	Class I	Class II	Unit
Maximum power dissipation (output not loaded)	165	165	mW
Supply voltage	5.0 ±10%	5.0 ±10%	V dc
Input voltage			
Low level	-0.5 min, 0.7 max	-0.5 min, 0.7 max	V
High level	2.0 min, V_{CC} max	2.0 min, V_{CC} max	V
Input current, low level			
A, B, C, and G1 inputs			
V_{IL} = 0.0 V	-0.43 max	-0.43 max	mA
V_{IL} = 0.4 V	-0.4 max	-0.4 max	mA
G2 inputs			
V_{IL} = 0.0 V	-0.86 max	-0.86 max	mA
V_{IL} = 0.4 V	-0.8 max	-0.8 max	mA
Input current, high level			
A, B, C, and G1 inputs			
V_{IH} = 2.5 V	20 max	20 max	µA
V_{IH} = 7.0 V	0.1 max	0.1 max	mA
G2 inputs			
V_{IH} = 2.5 V	40 max	40 max	µA
V_{IH} = 7.0 V	0.2 max	0.2 max	mA
Output voltage			
Low level (I_{OL} = 4.0 mA)	0.4 max	0.4 max	V
High level (I_{OH} = -400 µA)	2.5 min	2.5 min	V
Output drive current maximum capability			
Low level (V_{OL} = 0.4 V)	4.0	4.0	mA
High level (V_{OH} = 2.5 V)	-400	-400	µA
Propagation delay time (t_{PHL}), C_L = 50 pF			
G1 to output	2 min, 44 max	2 min, 45 max	ns
G2 to output	2 min, 38 max	2 min, 39 max	ns
Select to output (2 gate delay)	2 min, 47 max	2 min, 48 max	ns
Select to output (3 gate delay)	2 min, 45 max	2 min, 46 max	ns

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

	Class I	Class II	Unit
Propagation delay time (t_{PHL}), C_L = 150 pF			
G1 to output	5 min, 54 max	5 min, 55 max	ns
G2 to output	5 min, 48 max	5 min, 49 max	ns
Select to output (2 gate delay)	5 min, 57 max	5 min, 58 max	ns
Select to output (3 gate delay)	5 min, 55 max	5 min, 56 max	ns
Propagation delay time (t_{PLH}), C_L = 50 pF			
G1 to output	2 min, 32 max	2 min, 33 max	ns
G2 to output	2 min, 24 max	2 min, 25 max	ns
Select to output (2 gate delay)	2 min, 26 max	2 min, 27 max	ns
Select to output (3 gate delay)	2 min, 33 max	2 min, 34 max	ns
Propagation delay time (t_{PLH}), C_L = 150 pF			
G1 to output	5 min, 42 max	5 min, 43 max	ns
G2 to output	4 min, 34 max	4 min, 35 max	ns
Select to output (2 gate delay)	3 min, 36 max	3 min, 37 max	ns
Select to output (3 gate delay)	4 min, 43 max	4 min, 44 max	ns

* 6.5 Module function. This module contains three independent 3-to-8 line decoders with separate enables.

6.5.1 Input to output relationship. Each decoder has the input to output relationship of table II for positive logic.

TABLE II. Input to output relationship. 1/ - 4/

Inputs					Outputs							
Enable		Select										
G1	G2	C	B	A	Y0	Y1	Y2	Y3	Y4	Y5	Y6	Y7
X	H	X	X	X	H	H	H	H	H	H	H	H
L	X	X	X	X	H	H	H	H	H	H	H	H
H	L	L	L	L	L	H	H	H	H	H	H	H
H	L	L	L	H	H	L	H	H	H	H	H	H
H	L	L	H	L	H	H	L	H	H	H	H	H
H	L	L	H	H	H	H	H	L	H	H	H	H
H	L	H	L	L	H	H	H	H	L	H	H	H
H	L	H	L	H	H	H	H	H	H	L	H	H
H	L	H	H	L	H	H	H	H	H	H	L	H
H	L	H	H	H	H	H	H	H	H	H	H	L

1/ H = High-voltage level.
2/ L = Low-voltage level.
3/ X = Irrelevant.
4/ Decoder circuit 3 has no G1 enable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

6.5.2 Parallel outputs. Paralleling of outputs is not permissible.


6.6 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N391)


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTES:
1. R1-R3 = 1.27 kΩ ±1%, 1/4 W.
2. R4 = 1 kΩ ±5%, 1/4 W.
3. R5 = 51Ω ±5%, 1/2 W.
4. Item J01 setup:
   PW = 500 ±100 ns.
   Frequency = 1 MHz ±20%.
   $t_{TLH} = t_{THL}$ = 50 ±25 ns.
   PA = 4.0 ±1.0 V.

* FIGURE 2. Operating temperature and life test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTES:
1. R1 = 1 kΩ ±5%, 1/4 W.
2. R2-R4 = 1.27 kΩ ±1%, 1/4 W.

FIGURE 3. Component temperature test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.





FIGURE 4. Vibration test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE III. Isolation test.

Test condition	Parameter	Connect		Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	Min	Max		
A	Isolation	All pins	Frame	10	∞	MΩ	5

Source: https://assist.dla.mil -- Downloaded: 2026
Check the source to verify that this is the current ve



WARNING

When using a megohm bridge, high voltage may be present at any of the output binding posts. Always set the megohm bridge function switch to "discharge" before connecting or disconnecting the test leads.

NOTE: Penetrate the anodized finish on the module frame with a sharply pointed probe connected to the negative terminal.

AFA MODULE	
1(V_{CC})	(1Y0) 7
	(1Y1) 27
10(GND)	(1Y2) 6
	(1Y3) 26
22(1G2)	(1Y4) 5
2(1G1)	(1Y5) 25
	(1Y6) 4
24(1A)	(1Y7) 21
3(1B)	
23(1C)	(2Y0) 11
	(2Y1) 32
	(2Y2) 34
31(2G2)	(2Y3) 14
30(2G1)	(2Y4) 13
	(2Y5) 33
28(2A)	(2Y6) 12
8(2B)	(2Y7) 29
9(2C)	
	(3Y0) 37
	(3Y1) 18
17(3G2)	(3Y2) 38
	(3Y3) 39
35(3A)	(3Y4) 19
15(3B)	(3Y5) 40
36(3C)	(3Y6) 20
	(3Y7) 16

FIGURE 5. Isolation test circuit for table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE IV. V_{OUT} (low-loaded) test.


Test condition	Parameter	Connect			Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	Min	Max		
B1	1Y0 V_{OUT} (low loaded)	7	3,22,23,24	2	10	800	mV	6
B2	1Y1 "	27	3,22,23	2,24	"	"	"	"
B3	1Y2 "	6	22,23,24	2,3	"	"	"	"
B4	1Y3 "	26	22,23	2,3,24	"	"	"	"
B5	1Y4 "	5	3,22,24	2,23	"	"	"	"
B6	1Y5 "	25	3,22	2,23,24	"	"	"	"
B7	1Y6 "	4	22,24	2,3,23	"	"	"	"
B8	1Y7 "	21	22	2,3,23,24	"	"	"	"
B9	2Y0 "	11	8,9,28,31	30	"	"	"	"
B10	2Y1 "	32	8,9,31	28,30	"	"	"	"
B11	2Y2 "	34	9,28,31	8,30	"	"	"	"
B12	2Y3 "	14	9,31	8,28,30	"	"	"	"
B13	2Y4 "	13	8,28,31	9,30	"	"	"	"
B14	2Y5 "	33	8,31	9,28,30	"	"	"	"
B15	2Y6 "	12	28,31	8,9,30	"	"	"	"
B16	2Y7 "	29	31	8,9,28,30	"	"	"	"
B17	3Y0 "	37	15,17,35, 36	Open	"	"	"	"
B18	3Y1 "	18	15,17,36	35	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE IV. V_{OUT} (low-loaded) test - Continued.

Test condition	Parameter	Connect			Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	Min	Max		
B19	3Y2 V_{OUT} (low loaded)	38	17,35,36	15	10	800	mV	6
B20	3Y3 "	39	17,36	15,35	"	"	"	"
B21	3Y4 "	19	15,17,35	36	"	"	"	"
B22	3Y5 "	40	15,17	35,36	"	"	"	"
B23	3Y6 "	20	17,35	15,36	"	"	"	"
B24	3Y7 "	16	17	15,35,36	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026
Check the source to verify that this is the current v



NOTE: R1 = 1.27 kΩ ±1%, 1/4 W.

* FIGURE 6. V_{OUT} (low-loaded) test circuit for table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE V. Input breakdown current test.


Test condition	Parameter		Connect		Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	Min	Max		
C1	1G2	Input breakdown current	22	2,24,3,23, 31,30,28,8, 9,17,35,15, 36	0	200	µA	7
C2	1G1	"	2	22,24,3,23, 31,30,28,8, 9,17,15,35, 36	"	100	"	"
C3	1A	"	24	2,22,3,23, 31,30,28,8, 9,17,15,35, 36	"	"	"	"
C4	1B	"	3	2,22,24,23, 31,30,28,8, 9,17,35,15, 36	"	"	"	"
C5	1C	"	23	2,22,24,3, 31,30,28,8, 9,17,35,15, 36	"	"	"	"
C6	2G2	"	31	2,22,24,3, 23,30,28,8, 9,17,35,15, 36	"	200	"	"
C7	2G1	"	30	2,22,24,3, 23,31,28,8, 9,17,35,15, 36	"	100	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE V. Input breakdown current test - Continued.

Test condition	Parameter	Connect A to pin	Connect B to pin	Initial limits 25° ±5°C ambient Min	Initial limits 25° ±5°C ambient Max	Unit	Test figure
C8	2A Input breakdown current	28	2,22,24,3,31,30,8,9,17,35,15,23,36	0	100	µA	7
C9	2B "	8	2,22,24,3,23,31,30,28,9,17,35,15,36	"	100	"	"
C10	2C "	9	2,22,24,23,31,30,28,8,17,35,15,36,3	"	100	"	"
C11	3G2 "	17	2,22,24,3,23,31,30,28,8,9,35,15,36	"	200	"	"
C12	3A "	35	2,22,24,3,23,31,30,28,8,9,17,15,36	"	100	"	"
C13	3B "	15	2,22,24,3,23,31,30,28,8,9,17,35,36	"	100	"	"
C14	3C "	36	2,22,24,3,23,31,30,28,8,9,17,15,35	"	100	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



CAUTION

Do not isolate the chassis of ammeter X01 from earth ground.

NOTE Item P01-2 shall be current limited to 5.0 mA.

FIGURE 7. Input breakdown current test circuit for table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test.


Test condition	Parameter		Connect			Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	Min	Max		
D1	1Y0	Output short circuit current	17,22,31	7	2,3,8,9, 15,23,24, 28,30,35, 36	-6	-100	mA	8
D2	1Y1	"	"	27	"	"	"	"	"
D3	1Y2	"	"	6	"	"	"	"	"
D4	1Y3	"	"	26	"	"	"	"	"
D5	1Y4	"	"	5	"	"	"	"	"
D6	1Y5	"	"	25	"	"	"	"	"
D7	1Y6	"	"	4	"	"	"	"	"
D8	1Y7	"	"	21	"	"	"	"	"
D9	2Y0	"	"	11	"	"	"	"	"
D10	2Y1	"	"	32	"	"	"	"	"
D11	2Y2	"	"	34	"	"	"	"	"
D12	2Y3	"	"	14	"	"	"	"	"
D13	2Y4	"	"	13	"	"	"	"	"
D14	2Y5	"	"	33	"	"	"	"	"
D15	2Y6	"	"	12	"	"	"	"	"
D16	2Y7	"	"	29	"	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE VI. Output short circuit current test - Continued.

Test condition	Parameter		Connect			Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	Min	Max		
D17	3Y0	Output short circuit current	17,22,31	37	2,3,8,9, 15,23,24, 28,30,35, 36	-6	-100	mA	8
D18	3Y1	"	"	18	"	"	"	"	"
D19	3Y2	"	"	38	"	"	"	"	"
D20	3Y3	"	"	39	"	"	"	"	"
D21	3Y4	"	"	19	"	"	"	"	"
D22	3Y5	"	"	40	"	"	"	"	"
D23	3Y6	"	"	20	"	"	"	"	"
D24	3Y7	"	"	16	"	"	"	"	"

Source: https://assist.dla.mil - Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



CAUTION

Do not isolate the chassis of ammeter XOI from earth ground.

NOTE.
When performing the output short circuit current test, only one output shall be shorted at a time and the duration of the test shall not exceed 1 second.


FIGURE 8. Output short circuit current test circuit for table VI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE VII. Output leakage current test.

Test condition	Parameter	Connect A to pin	Initial limits 25° ±5°C ambient Min	Initial limits 25° ±5°C ambient Max	Unit	Test figure
E1	1Y0 Output leakage current	7	0	1	mA	9
E2	1Y1 "	27	"	"	"	"
E3	1Y2 "	6	"	"	"	"
E4	1Y3 "	26	"	"	"	"
E5	1Y4 "	5	"	"	"	"
E6	1Y5 "	25	"	"	"	"
E7	1Y6 "	4	"	"	"	"
E8	1Y7 "	21	"	"	"	"
E9	2Y0 "	11	"	"	"	"
E10	2Y1 "	32	"	"	"	"
E11	2Y2 "	34	"	"	"	"
E12	2Y3 "	14	"	"	"	"
E13	2Y4 "	13	"	"	"	"
E14	2Y5 "	33	"	"	"	"
E15	2Y6 "	12	"	"	"	"
E16	2Y7 "	29	"	"	"	"
E17	3Y0 "	37	"	"	"	"
E18	3Y1 "	18	"	"	"	"
E19	3Y2 "	38	"	"	"	"
E20	3Y3 "	39	"	"	"	"
E21	3Y4 "	19	"	"	"	"
E22	3Y5 "	40	"	"	"	"
E23	3Y6 "	20	"	"	"	"
E24	3Y7 "	16	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



CAUTION

Do not isolate the chassis of ammeter X01 from earth ground.

NOTES:
1. R1 = 1 kΩ ±5%, 1/4 W.
2. Item P01-2 shall be current limited to 5.0 mA.


FIGURE 9. Output leakage current test circuit for table VII.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE VIII. Input clamp diode voltage test.

Test condition	Parameter	Connect A to pin	Initial limits 25° ±5°C ambient Min	Initial limits 25° ±5°C ambient Max	Unit	Test figure
F1	1G2 Input clamp diode voltage	22	-0.4	-1.5	V	10
F2	1G1 "	2	"	"	"	"
F3	1A "	24	"	"	"	"
F4	1B "	3	"	"	"	"
F5	1C "	23	"	"	"	"
F6	2G2 "	31	"	"	"	"
F7	2G1 "	30	"	"	"	"
F8	2A "	28	"	"	"	"
F9	2B "	8	"	"	"	"
F10	2C "	9	"	"	"	"
F11	3G2 "	17	"	"	"	"
F12	3A "	35	"	"	"	"
F13	3B "	15	"	"	"	"
F14	3C "	36	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTE. R1 = 750Ω ±1%, 1/4 W

* FIGURE 10. Input clamp diode voltage test circuit for table VIII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE IX. Output voltage (low-level) test.

Test condition	Parameter		Connect A to pin	Connect B to pin	Connect C to pin	Initial limits 25° ±5°C ambient Min	Initial limits 25° ±5°C ambient Max	Unit	Test figure
G1	1Y0	Output voltage, low level	2	22,24,23,3	7	0	400	mV	11
G2	1Y1	"	2,24	22,23,3	27	"	"	"	"
G3	1Y2	"	2,3	22,24,23	6	"	"	"	"
G4	1Y3	"	2,3,24	22,23	26	"	"	"	"
G5	1Y4	"	2,23	22,3,24	5	"	"	"	"
G6	1Y5	"	2,23,24	22,3	25	"	"	"	"
G7	1Y6	"	2,3,23	22,24	4	"	"	"	"
G8	1Y7	"	2,3,23,24	22	21	"	"	"	"
G9	2Y0	"	30	31,8,9,28	11	"	"	"	"
G10	2Y1	"	30,28	31,8,9	32	"	"	"	"
G11	2Y2	"	30,8	31,9,28	34	"	"	"	"
G12	2Y3	"	30,8,28	31,9	14	"	"	"	"
G13	2Y4	"	30,9	31,8,28	13	"	"	"	"
G14	2Y5	"	30,9,28	31,8	33	"	"	"	"
G15	2Y6	"	30,9,8	31,28	12	"	"	"	"
G16	2Y7	"	30,8,9,28	31	29	"	"	"	"
G17	3Y0	"	Open	17,15,35, 36	37	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE IX. Output voltage (low-level) test - Continued.

Test condition	Parameter		Connect			Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	Min	Max		
G18	3Y1	Output voltage, low level	35	17,15,36	18	0	400	mV	11
G19	3Y2	"	15	17,35,36	38	"	"	"	"
G20	3Y3	"	15,35	17,36	39	"	"	"	"
G21	3Y4	"	36	17,15,35	19	"	"	"	"
G22	3Y5	"	35,36	17,15	40	"	"	"	"
G23	3Y6	"	15,36	17,35	20	"	"	"	"
G24	3Y7	"	15,35,36	17	16	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2020-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE X. Output voltage (high-level) test.


Test condition	Parameter		Connect			Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	Min	Max		
H1	1YO	Output voltage, high level	22	Open	7	2.5	4.5	V	11
H2	1Y1	"	"	"	27	"	"	"	"
H3	1Y2	"	"	"	6	"	"	"	"
H4	1Y3	"	"	"	26	"	"	"	"
H5	1Y4	"	"	"	5	"	"	"	"
H6	1Y5	"	"	"	25	"	"	"	"
H7	1Y6	"	"	"	4	"	"	"	"
H8	1Y7	"	"	"	21	"	"	"	"
H9	2YO	"	31	"	11	"	"	"	"
H10	2Y1	"	"	"	32	"	"	"	"
H11	2Y2	"	"	"	34	"	"	"	"
H12	2Y3	"	"	"	14	"	"	"	"
H13	2Y4	"	"	"	13	"	"	"	"
H14	2Y5	"	"	"	33	"	"	"	"
H15	2Y6	"	"	"	12	"	"	"	"
H16	2Y7	"	"	"	29	"	"	"	"
H17	3YO	"	17	"	37	"	"	"	"
H18	3Y1	"	17	"	18	"	"	"	"

Source: https://assist.dla.mil - Downloaded: 2026-10-20 17:24Z
Check the source to verify that this is the current version before use.

TABLE X. Output voltage (high-level) test - Continued.

Test condition	Parameter	Connect			Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	Min	Max		
H19	3Y2 Output voltage, high level	17	Open	38	2.5	4.5	V	11
H20	3Y3 "	"	"	39	"	"	"	"
H21	3Y4 "	"	"	19	"	"	"	"
H22	3Y5 "	"	"	40	"	"	"	"
H23	3Y6 "	"	"	20	"	"	"	"
H24	3Y7 "	"	"	16	"	"	"	"


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTE: R1 = R2 = 51Ω ±5%, 1/2 W.

* FIGURE 11. Output voltage (low-level and high-level) test circuit for tables IX and X.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTES:
1. CR1 = 1N3600, 1N4150, or equivalent.
2. R1 = Select value for a current flow of 4.0 mA ±5% out of point L with point L held at 0.4 V.
3. R2 = 6.19 kΩ ±1%, 1/8 W.
4. Test type S:
   C_L = 50 ±5 pF (including probe and fixture capacitance).
   Test type Q:
   C_L = 150 ±5 pF (including probe and fixture capacitance) except for test conditions R and S where C_L = 50 ±5 pF (including probe and fixture capacitance).
5. Capacitor C_L is not required for dc electrical test conditions G1-G24 and H1-H24.

* FIGURE 12. AFA load circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XI. Input current (high-level) test.


Test condition	Parameter		Connect		Initial limits 25 ±5°C ambient		Unit	Test figure
			A to pin	B to pin	Min	Max		
J1	1G2	Input current, high level	22	2,3,8,9,15, 17,23,24,28, 30,31,35,36	0	40	µA	13
J2	1G1	"	2	3,8,9,15,17, 22,23,24,28, 30,31,35,36	"	20	"	"
J3	1A	"	24	2,3,8,9,15, 17,22,23,28, 30,31,35,36	"	"	"	"
J4	1B	"	3	2,8,9,15,17, 22,23,24,28, 30,31,35,36	"	"	"	"
J5	1C	"	23	2,3,8,9,15, 17,22,24,28, 30,31,35,36	"	"	"	"
J6	2G2	"	31	2,3,8,9,15, 17,22,23,24, 28,30,35,36	"	40	"	"
J7	2G1	"	30	2,3,8,9,15, 17,22,23,24, 28,31,35,36	"	20	"	"
J8	2A	"	28	2,3,8,9,15, 17,22,23,24, 30,31,35,36	"	20	"	"
J9	2B	"	8	2,3,9,15,17, 22,23,24,28, 30,31,35,36	"	20	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XI. Input current (high-level) test - Continued.

Test condition	Parameter		Connect		Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	Min	Max		
J10	2C	Input current, high level	9	2,3,8,15,17, 22,23,24,28, 30,31,35,36	0	20	µA	13
J11	3G2	"	17	2,3,8,9,15, 22,23,24,28, 30,31,35,36	"	40	"	"
J12	3A	"	35	2,3,8,9,15, 17,22,23,24, 28,30,31,36	"	20	"	"
J13	3B	"	15	2,3,8,9,17, 22,23,24,28, 30,31,35,36	"	20	"	"
J14	3C	"	36	2,3,8,9,15, 17,22,23,24, 28,30,31,35	"	20	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



CAUTION

Do not isolate the chassis of ammeter X01 from earth ground.


FIGURE 13 Input current (high-level) test circuit for table XI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XII. Input current (low-level) test.

Test condition	Parameter		Connect A to pin	Initial limits 25° ±5°C ambient Min	Initial limits 25° ±5°C ambient Max	Unit	Test figure
K1	1G2	Input current, low level	22	-0.01	-0.86	mA	14
K2	1G1	"	2	"	-0.43	"	"
K3	1A	"	24	"	"	"	"
K4	1B	"	3	"	"	"	"
K5	1C	"	23	"	"	"	"
K6	2G2	"	31	"	-0.86	"	"
K7	2G1	"	30	"	-0.43	"	"
K8	2A	"	28	"	"	"	"
K9	2B	"	8	"	"	"	"
K10	2C	"	9	"	"	"	"
K11	3G2	"	17	"	-0.86	"	"
K12	3A	"	35	"	-0.43	"	"
K13	3B	"	15	"	-0.43	"	"
K14	3C	"	36	"	-0.43	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



CAUTION

Do not isolate the chassis of ammeter X01 from earth ground.


FIGURE 14. Input current (low-level) test circuit for table XII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XIII. Power supply current test.

Test condition	Parameter	Connect A to pin	Initial limits 25° ±5°C ambient Min	Initial limits 25° ±5°C ambient Max	Unit	Test figure
L	Power supply current	17,22,31	0.1	30.0	mA	15

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



CAUTION

Do not isolate the chassis of ammeter X01 from earth ground.

FIGURE 15. Power supply current test circuit for table XIII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test.

Test condition	Parameter	Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	Min	Max		
M1	1Y0 Transition time (t_{TLH}), C_L = 50 pF	2	3,22,24	23	7	5	50	ns	16,17
M2	1Y1 "	2,24	3,22	"	27	"	"	"	"
M3	1Y2 "	2,3	22,24	"	6	"	"	"	"
M4	1Y3 "	2,3,24	22	"	26	"	"	"	"
M5	1Y4 "	2	3,22,24	"	5	"	"	"	"
M6	1Y5 "	2,24	3,22	"	25	"	"	"	"
M7	1Y6 "	2,3	22,24	"	4	"	"	"	"
M8	1Y7 "	2,3,24	22	"	21	"	"	"	"
M9	2Y0 "	30	8,28,31	9	11	"	"	"	"
M10	2Y1 "	28,30	8,31	"	32	"	"	"	"
M11	2Y2 "	8,30	28,31	"	34	"	"	"	"
M12	2Y3 "	8,28,30	31	"	14	"	"	"	"
M13	2Y4 "	30	8,28,31	"	13	"	"	"	"
M14	2Y5 "	28,30	8,31	"	33	"	"	"	"
M15	2Y6 "	8,30	28,31	"	12	"	"	"	"
M16	2Y7 "	8,28,30	31	"	29	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter	Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	Min	Max		
M17	3Y0 Transition time (t_{TLH}), C_L = 50 pF	Open	15,17,35	36	37	5	50	ns	16,17
M18	3Y1 "	35	15,17	"	18	"	"	"	"
M19	3Y2 "	15	17,35	"	38	"	"	"	"
M20	3Y3 "	15,35	17	"	39	"	"	"	"
M21	3Y4 "	Open	15,17,35	"	19	"	"	"	"
M22	3Y5 "	35	15,17	"	40	"	"	"	"
M23	3Y6 "	15	17,35	"	20	"	"	"	"
M24	3Y7 "	15,35	17	"	16	"	"	"	"
M25	1Y0 Transition time (t_{TLH}), C_L = 150 pF	2	3,22,24	23	7	10	80	"	"
M26	1Y1 "	2,24	3,22	"	27	"	"	"	"
M27	1Y2 "	2,3	22,24	"	6	"	"	"	"
M28	1Y3 "	2,3,24	22	"	26	"	"	"	"
M29	1Y4 "	2	3,22,24	"	5	"	"	"	"
M30	1Y5 "	2,24	3,22	"	25	"	"	"	"
M31	1Y6 "	2,3	22,24	"	4	"	"	"	"
M32	1Y7 "	2,3,24	22	"	21	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter	Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	Min	Max		
M33	2Y0 Transition time (t_{TLH}), C_L = 150 pF	30	8,28,31	9	11	10	80	ns	16,17
M34	2Y1 "	28,30	8,31	"	32	"	"	"	"
M35	2Y2 "	8,30	28,31	"	34	"	"	"	"
M36	2Y3 "	8,28,30	31	"	14	"	"	"	"
M37	2Y4 "	30	8,28,31	"	13	"	"	"	"
M38	2Y5 "	28,30	8,31	"	33	"	"	"	"
M39	2Y6 "	8,30	28,31	"	12	"	"	"	"
M40	2Y7 "	8,28,30	31	"	29	"	"	"	"
M41	3Y0 "	Open	15,17,35	36	37	"	"	"	"
M42	3Y1 "	35	15,17	"	18	"	"	"	"
M43	3Y2 "	15	17,35	"	38	"	"	"	"
M44	3Y3 "	15,35	17	"	39	"	"	"	"
M45	3Y4 "	Open	15,17,35	"	19	"	"	"	"
M46	3Y5 "	35	15,17	"	40	"	"	"	"
M47	3Y6 "	15	17,35	"	20	"	"	"	"
M48	3Y7 "	15,35	17	"	16	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter	Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	Min	Max		
N1	1Y0 Transition time (t_{THL}), C_L = 50 pF	2	3,22,24	23	7	3	18	ns	16,17
N2	1Y1 "	2,24	3,22	"	27	"	"	"	"
N3	1Y2 "	2,3	22,24	"	6	"	"	"	"
N4	1Y3 "	2,3,24	22	"	26	"	"	"	"
N5	1Y4 "	2	3,22,24	"	5	"	"	"	"
N6	1Y5 "	2,24	3,22	"	25	"	"	"	"
N7	1Y6 "	2,3	22,24	"	4	"	"	"	"
N8	1Y7 "	2,3,24	22	"	21	"	"	"	"
N9	2Y0 "	30	8,28,31	9	11	"	"	"	"
N10	2Y1 "	28,30	8,31	"	32	"	"	"	"
N11	2Y2 "	8,30	28,31	"	34	"	"	"	"
N12	2Y3 "	8,28,30	31	"	14	"	"	"	"
N13	2Y4 "	30	8,28,31	"	13	"	"	"	"
N14	2Y5 "	28,30	8,31	"	33	"	"	"	"
N15	2Y6 "	8,30	28,31	"	12	"	"	"	"
N16	2Y7 "	8,28,30	31	"	29	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition		Parameter	Connect				Initial limits .25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
N17	3Y0	Transition time (t_{THL}), C_L = 50 pF	Open	15,17,39	36	37	3	18	ns	16,17
N18	3Y1	"	35	15,17	"	18	"	"	"	"
N19	3Y2	"	15	17,35	"	38	"	"	"	"
N20	3Y3	"	15,35	17	"	39	"	"	"	"
N21	3Y4	"	Open	15,17,35	"	19	"	"	"	"
N22	3Y5	"	35	15,17	"	40	"	"	"	"
N23	3Y6	"	15	17,35	"	20	"	"	"	"
N24	3Y7	"	15,35	17	"	16	"	"	"	"
N25	1Y0	Transition time (t_{THL}), C_L = 150 pF	2	3,22,24	23	7	6	40	"	"
N26	1Y1	"	2,24	3,22	"	27	"	"	"	"
N27	1Y2	"	2,3	22,24	"	6	"	"	"	"
N28	1Y3	"	2,3,24	22	"	26	"	"	"	"
N29	1Y4	"	2	3,22,24	"	5	"	"	"	"
N30	1Y5	"	2,24	3,22	"	25	"	"	"	"
N31	1Y6	"	2,3	22,24	"	4	"	"	"	"
N32	1Y7	"	2,3,24	22	"	21	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter	Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	Min	Max		
N33	2Y0 Transition time (t_{THL}), C_L = 150 pF	30	8,28,31	9	11	6	40	ns	16,17
N34	2Y1 "	28,30	8,31	"	32	"	"	"	"
N35	2Y2 "	8,30	28,31	"	34	"	"	"	"
N36	2Y3 "	8,28,30	31	"	14	"	"	"	"
N37	2Y4 "	30	8,28,31	"	13	"	"	"	"
N38	2Y5 "	28,30	8,31	"	33	"	"	"	"
N39	2Y6 "	8,30	28,31	"	12	"	"	"	"
N40	2Y7 "	8,28,30	31	"	29	"	"	"	"
N41	3Y0 "	Open	15,17,35	36	37	"	"	"	"
N42	3Y1 "	35	15,17	"	18	"	"	"	"
N43	3Y2 "	15	17,35	"	38	"	"	"	"
N44	3Y3 "	15,35	17	"	39	"	"	"	"
N45	3Y4 "	Open	15,17,35	"	19	"	"	"	"
N46	3Y5 "	35	15,17	"	40	"	"	"	"
N47	3Y6 "	15	17,35	"	20	"	"	"	"
N48	3Y7 "	15,35	17	"	16	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P1	1G1-1Y0	Propagation delay time (t_{PLH}), C_L = 50 pF	Open	3,22,23,24	2	7	2	30	ns	16,17
P2	1G1-1Y1	"	24	3,22,23	"	27	"	"	"	"
P3	1G1-1Y2	"	3	22,23,24	"	6	"	"	"	"
P4	1G1-1Y3	"	3,24	22,23	"	26	"	"	"	"
P5	1G1-1Y4	"	23	3,22,24	"	5	"	"	"	"
P6	1G1-1Y5	"	23,24	3,22	"	25	"	"	"	"
P7	1G1-1Y6	"	3,23	22,24	"	4	"	"	"	"
P8	1G1-1Y7	"	3,23,24	22	"	21	"	"	"	"
P9	2G1-2Y0	"	Open	8,9,28,31	30	11	"	"	"	"
P10	2G1-2Y1	"	28	8,9,31	"	32	"	"	"	"
P11	2G1-2Y2	"	8	9,28,31	"	34	"	"	"	"
P12	2G1-2Y3	"	8,28	9,31	"	14	"	"	"	"
P13	2G1-2Y4	"	9	8,28,31	"	13	"	"	"	"
P14	2G1-2Y5	"	9,28	8,31	"	33	"	"	"	"
P15	2G1-2Y	"	9,8	28,31	"	12	"	"	"	"
P16	2G1-2Y7	"	8,9,28	31	"	29	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P17	1G1-1Y0	Propagation delay time (t_{PLH}), C_L = 150 pF	Open	3,22,23,24	2	7	5	40	ns	16,17
P18	1G1-1Y1	"	24	3,22,23	"	27	"	"	"	"
P19	1G1-1Y2	"	3	22,23,24	"	6	"	"	"	"
P20	1G1-1Y3	"	3,24	22,23	"	26	"	"	"	"
P21	1G1-1Y4	"	23	3,22,24	"	5	"	"	"	"
P22	1G1-1Y5	"	23,24	3,22	"	25	"	"	"	"
P23	1G1-1Y6	"	3,23	22,24	"	4	"	"	"	"
P24	1G1-1Y7	"	3,23,24	22	"	21	"	"	"	"
P25	2G1-2Y0	"	Open	8,9,28,31	30	11	"	"	"	"
P26	2G1-2Y1	"	28	8,9,31	"	32	"	"	"	"
P27	2G1-2Y2	"	8	9,28,31	"	34	"	"	"	"
P28	2G1-2Y3	"	8,28	9,31	"	14	"	"	"	"
P29	2G1-2Y4	"	9	8,28,31	"	13	"	"	"	"
P30	2G1-2Y5	"	9,28	8,31	"	33	"	"	"	"
P31	2G1-2Y6	"	8,9	28,31	"	12	"	"	"	"
P32	2G1-2Y7	"	8,9,28	31	"	29	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P33	1G2-1Y0	Propagation delay time (t_{PLH}), C_L = 50 pF	2	3,23,24	22	7	2	22	ns	16,17
P34	1G2-1Y1	"	2,24	3,23	"	27	"	"	"	"
P35	1G2-1Y2	"	2,3	23,24	"	6	"	"	"	"
P36	1G2-1Y3	"	2,3,24	23	"	26	"	"	"	"
P37	1G2-1Y4	"	2,23	3,24	"	5	"	"	"	"
P38	1G2-1Y5	"	2,23,24	3	"	25	"	"	"	"
P39	1G2-1Y6	"	2,3,23	24	"	4	"	"	"	"
P40	1G2-1Y7	"	2,3,23,24	Open	"	21	"	"	"	"
P41	2G2-2Y0	"	30	8,9,28	31	11	"	"	"	"
P42	2G2-2Y1	"	28,30	8,9	"	32	"	"	"	"
P43	2G2-2Y2	"	8,30	9,28	"	34	"	"	"	"
P44	2G2-2Y3	"	8,28,30	9	"	14	"	"	"	"
P45	2G2-2Y4	"	9,30	8,28	"	13	"	"	"	"
P46	2G2-2Y5	"	9,28,30	8	"	33	"	"	"	"
P47	2G2-2Y6	"	8,9,30	28	"	12	"	"	"	"
P48	2G2-2Y7	"	8,9,28,30	Open	"	29	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P49	3G2-3Y0	Propagation delay time (t_{PLH}), C_L = 50 pF	Open	15,35,36	17	37	2	22	ns	16,17
P50	3G2-3Y1	"	35	15,36	"	18	"	"	"	"
P51	3G2-3Y2	"	15	35,36	"	38	"	"	"	"
P52	3G2-3Y3	"	15,35	36	"	39	"	"	"	"
P53	3G2-3Y4	"	36	15,35	"	19	"	"	"	"
P54	3G2-3Y5	"	35,36	15	"	40	"	"	"	"
P55	3G2-3Y6	"	15,36	35	"	20	"	"	"	"
P56	3G2-3Y7	"	15,35,36	Open	"	16	"	"	"	"
P57	1G2-1Y0	Propagation delay time (t_{PLH}), C_L = 150 pF	2	3,23,24	22	7	4	32	"	"
P58	1G2-1Y1	"	2,24	3,23	"	27	"	"	"	"
P59	1G2-1Y2	"	2,3	23,24	"	6	"	"	"	"
P60	1G2-1Y3	"	2,3,24	23	"	26	"	"	"	"
P61	1G2-1Y4	"	2,23	3,24	"	5	"	"	"	"
P62	1G2-1Y5	"	2,23,24	3	"	25	"	"	"	"
P63	1G2-1Y6	"	2,3,23	24	"	4	"	"	"	"
P64	1G2-1Y7	"	2,3,23,24	Open	"	21	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P65	2G2-2Y0	Propagation delay time (t_{PLH}), C_L = 150 pF	30	8,9,28	31	11	4	32	ns	16,17
P66	2G2-2Y1	"	28,30	8,9	"	32	"	"	"	"
P67	2G2-2Y2	"	8,30	9,28	"	34	"	"	"	"
P68	2G2-2Y3	"	8,28,30	9	"	14	"	"	"	"
P69	2G2-2Y4	"	9,30	8,28	"	13	"	"	"	"
P70	2G2-2Y5	"	9,28,30	8	"	33	"	"	"	"
P71	2G2-2Y6	"	8,9,30	28	"	12	"	"	"	"
P72	2G2-2Y7	"	8,9,28,30	Open	"	29	"	"	"	"
P73	3G2-3Y0	"	Open	15,35,36	17	37	"	"	"	"
P74	3G2-3Y1	"	35	15,36	"	18	"	"	"	"
P75	3G2-3Y2	"	15	35,36	"	38	"	"	"	"
P76	3G2-3Y3	"	15,35	36	"	39	"	"	"	"
P77	3G2-3Y4	"	36	15,35	"	19	"	"	"	"
P78	3G2-3Y5	"	35,36	15	"	40	"	"	"	"
P79	3G2-3Y6	"	15,36	35	"	20	"	"	"	"
P80	3G2-3Y7	"	15,35,36	Open	"	16	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P81	1C-1Y0	Propagation delay time (t_{PLH}), C_L = 50 pF	2	3,22,24	23	7	2	24	ns	16,17
P82	1C-1Y1	"	2,24	3,22	"	27	"	"	"	"
P83	1C-1Y2	"	2,3	22,24	"	6	"	"	"	"
P84	1C-1Y3	"	2,3,24	22	"	26	"	"	"	"
P85	1C-1Y4	"	2	3,22,24	"	5	"	31	"	"
P86	1C-1Y5	"	2,24	3,22	"	25	"	"	"	"
P87	1C-1Y6	"	2,3	22,24	"	4	"	"	"	"
P88	1C-1Y7	"	2,3,24	22	"	21	"	"	"	"
P89	1B-1Y0	"	2	22,23,24	3	7	"	24	"	"
P90	1B-1Y1	"	2,24	22,23	"	27	"	"	"	"
P91	1B-1Y4	"	2,23	22,24	"	5	"	"	"	"
P92	1B-1Y5	"	2,23,24	22	"	25	"	"	"	"
P93	1B-1Y2	"	2	22,23,24	"	6	"	31	"	"
P94	1B-1Y3	"	2,24	22,23	"	26	"	"	"	"
P95	1B-1Y6	"	2,23	22,24	"	4	"	"	"	"
P96	1B-1Y7	"	2,23,24	22	"	21	"	"	"	"
P97	1A-1Y0	"	2	3,22,23	24	7	"	24	"	"
P98	1A-1Y2	"	2,3	22,23	24	6	"	24	"	"
P99	1A-1Y4	"	2,23	3,22	24	5	"	24	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P100	1A-1Y6	Propagation delay time (t_{PLH}), C_L = 50 pF	2,3,23	22	24	4	2	24	ns	16,17
P101	1A-1Y1	"	2	3,22,23	"	27	"	31	"	"
P102	1A-1Y3	"	2,3	22,23	"	26	"	"	"	"
P103	1A-1Y5	"	2,23	3,22	"	25	"	"	"	"
P104	1A-1Y7	"	2,3,23	22	"	21	"	"	"	"
P105	2C-2Y0	"	30	8,28,31	9	11	"	24	"	"
P106	2C-2Y1	"	28,30	8,31	"	32	"	"	"	"
P107	2C-2Y2	"	8,30	28,31	"	34	"	"	"	"
P108	2C-2Y3	"	8,28,30	31	"	14	"	"	"	"
P109	2C-2Y4	"	30	8,28,31	"	13	"	31	"	"
P110	2C-2Y5	"	28,30	8,31	"	33	"	"	"	"
P111	2C-2Y6	"	8,30	28,31	"	12	"	"	"	"
P112	2C-2Y7	"	8,28,30	21	"	29	"	"	"	"
P113	2B-2Y0	"	30	9,28,31	8	11	"	24	"	"
P114	2B-2Y1	"	28,30	9,31	"	32	"	"	"	"
P115	2B-2Y4	"	9,30	28,31	"	13	"	"	"	"
P116	2B-2Y5	"	9,28,30	31	"	33	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P117	2B-2Y2	Propagation delay time (t_{PLH}), C_L = 50 pF	30	9,28,31	8	34	2	31	ns	16,17
P118	2B-2Y3	"	28,30	9,31	"	14	"	"	"	"
P119	2B-2Y6	"	9,30	28,31	"	12	"	"	"	"
P120	2B-2Y7	"	9,28,30	31	"	29	"	"	"	"
P121	2A-2Y0	"	30	8,9,31	28	11	"	24	"	"
P122	2A-2Y2	"	8,30	9,31	"	34	"	"	"	"
P123	2A-2Y4	"	9,30	8,31	"	13	"	"	"	"
P124	2A-2Y6	"	8,9,30	31	"	12	"	"	"	"
P125	2A-2Y1	"	30	8,9,31	"	32	"	31	"	"
P126	2A-2Y3	"	8,30	9,31	"	14	"	"	"	"
P127	2A-2Y5	"	9,30	8,31	"	33	"	"	"	"
P128	2A-2Y7	"	8,9,30	31	"	29	"	"	"	"
P129	3C-2Y0	"	Open	15,17,35	36	37	"	24	"	"
P130	3C-3Y1	"	35	15,17	"	18	"	"	"	"
P131	3C-3Y2	"	15	17,35	"	38	"	"	"	"
P132	3C-3Y3	"	15,35	17	"	39	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P133	3C-3Y4	Propagation delay time (t_{PLH}), C_L = 50 pF	Open	15,17,35	36	19	2	31	ns	16,17
P134	3C-3Y5	"	35	15,17	"	40	"	"	"	"
P135	3C-3Y6	"	15	17,35	"	20	"	"	"	"
P136	3C-3Y7	"	15,35	17	"	16	"	"	"	"
P137	3B-3Y0	"	Open	17,35,36	15	37	"	24	"	"
P138	3B-3Y1	"	35	17,36	"	18	"	"	"	"
P139	3B-3Y4	"	36	17,35	"	19	"	"	"	"
P140	3B-3Y5	"	35,36	17	"	40	"	"	"	"
P141	3B-3Y2	"	Open	17,35,36	"	38	"	31	"	"
P142	3B-3Y3	"	35	17,36	"	39	"	"	"	"
P143	3B-3Y6	"	36	17,35	"	20	"	"	"	"
P144	3B-3Y7	"	35,36	17	"	16	"	"	"	"
P145	3A-3Y0	"	Open	15,17,36	35	37	"	24	"	"
P146	3A-3Y2	"	15	17,36	"	38	"	"	"	"
P147	3A-3Y4	"	36	15,17	"	19	"	"	"	"
P148	3A-3Y6	"	15,36	17	"	20	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P149	3A-3Y1	Propagation delay time (t_{PLH}), C_L = 50 pF	Open	15,17,36	35	18	2	31	ns	16,17
P150	3A-3Y3	"	15	17,36	"	39	"	"	"	"
P151	3A-3Y5	"	36	15,17	"	40	"	"	"	"
P152	3A-3Y7	"	15,36	17	"	16	"	"	"	"
P153	1C-1Y0	Propagation delay time (t_{PLH}), C_L = 150 pF	2	3,22,24	23	7	3	34	"	"
P154	1C-1Y1	"	2,24	3,22	"	27	"	"	"	"
P155	1C-1Y2	"	2,3	22,24	"	6	"	"	"	"
P156	1C-1Y3	"	2,3,24	22	"	26	"	"	"	"
P157	1C-1Y4	"	2	3,22,24	"	5	4	41	"	"
P158	1C-1Y5	"	2,24	3,22	"	25	"	"	"	"
P159	1C-1Y6	"	2,3	22,24	"	4	"	"	"	"
P160	1C-1Y7	"	2,3,24	22	"	21	"	"	"	"
P161	1B-1Y0	"	2	22,23,24	3	7	3	34	"	"
P162	1B-1Y1	"	2,24	22,23	"	27	"	"	"	"
P163	1B-1Y4	"	2,23	22,24	"	5	"	"	"	"
P164	1B-1Y5	"	2,23,24	22	"	25	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P165	1B-1Y2	Propagation delay time (t_{PLH}), C_L = 150 pF	2	22,23,24	3	6	4	41	ns	16,17
P166	1B-1Y3	"	2,24	22,23	"	26	"	"	"	"
P167	1B-1Y6	"	2,23	22,24	"	4	"	"	"	"
P168	1B-1Y7	"	2,23,24	22	"	21	"	"	"	"
P169	1A-1Y0	"	2	3,22,23	24	7	3	34	"	"
P170	1A-1Y2	"	2,3	22,23	"	6	"	"	"	"
P171	1A-1Y4	"	2,23	3,22	"	5	"	"	"	"
P172	1A-1Y6	"	2,3,23	22	"	4	"	"	"	"
P173	1A-1Y1	"	2	3,22,23	"	27	4	41	"	"
P174	1A-1Y3	"	2,3	22,23	"	26	"	"	"	"
P175	1A-1Y5	"	2,23	3,22	"	25	"	"	"	"
P176	1A-1Y7	"	2,3,23	22	"	21	"	"	"	"
P177	2C-2Y0	"	30	8,28,31	9	11	3	34	"	"
P178	2C-2Y1	"	28,30	8,31	"	32	"	"	"	"
P179	2C-2Y2	"	8,30	28,31	"	34	"	"	"	"
P180	2C-2Y3	"	8,28,30	31	"	14	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P181	2C-2Y4	Propagation delay time (t_{PLH}), C_L = 150 pF	30	8,28,31	9	13	4	41	ns	16,17
P182	2C-2Y5	"	28,30	8,31	"	33	"	"	"	"
P183	2C-2Y6	"	8,30	28,31	"	12	"	"	"	"
P184	2C-2Y7	"	8,28,30	31	"	29	"	"	"	"
P185	2B-2Y0	"	30	9,28,31	8	11	3	34	"	"
P186	2B-2Y1	"	28,30	9,31	"	32	"	"	"	"
P187	2B-2Y4	"	9,30	28,31	"	13	"	"	"	"
P188	2B-2Y5	"	9,28,30	31	"	33	"	"	"	"
P189	2B-2Y2	"	30	9,28,31	"	34	4	41	"	"
P190	2B-2Y3	"	28,30	9,31	"	14	"	"	"	"
P191	2B-2Y6	"	9,30	28,31	"	12	"	"	"	"
P192	2B-2Y7	"	9,28,30	31	"	29	"	"	"	"
P193	2A-2Y0	"	30	8,9,31	28	11	3	34	"	"
P194	2A-2Y2	"	8,30	9,31	"	34	"	"	"	"
P195	2A-2Y4	"	9,30	8,31	"	13	"	"	"	"
P196	2A-2Y6	"	8,9,30	31	"	12	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P197	2A-2Y1	Propagation delay time (t_{PLH}), C_L = 150 pF	30	8,9,31	28	32	4	41	ns	16,17
P198	2A-2Y3	"	8,30	9,31	"	14	"	"	"	"
P199	2A-2Y5	"	9,30	8,31	"	33	"	"	"	"
P200	2A-2Y7	"	8,9,30	31	"	29	"	"	"	"
P201	3C-3Y0	"	Open	15,17,35	36	37	3	34	"	"
P202	3C-3Y1	"	35	15,17	"	18	"	"	"	"
P203	3C-3Y2	"	15	17,35	"	38	"	"	"	"
P204	3C-3Y3	"	15,35	17	"	39	"	"	"	"
P205	3C-3Y4	"	Open	15,17,35	"	19	4	41	"	"
P206	3C-3Y5	"	35	15,17	"	40	"	"	"	"
P207	3C-3Y6	"	15	17,35	"	20	"	"	"	"
P208	3C-3Y7	"	15,35	17	"	16	"	"	"	"
P209	3B-3Y0	"	Open	17,35,36	15	37	3	34	"	"
P210	3B-3Y1	"	35	17,36	"	18	"	"	"	"
P211	3B-3Y4	"	36	17,35	"	19	"	"	"	"
P212	3B-3Y5	"	35,36	17	"	40	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
P213	3B-3Y2	Propagation delay time (t_{PLH}), C_L = 150 pF	Open	17,35,36	15	38	4	41	ns	16,17
P214	3B-3Y3	"	35	17,36	"	39	"	"	"	"
P215	3B-3Y6	"	36	17,35	"	20	"	"	"	"
P216	3B-3Y7	"	35,36	17	"	16	"	"	"	"
P217	3A-3Y0	"	Open	15,17,36	35	37	3	34	"	"
P218	3A-3Y2	"	15	17,36	"	38	"	"	"	"
P219	3A-3Y4	"	36	15,17	"	19	"	"	"	"
P220	3A-3Y6	"	15,36	17	"	20	"	"	"	"
P221	3A-3Y1	"	Open	15,17,36	"	18	4	41	"	"
P222	3A-3Y3	"	15	17,36	"	39	"	"	"	"
P223	3A-3Y5	"	36	15,17	"	40	"	"	"	"
P224	3A-3Y7	"	15,36	17	"	16	"	"	"	"
Q1	1G1-1Y0	Propagation delay time (t_{PHL}), C_L = 50 pF	Open	3,22,23,24	2	7	2	42	"	"
Q2	1G1-1Y1	"	24	3,22,23	"	27	"	"	"	"
Q3	1G1-1Y2	"	3	22,23,24	"	6	"	"	"	"
Q4	1G1-1Y3	"	3,24	22,23	"	26	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q5	1G1-1Y4	Propagation delay time (t_{PHL}), C_L = 50 pF	23	3,22,24	2	5	2	42	ns	16,17
Q6	1G1-1Y5	"	23,24	3,22	"	25	"	"	"	"
Q7	1G1-1Y6	"	3,23	22,24	"	4	"	"	"	"
Q8	1G1-1Y7	"	3,23,24	22	"	21	"	"	"	"
Q9	2G1-2Y0	"	Open	8,9,28,31	30	11	"	"	"	"
Q10	2G1-2Y1	"	28	8,9,31	"	32	"	"	"	"
Q11	2G1-2Y2	"	8	9,28,31	"	34	"	"	"	"
Q12	2G1-2Y3	"	8,28	9,31	"	14	"	"	"	"
Q13	2G1-2Y4	"	9	8,28,31	"	13	"	"	"	"
Q14	2G1-2Y5	"	9,28	8,31	"	33	"	"	"	"
Q15	2G1-2Y6	"	9,8	28,31	"	12	"	"	"	"
Q16	2G1-2Y7	"	8,9,28	31	"	29	"	"	"	"
Q17	1G1-1Y0	Propagation delay time (t_{PHL}), C_L = 150 pF	Open	3,22,23,24	2	7	5	52	"	"
Q18	1G1-1Y1	"	24	3,22,23	"	27	"	"	"	"
Q19	1G1-1Y2	"	3	22,23,24	"	6	"	"	"	"
Q20	1G1-1Y3	"	3,24	22,23	"	26	"	"	"	"
Q21	1G1-1Y4	"	23	3,22,24	"	5	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q22	1G1-1Y5	Propagation delay time (t_{PHL}), C_L = 150 pF	23,24	3,22	2	25	5	52	ns	16,17
Q23	1G1-1Y6	"	3,23	22,24	2	4	"	"	"	"
Q24	1G1-1Y7	"	3,23,24	22	2	21	"	"	"	"
Q25	2G1-2Y0	"	Open	8,9,28,31	30	11	"	"	"	"
Q26	2G1-2Y1	"	28	8,9,31	"	32	"	"	"	"
Q27	2G1-2Y2	"	8	9,28,31	"	34	"	"	"	"
Q28	2G1-2Y3	"	8,28	9,31	"	14	"	"	"	"
Q29	2G1-2Y4	"	9	8,28,31	"	13	"	"	"	"
Q30	2G1-2Y5	"	9,28	8,31	"	33	"	"	"	"
Q31	2G1-2Y6	"	8,9	28,31	"	12	"	"	"	"
Q32	2G1-2Y7	"	8,9,28	31	"	29	"	"	"	"
Q33	1G2-1Y0	Propagation delay time (t_{PHL}), C_L = 50 pF	2	3,23,24	22	7	2	36	"	"
Q34	1G2-1Y1	"	2,24	3,23	"	27	"	"	"	"
Q35	1G2-1Y2	"	2,3	23,24	"	6	"	"	"	"
Q36	1G2-1Y3	"	2,3,24	23	"	26	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q37	1G2-1Y4	Propagation delay time (t_{PHL}), C_L = 50 pF	2,23	3,24	22	5	2	36	ns	16,17
Q38	1G2-1Y5	"	2,23,24	3	"	25	"	"	"	"
Q39	1G2-1Y6	"	2,3,23	24	"	4	"	"	"	"
Q40	1G2-1Y7	"	2,3,23,24	Open	"	21	"	"	"	"
Q41	2G2-2Y0	"	30	8,9,28	31	11	"	"	"	"
Q42	2G2-2Y1	"	28,30	8,9	"	32	"	"	"	"
Q43	2G2-2Y2	"	8,30	9,28	"	34	"	"	"	"
Q44	2G2-2Y3	"	8,28,30	9	"	14	"	"	"	"
Q45	2G2-2Y4	"	9,30	8,28	"	13	"	"	"	"
Q46	2G2-2Y5	"	9,28,30	8	"	33	"	"	"	"
Q47	2G2-2Y6	"	8,9,30	28	"	12	"	"	"	"
Q48	2G2-2Y7	"	8,9,28,30	Open	"	29	"	"	"	"
Q49	3G2-3Y0	"	Open	15,35,36	17	37	"	"	"	"
Q50	3G2-3Y1	"	35	15,36	"	18	"	"	"	"
Q51	3G2-3Y2	"	15	35,36	"	38	"	"	"	"
Q52	3G2-3Y3	"	15,35	36	"	39	"	"	"	"
Q53	3G2-3Y4	"	36	15,35	"	19	"	"	"	"
Q54	3G2-3Y5	"	35,36	15	"	40	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q55	3G2-3Y6	Propagation delay time (t_{PHL}), C_L = 50 pF	15,36	35	17	20	2	36	ns	16,17
Q56	3G2-3Y7	Propagation delay time (t_{PHL}), C_L = 50 pF	15,35,36	Open	17	16	2	36	"	"
Q57	1G2-1Y0	Propagation delay time (t_{PHL}), C_L = 150 pF	2	3,23,24	22	7	5	46	"	"
Q58	1G2-1Y1	"	2,24	3,23	"	27	"	"	"	"
Q59	1G2-1Y2	"	2,3	23,24	"	6	"	"	"	"
Q60	1G2-1Y3	"	2,3,24	23	"	26	"	"	"	"
Q61	1G2-1Y4	"	2,23	3,24	"	5	"	"	"	"
Q62	1G2-1Y5	"	2,23,24	3	"	25	"	"	"	"
Q63	1G2-1Y6	"	2,3,23	24	"	4	"	"	"	"
Q64	1G2-1Y7	"	2,3,23,24	Open	"	21	"	"	"	"
Q65	2G2-2Y0	"	30	8,9,28	31	11	"	"	"	"
Q66	2G2-2Y1	"	28,30	8,9	"	32	"	"	"	"
Q67	2G2-2Y2	"	8,30	9,28	"	34	"	"	"	"
Q68	2G2-2Y3	"	8,28,30	9	"	14	"	"	"	"
Q69	2G2-2Y4	"	9,30	8,28	"	13	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q70	2G2-2Y5	Propagation delay time (t_{PHL}), C_L = 150 pF	9,28,30	8	31	33	5	46	ns	16,17
Q71	2G2-2Y6	"	8,9,30	28	31	12	"	"	"	"
Q72	2G2-2Y7	"	8,9,28,30	Open	31	29	"	"	"	"
Q73	3G2-3Y0	"	Open	15,35,36	17	37	"	"	"	"
Q74	3G2-3Y1	"	35	15,36	"	18	"	"	"	"
Q75	3G2-3Y2	"	15	35,36	"	38	"	"	"	"
Q76	3G2-3Y3	"	15,35	36	"	39	"	"	"	"
Q77	3G2-3Y4	"	36	15,35	"	19	"	"	"	"
Q78	3G2-3Y5	"	35,36	15	"	40	"	"	"	"
Q79	3G2-3Y6	"	15,36	35	"	20	"	"	"	"
Q80	3G2-3Y7	"	15,35,36	Open	"	16	"	"	"	"
Q81	1C-1Y0	Propagation delay time (t_{PHL}), C_L = 50 pF	2	3,22,24	23	7	2	45	"	"
Q82	1C-1Y1	"	2,24	3,22	"	27	"	"	"	"
Q83	1C-1Y2	"	2,3	22,24	"	6	"	"	"	"
Q84	1C-1Y3	"	2,3,24	22	"	26	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q85	1C-1Y4	Propagation delay time (t_{PHL}), C_L = 50 pF	2	3,22,24	23	5	2	43	ns	16,17
Q86	1C-1Y5	"	2,24	3,22	"	25	"	"	"	"
Q87	1C-1Y6	"	2,3	22,24	"	4	"	"	"	"
Q88	1C-1Y7	"	2,3,24	22	"	21	"	"	"	"
Q89	1B-1Y0	"	2	22,23,24	3	7	"	45	"	"
Q90	1B-1Y1	"	2,24	22,23	"	27	"	"	"	"
Q91	1B-1Y4	"	2,23	22,24	"	5	"	"	"	"
Q92	1B-1Y5	"	2,23,24	22	"	25	"	"	"	"
Q93	1B-1Y2	"	2	22,23,24	"	6	"	43	"	"
Q94	1B-1Y3	"	2,24	22,23	"	26	"	"	"	"
Q95	1B-1Y6	"	2,23	22,24	"	4	"	"	"	"
Q96	1B-1Y7	"	2,23,24	22	"	21	"	"	"	"
Q97	1A-1Y0	"	2	3,22,23	24	7	"	45	"	"
Q98	1A-1Y2	"	2,3	22,23	"	6	"	"	"	"
Q99	1A-1Y4	"	2,23	3,22	"	5	"	"	"	"
Q100	1A-1Y6	"	2,3,23	22	"	4	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	G to pin	B to pin	Min	Max		
Q101	1A-1Y1	Propagation delay time (t_{PHL}), C_L = 50 pF	2	3,22,23	24	27	2	43	ns	16,17
Q102	1A-1Y3	"	2,3	22,23	"	26	"	"	"	"
Q103	1A-1Y5	"	2,23	3,22	"	25	"	"	"	"
Q104	1A-1Y7	"	2,3,23	22	"	21	"	"	"	"
Q105	2C-2Y0	"	30	8,28,31	9	11	"	45	"	"
Q106	2C-2Y1	"	28,30	8,31	"	32	"	"	"	"
Q107	2C-2Y2	"	8,30	28,31	"	34	"	"	"	"
Q108	2C-2Y3	"	8,28,30	31	"	14	"	"	"	"
Q109	2C-2Y4	"	30	8,28,31	"	13	"	43	"	"
Q110	2C-2Y5	"	28,30	8,31	"	33	"	"	"	"
Q111	2C-2Y6	"	8,30	28,31	"	12	"	"	"	"
Q112	2C-2Y7	"	8,28,30	31	"	29	"	"	"	"
Q113	2B-2Y0	"	30	9,28,31	8	11	"	45	"	"
Q114	2B-2Y1	"	28,30	9,31	"	32	"	"	"	"
Q115	2B-2Y4	"	9,30	28,31	"	13	"	"	"	"
Q116	2B-2Y5	"	9,28,30	31	"	33	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q117	2B-2Y2	Propagation delay time (t_{PHL}), C_L = 50 pF	30	9,28,31	8	34	2	43	ns	16,17
Q118	2B-2Y3	"	28,30	9,31	"	14	"	"	"	"
Q119	2B-2Y6	"	9,30	28,31	"	12	"	"	"	"
Q120	2B-2Y7	"	9,28,30	31	"	29	"	"	"	"
Q121	2A-2Y0	"	30	8,9,31	28	11	"	45	"	"
Q122	2A-2Y2	"	8,30	9,31	"	34	"	"	"	"
Q123	2A-2Y4	"	9,30	8,31	"	13	"	"	"	"
Q124	2A-2Y6	"	8,9,30	31	"	12	"	"	"	"
Q125	2A-2Y1	"	30	8,9,31	"	32	"	43	"	"
Q126	2A-2Y3	"	8,30	9,31	"	14	"	"	"	"
Q127	2A-2Y5	"	9,30	8,31	"	33	"	"	"	"
Q128	2A-2Y7	"	8,9,30	31	"	29	"	"	"	"
Q129	3C-3Y0	"	Open	15,17,35	36	37	"	45	"	"
Q130	3C-3Y1	"	35	15,17	"	18	"	"	"	"
Q131	3C-3Y2	"	15	17,35	"	38	"	"	"	"
Q132	3C-3Y3	"	15,35	17	"	39	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q133	3C-3Y4	Propagation delay time (t_{PHL}), C_L = 50 pF	Open	15,17,35	36	19	2	43	ns	16,17
Q134	3C-3Y5	"	35	15,17	"	40	"	"	"	"
Q135	3C-3Y6	"	15	17,35	"	20	"	"	"	"
Q136	3C-3Y7	"	15,35	17	"	16	"	"	"	"
Q137	3B-3Y0	"	Open	17,35,36	15	37	"	45	"	"
Q138	3B-3Y1	"	35	17,36	"	18	"	"	"	"
Q139	3B-3Y4	"	36	17,35	"	19	"	"	"	"
Q140	3B-3Y5	"	35,36	17	"	40	"	"	"	"
Q141	3B-3Y2	"	Open	17,35,36	"	38	"	43	"	"
Q142	3B-3Y3	"	35	17,36	"	39	"	"	"	"
Q143	3B-3Y6	"	36	17,35	"	20	"	"	"	"
Q144	3B-3Y7	"	35,36	17	"	16	"	"	"	"
Q145	3A-3Y0	"	Open	15,17,36	35	37	"	45	"	"
Q146	3A-3Y2	"	15	17,36	"	38	"	"	"	"
Q147	3A-3Y4	"	36	15,17	"	19	"	"	"	"
Q148	3A-3Y6	"	15,36	17	"	20	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q149	3A-3Y1	Propagation delay time (t_{PHL}), C_L = 50 pF	Open	15,17,36	35	18	2	43	ns	16,17
Q150	3A-3Y3	"	15	17,36	"	39	"	"	"	"
Q151	3A-3Y5	"	36	15,17	"	40	"	"	"	"
Q152	3A-3Y7	"	15,36	17	"	16	"	"	"	"
Q153	1C-1Y0	Propagation delay time (t_{PHL}), C_L = 150 pF	2	3,22,24	23	7	5	55	"	"
Q154	1C-1Y1	"	2,24	3,22	"	27	"	"	"	"
Q155	1C-1Y2	"	2,3	22,24	"	6	"	"	"	"
Q156	1C-1Y3	"	2,3,24	22	"	26	"	"	"	"
Q157	1C-1Y4	"	2	3,22,24	"	5	"	53	"	"
Q158	1C-1Y5	"	2,24	3,22	"	25	"	"	"	"
Q159	1C-1Y6	"	2,3	22,24	"	4	"	"	"	"
Q160	1C-1Y7	"	2,3,24	22	"	21	"	"	"	"
Q161	1B-1Y0	"	2	22,23,24	3	7	"	55	"	"
Q162	1B-1Y1	"	2,24	22,23	"	27	"	"	"	"
Q163	1B-1Y4	"	2,23	22,24	"	5	"	"	"	"
Q164	1B-1Y5	"	2,23,24	22	"	25	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q165	1B-1Y2	Propagation delay time (t_{PHL}), C_L = 150 pF	2	22,23,24	3	6	5	53	ns	16,17
Q166	1B-1Y3	"	2,24	22,23	"	26	"	"	"	"
Q167	1B-1Y6	"	2,23	22,24	"	4	"	"	"	"
Q168	1B-1Y7	"	2,23,24	22	"	21	"	"	"	"
Q169	1A-1Y0	"	2	3,22,23	24	7	"	55	"	"
Q170	1A-1Y2	"	2,3	22,23	"	6	"	"	"	"
Q171	1A-1Y4	"	2,23	3,22	"	5	"	"	"	"
Q172	1A-1Y6	"	2,3,23	22	"	4	"	"	"	"
Q173	1A-1Y1	"	2	3,22,23	"	27	"	53	"	"
Q174	1A-1Y3	"	2,3	22,23	"	26	"	"	"	"
Q175	1A-1Y5	"	2,23	3,22	"	25	"	"	"	"
Q176	1A-1Y7	"	2,3,23	22	"	21	"	"	"	"
Q177	2C-2Y0	"	30	8,28,31	9	11	"	55	"	"
Q178	2C-2Y1	"	28,30	8,31	"	32	"	"	"	"
Q179	2C-2Y2	"	8,30	28,31	"	34	"	"	"	"
Q180	2C-2Y3	"	8,28,30	31	"	14	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q181	2C-2Y4	Propagation delay time (t_{PHL}), C_L = 150 pF	30	8,28,31	9	13	5	53	ns	16,17
Q182	2C-2Y5	"	28,30	8,31	"	33	"	"	"	"
Q183	2C-2Y6	"	8,30	28,31	"	12	"	"	"	"
Q184	2C-2Y7	"	8,28,30	31	"	29	"	"	"	"
Q185	2B-2Y0	"	30	9,28,31	8	11	"	55	"	"
Q186	2B-2Y1	"	28,30	9,31	"	32	"	"	"	"
Q187	2B-2Y4	"	9,30	28,31	"	13	"	"	"	"
Q188	2B-2Y5	"	9,28,30	31	"	33	"	"	"	"
Q189	2B-2Y2	"	30	9,28,31	"	34	"	53	"	"
Q190	2B-2Y3	"	28,30	9,31	"	14	"	"	"	"
Q191	2B-2Y6	"	9,30	28,31	"	12	"	"	"	"
Q192	2B-2Y7	"	9,28,30	31	"	29	"	"	"	"
Q193	2A-2Y0	"	30	8,9,31	28	11	"	55	"	"
Q194	2A-2Y2	"	8,30	9,31	"	34	"	"	"	"
Q195	2A-2Y4	"	9,30	8,31	"	13	"	"	"	"
Q196	2A-2Y6	"	8,9,30	31	"	12	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.


Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q197	2A-2Y1	Propagation delay time (t_{PHL}), C_L = 150 pF	30	8,9,31	28	32	5	53	ns	16,17
Q198	2A-2Y3	"	8,30	9,31	"	14	"	"	"	"
Q199	2A-2Y5	"	9,30	8,31	"	33	"	"	"	"
Q200	2A-2Y7	"	8,9,30	31	"	29	"	"	"	"
Q201	3C-3Y0	"	Open	15,17,35	36	37	"	55	"	"
Q202	3C-3Y1	"	35	15,17	"	18	"	"	"	"
Q203	3C-3Y2	"	15	17,35	"	38	"	"	"	"
Q204	3C-3Y3	"	15,35	17	"	39	"	"	"	"
Q205	3C-3Y4	"	Open	15,17,35	"	19	"	53	"	"
Q206	3C-3Y5	"	35	15,17	"	40	"	"	"	"
Q207	3C-3Y6	"	15	17,35	"	20	"	"	"	"
Q208	3C-3Y7	"	15,35	17	"	16	"	"	"	"
Q209	3B-3Y0	"	Open	17,35,36	15	37	"	55	"	"
Q210	3B-3Y1	"	35	17,36	"	18	"	"	"	"
Q211	3B-3Y4	"	36	17,35	"	19	"	"	"	"
Q212	3B-3Y5	"	35,36	17	"	40	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

*TABLE XIV. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
Q213	3B-3Y2	Propagation delay time (t_{PHL}), C_L = 150 pF	Open	17,35,36	15	38	5	53	ns	16,17
Q214	3B-3Y3	"	35	17,36	"	39	"	"	"	"
Q215	3B-3Y6	"	36	17,35	"	20	"	"	"	"
Q216	3B-3Y7	"	35,36	17	"	16	"	"	"	"
Q217	3A-3Y0	"	Open	15,17,36	35	37	"	55	"	"
Q218	3A-3Y2	"	15	17,36	"	38	"	"	"	"
Q219	3A-3Y4	"	36	15,17	"	19	"	"	"	"
Q220	3A-3Y6	"	15,36	17	"	20	"	"	"	"
Q221	3A-3Y1	"	Open	15,17,36	"	18	"	53	"	"
Q222	3A-3Y3	"	15	17,36	"	39	"	"	"	"
Q223	3A-3Y5	"	36	15,17	"	40	"	"	"	"
Q224	3A-3Y7	"	15,36	17	"	16	"	"	"	"


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTE: R1 = 51Ω ±5%, 1/2 W.

* FIGURE 16. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test circuit for table XIV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTES:
1. Input pulse parameters:
   PW = 500 ±50 ns.
   PRP = 1000 ±100 ns.
   $t_{TLHI} = t_{THLI}$ = 6 ±2 ns.
2. Before making the measurements, verify that the output pulse high level is ≥ 2.5 V and the low level is ≤ 0.4 V.
3. All voltages are referenced to ground.

* FIGURE 17. Transition time (t_{TLH} and t_{THL}) and propagation delay time (t_{PLH} and t_{PHL}) test circuit waveforms for table XIV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XV. Output crosstalk (low-level and high-level) test.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
R1	1Y0	Output crosstalk, low level	2,30,35	3,17,22, 23,24,31	8,9,15, 28,36	7	0	500	mV	18,19
R2	1Y1	"	2,24,28, 30	3,8,17,22, 23,31,36	9,15,35	27	"	"	"	"
R3	1Y2	"	2,3,30,35	17,22,23, 24,31	8,9,15, 28,36	6	"	"	"	"
R4	1Y3	"	2,3,24,28, 30	8,17,22, 23,31,36	9,15,35	26	"	"	"	"
R5	1Y4	"	2,23,30,35	3,17,22, 24,31	8,9,15,28, 36	5	"	"	"	"
R6	1Y5	"	2,23,24, 30,35	3,17,22,31	8,9,15,28, 36	25	"	"	"	"
R7	1Y6	"	2,3,23, 30,35	17,22,24, 31	8,9,15,28, 36	4	"	"	"	"
R8	1Y7	"	2,3,23, 24,28,30	8,17,22, 31,36	9,15,35	21	"	"	"	"
R9	2Y0	"	2,30,35	8,9,17, 22,23,24, 28,31	3,15,36	11	"	"	"	"
R10	2Y1	"	2,28,30,24	8,9,17, 22,23,31, 36	3,15,35	32	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XV. Output crosstalk (low-level and high-level) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
R11	2Y2	Output crosstalk, low level	2,8,30,24	9,17,22, 23,28,31,36	3,15,35	34	0	500	mV	18,19
R12	2Y3	"	2,8,28,30, 35	9,17,22, 23,24,31	3,15,36	14	"	"	"	"
R13	2Y4	"	2,9,30,35	8,17,22, 23,24,28, 31	3,15,36	13	"	"	"	"
R14	2Y5	"	2,9,24,28, 30	8,17,22,23, 31,36	3,15,35	33	"	"	"	"
R15	2Y6	"	2,8,9,30, 35	17,22,23, 24,28,31	3,15,36	12	"	"	"	"
R16	2Y7	"	2,8,9, 28,30,35	17,22,23, 24,31	3,15,36	29	"	"	"	"
R17	3Y0	"	2,8,24, 30	9,15,17,22, 23,31,35, 36	3,28	37	"	"	"	"
R18	3Y1	"	2,30,35	9,15,17, 22,23,24, 31,36	3,8,28	18	"	"	"	"
R19	3Y2	"	2,15,30	9,17,22, 23,24,31, 35,36	3,8,28	38	"	"	"	"
R20	3Y3	"	2,8,15,24, 30,35	9,17,22, 23,31,36	3,28	39	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE IV Output crosstalk (low level and high-level) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
R21	3Y4	Output crosstalk, low level	2,30,36	9,15,17, 22,23,24, 31,35	3,8,28	19	0	500	mV	18,19
R22	3Y5	"	2,8,24, 30,35,36	9,15,17, 22,23,31	3,28	40	"	"	"	"
R23	3Y6	"	2,15,30, 36	9,17,22, 23,24,31, 35	3,8,28	20	"	"	"	"
R24	3Y7	"	2,15,30, 35,36	9,17,22, 23,24,31	3,8,28	16	"	"	"	"
S1	1Y0	Output crosstalk, high level	22,30,35	2,17,31	8,9,15, 28,36	7	"	400	"	"
S2	1Y1	"	22,28,30	2,8,17, 31,36	9,15,35	27	"	"	"	"
S3	1Y2	"	22,30,35	2,17,31	8,9,15, 28,36	6	"	"	"	"
S4	1Y3	"	22,28,30	2,8,17, 31,36	9,15,35	26	"	"	"	"
S5	1Y4	"	22,30,35	2,17,31	8,9,15, 28,36	5	"	"	"	"
S6	1Y5	"	22,30,35	2,17,31	8,9,15, 28,36	25	"	"	"	"
S7	1Y6	"	22,30,35	2,17,31	8,9,15, 28,36	4	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XV. Output crosstalk (low-level and high-level) test - Continued.


Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
S8	1Y7	Output crosstalk, high level	22,28,30	2,8,17, 31,36	9,15,35	21	0	400	mV	18,19
S9	2Y0	"	2,31,35	17,22,23, 24,30	3,15,36	11	"	"	"	"
S10	2Y1	"	2,24,31	17,22,23, 30,36	3,15,35	32	"	"	"	"
S11	2Y2	"	2,24,31	17,22,23, 30,36	3,15,35	34	"	"	"	"
S12	2Y3	"	2,31,35	17,22,23, 24,30	3,15,36	14	"	"	"	"
S13	2Y4	"	2,31,35	17,22,23, 24,30	3,15,36	13	"	"	"	"
S14	2Y5	"	2,24,31	17,22,23, 30,36	3,15,35	33	"	"	"	"
S15	2Y6	"	2,31,35	17,22,23, 24,30	3,15,36	12	"	"	"	"
S16	2Y7	"	2,31,35	17,22,23, 24,30	3,15,36	29	"	"	"	"
S17	3Y0	"	2,8,17, 24,30	9,22,23, 31	3,28	37	"	"	"	"
S18	3Y1	"	2,17,30	9,22,23, 24,31	3,8,28	18	"	"	"	"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XV. Output crosstalk (low-level and high-level) test - Continued.

Test condition	Parameter		Connect				Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	C to pin	D to pin	Min	Max		
S19	3Y2	Output crosstalk, high level	2,17,30	9,22,23, 24,31	3,8,28	38	0	400	mV	18,19
S20	3Y3	"	2,8,17, 24,30	9,22,23, 31	3,28	39	"	"	"	"
S21	3Y4	"	2,17,30	9,22,23, 24,31	3,8,28	19	"	"	"	"
S22	3Y5	"	2,8,17, 24,30	9,22,23, 31	3,28	40	"	"	"	"
S23	3Y6	"	2,17,30	9,22,23, 24,31	3,8,28	20	"	"	"	"
S24	3Y7	"	2,8,17, 24,30	9,22,23, 31	3,28	16	"	"	"	"


Source: https://assist.dla.mil -- Downloaded: 2016-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTES:
1. R1 = R2 = 51Ω ±5%, 1/2 W.
2. Load all outputs per figure 12. C_L = 50 pF for table XV test.

FIGURE 18. Output crosstalk (low-level and high-level) test circuit for table XV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTE: Input pulse parameters:
$t_{THL} = t_{TLH} = 3.5 \pm 1.5$ ns (verified at all input pins).
PW = 500 ±50 ns.
PRP = 1000 ±100 ns.

FIGURE 19. Output crosstalk (low-level and high-level) test circuit waveforms for table XV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XVI. Power supply transient amplitude test.

Test condition	Parameter	Initial limits 25° ±5°C ambient		Unit	Test figure
		Min	Max		
T	Power supply transient amplitude	0	400	mV	20,21

TABLF XVII. Power supply filter capacitance test.


Test condition	Parameter	Connect		Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	Min	Max		
U	Power supply filter capacitance	Open	1	1.6	3.0	µF	22

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XVIII. Input capacitance test.

Test condition	Parameter		Connect		Initial limits 25° ±5°C ambient		Unit	Test figure
			A to pin	B to pin	Min	Max		
V1	1G2	Input capacitance	22	Open	5	30	pF	22
V2	1G1	"	2	"	"	15	"	"
V3	1A	"	24	"	"	"	"	"
V4	1B	"	3	"	"	"	"	"
V5	1C	"	23	"	"	"	"	"
V6	2G2	"	31	"	"	30	"	"
V7	2G1	"	30	"	"	15	"	"
V8	2A	"	28	"	"	"	"	"
V9	2B	"	8	"	"	"	"	"
V10	2C	"	9	"	"	"	"	"
V11	3G2	"	17	"	"	30	"	"
V12	3A	"	35	"	"	15	"	"
V13	3B	"	15	"	"	15	"	"
V14	3C	"	36	"	"	15	"	"


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTE R1 = 51Ω ±5%, 1/2 W.

FIGURE 20. Power supply transient amplitude test circuit for table XVI.


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTE: Input parameters:
$t_{THL} = t_{TLH} = 3.5 \pm 1.5$ ns (verified at each input pin).
PW = 500 ±50 ns.
PRP = 1000 ±100 ns.

FIGURE 21. Power supply transient amplitude test circuit waveforms for table XVI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTES:
1. Null out the effects of the test leads prior to connecting the module.
2. Do not attach test connector or wires to any of the module pins other than pin 10 and the pin under test. Stray capacitance added to other pins may affect the readings.
3. Item C01 setup:
   Frequency = 120 Hz.
   V_{pk} = 0.3 V maximum.

FIGURE 22 Power supply filter and input capacitance test circuit for tables XVII and XVIII

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XIX. Functional test.

Test condition	Parameter	Connect			Output logic states 1/																							Test figure
		A to pin	B to pin	C to pin	1Y0	1Y1	1Y2	1Y3	1Y4	1Y5	1Y6	1Y7	2Y0	2Y1	2Y2	2Y3	2Y4	2Y5	2Y6	2Y7	3Y0	3Y1	3Y2	3Y3	3Y4	3Y5	3Y6	3Y7	
W1	Functional	2,17,31	3,22,23,24	2/ 3/	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	23
W2	"	2,17,24,31	3,22,23	"	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W3	"	2,3,17,31	22,23,24	"	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W4	"	2,3,17,24,31	22,23	"	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W5	"	2,17,23,31	3,22,24	"	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W6	"	2,17,23,24,31	3,22	"	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W7	"	2,3,17,23,31	22,24	"	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W8	"	2,3,17,23,24,31	22	"	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W9	"	17,22,30	8,9,28,31	"	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W10	"	17,22,28,30	8,9,31	"	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W11	"	8,17,22,30	9,28,31	"	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W12	"	8,17,22,28,30	9,31	"	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	H	"
W13	"	9,17,22,30	8,28,31	"	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	H	"
W14	"	9,17,22,28,30	8,31	"	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	H	"
W15		8,9,17,22,28,31			H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	H	"
W16		9,17,22,28,31		"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	H	"
W17		2,3	15,17,30	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	H	"
W18		17,31,35	15,17,	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	H	"
W19		2,3,15	15,	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	H	"
W20		22,31	15,36	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	H	"

1/ See footnote

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XIX Functional test - Continued

Test condition	Parameter	Connect			Output logic states 1/																								Test figure
		A to pin	B to pin	C to pin	1Y0	1Y1	1Y2	1Y3	1Y4	1Y5	1Y6	1Y7	2Y0	2Y1	2Y2	2Y3	2Y4	2Y5	2Y6	2Y7	3Y0	3Y1	3Y2	3Y3	3Y4	3Y5	3Y6	3Y7	
W21	Functional	22,31,36	5,17,35	2/ 3/	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	H	23
W22	"	22,31,35, 36	15,17	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	H	"
W23	"	15,22,31, 36	17,35	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	H	"
W24	"	15,22,31, 35,36	17	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	"
W25	"	2,17,22, 30,31	3,8,9,15, 23 24,28, 35,36	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W26	"	2,17,22, 24,28,30, 31,35	3,8,9,15, 23,36	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W27	"	2,3,8,15, 17,22,30, 31	9,23,24, 28,35,36	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W28	"	2,3,8,15, 17,22,24, 28,30,31, 35	9,23,36	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W29	"	2,9,17,22, 23,30,31, 36	3,8,15,24, 28,35	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W30	"	2,9,17,22, 23,24,28, 30,31,35, 36	3,8,15	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W31	"	2,3,8,9, 15,17,22, 23,30,31, 36	24,28,35	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W32	"	2,3,8,9, 15,17,22, 23,24,28, 30,31,35, 36	Open	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W33	"	15,17,35, 36	2,3,8,9, 22,23,24, 28,30,31	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

TABLE XIX. Functional test - Continued.

Test condition	Parameter	Connect			Output logic states 1/																								Test figure
		A to pin	B to pin	C to pin	1Y0	1Y1	1Y2	1Y3	1Y4	1Y5	1Y6	1Y7	2Y0	2Y1	2Y2	2Y3	2Y4	2Y5	2Y6	2Y7	3Y0	3Y1	3Y2	3Y3	3Y4	3Y5	3Y6	3Y7	
W34	Functional	15,17,24, 28,35,36	2,3,8,9, 22,23,30, 31	2/ 3/	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	23
W35	"	3,8,15,17, 35,36	2,9,22,23, 24,28,30, 31	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W36	"	3,8,15,17, 24,28,35, 36	2,9,22,23, 30,31	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W37	"	9,15,17, 23,35,36	2,3,8,22, 24,28,30, 31	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W38	"	9,15,17, 23,24,28, 35,36	2,3,8,22, 30,31	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W39	"	3,8,9,15, 17,23,35, 36	2,22,24, 28,30,31	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"
W40	"	3,8,9,15, 17,23,24, 28,35,36	2,22,30, 31	"	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	"


1/ Output logic states

L = low level = 0.0 V to 0.5 V.
H = High level = 2.5 V to 4.5 V.

2/ For test conditions W1-W40, verification of the output logic states in footnote 1 is obtained by connecting item M02, point C, to each output pin in succession after input conditions have been accomplished.

3/ 1Y0-1Y7, 2Y0-2Y7, and 3Y0-3Y7 output logic states are measured at output pins 7, 27, 6, 26, 5, 25, 4, 21, 11, 32, 34, 14, 13, 33, 12, 29, 37, 18, 38, 39, 19, 40, 20, and 16, respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.



NOTE R1 = R2 = 51Ω ±5%, 1/2 W.

* FIGURE 23 Functional test circuit for table XIX.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, wa too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STAT

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commander
Naval Electronic Systems Command (ELEX 8111)
Washington, DC 20360

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*:
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426

Source: https://assist.dla.mil – Downloaded: 2026-10-20T17:24Z
Check the source to verify that this is the current version before use.