INCH-POUND
A-A-59824
23 Feb 2009

COMMERCIAL ITEM DESCRIPTION

TEST SET, SPRAY PATTERN

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE

1.1 Scope. This commercial item description (CID) describes a Fuel Spray Pattern Test Set which hereafter will be referred to as the test set. The test set is capable of measuring the spray pattern angle and check for external leakage of a fuel atomizer assembly applicable to the A/M32A gas turbine engines. This CID describes the minimum provisions for ISO 9001 certified manufacturers that meet or exceed these requirements.

2. SALIENT CHARACTERISTICS

2.1 General. The equipment shall be capable of operation within the accuracies, limits, and specifications herein. Equipment covered by this CID shall be commercially available equipment and may be modified to the extent necessary to meet the following description.

2.2 Order of precedence. In the event of a conflict between the text of this CID and the references cited herein (except for associated detail specifications, specification sheets or MS standards) the text of this CID shall take precedence. Nothing in this CID, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

2.3 Physical characteristics. Overall Dimensions:

Height	24 to 52 Inches
Length	24 to 56 Inches
Width	16 to 28 Inches
Weight	Not to exceed 275 LBS

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: WR-ALC 542 CSW/CBSSS, 295 Byron Street, Robins AFB, GA 31098-1611.

AMSC N/A FSC 4920

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

2.4 Electrical Characteristics. Test set shall operate at power requirements of 220 VAC; 60 cycles per second.

2.5 Fluid pressure gauges. The fluid pressure gauges shall have an accuracy of +/- .25% with a range of 0 to 400 psig. The gauges shall also be no less than four and a half (4 ½) inches to no more than six (6) inches in diameter.

2.6 Test Fluid Requirements. The test set shall be in accordance with the MIL-PRF-7024 test fluid specification with approximately eight (8) to ten (10) gallons. MIL-PRF-7024 test fluid shall be used in lieu of JP-8 during testing.

2.7 Safety. The test set shall be classified for use in hazardous work areas.

2.8 Marking. Test sets supplied to this CID shall be affixed with the manufacturer's standard commercial part number.

2.9 Illumination. A lighting fixture, which is switched on either with a separate switch or with the supply pump, shall have enough illumination inside of the spray chamber to aide in the observation of the spray quality while not shining directly into the operator's eyes.

2.10 Semi-circular protractor. A protractor, to indicate the angle of the spray pattern, shall be fixed inside the spray chamber. Increments shall not be less than one (1) degree and not more than five (5) degrees.

2.11 Calibration. The test set shall have a calibration interval of at least 180 days.

2.11.1 Calibration procedure. The test set shall provide for readily accessible calibration adjustments and maintenance adjustments. The manufacturer shall provide a calibration procedure so that minor repairs and calibration can be performed at the field level.

2.12 Manuals. Each test set shall be delivered with each unit, which is to include operator's maintenance, basic operation instructions, and calibration procedures that have been approved by WR-ALC. The manufacturer shall also provide a list of all available options, as well as ordering information.

3. REGULATORY REQUIREMENTS

3.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or refurbished items shall not be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

4. PRODUCT CONFORMANCE PROVISIONS.

4.1 Product conformance. The test set provided shall meet the salient characteristics of this CID, conform to the manufacturer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

5. PACKAGING

5.1 Packaging. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents.

6.1.1 Department of Defense and Federal documents may be obtained at http://assist.daps.dla.mil or from the Document Automation and Production Service, Bldg 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia PA 19111-5094.

6.1.2 The Code of Federal Regulations (CFR) may be obtained at http://www.gpoaccess.gov/cfr/ or from the Superintendent of Documents, U.S. Government Printing Office, Washington DC 20402.

6.2 Submitted products. The test sets submitted for sample testing shall be a representative of the commercial off the shelf product. All features, performance, and environmental protection of the product tested shall be provided under any resulting contract or order.

6.3 Ordering data. The contract or order should specify the following: CID title and document number, product conformance provisions, and packaging requirements.

6.4 Commercial products. At the time of this CID preparation and coordination, the manufacturer listed was known to have commercial products that would meet the requirements of this CID. All other manufacturers must meet the requirements of this CID and submit testing and certification as required. (NOTE: This information should not be considered as a list of only approved manufacturers or be used to restrict procurement to only the manufacturers shown below.)

Company	Location	CAGE	POC	POC Phone	Mfr. Model/Part No.
Bauer Inc. http://www.bauerct.com	175 Century Dr. Bristol, CT 06010-7482	70882	Andrew Parfitt	1-860-583-9100 ext. 183	1019003

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

6.5 Key Words.

External Leakage
Fuel Atomizer
Measure of Angle

Custodian:
Air Force - 84

Reviewer:
Air Force - 99

Preparing activity:
Air Force - 84

Agent:
Air Force – 99

Project 4920-2009-001

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.