INCH-POUND
A-A-59829A
25 JUNE 2014
SUPERSEDING
A-A-59829
29 JULY 2009

COMMERCIAL ITEM DESCRIPTION

TRUCK, LIFT, FORK, ELECTRIC, SIT DOWN, SOLID TIRES, 12000 POUND CAPACITY AT 24 INCH LOAD CENTER, 184 INCHES MINIMUM LIFT HEIGHT

The General Services Administration has authorized the use of this Commercial Item Description (CID) for all federal agencies.

1. SCOPE

1.1 Scope. This Commercial Item Description (CID) covers the general requirements for an electric, front wheel drive, rear wheel steer, sit down operator, solid tired, 12,000 pound at 24 inch load center capacity, Forklift Truck. The forklift is intended for handling cargo in and around warehouses, loading platforms, docks, and on paved or other hard surfaces.

2. SALIENT CHARACTERISTICS

2.1 Safety. The forklift shall conform to ANSI/ITSDF B56.1, UL 583, and OSHA standards in effect at the time of manufacture. Unless otherwise specified in the contract (see 6.3), the forklift shall have an electrical class rating Type EE in accordance with UL 583. A commercial fire extinguisher shall be mounted on the truck in an easily accessible location. The fire extinguisher shall be at the very minimum, a 2 ½ pound capacity ABC type or equivalent UL listed type. An operator's seatbelt conforming to SAE J386 in conjunction with restraint devices designed to ensure the operator's upper body remains entirely within the protection of the overhead guard in the event of tip-over shall be provided. Unless otherwise specified in the contract (see 6.3), the final color of the forklift truck shall be the manufacturer's standard commercial color for safe operation in an indoor environment.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: WR-ALC [AFMC AFLCMC/WNZ], 235 Byron Street, Suite 19A, Robins AFB GA 31098-1813. Since contact information can change, you may want to verify the currency of this address information using the ASSIST database at https://assist.dla.mil.

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

2.2 Environmental requirements. The forklift truck shall be capable of operating in temperatures ranging from 0 degrees F to +125 degrees F.

2.3 Battery. The battery shall be a commercially available 48, 72 or 80 volt battery with 1600 amp hours. The battery-mounted, half connector shall be equipped with "SB" type locking half connectors. When specified (see 6.3), an additional battery and/or the appropriate battery charger shall be shipped with the forklift truck.

2.4 Hydraulic system(s). A pressure relief protection device shall be required along with pump(s), cylinders, control valves, filter(s), reservoir, hoses, and all other applicable components necessary to make a complete hydraulic system. The hydraulic system shall also be designed to prevent forward tilt in the event of system failure; tilt angle shall not deviate more than two degrees if failure occurs at any position during load handling operations. The hydraulic lift system shall be designed so that in the event of hydraulic hose or pump failure, the load shall not descend (freefall) at an uncontrolled rate; lowering speed shall not exceed eight (8) inches per second under any load condition. A manual override for the tilt function shall also be provided to allow for load removal.

2.5 Uprights and carriage. With no load on the forks, the seated operator with seatbelt engaged shall be able to see at least one fork tip at all lift heights and fork positions.

2.6 Forks and carriage. Fork tines shall have the standard dimensions shown in Table I. The forks shall be mounted so that when fully lowered and forklift operating in reverse, there is no damage or degradation to the fork tines, their attachment, or any other component of the carriage, including fork positioner and side shift. When specified (see 6.3), optional forks shall be furnished.

TABLE 1. Fork tine dimensions

Dimension	Standard Forks	Optional Forks
Length	48 ± 1 inches	72 ± 1 inches
Width	6 inches (maximum)	6 inches (maximum)
Thickness	2.5 inches maximum	2.5 inches (maximum)

2.7 Fork Positioner. A hydraulically powered fork positioner shall be furnished that is controlled by the operator while seated. The fork positioner shall allow tine spacing of 18 inches (or less) to 60 inches (or more), measured between centerlines of the forks.

2.8 Side shift. A hydraulically powered fork side shift capability shall be furnished. It shall be controlled by the seated operator, and shall provide at least six inch side shift capability each side of center (or 12.0 inches minimum total travel) with rated load on the forks.

2.9 Load backrest. The load backrest, in conjunction with the forks and carriage, shall provide a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

vertical rear load guard of at least 48 inches high, measured from the load carrying surfaces of the forks.

2.10 Steering. Power steering, with emergency steering in the event of power failure, shall be furnished.

2.11 Service Brakes. Power brakes conforming to ANSI/ITSDF B56.1 shall be furnished.

2.12 Parking brake. Parking brakes conforming to ANSI/ITSDF B56.1 shall be furnished.

2.13 Electrical system. A 48, 72, or 80 volt direct current (VDC) electrical system shall be furnished. The electrical system shall consist of all electrical components necessary for operation of the forklift. The forklift shall have sufficient electrical grounding to prevent static discharge.

2.14 Instruments and controls. In addition to the instruments supplied on the standard commercial forklift, an hour meter shall be installed in the instrument panel. All instruments shall illuminate, except the hour meter. All load motion controls shall be right hand operation controls and of the self-centering type, specifically, the controls shall return to the neutral position when released.

2.15 Lighting. Minimum two sealed beam floodlights, one facing forward and one facing rearward shall be furnished. Tail light(s) and brake stop light(s) shall be installed. All lights shall be protected by location or guards. Individual operator controlled switches shall be provided for front floodlight, and rear floodlight.

2.16 Horn. Horn button shall be located in the center of the steering wheel.

2.17 Operator's overhead guard. The overhead guard shall be a falling-object-protective-structure (FOPS) conforming to ANSI/ITSDF B56.1. The overhead guard height from ground to top of guard shall be 102 inches maximum.

2.18 Cab. When specified (see 6.3), the forklift, shall be equipped with an enclosed cab that shall incorporate FOPS requirements of ANSI/ITSDF B56.1. The cab shall have a door on each side of the vehicle with at least one window per door which can be opened for ventilation. The doors shall be capable of being locked in either the open or closed positions. In addition to the door windows, the cab shall be furnished with a front windshield, rear window, and roof window. The windshield and all windows shall be safety glass. The cab interior shall be furnished with water-resistant non-absorbent thermal insulation. A commercial fire extinguisher shall be mounted on the truck in an easily accessible location. The fire extinguisher shall be a minimum 2-1/2 pound capacity ABC type, or equivalent. The fire extinguisher shall be UL listed. The manufacturer's heaviest duty heater and defroster shall be furnished. There shall be at least two wipers furnished, one on the front windshield and one on the rear window.

2.19 Tires. Tire loading shall not exceed those specified in the Tire and Rim Association (TRA) Yearbook.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

2.20 Performance.

a. Capability to safely handle a 12,000 pound, 48 inch per side cube with the center of gravity at the center of the cube. It shall be able to handle this load at all lift heights that the forklift is capable of attaining.
b. Lifting speed. At least 7.0 inches per second with rated load on the forks.
c. Lowering speed. Not more than 18 inches per second with rated load on the forks. Not less than 6 inches per second with no load and with engine at idle speed.
d. Right angle turn. With rated load on the forks, forklift positioned perpendicular to a wall, and with the front of the load against the wall, the truck shall be able to back up and make a complete right angle turn (ending up parallel to the wall) within 200 inches.
e. Travel speed. While carrying the rated load on the forks, the travel speed shall be 7 miles per hour (mph) minimum (not to exceed 15 mph), in both forward and reverse. The vehicle speed shall be governed so that the maximum speed for safe operations is not exceeded.
f. Slope ascension. With the truck facing up the slope and with rated load on the forks, the truck shall be able to accelerate up a 15% (8.5 degree) slope from a dead stop.
g. Upright tilt. With no load on the truck, the forks shall have at least 5.0 degrees of forward tilt, and at least 8.0 degrees of rear tilt.
h. Upright height (collapsed mast height) and Maximum fork lift height. With no load on the forks and the forks on the ground, the maximum upright height shall be 92 inches. The maximum fork “lift height” shall be at least 184 inches with rated load on the forks and the forks horizontal.
i. Ground clearance. With rated load on the forks and mast vertical, ground clearance beneath the mast shall be at least 4.0 inches. With no load on the forks, the ground clearance of the truck other than the mast and axles shall be at least 5.0 inches.
j. Load drift. With hydraulic fluid at normal operating temperature, the lift assembly shall hold rated load at maximum lift height for at least 10.0 minutes with not more than 1-¾ inch of vertical drift, and not more than 1.0 degree of rotational drift.
k. Stability. The forklift shall meet the ANSI/ITSDF B56.1 "forward stacking", "forward travel", "lateral stacking", and "lateral travel" stability requirements.
l. Noise limits. Maximum allowable noise level shall not exceed 84dB(A) at the operator's ear. If the noise level at the operator's ear exceeds 84 dB(A) (85 to 92 dB(A)), a permanent warning decal or placard shall be installed inside the cab clearly visible to the operator. Noise level limits that exceed 92dB(A) are not acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

2.21 Painting. The forklift shall be primed and painted using standard commercial practices. The final paint shall be a standard, commercially available polyurethane. The paint finish shall show no evidence of uneven application, curtains, runs snags, orange peel, lack of adhesion, or other defects. The color shall be the manufacturer's standard color. When specified (see 6.3), the manufacturer shall make color 24502 of FED-STD-595 available. If any components on the truck are not painted, the components shall have a commercially available, protective coating (such as zinc plating).

2.22 Identification plates. Corrosion resistant identification plate shall be provided and mounted on the vehicle. The identification plate shall contain the following information:

- Nomenclature:
- Make and Model:
- Manufacturers Serial Number (VIN):
- Registration Number:
- National Stock Number (NSN):
- Vehicle Curb Weight (lbs):
- Payload, Maximum (lbs):
- Gross Weight, Maximum (lbs):
- Date of Delivery:
- Warranty (months/miles):
- Contract Number:
- Ship to _____ Mark for _____
- U S Property

2.23 Walkway coating. Floor plates and step surfaces shall be coated with a nonslip coating compound, or be furnished with a nonslip metal or Tread Plate surface.

2.24 Lifting and tiedown provisions. There shall be permanently installed lifting devices that enable the forklift to be lifted in its normal travel configuration, and tiedown devices that enable the forklift to be tied down to the floor of the transportation media. All devices shall have an inside diameter of 3.0 inches and minimum structural safety factor of 2:1, based on static load. The notation "LIFT HERE" and "TIEDOWN" shall be stenciled, in black, near each lifting and tiedown device.

2.25 Electromagnetic interference (EMI) suppression. The forklift shall comply with the EMI requirements shown in Table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

Table II. Electromagnetic Interference (EMI)

Name	Description	Parameters
SAE J551/1	Compatibility	N/A
CISPR 12 & CISPR 25	Emissions	(Frequency Range: 30 to 1000 MHz)
MIL-STD-461, RS-103	Susceptibility	(Frequency Range: 100 kHz to 18 GHz) 20 V/m (100 kHz to 200 MHz) 50 V/m (above 200 MHz)

2.26 Highway transportability. The forklift truck, when loaded on a semitrailer, shall be within the highway permit limits for all states.

2.27 Backup alarm. An audible backup alarm shall be furnished. The alarm shall automatically activate when the transmission selector is placed in reverse.

2.28 Flashing light. When specified (see 6.3), a flashing or strobe light shall be installed on the vehicle. The light shall not increase the overall height of the vehicle.

2.29 Workmanship. The truck shall withstand any operation specified herein without permanent deformation, breakage of connections, malfunction, or component interference caused by incorrect workmanship. Riveted and bolted connections shall be adequately designed. Welding shall be performed by a certified welder.

3. REGULATORY REQUIREMENTS

3.1 The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated in the forklift.

4. PRODUCT CONFORMANCE PROVISIONS

4.1 Product Conformance. The forklift truck provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same forklift truck offered for sale in the commercial market. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5. PACKAGING

5.1 Packaging. Preservation, packing, and marking shall be as specified in the contract. Unless otherwise specified in the contract (see 6.3), the packaging shall be according to normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipment, handling, and storage. Shipping containers shall be properly marked and in compliance with both national and uniform motor

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

freight classifications.

6. NOTES

6.1 Intended use. The forklift truck is intended for use in handling 12,000 pound capacity cargo in and around warehouses, loading platforms, and docks and on paved or other hard surfaces

6.2 Source of documents.

6.2.1 Government documents. Military Specifications, Standards, and Handbooks referenced herein may be obtained online at http://quicksearch.dla.mil/ or from the Standardization Document Order Desk, Building 4, Section D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

6.2.2 ITSDF Standards. Copies of ITSDF standard may be obtained online at http://www.itsdf.org/ or from the Industrial Truck Standards Development Foundation, Suite 460, 1750 K Street NW, Washington, DC 20006.

6.2.3 SAE Standards. Copies of SAE standards may be obtained online at http://www.sae.org/ or from the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.

6.2.4 TRA Standards. Copies of TRA standards may be obtained online at http://www.us-tra.org/ or from the Tire and Rim Association, 175 Montrose West, Suite 150, Copley, OH 44321.

6.2.5 UL Standards. Copies of UL standards may be obtained online at http://www.ul.com/ or from the Underwriters Laboratories INC., 333 Pfingsten Road Northbrook, IL 60062.

6.2.6 The FAR. Copy references of the FAR may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh PA 15250-7954 or online at https://www.acquisition.gov/far/.

6.3. Ordering data. Procurement documents should specify the following:

a. Number and date of this CID
b. Type EE, unless otherwise specified (see 2.1)
c. Additional battery and/or battery charger (see 2.3)
d. Optional forks, if required (see 2.6)
e. Enclosed Cab (see 2.18)
f. Final color, unless otherwise specified (see 2.21)
g. flashing light (see2.28)
h. Packaging requirements, if different (see 5.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.

6.4 National Stock Number (NSN). The following is a list of NSNs assigned that correspond to this CID. The list may not be indicative of all possible NSNs associated with this CID.

NSN	3930-01-502-7497

6.5 Keywords.

Front wheel drive
Hydraulic
Rear-wheel steer

MILITARY INTERESTS:

Custodians:
Air Force – 84

Reviewer:
Air Force - 99

Preparing Activity:
Air Force - 84

Agent:
Air Force - 99
(Project 3930-2014-003)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:28Z
Check the source to verify that this is the current version before use.