INCH-POUND

MIL-M-28787/18B (SH)
AMENDMENT 1
29 June 1990

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE LDQ

This amendment forms a part of Military Specification MIL-M-28787/18B (SH), dated 27 April 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions H1-H12, Test type column: Delete "X" and substitute "S".

PAGE 5

TABLE I, Test conditions V1-V24, Max columns: Delete "15" (five places) and substitute "19" (five places).

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through W shall be performed in any order with the following exceptions. Test conditions A, B, C, H, and U are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, H, or U are part of a sequence of tests, the order of testing shall be as follows: U, A, B, C, and H where applicable, followed by the remaining tests in the sequence."

4.5.1, fifth line: Delete "C through N and T" and substitute "D through G, J through N and T".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:28Z
Check the source to verify that this is the current version before use.

4.5.3, third line: Delete "C" and substitute "D through G, J".

4.5.3, fifth and sixth lines: Delete "C through W" and substitute "D through G, J through N and T".

PAGES 48 and 49

TABLE XIX, Test conditions V1 through V24, Max columns: Delete "15" (two places) and substitute "19" (two places).

Preparing activity:
Navy - SH

(Project 5963-N762)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:28Z
Check the source to verify that this is the current version before use.