MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE LDN

This amendment forms a part of MIL-M-28787/19B(EC), dated 21 April, 1983, and is approved for use within the Space and Warfare Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions J1 and J2, Parameter column: Delete the word "circuit" (two places) and substitute "current" (two places).

PAGE 6

4.4.2, delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through V shall be performed in any order with the following exceptions. Test conditions A, B, C, H, and U are stress tests and will be performed only at 25°C ±5°C. If test conditions A, B, C, H, or U are part of a sequence of tests, the order of testing shall be as follows: U, A, B, C, H where applicable, followed by the remaining tests in the sequence."

4.5.1, lines five and six: Delete "C through R and T" and substitute "D through G, J through R, and T".

4.5.3, lines three and four: Delete "C through R and T" and substitute "D through G, J through R, and T".

4.5.3, line six: Delete "C through V" and substitute "D through G, J through T, and V".

PAGE 7

6.5, Output drive current, High level: Delete "1 mA" and substitute "400 µA".

PAGE 24

FIGURE 9, NOTES: Delete "Note 1" and substitute new Note 1:

"1. R1 = 6.04 kΩ ±1%, 1/4 W, metal film."

PAGE 38

FIGURE 14, ITEM P01-2: Delete "3.5 ±1%" and substitute "3.5 V ±1%".

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5963-N682)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:28Z
Check this source to verify that this is the current version before use.
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.