MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE WDU

This amendment forms a part of MIL-M-28787/21B(EC), dated 22 June 1982, and is approved for use within the Space and Naval Warfare Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

4.4.2, delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through U shall be performed in any order with the following exceptions. Test conditions A, B, C, H, and Q are stress tests and will be performed only at 25°C ±5°C. If test conditions A, B, C, H, or Q are part of a sequence of tests, the order of testing shall be as follows: Q, A, B, C, H where applicable, followed by the remaining tests in the sequence."

4.5.1 delete and substitute the following:

"4.5.1 Operating temperature tests. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test condition A through U in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ±5°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions D through G1, and J through P, R, S and U shall be performed in the order specified in 4.4.2, using the initial limits for applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2."

4.5.2, delete and substitute the following:

"4.5.2 Vibration tests. The vibration tests shall be conducted in accordance with MIL-M-28787. During the vibration tests, the module shall be operated in the test circuit shown on figure 4. Following the vibration tests, the electrical tests of table I which are marked with an "X" in the test type column, and test condition U shall be performed using the initial limits at 25°C ±5°C ambient."

4.5.3, delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests D through G1, and J through P and R through U shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements of table I. Following the return of the module to 25°C, electrical tests D through G1, and J through P and R through U shall be performed in the order specified in 4.4.2 using the 25°C ±5°C ambient end-of-life requirements of table I."

PAGE 22

FIGURE 9, ITEM P01, POWER SUPPLY block: Add "+" and "-".

PAGE 41

FIGURE 13, INPUT PULSE WAVEFORM: Delete "PA" and substitute "PA = 3.0 ±0.1V".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:30Z
Check the source to verify that this is the current version before use.

PAGE 47

FIGURE 17, ITEM P01-2: Delete "V_{in}" and substitute "V_{IN}".

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5963-N684)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:30Z
Check the source to verify that this is the current version before use.