MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

RECTIFIER, LOW CURRENT, POWER, KEY CODE GPR

This amendment forms a part of Military Specification MIL-M-28787/24A(EC), dated 21 March 1979, and is approved for use by the Naval Electronic Systems Command; Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2, Module description, Maximum power dissipation: Delete "3 W" and substitute "2.5 W".

1.2, Module description, Rectifier forward voltage drop, If = 0.5 mA: Delete "0.60 V maximum" and substitute "0.65 V maximum".

1.2, Module description, Rectifier forward voltage drop: Delete "If = 1.75 A" and substitute "If = 1.00 A".

PAGE 2

1.2, Module description, Maximum required limits, Rectifier continuous forward current: Delete "1.75 A" and substitute "1.00 A".

1.3, Module function: Delete "1.75 A" and substitute "1.00 A".

1.3.1, Forward current, delete and substitute:

"1.3.1 Forward current. When three rectifiers per module are operated, the continuous forward current shall not exceed 1.00 A; however, any other combinations of rectifiers may be operated provided the 2.5 W maximum module power dissipation requirement is not exceeded."

2.1, following STANDARDS, MILITARY: Delete

"(All military standards and military specifications shall be ordered from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.)"

and substitute:

"(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)"

PAGE 3

3.5.8, Marking, second line: Delete "M28787/24" and substitute "M28787/24-1".

* 4.3, Test equipment, delete and substitute:

"4.3 Test equipment. Test equipment specified on figures and in tables with a type designator shall be as specified in MIL-STD-1665. Other equipment and components shall be as specified on the figures. All resistors shall be metal film and all capacitors shall be ceramic unless otherwise specified."

PAGE 5

TABLE I, Test condition B1-B18, delete columnar data in its entirety and substitute:

*	B1-B18	Forward voltage drop (If = 0.5 mA)	III	X	0.35	0.55	0.30	0.60	0.27	0.60	0.23	0.65	V

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:31Z
Check the source to verify that this is the current version before use.