MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

COUNTER, UP/DOWN, BCD, PRESETTABLE, KEY CODE JDD

This amendment forms a part of Military Specification MIL-M-28787/31B(EC), dated 19 January 1983, and is approved for use by the Space and Naval Warfare Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

4.4.2, delete and substitute:

"4.4.2 Order of testing. Test conditions A through EE shall be performed in any order with the following exceptions. Test conditions A, B, and C are stress tests and will be performed only at 25°C ±5°C. If test conditions A, B, C, or G are part of a sequence of tests, the order of testing shall be as follows: C, A, B, G where applicable, followed by the remaining tests in the sequence."

PAGE 8

6.4 Module description, Output voltage, Low level: Delete "(I_{OH} = 16.0 mA)" and substitute "(I_{OL} = 16.0 mA)".

PAGE 69

FIGURE 25, NOTE: Delete "PWC = 175 ±10 ns" and substitute "PWB = 175 ±10 ns".

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N673)

FSC 5963

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:34Z
Check the source to verify that this is the current version before use.