INCH-POUND

MIL-M-28787/32B
AMENDMENT 1
31 December 1992

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

FLIP-FLOP, D TYPE, DIGITAL, KEY CODE KBR

This amendment forms a part of Military Specification MIL-M-28787/32B(EC), dated 15 June 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions J1-J12, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions J13 and J14, Test type column: Delete "X" and substitute "S".

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through X shall be performed in any order with the following exceptions. Test conditions A, B, C, and J are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, or J are part of a sequence of tests, the order of testing shall be as follows: C, A, B, and J where applicable, followed by the remaining tests in the sequence."

4.5.1, line 5: Delete "E through X" and substitute "E through H and K through X".

4.5.3, line 3: Delete "C through X" and substitute "D through H and K through X".

4.5.3, line 6: Delete "C through X" and substitute "D through H and K through X".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:35Z
Check the source to verify that this is the current version before use.