FEDERAL SPECIFICATION

CANS, FLAMMABLE WASTE

This amendment, which forms a part of Federal Specification RR-C-114c, dated September 21, 1964, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

Table II, delete and substitute:

TABLE II. *Dimensions and capacities*

Maximum inside width and length or diameter (inches)	Maximum inside height (inches)	Nominal capacity (gallons)
12	13-3/8	6
14	15-1/2	10
20	19-15/16	21

PAGE 6

Paragraph 3.5.4.10, delete and substitute:

3.5.4.10 *Supports, can.* The cans shall have 3 or more pressed-steel, strap-steel, or malleable-iron legs shaped to provide flat floor rests equally spaced around the bottom panel, or a cylindrical support suitably perforated for venting. Each leg shall be riveted to the body or bottom panel with one or more rivets. The bottom cylindrical support shall be integral with the body panel or at the option of the contractor, a separate steel cylindrical ring. When integral with the body, the edge of the body panel shall have a hollow rolled rim 1/4 inch diameter. When a separate steel strap is attached, it shall be not less than 1/8 inch thick and not less than 1-3/4 inches wide. The ring shall be either riveted or spot welded to the can body panel. The rivets or spot welds of the legs or cylindrical ring, shall withstand a shear load of 500 pounds when tested as specified in 4.4.4. There shall be at least eight 1 inch diameter holes in the support below the bottom panel or the equivalent area opening in not less than three holes. The completed empty can shall not tip over its own accord when placed in an upright position on an inclined plane surface which forms an angle of 30° with the horizontal.

Paragraph 4.2, line 6, delete "4.4.3" and substitute "4.4.4".

PAGE 10

Paragraph 4.4, add the following:

4.4.4 *Weld or rivet strength test.* The welds or rivets of each can shall be subjected to a shear load by placing a 500 pound weight on the closed lid of the can, and the weight allowed to remain for 5 minutes. Examination shall then be made to determine compliance with 3.5.4.10.

Paragraph 5.1.1, line 3, delete "type I or II, class 1" and substitute "type CF or SF, class domestic."

Paragraph 5.2.1, line 5, delete "class 2."

Paragraph 5.2.2, line 5, delete "type I or II, class 1", and substitute "type CF or SF, class domestic"; delete last sentence and substitute "Closure shall be in accordance with method II of the appendix of the container specification."

PAGE 11

Paragraph 6.4, "Transportation description", renumber to paragraph "6.5".

FSC 7240

Source: https://assist.dla.mil -- Downloaded: 2026-04-26T12:09Z
Check the source to verify that this is the current version before use.