A-A-2369A
January 6, 1986
SUPERSEDING
A-A-2369
August 30, 1985

COMMERCIAL ITEM DESCRIPTION

HOLDER, FLOOR POLISHING MACHINE PAD

The General Services Administration has authorized the use of this commercial item description in preference to type III of Interim Federal Specification OO-P-0040.

This commercial item description covers three types of floor maintenance pad holders, also known as drivers, that hold the floor pads used for polishing, buffing, scrubbing, and stripping floors. The holders are for mounting on power-driven, rotary-disc type floor maintenance machines which have a speed range between 150 and 350 rpm.

The floor pad holders (drivers) are intended for use in heavy duty floor care maintenance. The floor pad holding medium shall be of the following types (see notes):

Type I - Wood block with stiff, plastic bristles without shower feed. (Malish "Pad-lok" type material).
Type II - Rubber backing with stiff, plastic bristles with shower feed. ("Insta-lok" type material).
Type III - Rubber backing with stiff, molded plastic hooks with shower feed. ("EWU" type material).

The size and diameter of the floor pad holder (driver) is the diameter of the block, not the machine size (see notes):

Size 13 - 13 inches diameter
Size 14 - 14 inches diameter
Size 15 - 15 inches diameter
Size 16 - 16 inches diameter
Size 17 - 17 inches diameter
Size 18 - 18 inches diameter
Size 19 - 19 inches diameter
Size 20 - 20 inches diameter
Size 21 - 21 inches diameter
Size 22 - 22 inches diameter
Size 23 - 23 inches diameter
Size 24 - 24 inches diameter

Salient characteristics.

The floor pad holder (driver) assembly shall provide for the centering, holding, and quick changing of the floor pad. The driver assembly shall be constructed of suitable corrosion-resisting materials and shall include either a molded or formed block and riser (or a block and riser with the riser firmly mounted on the block); a medium for driving the pad; and,if required, a retaining collar or centering ring. The adapter or clutch plate, when provided, shall mate with a similar drive plate on the user's machine (see notes). The block should be 1 inch smaller in diameter (manufacturer's tolerances shall apply) than the size of the floor machine and shall extend

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:22Z
Check the source to verify that this is the current version before use.

below the skirt of the machine when in place. The retaining collar is for centering the pad and to help hold the pad in place. The medium for driving the floor pad shall provide for a quick change, non-slip, positive rotation of the pad capability. Positive rotation shall be accomplished without the use of mechanical devices. The driving medium shall be capable of holding the pad in place when the machine is tilted back without the assistance of the retaining collar. The drive assemblies for holders between 14 inches and 20 inches in diameter shall provide for a flow through or shower feed capability, except as noted. When specified, other size holders shall be so equipped (see notes).

The Type I floor pad holder (driving medium) shall consist of a flat-faced, wood block with short, stiff, plastic bristles (Malish "Pad-lok" type material) protruding from the face. The type I pad holder does not have the shower feed capability. The riser can either be an integral part of the wood block or attached to it by means of screws or other mechanical means.

The Type II floor pad holder (driving medium) shall consist of short, stiff, plastic bristles protruding from a non-porous backing material ("Insta-lok" type material). This backing is glued to a closed cell, sponge rubber cushion. The sponge rubber cushion is glued to a stiff, non-porous backing. This unit can either be an integral part of a molded block and riser or attached to a block and riser by screws or other mechanical means.

The Type III floor pad holder (driving medium) shall consist of short, molded plastic hooks protruding from a non-porous backing material ("EWU" type material). This backing is glued to a closed cell, sponge rubber cushion. The sponge rubber cushion is glued to a stiff, non-porous backing. This unit can either be an integral part of a molded block and riser or attached to a block and riser by screws or other mechanical means.

Workmanship. The floor pad holders (drivers) shall be free from any defects, imperfections, or material that would adversely affect either performance or may cause undesirable effects during use, such as marring the floor when heeling.

Regulatory requirements. In accordance with the Section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Responsibility for inspection. Unless otherwise specified, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or purchase order. The Government reserves the right to perform any of the inspections set forth in the CID where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:22Z
Check the source to verify that this is the current version before use.

Inspection of the end item. Sampling shall be in accordance with MIL-STD-105, Sampling Procedures and Tables for Inspection by Attributes.

Visual and dimensional examination. The pad holder shall be examined for defects in finish, material, construction, workmanship, marking, and nonconformance with dimensional requirements. Defects shall be as classified in Table I. The inspection level shall be level II with an acceptance quality level (AQL) of 4.0 for major defects and 6.5 for minor defects, expressed in terms of defects per hundred units.

TABLE I - Classification of defects

Examine	Defects	Classification Major	Minor
General	Not type specified	X	
	Not size specified	X	
	Drive medium will not hold pad in place	X	
	Drive assembly not corrosion resistant	X	
	Shower feed not as required	X	
	Packaging, packing, and marking not as specified.		X

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or purchase order.

Notes. Purchaser must specify type and size floor pad holder required, shower feed if other than sizes specified, the manufacturer's make and model number of the polishing machine if an adapter plate is required with the drive assembly, and type of centering ring or retaining collar, if required.

Copies of military standards may be obtained from the procuring activity or as directed by the contracting officer.

WHEN THIS COMMERCIAL ITEM DESCRIPTION IS USED FOR PROCUREMENT, THE COMMERCIAL ITEM CERTIFICATION CLAUSE DOES NOT NEED TO APPEAR IN THE SOLICITATION.

MILITARY INTEREST:

Military Coordinating Activity

Air Force - 99

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:22Z
Check the source to verify that this is the currentversion before use.