MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, PLASTIC (OR PAPER-PLASTIC) DIELECTRIC, AXIAL-WIRE TERMINAL, THREADED-STUD RETAINER, TUBULAR (UNINSULATED) (HERMETICALLY SEALED IN METAL CASES), ESTABLISHED RELIABILITY, STYLE CQR13

This amendment forms a part of Military Specification Sheet MIL-C-19978/11, dated 20 October 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Following title, insert: " FAILURE RATE LEVEL 'L' IS INACTIVE FOR DESIGN AFTER 14 September 1983 "

PAGE 4

TABLE II, column 7, lines 1 through 13: Delete ".235" or ".312" as applicable, and substitute ".400".

NOTE: The margin of this amendment is marked with an asterisk to indicate where a change (addition) from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - AS, MC, OS, SH

Agent:
DLA - ES

Preparing activity:
Air Force - 85

(Project 5910-1455-6)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:04Z
Check the source to verify that this is the current version before use.