INCH-POUND

MIL-PRF-19978/14A
27 May 1999
SUPERSEDING
MIL-C-19978/14
20 October 1972

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, PLASTIC DIELECTRIC, AXIAL-WIRE TERMINAL, TANGENTIAL RETAINER, TUBULAR (UNINSULATED) (HERMETICALLY SEALED IN METAL CASES), ESTABLISHED RELIABILITY, STYLE CQR32

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the capacitors described herein shall consist of this specification and MIL-PRF-19978.



Inches	mm	Inches	mm	Inches	mm
.001	.03	.0625	1.59	.250	6.35
.004	.10	.144	3.66	.312	7.92
.005	.13	.156	3.96	.400	10.16
.020	.51	.172	4.37	.438	11.13
.025	.64	.175	4.45	.500	12.70
.031	.79	.188	4.78	.562	14.27
.032	.81	.195	4.95	1.000	25.40
.062	1.57	.235	5.97	1.625	41.28

Case dimension D	H ± .062	G ± .062	E ± .031	F ± .005
Less than .500	.312	.250	.188	.144
.500 and up	.438	.500	.250	.156

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Leads shall be of tinned solid wire, .020 (No. 24 AWG) for cases .175 and .195 in diameter; .025 (No. 22 AWG) for cases .235 through .312 diameter; and .032 (No. 20 AWG) for cases .400 diameter and above. Tolerance on all lead wire diameters shall be + .004, -.001.

FIGURE 1. Style CQR32 capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:06Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration - See figure 1 and table II.

Case material - Nonmagnetic (end seal may be of magnetic material).

Terminals - Axial-wire lead (see figure 1).



Rated voltage - See table II.

Rated temperature - -65°C to +85°C.

Capacitance (Cap.) (nom) - See table II.

Capacitance tolerance - See table II.

Dissipation factor (DF) (max) - 0.6 percent.

Failure rate level - In accordance with MIL-PRF-19978.

Reliability - In accordance with MIL-PRF-19978.

Burn-in: In accordance with MIL-PRF-19978.

Radiographic inspection: In accordance with MIL-PRF-19978.

Seal: Method 112 of MIL-STD-202, test condition letter A.

Barometric pressure: In accordance with MIL-PRF-19978.

Test points:

Circuit diagram 1 - Between terminals and case.

Circuit diagram 3 - Between ungrounded terminal and case.

Insulation resistance (IR):

Terminal to terminal - See table I.

Vibration, high frequency: Method 204 of MIL-STD-202, test condition B, with the following exception:

Direction and duration of motion - 4 hours in each of two mutually perpendicular directions (total of 8 hours), one parallel and the other perpendicular to the cylindrical axis.

Salt spray: In accordance with MIL-PRF-19978.

Solderability: In accordance with MIL-PRF-19978.

Terminal strength: Method 211 of MIL-STD-202, test condition letter D.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:06Z
Check the source to verify that this is the current version before use.

TABLE I. Terminal-to-terminal insulation resistance.

Capacitance rating	Minimum insulation resistance
Characteristic M	
	At 25°C
0 to 0.68 microfarad	100,000 megohms
Greater than 0.68 microfarad	68,000 megohm-microfarads 1/
	At 85°C
0 to 0.2 microfarad	25,000 megohms
Greater than 0.2 microfarad	5,000 megohm-microfarads 1/

1/ Product obtained by multiplying the capacitance in microfarads by the insulation resistance in megohms.

TABLE II. STYLES CQR32 capacitors.

Part number 1/	DC voltage rating	Capacitance rating	Capacitance tolerance	Failure rate level	Case dimensions			
					Circuit 1		Circuit 3	
					L ±.031	D +.015, -.005	L ±.031	D +.015, -.005
	Volts	µF			Inches	Inches	Inches	Inches
CQR32A-MZ155-3-	30	1.5	G, J, K	M, P, R, S	1.625	.562	1.531	.562
CQR32A-MZ225-3-	30	2.2	G, J, K	M, P, R, S	1.875	.670	1.781	.670
CQR32A-MZ335-3-	30	3.3	G, J, K	M, P, R, S	1.875	.750	1.781	.750
CQR32A-MZ475-3-	30	4.7	G, J, K	M, P, R, S	2.625	.750	2.531	.750
CQR32A-MZ685-3-	30	6.8	G, J, K	M, P, R, S	2.125	1.000	2.031	1.000
CQR32A-MZ106-3-	30	10.0	G, J, K	M, P, R, S	2.375	1.000	2.281	1.000
CQR32A-MA102-3-	50	.0010	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA122-3-	50	.0012	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA152-3-	50	.0015	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA182-3-	50	.0018	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA222-3-	50	.0022	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA272-3-	50	.0027	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA332-3-	50	.0033	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA392-3-	50	.0039	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA472-3-	50	.0047	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA562-3-	50	.0056	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA682-3-	50	.0068	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA822-3-	50	.0082	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA103-3-	50	.010	G, J, K	M, P, R, S	.500	.175	.406	.175
CQR32A-MA123-3-	50	.012	G, J, K	M, P, R, S	.500	.235	.406	.235
CQR32A-MA153-3-	50	.015	G, J, K	M, P, R, S	.500	.235	.406	.235
CQR32A-MA183-3-	50	.018	G, J, K	M, P, R, S	.500	.235	.406	.235
CQR32A-MA223-3-	50	.022	G, J, K	M, P, R, S	.500	.235	.406	.235
CQR32A-MA273-3-	50	.027	G, J, K	M, P, R, S	.500	.312	.406	.312
CQR32A-MA333-3-	50	.033	G, J, K	M, P, R, S	.500	.312	.406	.312
CQR32A-MA393-3-	50	.039	G, J, K	M, P, R, S	.500	.312	.406	.312
CQR32A-MA473-3-	50	.047	G, J, K	M, P, R, S	.500	.312	.406	.312
CQR32A-MA563-3-	50	.056	G, J, K	M, P, R, S	.562	.312	.468	.312
CQR32A-MA683-3-	50	.068	G, J, K	M, P, R, S	.562	.312	.468	.312
CQR32A-MA124-3-	50	.12	G, J, K	M, P, R, S	.875	.312	.781	.312
CQR32A-MA154-3-	50	.15	G, J, K	M, P, R, S	.875	.312	.781	.312
CQR32A-MA184-3-	50	.18	G, J, K	M, P, R, S	.875	.400	.781	.400
CQR32A-MA224-3-	50	.22	G, J, K	M, P, R, S	.875	.400	.781	.400
CQR32A-MA274-3-	50	.27	G, J, K	M, P, R, S	.875	.400	.781	.400

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:06Z
Check the source to verify that this is the current version before use.

TABLE II. STYLES CQR32 capacitors - Continued.

Part number 1/	DC voltage rating	Capacitance rating	Capacitance tolerance	Failure rate level	Case dimensions			
					Circuit 1		Circuit 3	
					L ±.031	D +.015, -.005	L ±.031	D +.015, -.005
	Volts	µF			Inches	Inches	Inches	Inches
CQR32A-MA334-3-	50	.33	G, J, K	M, P, R, S	1.000	.400	.906	.400
CQR32A-MA394-3-	50	.39	G, J, K	M, P, R, S	1.125	.400	1.031	.400
CQR32A-MA474-3-	50	.47	G, J, K	M, P, R, S	1.125	.400	1.031	.400
CQR32A-MA564-3-	50	.56	G, J, K	M, P, R, S	1.375	.400	1.281	.400
CQR32A-MA684-3-	50	.68	G, J, K	M, P, R, S	1.375	.400	1.281	.400
CQR32A-MA824-3-	50	.82	G, J, K	M, P, R, S	1.125	.562	1.031	.562
CQR32A-MA105-3-	50	1.0	G, J, K	M, P, R, S	1.125	.562	1.031	.562
CQR32A-MA125-3-	50	1.2	G, J, K	M, P, R, S	1.375	.562	1.281	.562
CQR32A-MB125-3-	100	1.2	G, J, K	M, P, R, S	1.625	.670	1.531	.670
CQR32A-MB155-3-	100	1.5	G, J, K	M, P, R, S	1.625	.670	1.531	.670
CQR32A-MB185-3-	100	1.8	G, J, K	M, P, R, S	1.625	.670	1.531	.670
CQR32A-MB225-3-	100	2.2	G, J, K	M, P, R, S	1.875	.750	1.781	.750
CQR32A-MB275-3-	100	2.7	G, J, K	M, P, R, S	2.125	.750	2.031	.750
CQR32A-MB335-3-	100	3.3	G, J, K	M, P, R, S	2.375	.750	2.281	.750
CQR32A-MB395-3-	100	3.9	G, J, K	M, P, R, S	1.875	1.000	1.781	1.000
CQR32A-MB475-3-	100	4.7	G, J, K	M, P, R, S	2.125	1.000	2.031	1.000
CQR32A-MB565-3-	100	5.6	G, J, K	M, P, R, S	2.375	1.000	2.281	1.000
CQR32A-MB685-3-	100	6.8	G, J, K	M, P, R, S	2.625	1.000	2.531	1.000
CQR32A-MC102-3-	200	.0010	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC122-3-	200	.0012	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC152-3-	200	.0015	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC182-3-	200	.0018	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC222-3-	200	.0022	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC272-3-	200	.0027	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC332-3-	200	.0033	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC392-3-	200	.0039	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC472-3-	200	.0047	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC562-3-	200	.0056	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC682-3-	200	.0068	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC822-3-	200	.0082	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC103-3-	200	.010	G, J, K	M, P, R, S	.750	.175	.656	.175
CQR32A-MC123-3-	200	.012	G, J, K	M, P, R, S	.719	.195	.625	.195
CQR32A-MC153-3-	200	.015	G, J, K	M, P, R, S	.719	.195	.625	.195
CQR32A-MC183-3-	200	.018	G, J, K	M, P, R, S	.719	.235	.625	.235
CQR32A-MC223-3-	200	.022	G, J, K	M, P, R, S	.719	.235	.625	.235
CQR32A-MC273-3-	200	.027	G, J, K	M, P, R, S	.719	.235	.625	.235
CQR32A-MC333-3-	200	.033	G, J, K	M, P, R, S	.719	.235	.625	.235
CQR32A-MC393-3-	200	.039	G, J, K	M, P, R, S	.719	.312	.625	.312
CQR32A-MC473-3-	200	.047	G, J, K	M, P, R, S	.719	.312	.625	.312
CQR32A-MC563-3-	200	.056	G, J, K	M, P, R, S	.844	.312	.750	.312
CQR32A-MC683-3-	200	.068	G, J, K	M, P, R, S	.844	.312	.750	.312
CQR32A-MC823-3-	200	.082	G, J, K	M, P, R, S	.844	.312	.750	.312
CQR32A-MC104-3-	200	.10	G, J, K	M, P, R, S	.844	.312	.750	.312
CQR32A-MC124-3-	200	.12	G, J, K	M, P, R, S	.812	.400	.719	.400
CQR32A-MC154-3-	200	.15	G, J, K	M, P, R, S	.812	.400	.719	.400
CQR32A-MC184-3-	200	.18	G, J, K	M, P, R, S	1.062	.400	.969	.400
CQR32A-MC224-3-	200	.22	G, J, K	M, P, R, S	1.062	.400	.969	.400
CQR32A-MC274-3-	200	.27	G, J, K	M, P, R, S	1.250	.400	1.156	.400
CQR32A-MC334-3-	200	.33	G, J, K	M, P, R, S	1.250	.400	1.156	.400
CQR32A-MC394-3-	200	.39	G, J, K	M, P, R, S	1.188	.500	1.094	.500

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:06Z
Check the source to verify that this is the current version before use.

TABLE II. STYLES CQR32 capacitors - Continued.

Part number 1/	DC voltage rating	Capacitance rating	Capacitance tolerance	Failure rate level	Case dimensions			
					Circuit 1		Circuit 3	
					L ±.031	D +.015, -.005	L ±.031	D +.015, -.005
	Volts	µF			Inches	Inches	Inches	Inches
CQR32A-MC474-3-	200	.47	G, J, K	M, P, R, S	1.188	.500	1.094	.500
CQR32A-MC564-3-	200	.56	G, J, K	M, P, R, S	1.375	.562	1.281	.562
CQR32A-MC684-3-	200	.68	G, J, K	M, P, R, S	1.375	.562	1.281	.562
CQR32A-MC824-3-	200	.82	G, J, K	M, P, R, S	1.875	.562	1.781	.562
CQR32A-MC105-3-	200	1.0	G, J, K	M, P, R, S	1.875	.562	1.781	.562
CQR32A-ME102-3-	400	.0010	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-ME122-3-	400	.0012	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-ME152-3-	400	.0015	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-ME182-3-	400	.0018	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-ME222-3-	400	.0022	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-ME272-3-	400	.0027	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-ME332-3-	400	.0033	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-ME392-3-	400	.0039	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-ME472-3-	400	.0047	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-ME562-3-	400	.0056	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-ME682-3-	400	.0068	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-ME822-3-	400	.0082	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-ME103-3-	400	.010	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-ME123-3-	400	.012	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-ME153-3-	400	.015	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-ME183-3-	400	.018	G, J, K	M, P, R, S	1.062	.312	.969	.312
CQR32A-ME223-3-	400	.022	G, J, K	M, P, R, S	1.062	.312	.969	.312
CQR32A-ME273-3-	400	.027	G, J, K	M, P, R, S	.938	.400	.844	.400
CQR32A-ME333-3-	400	.033	G, J, K	M, P, R, S	.938	.400	.844	.400
CQR32A-ME393-3-	400	.039	G, J, K	M, P, R, S	1.062	.400	.969	.400
CQR32A-ME473-3-	400	.047	G, J, K	M, P, R, S	1.062	.400	.969	.400
CQR32A-ME563-3-	400	.056	G, J, K	M, P, R, S	1.250	.400	1.156	.400
CQR32A-ME683-3-	400	.068	G, J, K	M, P, R, S	1.250	.400	1.156	.400
CQR32A-ME823-3-	400	.082	G, J, K	M, P, R, S	1.562	.400	1.469	.400
CQR32A-ME104-3-	400	.10	G, J, K	M, P, R, S	1.562	.400	1.469	.400
CQR32A-ME124-3-	400	.12	G, J, K	M, P, R, S	1.281	.562	1.188	.562
CQR32A-ME154-3-	400	.15	G, J, K	M, P, R, S	1.281	.562	1.188	.562
CQR32A-ME184-3-	400	.18	G, J, K	M, P, R, S	1.531	.562	1.438	.562
CQR32A-ME224-3-	400	.22	G, J, K	M, P, R, S	1.531	.562	1.438	.562
CQR32A-ME274-3-	400	.27	G, J, K	M, P, R, S	1.906	.562	1.812	.562
CQR32A-ME334-3-	400	.33	G, J, K	M, P, R, S	1.906	.562	1.812	.562
CQR32A-ME394-3-	400	.39	G, J, K	M, P, R, S	1.906	.670	1.812	.670
CQR32A-ME474-3-	400	.47	G, J, K	M, P, R, S	1.906	.670	1.812	.670
CQR32A-ME564-3-	400	.56	G, J, K	M, P, R, S	2.156	.750	2.062	.750
CQR32A-ME684-3-	400	.68	G, J, K	M, P, R, S	2.156	.750	2.062	.750
CQR32A-ME824-3-	400	.82	G, J, K	M, P, R, S	2.656	.750	2.562	.750
CQR32A-ME105-3-	400	1.0	G, J, K	M, P, R, S	2.656	.750	2.562	.750
CQR32A-MF102-3-	600	.0010	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-MF122-3-	600	.0012	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-MF152-3-	600	.0015	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-MF182-3-	600	.0018	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-MF222-3-	600	.0022	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-MF272-3-	600	.0027	G, J, K	M, P, R, S	.812	.235	.719	.235
CQR32A-MF332-3-	600	.0033	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MF392-3-	600	.0039	G, J, K	M, P, R, S	.938	.312	.844	.312

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:06Z
Check the source to verify that this is the current version before use.

TABLE II. STYLES CQR32 capacitors - Continued.

Part number 1/	DC voltage rating	Capacitance rating	Capacitance tolerance	Failure rate level	Case dimensions			
					Circuit 1		Circuit 3	
					L ±.031	D +.015, -.005	L ±.031	D +.015, -.005
	Volts	µF			Inches	Inches	Inches	Inches
CQR32A-MF472-3-	600	.0047	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MF562-3-	600	.0056	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MF682-3-	600	.0068	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MF822-3-	600	.0082	G, J, K	M, P, R, S	1.062	.312	.969	.312
CQR32A-MF103-3-	600	.010	G, J, K	M, P, R, S	1.062	.312	.969	.312
CQR32A-MF123-3-	600	.012	G, J, K	M, P, R, S	.938	.400	.844	.400
CQR32A-MF153-3-	600	.015	G, J, K	M, P, R, S	.938	.400	.844	.400
CQR32A-MF183-3-	600	.018	G, J, K	M, P, R, S	1.062	.400	.969	.400
CQR32A-MF223-3-	600	.022	G, J, K	M, P, R, S	1.062	.400	.969	.400
CQR32A-MF273-3-	600	.027	G, J, K	M, P, R, S	1.312	.400	1.219	.400
CQR32A-MF333-3-	600	.033	G, J, K	M, P, R, S	1.312	.400	1.219	.400
CQR32A-MF393-3-	600	.039	G, J, K	M, P, R, S	1.562	.400	1.469	.400
CQR32A-MF473-3-	600	.047	G, J, K	M, P, R, S	1.562	.400	1.469	.400
CQR32A-MF563-3-	600	.056	G, J, K	M, P, R, S	1.250	.562	1.156	.562
CQR32A-MF683-3-	600	.068	G, J, K	M, P, R, S	1.250	.562	1.156	.562
CQR32A-MF823-3-	600	.082	G, J, K	M, P, R, S	1.500	.562	1.406	.562
CQR32A-MF104-3-	600	.10	G, J, K	M, P, R, S	1.500	.562	1.406	.562
CQR32A-MF124-3-	600	.12	G, J, K	M, P, R, S	1.875	.562	1.781	.562
CQR32A-MF154-3-	600	.15	G, J, K	M, P, R, S	1.875	.562	1.781	.562
CQR32A-MF184-3-	600	.18	G, J, K	M, P, R, S	1.875	.670	1.781	.670
CQR32A-MF224-3-	600	.22	G, J, K	M, P, R, S	1.875	.670	1.781	.670
CQR32A-MF274-3-	600	.27	G, J, K	M, P, R, S	2.125	.750	2.031	.750
CQR32A-MF334-3-	600	.33	G, J, K	M, P, R, S	2.125	.750	2.031	.750
CQR32A-MF394-3-	600	.39	G, J, K	M, P, R, S	2.625	.750	2.531	.750
CQR32A-MF474-3-	600	.47	G, J, K	M, P, R, S	2.625	.750	2.531	.750
CQR32A-MF564-3-	600	.56	G, J, K	M, P, R, S	2.125	1.000	2.031	1.000
CQR32A-MF684-3-	600	.68	G, J, K	M, P, R, S	2.125	1.000	2.031	1.000
CQR32A-MG102-3-	1000	.0010	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MG122-3-	1000	.0012	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MG152-3-	1000	.0015	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MG182-3-	1000	.0018	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MG222-3-	1000	.0022	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MG272-3-	1000	.0027	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MG332-3-	1000	.0033	G, J, K	M, P, R, S	.938	.312	.844	.312
CQR32A-MG392-3-	1000	.0039	G, J, K	M, P, R, S	.938	.400	.844	.400
CQR32A-MG472-3-	1000	.0047	G, J, K	M, P, R, S	.938	.400	.844	.400
CQR32A-MG562-3-	1000	.0056	G, J, K	M, P, R, S	1.062	.400	.969	.400
CQR32A-MG682-3-	1000	.0068	G, J, K	M, P, R, S	1.062	.400	.969	.400
CQR32A-MG822-3-	1000	.0082	G, J, K	M, P, R, S	1.312	.400	1.219	.400
CQR32A-MG103-3-	1000	.010	G, J, K	M, P, R, S	1.312	.400	1.219	.400
CQR32A-MG123-3-	1000	.012	G, J, K	M, P, R, S	1.562	.400	1.469	.400
CQR32A-MG183-3-	1000	.018	G, J, K	M, P, R, S	1.562	.400	1.469	.400
CQR32A-MG223-3-	1000	.022	G, J, K	M, P, R, S	1.250	.562	1.156	.562
CQR32A-MG273-3-	1000	.027	G, J, K	M, P, R, S	1.250	.562	1.156	.562
CQR32A-MG333-3-	1000	.033	G, J, K	M, P, R, S	1.500	.562	1.406	.562
CQR32A-MG393-3-	1000	.039	G, J, K	M, P, R, S	1.875	.562	1.781	.562
CQR32A-MG473-3-	1000	.047	G, J, K	M, P, R, S	1.875	.562	1.781	.562
CQR32A-MG563-3-	1000	.056	G, J, K	M, P, R, S	1.875	.670	1.781	.670
CQR32A-MG683-3-	1000	.068	G, J, K	M, P, R, S	1.875	.670	1.781	.670
CQR32A-MG823-3-	1000	.082	G, J, K	M, P, R, S	2.125	.750	2.031	.750

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:06Z
Check the source to verify that this is the current version before use.

TABLE II. STYLES CQR32 capacitors - Continued.

Part number 1/	DC voltage rating	Capacitance rating	Capacitance tolerance	Failure rate level	Case dimensions			
					Circuit 1		Circuit 3	
					L ±.031	D +.015, -.005	L ±.031	D +.015, -.005
	Volts	µF			Inches	Inches	Inches	Inches
CQR32A-MG104-3-	1000	.10	G, J, K	M, P, R, S	2.125	.750	2.031	.750
CQR32A-MG124-3-	1000	.12	G, J, K	M, P, R, S	1.875	1.000	1.781	1.000
CQR32A-MG154-3-	1000	.15	G, J, K	M, P, R, S	1.875	1.000	1.781	1.000
CQR32A-MG184-3-	1000	.18	G, J, K	M, P, R, S	2.375	1.000	2.281	1.000
CQR32A-MG224-3-	1000	.22	G, J, K	M, P, R, S	2.375	1.000	2.281	1.000

1/ Complete part number shall include additional symbols to indicate circuit symbol, capacitance tolerance, and failure rate level, as applicable.

TABLE III. Multimeter equivalent of decimal inches.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
0.005	0.13	0.719	18.26	1.188	30.17	1.875	47.63
0.015	0.38	0.750	19.05	1.219	30.96	1.906	48.41
0.031	0.79	0.781	19.84	1.250	31.75	2.031	51.59
0.175	4.45	0.812	20.62	1.281	32.54	2.062	52.37
0.195	4.95	0.844	21.44	1.312	33.32	2.125	53.98
0.235	5.97	0.875	22.23	1.375	34.93	2.156	54.76
0.312	7.92	0.906	23.01	1.406	35.71	2.281	57.94
0.400	10.16	0.938	23.72	1.438	36.53	2.375	60.33
0.406	10.31	0.969	24.61	1.469	37.31	2.531	64.29
0.468	11.89	1.000	25.40	1.500	38.10	2.562	65.07
0.500	12.70	1.031	26.19	1.531	38.89	2.625	66.68
0.562	14.27	1.062	26.97	1.562	39.67	2.656	67.46
0.625	15.88	1.094	27.79	1.625	41.28		
0.656	16.66	1.125	28.58	1.781	45.24		
0.670	17.02	1.156	29.36	1.812	46.02		

Dielectric absorption (not applicable to values of 0.01 µF or less): 0.60 percent, maximum.

Stability at low and high temperature:

Low temperature:

Test temperature - -65°C +0°C, -5°C.

Capacitance change (max) - -7 percent.

High temperature:

Test temperature - +85°C +5°C, -0°C.

Capacitance change (max) - +5 percent.

Life:

Capacitance change (max) - ±5 of initial measured value percent.

Resistance to soldering heat: In accordance with MIL-PRF-19978.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:06Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Navy - MC
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5910-2016-10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:06Z
Check the source to verify that this is the current version before use.