MIL-S-19500/419(EL)
AMENDMENT-1
21 May 1969

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, THYRISTOR (CONTROLLED RECTIFIER), SILICON
TYPES 2N3027 THROUGH 2N3032, AND
TX2N3027 THROUGH TX2N3032

This Amendment forms a part of Military Specification MIL-S-19500/419(EL), 15 March 1969.

Page 3, paragraph 3.3.3: Replace with the following:

"3.3.3 Terminal-lead material and finish.- The terminal-lead material shall be Type K (Kovar) or Type F (Alloy 52) conforming to requirements in Standard MIL-STD-1276, except that a nickel under-plating of thickness: optionally up through 100 microinches maximum, may be used. The terminal-lead finish shall be gold (per pertinent requirements in Standard MIL-STD-1276); however, if so specified in the contract or order, the lead-material finish may be tin, or tin-coating over gold. This tin-finish requirement shall not be construed as affecting adversely the qualified-product status of the device, or applicable JAN marking. (See 6.3a herein.)

"3.3.3.1 Selectivity of terminal-lead material.- Where choice of lead material (see 3.3.3 above) is desired, stipulation for the particular material shall be made in contract or order. (See 6.3b herein.)"

Page 31, paragraph 6.3: Replace with the following:

"6.3 Ordering data.-

a. Terminal-lead finish: See 3.3.3 herein.
b. Terminal-lead material: See 3.3.3.1 herein.
c. Lot-inspection data: See 4.2.7 herein."

Custodian:
Army-EL

Preparing activity:
Army-EL

Project No. 5961-A249

FSC-5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T16:46Z
Check the source to verify that this is the current version before use.