INCH-POUND

MIL-PRF-49467A
AMENDMENT 1
20 April 1998

PERFORMANCE SPECIFICATION

CAPACITOR, FIXED, CERAMIC, MULTILAYER, HIGH VOLTAGE
(GENERAL PURPOSE), ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This amendment forms part of MIL-PRF-49467A, dated 19 May 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Table II, delete and substitute:

"TABLE II. Capacitance tolerance.

Symbol	Capacitance tolerance
J	± 5 percent
K	± 10 percent
M	± 20 percent

"

PAGE 18

4.8.2.2, second paragraph, delete and substitute:

"After completion of the test, the insulation resistance shall be measured at +125°C in accordance with 4.8.8, with the exception that the test potential shall be a minimum of 500 V dc and a maximum of rated voltage. The units shall then be allowed to stabilize at room temperature (+25°C). After stabilization at room temperature, the insulation resistance, capacitance and dissipation factor shall be measured as specified in 4.8.8, 4.8.3 and 4.8.4, respectively."

PAGE 28

A.4.1, add after last sentence:

"The BR characteristic parts shall qualify the BZ characteristic parts of equal or less capacitance."

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AT, AV, CR4, MI
Navy - MC
Air Force - 19, 99
DLA - CC

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-1973)

AMSC N/A FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:10Z
Check the source to verify that this is the current version before use.