MIL-K-20277G(MC)
19 February 1988
SUPERSEDING
MIL-K-20277F(MC)
7 July 1982

MILITARY SPECIFICATION

KNIFE, COMBAT: AND SHEATH

This specification is approved for use within the U. S. Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for one type of sheathed combat knife having a 7-inch [178-millimeter (mm)] blade. When specified (see 6.2.1), sheaths may be acquired separately.

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

O-L-164 - Leather Dressing, Mildew-Preventive.
V-T-295 - Thread, Nylon.
FF-R-556 - Rivets, Solid, Small; Rivets, Split, Small; Rivets Tubular Small, and Caps, Rivets; General Purpose.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Commanding General (LMA-2), Marine Corps Research, Development and Acquisition Command, Washington, D.C. 20380-0001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1095

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T07:32Z
Check the source to verify that this is the current version before use.

KK-L-165 - Leather, Cattlehide, Vegetable-Tanned, and Chrome Retanned Impregnated; and Soles.
KK-L-271 - Leather, Cattlehide, Strap, Vegetable-Tanned.
PPP-B-576 - Box, Wood, Cleated, Veneer, Paper Overlaid.
PPP-B-585 - Box, Wood, Wirebound.
PPP-B-591 - Boxes, Shipping, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated Plywood.
PPP-B-621 - Box, Wood, Nailed and Lock Corner.
PPP-B-636 - Box, Shipping, Fiberboard.
PPP-T-60 - Tape, Packaging, Waterproof.

MILITARY

MIL-B-117 - Bag, Sleeve, and Tubing, - Interior Packaging.
MIL-H-6875 - Heat Treatment of Steels Process for.
MIL-S-8559 - Steel Bars, Carbon, AISI (1095), Aircraft Quality.
MIL-F-10884 - Fasteners, Snap.
DOD-P-16232 - Phosphate Coating, Heavy, Manganese or Zinc Base (For Ferrous Metals).

STANDARDS

FEDERAL

FED-STD-66 - Steel, Chemical Composition and Hardenability.
FED-STD-151 - Metal, Test Methods.
FED-STD-311 - Leather, Methods of Sampling and Testing.
FED-STD-595 - Color.
FED-STD-751 - Stitches, Seams and Stitchings.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U. S. Military Property.
MS27980 - Fastener, Snap, Style 2 (Regular Wire Spring Clamp Type).

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

MARINE CORPS

81A5020A0000 - Knife, Combat.
81A5020A0001 - Sheath for Combat Knife.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, handbooks, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment document which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E112 - Estimating the Average Grain Size of Metals.
ASTM D3951-82 - Standard Practice For Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), the contractor shall furnish a first article consisting of two sheathed knives and two blades in the as quenched (untempered) condition, or two sheaths when acquired separately.

3.2 Materials. The materials shall be as specified herein. The materials may include reclaimed materials provided such materials will not jeopardize the intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which will restore them to the same chemical composition and physical properties as original materials.

3.3 Design. The design of the knife shall conform to Drawing No. 81A5020A0000 and the design of the sheath shall conform to Drawing No. 81A5020A0001.

3.4 Construction

3.4.1 Knife. The guard shall fit the tang snugly so that all edges of the slot are in contact. The slot shall provide for the tang fillet to allow the guard to be in full contact with the

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.

heel of the blade. The leather grip sections shall be assembled on the tang in appropriate sequence and of such thickness as to require compression thereof and permit the insertion of the pin through the butt plate to form a solid grip handle. This assembly shall be such that the grip shall form an integral part of the knife, with no play between the grip and the blade. The butt pin shall be peened at both ends and ground smooth. The end of the tang shall be flush with the butt plate. The handle assembly shall be deburred and colored to match the sheath. The blade shall contain a blood grove on each side. The cutting edge of the blade shall be ground and sharpened to a keen edge. The cutting edge at the back of the blade near the tip shall be ground to a sharp edge.

3.4.1.1 Grip. The grip shall be made of leather conforming to KK-L-165, except that class 5 material (OFFAL) shall not be used.

3.4.1.2 Blade. The blade shall be of the through tang type and shall be made of steel conforming to MIL-S-8559. The finished blade shall be hardened and tempered in accordance with MIL-H-6875, and shall have a Rockwell hardness range from C55 to C58, when inspected as specified in 4.10.5. There shall be a hardness transition zone from the heel of the blade to 0.75 inch (19.0 mm) onto the tang, having a hardness of C35 to C45 at the midpoint. The remainder of the tang shall have a maximum hardness of C30 using the Rockwell scale. After hardening, the blade shall have a fracture grain size no coarser than 8, when compared with the Shepherd fracture grain size standard specified in ASTM E112.

3.4.1.3 Guard, butt plate and pin. The guard, butt plate and pin shall be made of SAE 1018 or 1020 steel conforming to FED-STD-66.

3.4.2 Sheath. The leather sheath shall consist of a one-piece back section and a one-piece front section forming a pocket for the blade. The flesh side of the leather shall be on the inside of the assembled sheath. The front welt and back sections shall be sewn and riveted together along the edges. The strap for holding the handle shall be riveted to the sheath at its longitudinal center. The snap fasteners shall be centered and spaced on the holding strap. The strap, when snapped closed, shall firmly hold the handle against the top of the sheath and shall prevent movement of the knife when the sheath is inverted or jarred. The hole near the bottom of the sheath for the insertion of a thong shall be punched out, not cut. The punch shall be made after assembly to assure alignment. After assembly, the sheath shall be trimmed to remove all loose ends, and rough edges shall be dyed to match the finished leather. The sheath and welt filler shall be made of leather conforming to type II, Class 1, section 3 of KK-1-271. The outer surface shall not be flaky and shall be free of all other defects (see 4.9.2). The thread shall be nylon conforming to type I or II, letter size F of V-T-295. The color shall closely match the color of the sheath. Colorfastness is not applicable (see 4.9.2). The rivets shall be split type conforming to type XI, class 1, Grade F

Source: https://assist.dla.mil -- Downloaded: 20261O-19T07:32Z
Check the source to verify that this is the current version before use.

of FF-R-556, black chemical finish (see 4.10). The snap fasteners shall conform to style 2, finish 2 of MIL-F-10884 and MS27980 (see 4.9.2).

3.4.2.1 Leather. The leather shall be rendered mildew proof in accordance with type I or II of O-L-164. The treated leather shall contain between 0.2 and 0.5 percent paranitrophenol (see 4.10.6).

3.4.2.2 Sewing. All sewing shall be with nylon thread specified in 3.4.2. The stitch shall be type 301 conforming to FED-STD-751, five to seven stitches per inch (five to seven stitches per 25.4 mm). The stitching shall be straight and parallel to the leather edge. The sheath shall not contain any thread breaks, skips, run-offs, or needle chews. The thread ends shall be neatly trimmed (see 4.9.2).

3.4.2.3 Riveting. The sheath shall be riveted together with rivets as specified in 3.4.2. The head of the rivet shall be on upper side of the sheath and the split portion shall be flat against the underside of the sheath. All sharp edges shall be removed or turned under. The rivets shall be securely set but shall not straddle or cut the stitching, or unduly cut into the leather (see 4.9.2).

3.4.2.4 Color. The color of all components shall be black and match chip number 37038 of FED-STD-595 (see 4.9.2).

3.5. Performance. The performance characteristics of the knife shall be as follows:

3.5.1 Holding of the handle by the strap. When tested as specified in 4.10.1, the knife shall not move out of the position by more than 0.25 inch (6.35 mm).

3.5.2 Cutting. When tested as specified in 4.10.2, the blade shall show no undue wear, such as turning over, nicking or breaking of any part of the cutting edge.

3.5.3 Flexibility. When tested as specified in 4.10.3, the blade shall not break, or fail to return to the original shape, when bent through an angle of 9°.

3.6 Finish. All metal components of the knife shall be given a protective coating in accordance with type Z, class 2 of DOD-P-16232, after deburring and prior to assembly (see 4.9.2).

3.7 Identification of product. The letters US and the name or trademark of the manufacturer shall be stamped on the heel end of the blade as shown on Drawing number 81A5020A0000. The blade shall be indent stamped, without damage to the knife, with durable and legible letters in accordance with MIL-STD-130 (see 4.9.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.

3.8 Workmanship. Combat knives and/or sheaths shall be of high and uniform quality. The combat knife shall be free of sharp burrs and the sheath shall be free of sharp burrs or edges which may injure the hand of the user or adversely effect performance, reliability and durability. The appearance shall be the highest commercial practice for this type item (see 4.9.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Test equipment and inspection facilities. The manufacturer shall insure that test and inspection facilities of sufficient accuracy, quality and quantity are established and maintained to permit performance of required inspections.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformation inspection (see 4.4).
(c) Inspection of packaging (see 4.11).

4.3 First article inspection. The first articles shall be subjected to inspection and tests specified in Table I.

4.4 Quality conformance inspection. Quality conformance inspection and tests shall be as specified in Table I.

4.4.1 Sample. Sampling shall be in accordance with MIL-STD-105 with the lot or batch size the same as the total quantity of the

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:32Z
Check the source to verify that this is the current version before use.

contract unless otherwise directed by the contracting officer. The inspection level and acceptable quality level (AQL) shall be as specified in 4.6. Blades for inspection shall be in the as quenched (untempered) condition.

4.5 Inspection of packaging. Inspection of packaging shall be as specified in Table I.

4.5.1 Sample. Sampling shall be in accordance with MIL-STD-105 with each fully prepared shipping container containing sheathed knives, or sheaths if separate acquisition, representing one lot. The shipping container need not be sealed.

TABLE I. First article and quality conformance inspection.

Inspection	Requirement Paragraph	Inspection Paragraph
Group A		
Dimension	3.3	4.9.1
Visual	3.4	4.9.2
Group B		
Strap holding	3.5.1	4.10.1
Cutting	3.5.2	4.10.2
Flexibility	3.5.3	4.10.3
Group C		
Grain Size	3.4.1.2	4.10.4
Hardness	3.4.1.2	4.10.5
Paranitrophenol (for sheath)	3.4.2.1	4.10.6
Packaging (not applicable to First Article Inspections)	5.1, 5.2, 5.3	4.11

4.6 Classification of inspections. First article, quality conformance and packaging inspections shall be classified into groups A, B and C in accordance with the following groupings:

Group A - Nondestructive inspection shall be made in accordance with MIL-STD-105, general inspection level II, normal inspection AQL of 4.0.

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:32Z
Check the source to verify that this is the current version before use.

Group B - Generally nondestructive inspection shall be made in accordance with MIL-STD-105, general inspection level S-1, normal inspection AQL of 2.5.

Group C - Destructive inspections shall be made on two samples per batch of similar equipment or procedure and zero rejects are allowed.

4.7 Classification of defects. Defects are classified as major or minor in accordance with MIL-STD-105.

4.8 Numbering of defects. Defects are numbered for identification and reference purposes in accordance with the following:

101 through 199 - Major

200 through 299 - Minor

4.9 Inspection

4.9.1 Dimensional. The knife and sheath, or the sheath when separate acquired, shall be inspected for any nonconformance with the dimensional requirements of Drawing Nos. 81A5020A0000 and 81A5020A0001. Any noncompliance with the dimension shall be classified as a major defect.

4.9.2 Visual. The knife and sheath, or the sheath when separate acquisition, shall be inspected for the defects shown in Table II. Defects shall be classified as shown in Table II.

TABLE II. Classification of defects for visual examination.

Defect	Classification	
	Major	Minor
1. Metal components:		
(a) Surface rough, misaligned, or containing cracks, burrs, dents, pit marks or otherwise defective.	101	
(b) Surface unclean or containing embedded foreign matter.	102	(See Note 1)
(c) Dented, misshaped, distorted or otherwise defective.	103	
(d) Phosphate or preservative coating missing.	104	
2. Leather:		
(a) Open briar, scratches or scars:		

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:32Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects for visual examination - Continued.

Defect	Classification	
	Major	Minor
- Single scratch longer than 2 inches (50.8 mm).	105	
- Any scratch wider than 0.0625 inch (1.59 mm).	106	
- Three or more short scratches.	107	
- Single scratch longer than 0.5 inch (12.7 mm) but less than 2 inches (50.8 mm).		201
- Two scratches, each less than 0.5 inch (12.7 mm).		202
- Any die stab holes or cracky leather.		203
(b) Bronzing.	108	
(c) Fat wrinkles and heel scratches conspicuous at a distance of 4 feet (1.22 m).	109	
(d) Bloom, hard or boney leather.		204
(e) Pitted leather:		
- Six pits anywhere or four pits within 0.25 inch (6.35 mm).	110	
- Four pits anywhere or three pits within 0.25 inch (6.35 mm).		205
(f) Slaughter cuts:		
- Cut longer than 0.50 inch (12.7 mm).	111	
- Cut deeper than 0.25 of the thickness.	112	
- Cut wider than 0.0156 inch (0.397 mm).	113	
- All other slaughter cuts.	114(See Note 1)	
(g) Cleanness:		
- More than one permanent spot.	115	
- Removable spots or stains not removed.		206
- Unremoved hair or other appearance factors.		207
(h) Flaky leather:		
- Two or more adjacent folds or wrinkles, each wider than 0.0625 inch (1.59 mm).	116	

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:32Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects for visual examination - Continued.

Defect	Classification	
	Major	Minor
- Three adjacent folds or wrinkles, each over 0.0312 inch (0.794 mm), but less than 0.0625 inch (1.59 mm) wide.		208
3. Sheath components and assembly:		
(a) Any defective component or defect in assembly not classified herein.	117(See Note 1)	
(b) Any component or required operation omitted, but not classified herein.	118(See Note 1)	
(c) Flesh side of the leather on the outer side of the sheath.	119	
(d) Skived end of back inadequately attached.	120	
(e) Cut edges improperly colored or color not matching.		209
(f) Filler welt missing, improperly tapered or misaligned on outer edge.	121(See Note 1)	
(g) Sewing of sheath:		
(1) Needle chews.	122	
(2) Thread breaks, run-offs, incorrect type of stitch.	123	
(3) Thread color does not match the leather; various shades used.		210
(4) Loose seam.	124	
(5) Stitches per inch not within specified range.	125(See Note 1)	
(h) Strap holding not attached as required.	126(See Note 1)	
(i) Snap fastener:		
(1) Improper functioning.	127(See Note 2)	
(2) Loose, improperly clinched, cutting into leather.	128	

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:32Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects for visual examination - Continued.

Defect	Classification	
	Major	Minor
(3) Any sharp burrs or metal slivers.	129	
(4) Not centered on strap.	130(See Note 1)	
(j) Riveting:		
(1) Insecurely set (i.e., pulling away from leather).	131	
(2) Improperly clinched, cutting of leather or stitches.	132	
(3) Improperly located or inverted (clinched on outside).	133(See Note 1)	
(4) Any sharp burrs or metal slivers.	134	
4. Knife handle:		
(a) Any component loose, handle not integral with blade.	135	
(b) Leather portion not smooth, not grooved or not colored to match.	136(See Note 1)	
(c) Butt pin not peened or not ground smooth.	137	
(d) Tang protruding from butt plate surface.		211
(e) Guard not at right angles to the blade.	138(See Note 1)	
(f) Guard edges not flush with blade heel.	139	
5. Knife blade:		
(a) Blood groove not as specified.	140	
(b) Point broken or not sharp.	141	
(c) Cutting edge of blade not uniformly honed to a keen edge.	142	
(d) Cutting edge contains nicks or burrs.	143	
(e) Back edge of blade not ground to the tip.	144	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects for visual examination - Continued.

Defect	Classification	
	Major	Minor
(f) Contour lines not clearly defined.		212
(g) Identification markings:		
(1) Missing or illegible.		213
(2) Method of application weakens tang.	145	
6. Color: Not as specified.	146(See Note 1)	

Note 1: Major when it seriously affects the serviceability or appearance; otherwise, it is to be classified as a minor defect.

Note 2: The snap fasteners shall be checked for proper functioning by snapping closed and unsnapping at least three times.

4.10 Tests

4.10.1 Strap holding. The effectiveness of the strap in holding the knife in the sheath shall be determined by the following test: with the strap snapped shut over the handle of the sheathed knife, grasp the sheath near the tip end without pinching the blade; raise the arm overhead with the knife butt uppermost, then suddenly swing the arm downward through an arc in a rapid motion, stopped suddenly at the bottom of the arc. The guard of the knife shall not have moved away from the sheath at the completion of this hurl.

4.10.2 Cutting. The keenness of the blade shall be tested by cutting at least ten shavings, not less than 0.0625 inch (1.59 mm) thick, from a strip of oak or other wood of similar hardness. The blade shall enter into the wood at an angle of not less than 30° and all portions of the cutting edge shall be capable of producing a clean cut without undue effort. After ten shavings have been cut, the blade shall have no defects in the cutting edge.

4.10.3 Flexibility. The tip of the blade shall be secured by inserting the tip into a contoured metal fixture to a depth of 1.5 inches (38 mm) from the point. Pressure shall be of such magnitude that it shall cause bending of the blade through an angle of 9°. The blade shall not break during the bending and when the pressure is removed, the blade shall return to the original shape with no deformation. (See 3.5.3).

4.10.4 Grain size. The fracture grain size of the blade in the as quenched condition shall be determined by comparison with the

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:32Z
Check the source to verify that this is the current version before use.

ADDRESS (Include ZIP Code) IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:

Shepherd fracture grain size standards in ASTM E112. The blade shall be notched at the middle of the length and fractured by impact. (See 3.4.1.2)

4.10.5 Hardness. The Rockwell hardness of the steel shall be determined as specified in method 243, hardness scale C of FED-STD-151. The hardness of the blade shall be determined at the heel, center and point not less than 0.25 inch (6.35 mm) from the cutting edge. The hardness of the tang in the transition area shall be determined in the center on the opposite side to the marking. Three hardness determinations shall be made on the remaining portion of the tang evenly distributed along its length. (See 3.4.1.2).

4.10.6 Paranitrophenol. The paranitrophenol content in the leather shall be determined as specified in method 6711 of FED-STD-311.

4.11 Inspection of packaging. An inspection lot shall be expressed in units of one fully prepared shipping container containing sheathed knives, or sheaths, if separate acquisition, fully prepared for delivery, from essentially the same materials and components offered for acceptance at one time. The sample shipping container need not be sealed. Each of the fully prepared shipping containers selected as a sample unit from the lot shall be visually examined to determine that the packaging and marking requirements conform to the requirements specified herein. The defects shall be classified as specified in Table III.

TABLE III. Examination of packaging and marking.

Examine	Defect	Classification
		Major
Materials	Any nonconforming component; component omitted, damaged or otherwise defective.	147
Workmanship	Incomplete closure of case liners or container flaps; loose strapping; bulging or distortion of containers.	148
Weight and content	Number per container is more or less than required; gross weight exceeds maximum for container used.	149
Markings	Missing, incorrect, illegible; improper size, location, sequence or method of application.	150

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation and Packaging. Preservation and packaging shall be level A or commercial, as specified (see 6.2).

5.1.1 Level A. Each knife, prior to being packaged, shall be fully inserted into the sheath. The strap shall be snapped closed around the top of the handle. Each sheathed knife, or sheath when separate acquisition, shall then be heat sealed within a snug fitting bag conforming to type I, class B, style 2 of MIL-B-117. Prior to and during the heat sealing operation, excess air shall be exhausted to the extent necessary to permit packaging of the required quantity in the fiberboard box. Ten bagged sheathed knives, or sheaths when separate acquisition, shall be placed within a fiberboard box conforming to PPP-B-636, type CF or SF, domestic class, variety SW, grad 275. All seams and joints shall be sealed with minimum of 3-inch (76 mm) wide tape as specified in PPP-T-60.

5.1.2 Commercial. Commercial preservation and packaging shall be in accordance with ASTM D3951-82.

5.2 Packing. Packing shall be level A, B or commercial, as specified (see 6.2). Exterior containers (see 5.2.1, 5.2.2, and 5.2.3) shall be of a minimum tare weight and cube consistent with the protection required and shall contain equal quantities of identical stock.

5.2.1 Level A. Eight boxes, 80 sheathed knives, or sheaths when separate acquisition preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to one of the following:

PPP-B-576, class 2
PPP-B-585, class 3
PPP-B-591, class II
PPP-B-601, overseas type
PPP-B-621, class 2, style 4

or, four boxes, 40 sheathed knives, or sheaths when separate acquisition, preserved and packaged as specified in 5.1, shall be packed in a fiberboard container conforming to PPP-B-636, type CF or SF, weather resistant class, variety SW, grade V3c or V3s. Closure of wooden or fiberboard containers shall be as specified in the applicable box specification or appendix thereto.

5.2.2 Level B. A quantity of sheathed knives, or sheaths when separate acquisition, preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to one of the following:

PPP-B-576, class 1
PPP-B-585, class 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.

PPP-B-591, class 1
PPP-B-601, domestic type
PPP-B-621, class 1, style 4
PPP-B-636, type CF, domestic class

5.2.3 Commercial. Commercial packaging of supplies and equipment shall be as specified in ASTM D3951-82.

5.3 Marking. Marking shall be level A, B or commercial as specified (see 6.2).

5.3.1 Levels A and B. In addition to any special markings required by the contract, each unit pack, intermediate and exterior container and unitized load shall be marked as specified in MIL-STD-129.

5.3.2 Commercial. Commercial marking shall be as specified in ASTM D3951-82.

6. NOTES

6.1 Intended use. The knife with sheath covered by this specification is intended for combat use.

6.2 Ordering data

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) When sheaths are to be acquired separately (see 1.1).
(c) Whether first article is required (see 3.1).
(d) Level of preservation and packing required (see 5.1 and 5.2).
(e) Level of marking required (see 5.3).

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph no.	Data Requirements	Applicable DID no.	Options
4.3	First Article Inspection Procedure	DI-T-4901	------

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.

4.3	First Article Inspection Report	DI-T-4902	-------
4.4	Production/Acceptance Inspection Procedures	DI-T-4903	-------
4.4	Production Inspection Reports	DI-T-4904	

(Copies of DIDs required by contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.3 Subject term (key word) listing.
Blade
Combat
Grip
Knife
Sheath

6.4 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Preparing activity:
Navy - MC
Project No. 1095-N172

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-K-20277G(MC)	KNIFE, COMBAT: AND SHEATH

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding General
Marine Corps Research, Development
and Acquisition Command
Washington, D.C. 20380-0001

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:32Z
Check the source to verify that this is the current version before use.