MIL-F-20236D(SHIPS)
AMENDMENT-2
25 July 1969
SUPERSEDING[1]
AMENDMENT-1
22 June 1964

MILITARY SPECIFICATION

FITTINGS, TUBE AND PIPE, BUTT-WELDING,

300 P.S.I. AND 775° F. MAXIMUM

This amendment forms a part of Specification MIL-F-20236D(SHIPS), 1 August 1963.

Page 2

3.10, delete and substitute:

"3.10 Dimensions. The nominal dimensions of all fittings shall be as shown in USAS B16.9, except as specified in 3.10.1. Unless otherwise specified herein, the tolerances on fittings and dimensions shall be in accordance with USAS B16.9. The wall thickness shall be as shown in table II. For reducing fittings, the maximum wall thickness at any location shall be based on the external diameter at that location."

Page 3

Table II, make the following changes:
(a) Title, after "bends" insert ", reducers".
(b) Delete "Thickness T" and substitute "Thickness T min[2]".
(c) At the end of table, add: "[2] Fitting wall thickness shall not exceed 112.5 percent of T min."

3.11, delete and substitute:

"3.11 Marking. - Each fitting shall be legibly and permanently marked by means of electro-etch or electric pencil. The use of low stress stamping is permitted provided that the depth of the impression does not exceed 0.010 inch and the minimum wall thickness is maintained. The marking shall include the following:

(a) Size
(b) Pressure rating
(c) Manufacturers trade mark
(d) Specification number
(e) Heat number."

4.1, delete and substitute:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Page 4

Table III, under column "I.D. Socket" opposite "2 inch Nominal size of outlet": Delete "2.000" and substitute "2.406".

[1] CHANGES FROM PREVIOUS ISSUE. THE OUTSIDE MARGINS OF THIS DOCUMENT HAVE BEEN MARKED "#" TO INDICATE WHERE CHANGES (DELETIONS, ADDITIONS, ETC.) FROM THE PREVIOUS ISSUE HAVE BEEN MADE. THIS HAS BEEN DONE AS A CONVENIENCE ONLY AND THE GOVERNMENT ASSUMES NO LIABILITY WHATSOEVER FOR ANY INACCURACIES IN THESE NOTATIONS. BIDDERS AND CONTRACTORS ARE CAUTIONED TO EVALUATE THE REQUIREMENTS OF THIS DOCUMENT BASED ON THE ENTIRE CONTENT AS WRITTEN IRRESPECTIVE OF THE MARGINAL NOTATIONS AND RELATIONSHIP TO THE LAST PREVIOUS ISSUE.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T07:28Z
Check the source to verify that this is the current version before use.

Figure 1, title: Add "For 'C' dimension see 3.10.1".

Preparing activity:
Navy - SH
(Project 4730-N0983)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:28Z
Check the source to verify that this is the current version before use.