REVIEWER: GL MD MI MR PS
USER: MO SM

FED. SUP CLASS
6850

PART NUMBER	PACKAGING
MS36435-1	5 gal pail
MS36435-2	55 gal drum

SAFETY PRECAUTIONS: DANGER! HARMFUL OR FATAL IF SWALLOWED
WARNING! FLAMMABLE

If swallowed, do not induce vomiting. Avoid prolonged or repeated breathing of vapor. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid contact with eyes; in case of contact, flush with plenty of water for at least 15 minutes and get medical attention. The use of gloves and protective equipment is recommended.

INTENDED USE: For use in removing oils, greases, asphalts, tars, and some rust preventative compounds from copper alloy (brass, bronze) and ferrous surfaces. Not intended for use on aluminum or zinc.

MATERIAL: Clear liquid. Concentrated.

REQUIREMENTS: The compound shall be organic solvents, soap and water, soluble in water to form a clear or opalescent solution.

Minimum flash point, 180 degrees Fahrenheit, determined by the Cleveland OpenCup method. Maximum pour point, 10 degrees Fahrenheit.

The solvent content of the compound shall be not less than 45 percent by weight.

DIRECTIONS FOR USE: Dilution may be from two to ten parts of fresh water to one part of the compound as received, depending upon the type and degree of soil to be removed.

Apply the diluted compound to the soiled object by spraying, dipping or brushing, and allow to soak until the soil is softened. A high pressure water rinse will emulsify the compound and remove the soil.

For closed systems, such as fuel oil heaters, the following procedure shall be used: Drain the system and steam for one hour or until no more oily drops appear in the exit steam. Recirculate diluted compound heated to about 150 degrees Fahrenheit through the system for one to two hours. Rinse system with hot water for approximately 15 minutes and then steam for 15 to 30 minutes. If desired, a final blow-out with air may be made.

NOTE: 1. Referenced documents shall be of the issue in effect on date of invitations for bid.

APPROVED 12 March 1965 REVISED

This standard has been approved by the Munitions Command Department of the Army and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

P.A. MU Other Cust	TITLE CLEANING COMPOUND, SOLVENT heavy duty	MILITARY STANDARD MS36435(MU)
Procurement Specification MIL-C-20207	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:40Z
Check the source to verify that this is the current version before use.