
FED. SUP CLASS
5305



NOMINAL SIZE		#10 (.190)	1/4	5/16	3/8	1/2
THREADS PER INCH		32UNF-3A	28UNF-3A	24UNF-3A	24UNF-3A	20UNF-3A
D. BODY DIAMETER	MAX	.190	.250	.3125	.375	.500
	MIN	.1867	.2464	.3084	.3705	.4948
A HEAD DIAMETER	THEO. SHARP MAX	.411	.531	.656	.781	.937
	ABS. MIN	.359	.480	.600	.720	.872
H HEAD HEIGHT	REFERENCE MAX	.127	.161	.198	.234	.251
J SOCKET WIDTH ACROSS FLATS	MAX	.1270	.1582	.1895	.2207	.3155
	MIN	.1250	.1562	.1875	.2187	.3125
T KEY ENGAGEMENT	MIN	.087	.111	.135	.159	.172
R RADIUS	MAX	.019	.025	.031	.037	.050
MINIMUM BREAKING STRENGTH	LBS	1400	2550	4060	6150	11200

L LENGTH	TOL.	DASH No.	FIIN	DASH No.	FIIN	DASH No.	FIIN	DASH No.	FIIN	DASH No.	FIIN
3/8	+1/64 -1/64	1		9		17					
1/2		2		10		18					
5/8		3		11		19		25			
3/4		4		12		20		26			
1		5		13		21		27		32	
								28		33	
1-1/4	+1/32 -1/64	6		14		22		29		34	
1-1/2		7		15		23		30		35	
1-3/4										36	
2										37	

MATERIAL: STEEL, CORROSION RESISTING, IN ACCORDANCE WITH FEDERAL STANDARD #66, CLASS 303 OR CLASS 304; ULTIMATE LOAD - 70,000 PSI MIN TENSILE STRENGTH; PROOF LOAD - 30,000 PSI MIN YIELD STRENGTH; ELONGATION - 35 PERCENT MIN.

PROTECTIVE COATING: PASSIVATED IN ACCORDANCE WITH THE PROCUREMENT SPECIFICATION.

THREADS: THE THREADS SHALL BE IN ACCORDANCE WITH SCREW-THREAD STANDARDS FOR FEDERAL SERVICES, HANDBOOK H-28.

MINIMUM THREAD LENGTH: THE MINIMUM USABLE THREAD LENGTH SHALL BE EQUAL TO 2D PLUS 1/2". THE THREAD LENGTH TOLERANCE SHALL BE EQUAL TO THE NOMINAL DIAMETER. SCREWS TOO SHORT FOR APPLICATION OF THE FORMULA SHALL BE THREADED AS CLOSE TO THE HEAD AS PRACTICABLE.

POINT CHAMFER: THE POINTS SHALL BE FLAT AND CHAMFERED. THE FLAT SHALL BE NORMAL TO THE AXIS OF THE SCREW. THE CHAMFER SHALL EXTEND SLIGHTLY BELOW THE ROOT OF THE THREAD AND THE EDGE BETWEEN THE FLAT AND THE CHAMFER MAY BE ROUNDED. THE INCLUDED ANGLE OF THE THREADED POINT SHALL BE APPROXIMATELY 90°. CHAMFERING OF SCREW SIZES UP TO AND INCLUDING #8 SHALL BE AT THE OPTION OF THE MANUFACTURER.

DIMENSIONS: ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.

PART NUMBER: THE MS PART NUMBER CONSISTS OF THE MS NUMBER, PLUS THE DASH NUMBER. EXAMPLE: MS24672 -1.

NOTES: (1) REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
(2) THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.

Ⓐ CANCELLED AFTER 27 MAR. 61.
NO SUPERSEDING STANDARD

APPROVED GAAP 60 REVISED Ⓐ 27 MAR. 61.

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A.	TITLE	MILITARY STANDARD
ORD Other Cust SHIPS	SCREW, CAP, SOCKET HEAD, FLAT COUNTERSUNK, CORROSION RESISTING STEEL, UNF-3A	MS24672
PROCUREMENT SPECIFICATION FF-S-86	SUPERSEDES:	SHEET 1 OF 1

DD FORM SEP 67 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:59Z
Check the source to verify that this is the current version before use.