INCH-POUND


MS28759D
19 April 2007
SUPERSEDING
MS28759C
6 April 2001

DETAIL SPECIFICATION SHEET

HOSE ASSEMBLY, RUBBER, HYDRAULIC 3,000 PSI, STRAIGHT TO STRAIGHT, FLARED TUBE FIELD ATTACHABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-8790.



Dash size number (see note 4)	Tubing OD ref. inch (mm)	Hose ID ref. inch (mm)	End fittings PIN (see note 5)
-4	.25 (6.35)	.22 (5.59)	MS28760-4
-5	.31 (7.87)	.28 (7.11)	MS28760-5
-6	.38 (9.65)	.34 (8.64)	MS28760-6
-8	.50 (12.70)	.44 (11.18)	MS28760-8
-10	.63 (16.00)	.56 (14.22)	MS28760-10
-12	.75 (19.05)	.69 (17.53)	MS28760-12
-16	1.00 (25.40)	.88 (22.35)	MS28760-16

FIGURE 1. Hose assembly, flared tube dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:58Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are for information only.
3. Hose assembly lengths (L) shall be as specified with the following tolerances:
   a. Under 18 inches (0.46 m) long (± .13 inch (3.3 mm)).
   b. Over 18 to 36 inches (0.46 to 0.91 m) long (± .25 inch (6.4 mm)).
   c. Over 36 to 50 inches long (0.91 to 1.27 m) (± .50 inch (12.7 mm)).
   d. Over 50 inches long (Tolerance ± 1%).
4. Dash size number refers to the nominal outside diameter of the passageway in sixteenths (1/16) of an inch. A dash 8 (-8) has an outside diameter of one-half inch (8/16).
5. Part or Identifying Number (PIN).


FIGURE 1. Hose assembly, flared tube dimensions and configuration - Continued.

REQUIREMENTS:

Hose assemblies shall be as specified on figure 1.

The hose assembly identification shall be marked in accordance with MIL-DTL-8790.

PIN example:



Example of a PIN: MS28759-80164. MS28759 hose assembly, .500 inch (1/2 inch) passageway diameter, length 16.500 inches.

For supersession data, see table I.

TABLE I. Supersession table.

Old PIN	Superseding PIN
MS28759-4-XXXX	MS28759EXXXX
MS28759-5-XXXX	MS28759FXXXX
MS28759-6-XXXX	MS28759GXXXX
MS28759-8-XXXX	MS28759HXXXX
MS28759-10-XXXX	MS28759JXXXX
MS28759-12-XXXX	MS28759KXXXX
MS28759-16-XXXX	MS28759MXXXX

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:58Z
Check the source to verify that this is the current version before use.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-8790, this document references the following:

MS28760
MIL-DTL-8788

CONCLUDING MATERIAL

Custodians:
Army - AT
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4720-2005-021)

Review activities:
Army - AV, MI
Navy - SA
Air Force - 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:58Z
Check the source to verify that this is the current version before use.