NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/89C
1 May 1997
SUPERSEDING
MIL-D-3943/89B
24 June 1994

DETAIL SPECIFICATION SHEET

DECORATION, NATIONAL INTELLIGENCE DISTINGUISHED SERVICE MEDAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



MATERIAL:
BASE: Gilding Metal
DEVICE: Red Brass

DASH NO.
-1: Regular Size
-2: Miniature Size

FINISH:
BASE: Hard Enameled, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.
DEVICE: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
BASE: HEIGHT (Including Lug):
-1: 1-9/16 inches (3.97 cm) (REF)
-2: 25/32 inch (1.98 cm) (REF)
WIDTH (Overall):
-1: 1-1/2 inches (3.81 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:27Z
Check the source to verify that this is the current version before use.

THICKNESS (At Thickest Point):
-1: 0.100 inch ± 0.005 inch (0.254 cm ± 0.012 cm)
-2: 0.070 inch ± 0.005 inch (0.178 cm ± 0.012 cm)
DEVICE:
DIAMETER:
-1: 13/16 inch (2.06 cm) (REF)
-2: 13/32 inch (1.03 cm) (REF)
THICKNESS (At Thickest Point):
-1: 0.100 inch ± 0.005 inch (0.254 cm ± 0.012 cm)
-2: 0.080 inch ± 0.005 inch (0.103 cm ± 0.012 cm)
ASSEMBLED THICKNESS (At Eagle's Shield):
-1: 0.200 inch ± 0.010 inch (0.508 cm ± 0.025 cm)
-2: 0.150 inch ± 0.010 inch (0.381 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enamel colors shall be as indicated. The colors shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NO.
Blue	18
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. The device shall be soft soldered to the base in the position shown.

5. Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type XII, Style 3 with a Class 1 or 1A pad.

6. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/224.

7. The lapel button shall conform to MIL-DTL-11484/118.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 45
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
Navy - MC
Coast Guard - CG
DLA - CT

(Project No. 8455-0887)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:27Z
Check the source to verify that this is the current version before use.