NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/92E
1 May 1997
SUPERSEDING
MIL-D-3943/92D
24 June 1994

DETAIL SPECIFICATION SHEET

DECORATION, COMMANDER'S AWARD FOR CIVILIAN SERVICE, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:
HEIGHT (Including Lug):
-1: 1-7/16 inches (3.65 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T00:41Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
-1: 1-3/16 inches (3.02 cm) (REF)
-2: 5/8 inch (1.59 cm) (REF)

THICKNESS (Bottom Edge):
-1: 0.085 inch ± 0.010 inch (0.216 cm ± 0.025 cm)
-2: 0.070 inch ± 0.010 inch (0.178 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type XVI with a Type XVI, Class 1 or 3 pad.

3. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/231.

4. The label button shall conform to MIL-DTL-11484/121.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0887)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T00:41Z
Check the source to verify that this is the current version before use.