MIL-T-5421B
AMENDMENT 1
10 May 1978

MILITARY SPECIFICATION

TUBES, PITOT, ELECTRICALLY HEATED, AIRCRAFT

This amendment forms a part of Military Specification MIL-T-5421B, dated 20 May 1969, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add boxed paragraph to bottom center of page.

> Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: HQ AFLC CASO/LODS, Federal Center, Battle Creek, MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

3.2, add the following sentence to the end of paragraph:

"Reclaimed materials shall be utilized to the maximum extent possible within the quality limits required by this document."

PAGE 9

4.5, delete and substitute the following:

" 4.5 Packaging inspection

4.5.1 Quality conformance. The inspection of the preservation-packaging and interior package marking shall be in accordance with group A and B quality conformance inspection requirements, section 4 of MIL-P-116. The sampling and inspection of the packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of applicable container specification and the marking requirements of MIL-STD-129.

4.5.2 First article. When the unit container is capable of serving as the shipping container First Article Inspection, and rough handling tests as outlined in section 4 of MIL-P-116, shall be accomplished followed by a functional test of the unit to insure freedom from operational malfunction."

FSC 6610

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:38Z
Check the source to verify that this is the current version before use.

5., delete in its entirety and substitute the following:

" 5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A, B, or specified by procuring activity.

5.1.1 Level A.

5.1.1.1 Cleaning. Unit shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Immediately after cleaning, the unit shall be dried following any one or combination of the drying procedures of MIL-P-116. The drying procedures employed shall not be injurious to the unit.

5.1.1.3 Preservation application. Not required.

5.1.1.4 Unit packaging. Unless otherwise specified by the procuring activity, each unit shall be packaged in quantity unit packs of one each in accordance with method 1A of MIL-P-116. Overbox each completed pack in a PPP-B-636 fiberboard, weather-resistant class box. Cushioning material between bag and container shall be of a type, density, and thickness that will protect the unit from impact shock damage when tested as specified in paragraph 4.5.2 of this specification.

5.1.2 Level B. Each unit shall be packaged as indicated for Level A except that a specification PPP-B-636 class domestic box shall be used as the unit container.

5.1.3 Level C. Units shall be cleaned, dried, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Units packaged as specified in 5.1 shall be packed in shipping containers conforming to specification PPP-B-636 weather-resistant. Closure and reinforcing requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:38Z
Check the source to verify that this is the current version before use.

shall be in accordance with the appendix of PPP-B-636. For the Army, specification PPP-B-601 plywood box, shall be used for the shipping container. Insofar as practicable, exterior containers shall be of a uniform shape and size and of minimum cube and tare consistent with the protection required.

5.2.2 Level B. Units packaged as specified in 5.1 shall be packed in shipping containers conforming to specification PPP-B-636, class domestic. Closure and reinforcing requirements shall be in accordance with the appendix of PPP-B-636. For the Army, the shipping containers shall conform to specification PPP-B-636 class weather resistant.

5.2.3 Level C. Packaged units shall be packed in shipping containers in a manner that will afford adequate protection against damage during direct domestic shipment from the supply source to the first receiving activity. These packs shall conform to applicable carrier rules and regulations.

5.3 Marking. In addition to any special marking required by the contract or order, each unit package and shipping container shall be marked in accordance with MIL-STD-129."

Custodian:
Air Force - 99
Army - AV
Navy - AS

Reviewer:
Air Force - 11

Preparing Activity:
Air Force - 99

Project Number:
6610-0403

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:38Z
Check the source to verify that this is the current version before use.