MIL-P-10585A
12 AUGUST 1952
SUPERSEDING
MIL-P-10585(CmlC)
5 OCTOBER 1950

MILITARY SPECIFICATION

PLUG, FILLING, PORTABLE FLAME THROWER, C23

This specification was approved by the Departments of the Army, the Navy, and the Air Force for the use of procurement services of the respective Departments.

1. SCOPE

1.1 This specification covers one type of filling plug for use with the M2A1 portable flame thrower.

2. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS

2.1 The following specification, standards, and drawings, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATION

FEDERAL

NN-B-621 —Boxes, Wood, Nailed and Lock-Corner.

MILITARY

JAN-P-106 —Packaging and Packing for Overseas Shipment Boxes, Wood, Nailed.

MIL-P-116 —Preservation, Methods of.

JAN-P-120 —Packaging and Packing for Overseas Shipment Cartons, Folding, Paperboard.

JAN-P-133 —Packaging and Packing for Overseas Shipment Boxes; Set-Up, Paperboard.

MIL-L-10547 —Liners, Case, Waterproof.

NAVY DEPARTMENT

General Specifications for Inspection of Material.

STANDARDS

MILITARY

MIL-STD-10 —Surface Roughness, Waviness, and Lay.

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129—Marking of Shipments.

DRAWINGS

CHEMICAL CORPS

C81-1-2450 —Plug, Filling, Portable Flame Thrower, C23—Assembly and Bill of Material.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 **Material.**—All materials and components used in the manufacture and assembly of the plug shall conform to the specifications and drawings forming a part of this specification.

3.2 **Manufacture and assembly.**—The plug shall be manufactured and assembled as

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:15Z
Check the source to verify that this is the current version before use.

specified on Drawing C81-1-2450 and subsidiary drawings listed thereon. Surface roughness, waviness, and lay specified by symbols on detail drawings shall comply with the applicable classes specified in Standard MIL-STD-10.

3.3 **Leakage.**—The plug shall not leak when tested as specified in 4.4.

3.4 **Workmanship.**—All work shall be done in a neat and workmanlike manner.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 **Lot.**—A lot shall consist of the plugs produced by one manufacturer, from the same materials, and under essentially the same manufacturing conditions. The inspection lot for nondestructive inspection, within the above limitations, shall be designated by the inspector.

4.2 **Sampling for nondestructive inspection.**—Sampling for nondestructive inspection shall be conducted in accordance with the authorized classification of defects (4.3.4) and Standard MIL-STD-105.

4.3 **Inspection.**

4.3.1 *Components.*—The inspector shall ascertain that, prior to assembly, all materials or components of the plug procured under separate specifications or drawings have been inspected, tested, and accepted in accordance with their respective specifications or drawings.

4.3.2 *Packaging, packing, and marking.*—The inspector shall inspect the packaging, packing, and marking of the plug for compliance with section 5.

4.3.3 *Procedures.* — For Navy purchases, the general inspection procedures shall be in accordance with General Specifications for Inspection of Material.

4.3.4 *Classification of defects.*—Inspection of the plug shall be conducted as follows:

4.3.4.1 *Plug, filling, portable flame thrower, C23—assembly.*—(Dwg. C81-1-2450)

Categories and defects	*Gage or other method of inspection*
Major A AQL 0.1 percent	
1a. Leakage	4.4
Major AQL 0.5 percent	
1. Thread pitch diameter and major diameter	E24-1-135 and E24-1-212
2. Component missing	Visual
3. Component assembled incorrectly	Visual
4. Component damaged	Visual
5. Valve nonfunctioning	Functional
6. Stamping missing, illegible, or incorrect	Visual
Minor AQL 1.0 percent	
51. Coating missing, inadequate, or incorrect	Visual
Incidental AQL 10 percent	
101. Contamination	Visual

4.4 **Leakage test.**—The plug shall be tested as follows: Assemble the plug, hand-tight, into a suitable adapter connected to the source of pressure. Open the valve in the plug and then close it hand-tight. Build up an air pressure to 500 p.s.i. and observe for leaks by use of a soap solution. Bleed the valve slightly, reclose by hand, and again observe for leaks.

5. PREPARATION FOR DELIVERY

5.1 **Packaging.**

5.1.1 *For shipment to assembly plants.*—The plug shall be packaged in either a paperboard folding carton or a paperboard set-up box conforming to Specification JAN-P-120 or JAN-P-133 as applicable.

5.1.2 *For shipment as spare parts.*—The plug shall be packaged in either a paperboard folding carton or a paperboard set-up box conforming to Specification JAN-P-120 or JAN-P-133 as applicable. The carton or

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:15Z
Check the source to verify that this is the currentversion before use.

box shall be wrapped and sealed in accordance with method IA–2 of Specification MIL–P–116.

5.2 **Packing.**

5.2.1 *For shipment to assembly plants.*—One hundred plugs, packaged as specified in 5.1.1, shall be packed in a style 2, 2½, or 4 nailed wood box conforming to Specification NN–B–621.

5.2.2 *For shipment as spare parts.*—One hundred plugs, packaged as specified in 5.1.2, shall be packed in a style 2, 2½, or 4 nailed wood box conforming to Specification JAN–P–106. The box shall be fitted with a waterproof case liner conforming to Specification MIL–L–10547 and sealed in accordance with appendix I thereto. The box shall be bound in accordance with appendix I to Specification JAN–P–106.

5.3 **Marking.**—In addition to any special marking required by the contract or order, all individual packages and all shipping containers shall be marked in accordance with Standard MIL–STD–129.

6. NOTES

6.1 **Ordering data.** — Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Whether shipment to assembly plants or as spare parts is required.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Custodians:
Army—Chemical Corps
Navy—Marine Corps

Other Interest:
Army—T.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:15Z
Check the source to verify that this is the current version before use.