MIL-R-10572C(ME)
7 April 1976
SUPERSEDING
MIL-R-10572B(MO)
28 August 1964

MILITARY SPECIFICATION

RAILWAY CARS, TRAILER: MAINTENANCE, 36-, 39-3/8-, 42-, 56-1/2-, 60-, 63-, AND 66-INCH GAGES, 5-TON, 4-WHEEL, DOMESTIC AND FOREIGN SERVICE

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers 5-ton trailer roadway maintenance cars.

1.2 Classification. Trailer cars shall be one of the following gages, as specified (see 6.2):

Gage:

36-inch
39-3/8-inch
42-inch
56-1/2-inch
60-inch
63-inch
66-inch

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

FSC 2230

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-P-3320	- Painting and Marking: Freight and Maintenance Cars.
MIL-P-3558	- Plates, Identification: Locomotives, Railway Cars, and Work Equipment.
MIL-B-26195	- Boxes, Wood-Cleated, Skidded, Load-Bearing Base.

STANDARDS

FEDERAL

FED. STD. No. 356	- Commercial Packaging of Supplies and Equipment.

MILITARY

MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.
MS35832	- Diagram; Equipment, Composite, Railway, 36-, 39-3/8-, and 42-In. Gages, Foreign Service.
MS35833	- Diagram, Equipment, Composite, Railway, 56-1/2-, 60-, 63-, and 66-In. Gages, Foreign Service.

Copies of specifications and standards required by contractors in nection with specific procurement functions should be obtained from procuring activity or as directed by the contracting officer.)

.2 Other publications. The following documents form a part of s specification to the extent specified herein. Unless otherwise icated, the issue in effect on date of invitation for bids or request proposal shall apply.

MERICAN RAILWAY ENGINEERING ASSOCIATION (AREA)

Manual of Recommended Practice, Chapter 27, Part 2 - Roadway Machines.

Application for copies should be addressed to the American Railway ineering Association, 59 East Van Buren Street, Chicago, IL 60605.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 53 - Welded and Seamless Steel Pipe.
A 307 - Low Carbon Steel Externally and Internally Threaded Standard Fasteners.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AMERICAN WELDING SOCIETY, INC. (AWS)

D1.1 - Structural Welding Code.

(Application for copies should be addressed to the American Welding Society, Inc., 2501 North West Seventh Street, Miami, FL 33125.)

ASSOCIATION OF AMERICAN RAILROADS (AAR)

Manual of Standards and Recommended Practices, Section A - Specifications for Materials:

M-110 - Rivet Steel and Rivets.
M-116 - Steel, Structural, Shapes, Plates, and Bars.
M-129 - Bars and Shafting, Carbon Steel, Cold Finished.
M-907 - Lumber.

Electrical Manual of Standard and Recommended Practice, Section 6 - Welding and Cutting.

Supplement to Manual of Standards and Recommended Practices:

Plate B - Equipment Diagram for Unrestricted Interchange Service.

(Application for copies should be addressed to the Association of American Railroads, 1920 L Street, NW, Washington, DC 20036.)

NATIONAL BUREAU OF STANDARDS (NBS)

Handbook H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

Technical society and technical association specifications and stand-
s are generally available for reference from libraries. They are
o distributed among technical groups and using Federal agencies.)

. REQUIREMENTS

.1 Description. The trailer maintenance cars shall be of 5-ton
acity, shall be supported on four wheels equipped with adjustable
xes, and shall be capable of transporting a minimum of 10,000 pounds
supplies for use in maintenance of way work in both domestic and
eign service.

.2 First article (first-produced trailer car). The contractor shall
nish one or more trailer cars of each gage as specified (see 6.2) for
mination and testing within the time frame specified (see 6.2) to
ve that his production methods will produce trailer cars that comply
h the requirements of this specification. Examination and tests shall
as specified in Section 4 and shall be subject to surveillance and
roval by the Government (see 6.3).

.3 Material. Material shall be as specified herein. Materials not
cified shall conform to AREA requirements.

.3.1 Steel. Steel shall conform to AAR Specification M-116 or M-129.

.3.2 Bolts, nuts, and rivets. Bolts and nuts shall conform to ASTM
07 or better. Rivets shall conform to AAR Specification M-110.

.3.3 Pipe. Pipe shall conform to ASTM A 53.

.3.4 Lumber. Lumber shall be kiln-dried wood, select grade, conforming
AAR Specification M-907. Moisture content shall not exceed 15 percent.

.4 Dimensions and weights. Dimensions and weights shall be as
lows:

Overall length (deck)	- 84 inches (nominal)
Overall width	- 67 inches (nominal)
Wheel diameter	- 16 inches (nominal)
Capacity	- 5 tons (minimum)
Weight	- 1000 pounds (maximum)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

3.4.1 Maximum load. The car shall support a maximum static load of 12,500 pounds (6.25 tons) for a period of not less than 10 minutes. The load shall be evenly distributed over the entire deck of the car. The car shall roll free on a straight tangent level track.

3.4.2 Deck camber. The allowable deflection and negative camber of the car deck when loaded with 5 tons (10,000 pounds) static load shall be not greater than 1/4 inch.

3.5 Clearances. Cars shall not exceed the following clearance limitations:

Narrow gage (36-, 39-3/8-, and 42-inch gages) - MS35832
Broad gage (56-1/2-, 60-, 63-, and 66-inch gages) - MS35833
Standard gage (56-1/2-inch gage) - AAR Plate B.

3.6 Maintainability. All parts and components subject to adjustment or replacement by operating or maintenance personnel shall be accessible. Adjusting facilities, where provided, shall operate without interference and shall maintain such adjustments under all conditions of service.

3.7 Tolerances and fits. Unless otherwise specified herein, tolerances and fits shall conform to AREA requirements.

3.8 Curvature. The trailer cars shall be capable of negotiating a 150-foot radius curve.

3.9 Underframe. Underframe shall be structural steel. The frame shall be braced and gusseted with all parts welded, riveted, or bolted together in a manner to maintain alinement under all operational conditions.

3.10 Deck. Decking shall be fabricated from seasoned lumber as specified herein and shall be bolted to the diagonal bracing. An angle of steel as specified herein shall be applied to the ends and sides of the deck.

3.11 Lifting handles. Fixed lifting handles shall be provided at each end of the car. Handles shall be fabricated of steel pipe as specified herein.

3.12 Coupler drawhead. The coupler drawhead, fabricated in accordance with AREA requirements, shall extend the full length of the car

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

shall be bolted to the underframe at each diagonal brace. Steel
ll conform to AAR Specification M-116.

.13 Wheels. Wheels shall be 16 inches x 5/16 inch, cold pressed
n low-carbon steel plate conforming to AAR Specification M-116.
els shall be demountable and insulated.

.14 Axles. Axles shall be of medium carbon steel conforming to
Specification M-129 and shall be designed for heavy-duty service.
es shall have provisions for taper roller bearings and adjustable
ist collars.

.15 Brakes. Brakes shall be four wheel, with detachable brake
ile, shall be adjustable, and shall be in accordance with AREA Manual
Recommended Practice, Paragraph 6e, Part 2, Chapter 27.

.16 Lubrication fittings. The components and bearing surfaces
iring lubrication shall be provided with the appropriate fittings
ccordance with AREA recommended practice.

.17 Identification plate. An identification plate conforming to
-P-3558, Type III shall be permanently attached to the underframe
he trailer car in a conspicuous location.

18 Treatment and painting. The trailer cars shall be cleaned,
ted, and painted in accordance with MIL-P-3320 for maintenance cars.

.19 Interchangeability of components. Jigs, templates, gages, and
ures shall be used to insure interchangeability of like components
respect to assembly, performance, and quality.

20 Threaded parts. Screw threads shall conform to NBS Handbook
Pipe threads shall conform to the American National Taper Pipe
ad Series.

21 Workmanship.

21.1 Welding. The surfaces of all parts to be welded shall be free
rust, scale, paint, grease, and other foreign matter. All welding
l be in accordance with the latest applicable codes of the AWS or
Section 6 of the AAR Electrical Manual of Standard and Recommended
tice. Welders shall be qualified in accordance with AWS D1.1,
ctural Welding Code, Section 5, Qualification, or Electrical Manual
tandard and Recommended Practice, Section 6, Welding and Cutting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

3.21.2 Metal fabrication. Metal used in the fabrication of the trailer car shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame-cutting, using tips suitable for the thickness of the steel, may be employed instead of shearing and sawing. Burned surfaces of flame-cut material shall be ground or machined to remove slag, flame gougings, and cooling checks. All bends shall be made with controlled means to insure uniformity of size and shape. Precaution shall be taken to avoid overheating, and heated metal shall be allowed to cool slowly. External surfaces shall be free of burrs, sharp edges, and corners, except where sharp edges or corners are required or where they are not detrimental to safety.

3.21.3 Riveted connections. Rivets shall fill the holes completely. The upset rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the member.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First-produced trailer car inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 First-produced trailer car inspection.

4.3.1 Examination. The first-produced trailer car shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

.3.2 Tests. The first-produced trailer car shall be tested as cified in 4.5.2. Failure of any test shall be cause for rejection.

.4 Quality conformance inspection.

.4.1 Examination. Each trailer car shall be examined as specified 4.5.1. Presence of one or more defects shall be cause for rejection.

.4.2 Tests. Each trailer car shall be tested as specified in 4.5.2.1 ough 4.5.2.4. Failure of any test shall be cause for rejection.

.5 Inspection procedure.

.5.1 Examination. The trailer car shall be examined as specified ein for the following major defects:

101. Material not as specified.
102. Dimensions and weights not as specified.
103. Clearances not as specified.
104. Maintainability not as specified.
105. Tolerances and fits not as specified.
106. Parts and components missing, misalined, or not as specified.
107. Identification plate not as specified.
108. Treatment and painting not as specified.
109. Components not interchangeable.
110. Threaded parts not as specified.
111. Workmanship not as specified.

.5.2 Tests.

.5.2.1 Maximum load. Load the car with a static load of 12,500 nds evenly distributed over the entire deck of the car. Push the ded car along a level track and observe for freedom of movement. conformance to 3.4.1 shall constitute failure of this test.

.5.2.2 Deflection and camber. With the car positioned on a straight gent level track, load the car to 100 percent of specified capacity e 3.4) evenly distributed over the entire deck. Take instrument dings at nine points, two on each side of the car, two at each end of car, and one in the center of the car. Unload the car and at the e points take readings to determine the amount of permanent set. pare the readings taken in the loaded and unloaded conditions. Deter- e the amount of deflection and camber. Nonconformance to 3.4.2 shall stitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

4.5.2.3 Brakes. The brakes shall be applied to a trailer car loaded with a 5-ton static load. The loaded trailer car shall be coupled to a standard motor car and the brakes shall remain locked on all wheels when full power is applied to the motor car. Failure of the brakes to remain locked shall constitute failure of this test.

4.5.2.4 Clearance. Move the railway trailer car through a 150-foot radius curve. Stop the trailer at the point of maximum swing and measure the clearance at this point of maximum swing. Nonconformance to 3.5 or 3.8 shall constitute failure of this test.

4.6 Inspection of packaging. The packing and marking shall be examined to determine compliance with the requirements of Section 5 of this specification. Any defects in the packing, or any marking that is missing, illegible, incorrect, or incomplete, shall be cause for rejection.

5. PACKAGING

5.1 Packing. Packing shall be Level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each complete trailer maintenance car shall be packed in a close-fitting box conforming to MIL-B-26195, Type II, Style C, Class 2. The car shall be blocked, braced, and secured to the base of the box in a manner to prevent movement in accordance with MIL-STD-1186.

5.1.2 Commercial. Commercial packing shall be in accordance with FED. STD. No. 356.

5.2 Marking.

5.2.1 Level A. Level A marking shall be in accordance with MIL-STD-129.

5.2.2 Commercial. Commercial marking shall be in accordance with FED. STD. No. 356.

6. NOTES

6.1 Intended use. This specification covers 5-ton railway maintenance trailer cars intended for use on domestic and foreign railways for transporting tools and material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

2 Ordering data. Procurement documents should specify the owing:

(a) Title, number, and date of this specification.
(b) Gage of trailer cars required (see 1.2).
(c) Time frame required for submission of the first-produced trailer car, and number of cars required (see 3.2).
(d) Degree of packing required (see 5.1).

3 First-produced trailer cars. Any changes or deviations of produc- trailer cars from the approved first-produced trailer car during uction will be subject to the approval of the contracting officer. oval of the first-produced trailer car will not relieve the contractor is obligation to furnish trailer cars conforming to this specifica- .

4 Classification changes. Changes in classification of the trailer between this revision of the specification and the previous edition as follows:

Old Designation	New Designation Gage
pe I - Standard gage (56-1/2-inch), domestic service.	36-inch 39-3/8-inch
pe II - Narrow gage (36-, 39-3/8-, and 42-inch), foreign service.	42-inch 56-1/2-inch 60-inch
pe III - Broad gage (56-1/2-, 60-, 63-, and 66-inch), foreign service.	63-inch 66-inch

odian:
my - ME

Preparing activity:
Army - ME

Project No. 2230-0057

☆U.S. GOVERNMENT PRINTING OFFICE 1976-603-766/3871

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Mobility Equipment Research & Development Command
ATTN: DRDME-DS
Fort Belvoir, VA 22060

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.