MIL-S-10555H (PA)
5 September 1975
Superseding
MIL-S-10555G (MU)
9 June 1972

MILITARY SPECIFICATION

# SIMULATOR, BOOBY TRAP, ILLUMINATING M118 PARTS FOR, AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 This specification covers the parts manufacture, and loading, assembling and packing for one type simulator designated as Simulator, Booby Trap, Illuminating, M118.

## *2. APPLICABLE DOCUMENTS

*2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-Z-325 - Zinc Plating (Electrodeposited)
QQ-P-416 - Plating, Cadmium (Electrodeposited)

MILITARY

MIL-P-223 - Powder, Black
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

FSC: 1370

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-286 - Propellants, Solid: Sampling, Inspection and Testing
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1234 - Pyrotechnics, Sampling, Inspection and Testing

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKAGING DRAWINGS

8799712 - Box, Packing, Ammunition for Simulator, Booby Trap, Flash M117 or Simulator, Booby Trap, Illuminating M118
8799713 - Carton, Packing, Ammunition for Simulator, Booby Trap, Flash M117 or Simulator, Booby Trap, Illuminating M118
8848601 - Simulator, Booby Trap, Illuminating, M118 Assembly
2128176 - Pack, Shipping and Storage (for 50 Simulator, Booby Trap, Illuminating, M118 with Accessories)
3139675 - Package, Shipping and Storage (for 25 Simulator, Booby Trap, Illuminating, M118 with Accessories)

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

*2.2 Other Publications. - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issues in effect on date of invitation for bids shall apply.

Code of Federal Regulations, Title 49 - Transportation, Parts 100-199.

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders shall specify 49CFR 100-199 (latest revision)).



Source: https://assist.dla.mil -- Downloaded: 2024-10-17T14:14Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM Designation E300 - Industrial Chemicals, Recommended Practice for Sampling

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Penn. 19103).

3. REQUIREMENTS

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assembly. - The simulator assemblies shall comply with all requirements specified on drawing (dwg.) 8848601 and with all requirements specified in applicable specifications.

*3.3 Moisture content.

3.3.1 Moisture content of black powder. - The moisture content of the black powder at the loading station at time of loading shall not exceed 0.3 percent.

3.3.2 Moisture content of flare composition. - The moisture content of the flare composition at the loading station at time of loading shall not exceed 0.5 percent.

3.3.3 Felt, paper and paper products. - The moisture content of the felt, paper and paper products components of the simulator assembly at the loading station, at the time of loading, shall not exceed 6 percent.

3.3.4 Moisture content of fuze powder. - The moisture content of fuze powder, prior to the addition of the cellulose nitrate camphor, at the loading station at the time of loading shall not exceed 0.3 percent.

3.3.5 Moisture content of match head composition. - The moisture content of the match head composition at the loading station at the time of loading shall not exceed 0.1 percent.

3.4 Functioning. - The simulator assembly shall comply with the following requirements.

4577



Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

3.4.1 The simulator assembly shall ignite and burn for the required number of seconds (see dwg. 8848598).

3.4.2 The simulator assembly shall not explode during initiation or burning.

*3.5 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. (Required packing shall be dry).

3.6 Quick Leak Test. - The packed carton sealed in the barrier bag shall show no evidence of air or water leakage.

*3.7 First Article Inspection. - This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be specified in the contract.

3.8 Embrittlement of extension spring. - The extension spring (see dwg. 8848592) shall not break when stretched to the minimum point of permanent distortion.

*4. QUALITY ASSURANCE PROVISIONS

*4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

*4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection



4577

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:14Z
Check the source to verify that this is the current version before use.

*4.3 First Article Inspection.

*4.3.1 Submission. - The contractor shall submit a first article sample (see 6.2b) as designated by the Contracting Officer. The first article sample shall consist of 25 complete sets of parts and sub-assemblies (i.e. 25 each of every component and sub-assembly) and 50 loaded simulators. The first article sample shall be evaluated in accordance with the provisions of 4.3.2 and 4.3.3. Unless otherwise directed by the Contracting Officer, loaded components shall not be submitted to a Proving Ground for any test until the inert components and inert sub-assemblies submitted in accordance with this paragraph have been accepted.

*4.3.2 Inspections to be performed. - See MIL-A-48078 and paras 4.4.2.1 thru 4.4.2.17, testing per para 4.4.3, and Table I specified herein.

*4.3.3 Rejection. - (See MIL-A-48078)



4577

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

TABLE I

FIRST ARTICLE INSPECTION

**CLASSIFICATION OF DEFECTS & TESTS** MIL-S-10555H (PA)

| PARAGRAPH # | TITLE: Simulator, Booby Trap, Illuminating, M118, Inert Parts, Sub-assemblies, and complete Assemblies | SHEET 1 OF 3 | DRAWING NUMBER: See Below |
|---|---|---|---|
| | | | NEXT HIGHER ASSEMBLY |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| | Inert Parts (Dwg. 8848601) Examination for Defects | 25 (Note 1) | | 3.2 | 4.4.2.1 thru 4.4.2.9 |
| | Sub-assemblies Lower Disc Assembly (Dwg. 8848585) Examination for Defects | 25 | | 3.2 | 4.4.2.12 |
| | Upper Disc Assembly (Dwg. 8848584) Examination for Defects | 25 | | 3.2 | 4.4.2.13 |
| | Spool Assembly (Dwg 8848590) Examination for Defects | 25 | | 3.2 | 4.4.2.10 |
| | Scratcher Assembly (Dwg. 8848587) Examination for Defects | 25 | | 3.2 | 4.4.2.11 |
| | Flare Assembly (Dwg. 8848598) Examination for Defects | 25 | | 3.2 | 4.4.2.14 thru 4.4.2.15 |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

TABLE I

FIRST ARTICLE INSPECTION

**CLASSIFICATION OF DEFECTS & TESTS** MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 2 OF 3 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| | Continuation Sheet | | | | See Below |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Assembly (Dwg. 8848602) Examination for Defects | 50 (Note 2) | | 3.2 | 4.4.2.16 thru 4.4.2.17 |
| | Tests | | | | |
| | Protective coating of extension spring (Dwg. 8848592) | 25 (Note 3) | | 3.2 | 4.5.3 |
| | Protective coating of bracket (Dwg. 8848603) | 25 (Note 3) | | 3.2 | 4.5.3 |
| | Embrittlement of extension spring (Dwg. 8848592) | 25 (Note 4) | | 3.8 | 4.5.4 |
| | Functioning (Dwg. 8848601) | 50 (Note 5) | | 3.4 | 4.5.6 |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

TABLE I

FIRST ARTICLE INSPECTION

**CLASSIFICATION OF DEFECTS & TESTS** MIL-S-10555H (PA)

| PARAGRAPH | TITLE<br>Continuation Sheet | | SHEET 3 OF 3 | | DRAWING NUMBER<br>NEXT HIGHER ASSEMBLY |
|---|---|---|---|---|---|
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| NOTES: | (1) Twenty-five (25) of each and every inert component<br>(2) First fifty (50) complete assemblies<br>(3) Performed on springs and brackets from 1<br>(4) Performed on additional twenty-five (25) springs<br>(5) Performed on assemblies from (2) | | | | |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

*4.4 Quality Conformance Inspection.

*4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition inspection lots of Simulator, Booby Trap, Illuminating, M118 shall contain:

a. Parts from one lot interfix from one manufacturer.

b. Composition ingredients from not more than one lot from one manufacturer.

c. Fuze powder from not more than one lot.

d. Quickmatch from not more than one lot.

e. Match head composition, scratcher composition and charge composition of one or more batches produced under one continuous set of operating conditions, with each batch of the composition having been subjected to the same physical mixing process intended to make the batch homogeneous.

*4.4.2 Examination. - (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.



Source: https://assist.dla.mil -- Downloaded: 202640-17T14:44:27
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.1 | Disc, Top | | | | 8848593 |
| | | | | | NEXT HIGHER ASSEMBLY |
| | | | | | 8848601 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Thickness, min | | 0.65% | 3.2 | Gage |
| 202 | Diameter | | 0.65% | 3.2 | Gage |
| 203 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

LLSP

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.2 | Extension Spring | | | | 8848592 |
| | | | | | NEXT HIGHER ASSEMBLY |
| | | | | | 8848601 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major A | | | | | |
| 101 | Load at 2 times original length, min | | 0.40% | 3.2 | Gage |
| 102 | Load at 3 times original length, min | | 0.40% | 3.2 | Gage |
| Major B | | | | | |
| 131 | Spring takes permanent set when extended a minimum of 26 inches inside hooks | | 0.40% | 3.2 | Manual/Gage |
| NOTE: | The springs shall be tested in the order listed above | | | | |
| Minor | | | | | |
| 201 | Unloaded length | | 0.65% | 3.2 | Gage |
| 202 | Protective coating missing or contains bare spot | | 0.65% | 3.2 | Visual |
| 203 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

12

457

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 8848588 |
|---|---|---|---|---|---|
| *4.4.2.3 | Cap | | | | NEXT HIGHER ASSEMBLY 8848601 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Cap torn or punctured | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER |
|---|---|---|---|
| *4.4.2.4 | Tube, Body | | 8848586 |
| | | | NEXT HIGHER ASSEMBLY 8848599 |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Layers separated or tube damaged | | 0.40% | 3.2 | Visual |
| 132 | Location of hole | | 0.40% | 3.2 | Gage |
| Minor | | | | | |
| 201 | Length | | 0.65% | 3.2 | Gage |
| 202 | Thickness of wall, min. | | 0.65% | 3.2 | Gage |
| 203 | Inside diameter | | 0.65% | 3.2 | Gage |
| 204 | Crack | | 0.65% | 3.2 | Visual |
| 205 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

14

4577

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 8848595 |
|---|---|---|---|---|---|
| *4.4.2.5 | Tube, Outer | | | | NEXT HIGHER ASSEMBLY 8848601 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Layers separated or tube damaged | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Length | | 0.65% | 3.2 | Gage |
| 202 | Inside diameter | | 0.65% | 3.2 | Gage |
| 203 | Wall thickness, min. | | 0.65% | 3.2 | Gage |
| 204 | Crack | | 0.65% | 3.2 | Visual |
| 205 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 8848603 |
|---|---|---|---|---|---|
| #4.4.2.6 | Bracket | | | | NEXT HIGHER ASSEMBLY 8848601 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major A | | | | | |
| 101 | Mounting hole missing | | 0.40% | 3.2 | Visual |
| Major B | | | | | |
| 131 | Thickness, min. | | 0.40% | 3.2 | Gage |
| Minor | | | | | |
| 201 | Protective coating missing or contains bare spot | | 0.65% | 3.2 | Visual |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.7 | Disc | | | | 8848581 |
| | | | | | NEXT HIGHER ASSEMBLY 8848584 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Thickness, min. | | 0.65% | 3.2 | Gage |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.8 | Disc, Lower | | | | 8848582 |
| | | | | | NEXT HIGHER ASSEMBLY 8848585 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Thickness, min. | | 0.65% | 3.2 | Gage |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

18 4571

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.9 | Disc, Upper | | | | 8848583 |
| | | | | | NEXT HIGHER ASSEMBLY |
| | | | | | 8848584 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Thickness, min. | | 0.65% | 3.2 | Gage |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

Lush

QUALITY CONFORMANCE INSPECTION

**CLASSIFICATION OF DEFECTS & TESTS** MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.10 | Spool Assembly | | | | 8848590 |
| | | | | | NEXT HIGHER ASSEMBLY 8848601 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Protective coating missing or contains bare spot | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Spool split or cracked | | 0.65% | 3.2 | Visual |
| 202 | Wire insecure | | 0.65% | 3.2 | Visual/Manual |
| 203 | Protective coating not dry | | 0.65% | 3.2 | Visual/Manual |
| 204 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.



19

4571

20

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.11 | Scratcher Assembly | | | | 8248587 |
| | | | | | NEXT HIGHER ASSEMBLY 8848598 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major A | | | | | |
| 101 | Scratcher composition coating missing or unevenly distributed | | 0.40% | 3.2 | Visual |
| 102 | Scratcher composition not dry | | 0.40% | 3.2 | Manual |
| Minor | | | | | |
| 201 | Length, min. | | 0.65% | 3.2 | Gage |
| 202 | Width, min. | | 0.65% | 3.2 | Gage |
| 203 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

1454

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 8848585 |
|---|---|---|---|---|---|
| *4.4.2.12 | Lower Disc Assembly | | | | NEXT HIGHER ASSEMBLY 8848598 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Lower disc missing or insecure | | 0.65% | 3.2 | Visual/Manual |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.13 | Upper Disc Assembly | | | | 8848584 |
| | | | | | NEXT HIGHER ASSEMBLY 8848601 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major | None defined | | | | |
| Minor | | | | | |
| 201 | Upper disc missing or insecure | | 0.65% | 3.2 | Visual/Manual |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

1454

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.14 | Flare Assembly Prior to Assembling Upper Disc Assembly | | | | 8848598 |
| | | | | | NEXT HIGHER ASSEMBLY 8848601 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major A | | | | | |
| 101 | Flare Charge Missing | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

4574

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 8848598 |
|---|---|---|---|---|---|
| *4.4.2.15 | Flare Assembly | | | | NEXT HIGHER ASSEMBLY 8848601 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | | | | | |
| 1 | Flare tube ruptured | | 100% | 3.2 | Visual |
| Major A | | | | | |
| 101 | Match head composition missing or length less than min | | 0.40% | 3.2 | Visual/Scale |
| 102 | Starter paste coating incomplete | | 0.40% | 3.2 | Visual |
| 103 | Pull cord damaged to extent that function may be impaired | | 0.40% | 3.2 | Visual |
| 104 | Any component missing, improperly assembled, located or insecure | | 0.40% | 3.2 | Visual/Manual |
| 105 | Scratcher assembly and igniter pad improperly assembled (not permitting free passage of pull cord) | | 0.40% | 3.2 | Visual |
| 106 | Quick match insecure | | 0.40% | 3.2 | Visual/Manual |
| Minor | | | | | |
| 201 | Lower disc assembly insecure or improperly assembled | | 0.65% | 3.2 | Visual/Manual |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

4577

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.16 | Assembly, Prior to Assembling Cap | | | | 8848601 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | | | | | |
| 1 | Pull cord insecurely taped as evidenced by a slight pull parallel to longitudinal axis of assembly | | 100% | 3.2 | Visual/Manual |
| Major A | | | | | |
| 101 | Any component missing | | 0.40% | 3.2 | Visual |
| Major B | | | | | |
| 131 | Upper disc insecure | | 0.40% | 3.2 | Manual |
| 132 | Glue on pull cord | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Part or subassembly can be removed by applying slight finger pressure | | 0.65% | 3.2 | Manual |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

25

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

**CLASSIFICATION OF DEFECTS & TESTS** MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 8848601 |
|---|---|---|---|---|---|
| *4.4.2.17 | Assembly | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | | | | | |
| 1 | Sufficient paint leakage under cap to bond pull cord to cap | | 100% | 3.2 | Visual (Note 1) |
| Major A | | | | | |
| 101 | Bracket missing, damaged or insecure | | 0.40% | 3.2 | Visual/Manual |
| Minor | | | | | |
| 201 | Any component missing | | 0.65% | 3.2 | Visual |
| 202 | Bare spot on painted surface | | 0.65% | 3.2 | Visual |
| 203 | Marking misleading, missing, or unidentifiable | | 0.65% | 3.2 | Visual |
| 204 | Tape pull tab missing or inadequate | | 0.65% | 3.2 | Visual/Manual |
| 205 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:
Note 1 - Inspection for the presence of this defect need only by performed on those assemblies upon which the tape is insecure, applied less than 360 degrees, or has wrinkles extending from tape edge to beyond cap and outer joint.

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-01-17 14:14Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.18 | Unsealed Inner Carton | | | | 8799713 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major A | | | | | |
| 101 | Simulator missing or damaged | | 0.40% | 3.2 | Visual |
| 102 | Any accessory component missing or damaged | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

4517

28

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.19 | Unsealed Outer Carton | | | | 8799713 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Inner carton missing or improperly sealed | | 0.40% | 3.2 | Visual |
| 132 | Inner carton damaged to extent that contents are exposed | | 0.40% | 3.2 | Visual |
| 133 | Marking missing, misleading or unidentifiable | | 0.40% | 3.2 | Visual |
| 134 | Instruction sheet missing | | 0.40% | 3.2 | Visual |
| 135 | Carton filler or simulator obviously damp or wet | | 0.40% | 3.2 | Visual/Manual |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| #4.4.2.20 | Sealed Outer Carton | | | | 8799713 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Carton damaged to extent that contents are exposed | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Contents loose | | 0.65% | 3.2 | Manual |
| 202 | Marking missing, misleading or unidentifiable | | 0.65% | 3.2 | Visual |
| 203 | Sealing strip torn, badly wrinkled or incomplete | | 0.65% | 3.2 | Visual |
| 204 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

4577

30

QUALITY CONFORMANCE INSPECTION

**CLASSIFICATION OF DEFECTS & TESTS** MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET OF | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.21 | Sealed Packed Barrier Bag Prior to Packing in Wooden Box | | | | 8799713 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Waterproofness of barrier bag destroyed by rupture puncture or separation of heat seal | | 0.40% | 3.2 | Visual |
| 132 | Evidence of crushed carton | | 0.40% | 3.2 | Visual (Note 1) |
| 133 | Excess air not exhausted from bag prior to sealing | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Heat seal of barrier bag located so that one or more subsequent seals cannot be applied | | 0.65% | 3.2 | Visual |
| 202 | Marking missing, misleading or unidentifiable | | 0.65% | 3.2 | Visual |
| 203 | Carton corners not blunted prior to insertion into barrier bag | | 0.65% | 3.2 | Visual |
| 204 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

1. Package should be opened for inspection if there is evidence of crushing.

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

**CLASSIFICATION OF DEFECTS & TESTS** MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 8799712 |
|---|---|---|---|---|---|
| *4.4.2.22 | Packing Box, Prior to Sealing | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Packed barrier bag missing | | 0.40% | 3.2 | Visual |
| 132 | Packing component missing | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.23 | Sealed Wooden Packing Box | | | | 8799712 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Box damaged to extent that contents are exposed or liable to become exposed | | 0.40% | 3.2 | Visual |
| 132 | Strapping missing, broken or loose | | 0.40% | 3.2 | Visual/Manual |
| 133 | DOD symbol missing, misleading or unidentifiable | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Strapping mislocated or improperly engaged | | 0.65% | 3.2 | Visual |
| 202 | Contents loose | | 0.65% | 3.2 | Manual |
| 203 | Marking missing, misleading, or unidentifiable | | 0.65% | 3.2 | Visual |
| 204 | Metallic seal missing, unsealed, or incorrectly positioned | | 0.65% | 3.2 | Visual |
| 205 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

# CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER |
|---|---|---|---|
| #4.4.2.24 | Package, Shipping and Storage, Prior to Closing | | 3139675 |
| | | | NEXT HIGHER ASSEMBLY |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Any packing component missing or misassembled | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Number of dessicant units incorrect | | 0.65% | 3.2 | Visual |
| 202 | Dessicant bags not properly secured | | 0.65% | 3.2 | Visual |
| 203 | Indicator card missing | | 0.65% | 3.2 | Visual |
| 204 | Number of inner packages incorrect | | 0.65% | 3.2 | Visual |
| 205 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

45711

34

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.25 | Package, Shipping and Storage | | | | 3139675 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | | | | | |
| 1 | CFR markings missing or unidentifiable | | 100% | 3.2 | Visual |
| Major B | | | | | |
| 131 | Tray interferes with seal of lid | | 0.40% | 3.2 | Visual/Manual |
| Minor | | | | | |
| 201 | Descriptive marking missing, misleading or unidentifiable | | 0.65% | 3.2 | Visual |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

L47h

QUALITY CONFORMANCE INSPECTION

**CLASSIFICATION OF DEFECTS & TESTS** MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.26 | Pack, Shipping and Storage, Prior to Closing | | | | 2128176 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | None defined | | | | |
| Major B | | | | | |
| 131 | Package missing or improperly positioned | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

35

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

4.5.17

36

QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-S-10555H (PA)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| *4.4.2.27 | Pack, Shipping and Storage | | | | 2128179 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | | | | | |
| 1 | CFR markings missing or unidentifiable | | 100% | 3.2 | Visual |
| Major B | | | | | |
| 131 | Wire binding not properly secured | | 0.40% | 3.2 | Visual/Manual |
| 132 | Car seal missing | | 0.40% | 3.2 | Visual |
| Minor | | | | | |
| 201 | Descriptive marking missing, misleading or unidentifiable | | 0.65% | 3.2 | Visual |
| 202 | Evidence of poor workmanship | | 1.00% | 3.5 | Visual |

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

*4.4.3 Testing. - A representative sample shall be randomly selected for the chemical tests specified in 4.4.3.1 and 4.4.3.2. The procedure described in ASTM E300 shall be used to withdraw the samples.

4.4.3.1 Moisture Content. - The contractor shall provide adequate controls to insure that the materials comply with the requirements (see Table II). For verification, the contractor shall select and subject to test, one sample of each material from each 8 hours production. A composite sample shall not be used. If the moisture content of a sample exceeds the requirement, that quantity or sub lot of material represented by the sample shall not be used in production. If the quantity of material or sub-lot with excessive moisture has been used in loading and packing, the remaining unloaded and unpacked material shall not be used in production, and the loaded and packed simulators shall be rejected. Test shall be performed as specified in 4.5.1.

TABLE II

| Material | Defect | Reference |
|---|---|---|
| Black powder | Major A | 3.3.1 |
| Flare Composition | Major A | 3.3.2 |
| Felt, paper and paper products | Major A | 3.3.3 |
| Fuze powder | Major A | 3.3.4 |
| Match head Composition | Major A | 3.3.5 |
| Carton and carton packing material | Major A | Dwg. 8799713 |

4.4.3.2 Determination of match head, scratcher and flare compositions. - (See Table III) - A sample quantity of each composition shall be selected from each batch for these determinations. If the sample fails to meet the requirements specified, the batch shall be rejected. Test shall be performed as specified in 4.5.2.

TABLE III

| Composition | Defect | Reference |
|---|---|---|
| Match head | Major A | Dwg. 9269240 |
| Scratcher | Major A | Dwg. 9269237 |
| Flare | Major A | Dwg. 9270718 |



4577

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

*4.4.3.3 Functioning. - The simulator assemblies shall be observed for any evidence of failure to comply with the requirements as classified in Table IV, when tested as specified in 4.5.6.1.

TABLE IV

| Defect | Classification | Reference |
|---|---|---|
| Dud | Major A | 3.4.1 |
| Malfunction | Critical | 3.4.2 |
| Burning time less than requirement, but greater than requirement minus three (3) seconds | Major B | Dwg. 8848598 |
| Burning time less than requirement minus three (3) seconds | Major A | Dwg. 8848598 |
| Spring breaks or fails to function | Major A | 3.8 |

*4.4.3.3.1 Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the applicable requirements specified, one-hundred and twenty-five (125) simulator assemblies shall be selected from each lot for testing. The lot shall be rejected if during the test, one (1) or more critical defects as listed in Table IV occur, if five (5) or more assemblies exhibit any of the Major A defects listed in Table IV or if seven (7) or more assemblies exhibit a combination of the Major A and Major B defects listed in Table IV.

*4.4.3.3.2 After three (3) consecutive lots have complied with the acceptance criteria of 4.4.3.3.1 fifty (50) assemblies shall be selected from each lot for test. The lot shall be rejected if, during the test, one (1) or more critical defects as listed in Table IV occur, if two (2) or more assemblies exhibit the Major A defects as listed in Table IV, or if four (4) or more assemblies exhibit the Major A and Major B defects as listed in Table IV.

4.4.3.4 Quick leak test. - Major B defect - Ten (10) cartons in sealed barrier bags shall be selected from each lot for this test. If two (2) or more packages show evidence of air leakage during test or water leakage when package is opened the lot shall be rejected. The test shall be performed as specified in 4.5.7 to comply with the requirement of 3.6.



4577

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

4.4.3.5 Protective coating test of spring, extension (Dwg. 8848592) and bracket (Dwg. 8848603). - Major B defects - Sampling, acceptance and rejection shall be in accordance with QQ-Z-325 or QQ-P-416 whichever is applicable except that actual parts may be used in lieu of specimens. The test procedure shall be as specified in 4.5.3.

4.4.3.6 Embrittlement of extension spring. - Major A defect - Fifty (50) springs shall be selected from each heat treatment lot for test. If one or more springs fail to comply with the requirements (see 3.8), the heat treatment lot shall be rejected. The test procedure shall be as specified in 4.5.4. Springs used for this test shall not be returned to the lot.

4.4.3.7 Length of trip wire. - Major B defect - A sample of twenty (20) spool assemblies shall be selected from each lot for this test. The lot shall be rejected if one or more trip wires fail to meet the specified requirement (see Dwg. 8848590) when tested in accordance with 4.5.5.

*4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/ Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and paragraph 6.3 herein.

*4.5 Test Methods and Procedures.

*4.5.1 Moisture content. - These tests shall be performed using prescribed analytical procedure for replicate determinations given in standard analytical textbooks.

4.5.1.1 Flare composition. - The moisture content shall be determined in accordance with Method 102.1 of MIL-STD-1234.

*4.5.1.2 Match head composition. - An accurately weighed portion of approximately 5 grams of composition, prior to the addition of the lacquer, shall be transferred to a tared aluminum or glass dish approximately 60 millimeters (mm) in diameter. A tight fitting cover shall be fitted to the dish. The cover shall be removed, and the dish and contents placed in a desiccator containing a suitable desiccant such as calcium chloride, calcium sulfate or sulfuric acid. The desiccator shall be maintained at a temperature of 25 plus or minus 5 degrees Centigrade (C.). The dish and contents

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.



4577

shall remain in the desiccator until the loss in weight between subsequent weighings does not exceed 1 milligram. The loss in weight shall be calculated as follows:

$$\text{Percentage moisture} = \frac{100A}{W}$$

where:
A = loss in weight in grams.
W = weight of the sample in grams.

*4.5.1.3 Fuze powder. - Prior to adding the cellulose nitrate camphor binder, if used, an accurately weighed portion of approximately two (2) grams of the fuze powder shall be transferred to a tared weighing dish or watch glass. The container and contents shall be dried for four (4) hours in an oven at 70 plus or minus 5 degrees C. The dish and contents shall then be removed, covered, cooled in a desiccator and weighed. The loss in weight shall be calculated to the percentage of moisture in the sample.

*4.5.1.4 Felt, paper, chipboard, carton and carton packing material. - Ten (10) grams of each material shall be accurately weighed and placed in a tared weighing dish. Each dish and contents shall be weighed and placed in an oven and dried at 100 plus or minus 2 degrees C. for two (2) hours. Each dish and contents shall be cooled in a desiccator and weighed. The loss in weight shall be calculated as percent moisture in each sample.

*4.5.1.5 Black Powder. - The moisture content of the black powder shall be determined in accordance with MIL-P-223.

*4.5.1.6 Alternate method. - The moisture content shall be determined in accordance with Method 101.4 of MIL-STD-286. The timer shall be set to the minimum time required to obtain constant readings and the drying temperature shall be as specified in 4.5.1.5.

*4.5.2 Determination of compositions. - These tests shall be performed using prescribed analytical procedure for replicate determinations given in standard analytical textbooks.

*4.5.2.1 Match head. - Prior to adding the lacquer, a one gram sample shall be selected and analyzed as follows:



Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

*4.5.2.1.1 Antimony sulfide. - An accurately weighed portion of approximately one gram shall be transferred to a 150 milliliter (ml.) beaker. Twenty-five (25) ml. of 12N hydrochloric acid shall be added to the beaker, and heated on a steam bath for 30 minutes with occasional stirring, and then filtered into a tared medium porosity glass crucible with suction. The beaker and contents of the crucible shall be washed with a two-percent solution of hydrochloric acid and finally with four 5 ml. portions of water.

The crucible and contents shall be dried in an oven maintained at 100 plus or minus 5 degrees C. for one hour, cooled in a desiccator for 1 hour and weighed. The residue shall be saved for the red phosphorous determination (paragraph 4.5.2.1.2). The percentage of antimony sulfide in the sample shall be calculated as follows:

$$\text{Percentage of antimony sulfide} = \frac{A-[(B-C)+(DE)]x100}{A}$$

where:

A = weight of sample
B = weight of glass crucible and residue
C = weight of glass crucible
D = loss in weight of crucible and contents after extraction with 15N nitric acid as determined in 4.5.2.1.2.
E = factor required by the solubility of red phosphorus in hydrochloric acid (see 4.5.2.1.1.1).

*4.5.2.1.1.1 Calculation of factor E. - From the lot of red phosphorus used in the manufacture of the match head composition, 0.5300 plus or minus 0.0010 gm. shall be transferred to a 150 ml. beaker and 25 ml. of 12N hydrochloric acid added. The beaker and contents shall be heated on a steam bath for 30 minutes, stirred occasionally, and then filtered with the aid of a tared, medium porosity, glass crucible and suction. The beaker and contents of the crucible shall be washed with a two-percent solution of hydrochloric acid and finally with four 5 ml. portions of water. The crucible and residue shall be dried in an oven maintained at 100 plus or minus 5 degrees C. for one hour, cooled in a desiccator for 15 minutes, and weighed. The loss in weight of the crucible and contents shall be calculated to percentage of red phosphorus soluble in 12N



4577

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

hydrochloric acid. The factor represented by the letter E, given in the equation for calculating the percentage of antimony sulfide, shall be calculated as follows:

$$E = \frac{F}{G}$$

where:

F = percent solubility of the red phosphorus used in the composition, expressed as a decimal fraction.

G = percent of solubility of the red phosphorus subtracted from 100 and the result expressed as a decimal fraction.

*4.5.2.1.1.2 In the course of analysis of samples of match head composition, the solubility in hydrochloric acid of red phosphorus shall be recorded whenever practicable.

*4.5.2.1.2 Red phosphorus. - The residue obtained in 4.5.2.1.1 shall be transferred from the glass crucible to a 150 ml. glass beaker with the aid of a stirring rod and five 5 ml. portions of 15N nitric acid. The crucible shall be rinsed with four 5 ml. portions of distilled water, and the rinsings caught in the beaker. The contents of the beaker shall be heated on a steam bath for one hour and filtered into the previously used crucible using suction. The beaker and contents shall be washed with four 5 ml. portions of distilled water. The crucible and residue shall be dried in an oven maintained at 100 plus or minus 5 degrees C. for one hour, cooled in a desiccator for one hour and weighed. Percentage of red phosphorus in the sample shall be calculated as follows:

$$\text{Percentage of red phosphorus} = \frac{100D}{FA}$$

where:

D = loss in weight of crucible and contents due to extraction with 15N nitric acid.

F = factor obtained by subtracting the percent solubility of the red phosphorus from 100 and expressing the result as a decimal fraction.

A = weight of sample.

*4.5.2.1.3 Charcoal. - Percentage of charcoal in the sample shall be calculated as follows:



4577

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

$$\text{Percentage of charcoal} = \frac{G-C}{A} \times 100$$

where:

G = weight of crucible and charcoal.
C = weight of crucible.
A = weight of sample.

4.5.2.2 Scratcher composition. - A one gram sample shall be selected from each batch of scratcher composition and analyzed as specified in the following paragraphs.

*4.5.2.2.1 Antimony sulfide. - An accurately weighed portion of approximately one gram of the sample of scratcher composition which has been previously dried at 100 plus or minus 5 degrees C., shall be transferred to a 150 ml. beaker. Fifty (50) ml. of water shall be added to the beaker, the contents heated on a steam bath for one hour, and filtered using a tared, medium porosity sintered glass filtering crucible. The beaker and residue shall be washed five times with hot water, and the residue caught in the above mentioned crucible. The crucible and contents shall be dried for one hour at 100 to 105 degrees C., cooled in a desiccator and weighed. The filtrate shall be retained for the determination of potassium chlorate and dextrin. The gain in weight of the crucible shall be calculated to percentage of antimony sulfide in the sample.

*4.5.2.2.2 Potassium chlorate. - The filtrate obtained in 4.5.2.2.1 shall be diluted to 250 ml. in an accurately calibrated volumetric flask. A 25 ml. aliquot shall be transferred with a calibrated pipette to a 500 ml. Erlenmeyer flask, diluted to approximately 150 ml. and approximately 50 ml. of 18N sulfuric acid shall be added. The flask shall be stoppered with a rubber stopper equipped with a Bunsen valve and the contents heated almost to boiling. Fifty (50) ml. of a standardized solution of approximately four percent ferrous ammonium sulfate (Mohr's Salt) shall be added, using a calibrated pipette, and the solution boiled for two minutes, cooled, the valve loosened and the excess of Mohr's Salt titrated with a standardized 0.1N potassium permanganate solution. Concurrently conduct a blank determination using the same quantities of the reagents used for the analysis of the sample. The percentage of potassium chlorate in the sample shall be calculated as follows:



4577

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

$$\text{Percentage of potassium chlorate} = \frac{0.2043(V-v)(N)(100)}{W}$$

where:

V = volume of potassium permanganate required for blank titration, ml.
v = volume of potassium permanganate required for sample titration, ml.
N = normality of potassium permanganate solution.
W = weight of original sample, gm.

#4.5.2.2.3 Dextrin. - The percentage of dextrin in the sample shall be calculated by subtracting from 100 the combined percentages of antimony sulfide and potassium chlorate.

4.5.2.3 Flare composition. - The flare composition shall be analyzed as follows:

4.5.2.3.1 Red gum. - An accurately weighed portion of approximately one gram of the sample shall be transferred to a tared, medium-porosity filtering crucible. The contents of the crucible shall be treated with 50 ml. of absolute ethyl alcohol saturated with potassium perchlorate, in 10 ml. portions. Each portion of alcohol shall be allowed to remain in contact with the contents of the crucible for approximately one minute, before removing with the aid of suction. The complete extraction may be hastened by breaking up any lumps in the sample with a stirring rod. The crucible and contents shall be placed in an oven at 100 degrees to 105 degrees C. for 1 hour, cooled in a desiccator, and weighed. The loss in weight shall be recorded, and then the residue in the crucible shall be treated with 50 ml. of hot distilled water in 10 ml. portions. Each portion of water shall be allowed to remain in contact with the residue for about one minute before suction is applied. The water extract shall be retained for determination of potassium perchlorate. The crucible and contents shall be placed in an oven at 100 degrees to 105 degrees C. for 2 hours, cooled in a desiccator and weighed. The percent red gum shall be calculated as follows:

Percentage of red gum = (A divided by W) 100

where:

A = loss in weight from alcoholic extraction, gm.
W = weight of the moisture-free sample, gm.



4517

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:14Z
Check the source to verify that this is the current version before use.

4.5.2.3.2 Potassium perchlorate. - Ten (10) ml. of 36N sulfuric acid and 10 ml. of 15N nitric acid shall be added to the water extract obtained in the determination of red gum. The mixture shall be evaporated to sulfur trioxide fumes and 5 ml. of 15N nitric acid added. The solution shall again be evaporated to sulfur trioxide fumes and an additional 5 ml. of 15N nitric acid added. The above mentioned evaporation to sulfur trioxide and the addition of 5 ml. portions of 15N nitric acid shall be repeated until a total of 25 ml. of nitric acid is added. The mixture shall be evaporated just to dryness and the residue transferred quantitatively to a tared platinum crucible with the aid of water. The contents of the crucible shall be evaporated to dryness keeping the temperature at a point that will not cause spattering of the contents of the crucible. The crucible and contents shall be placed in a muffle furnance, maintained at approximately 750 degrees C. for 1 hour, cooled in a desiccator, and weighed. The percentage of potassium perchlorate in the sample shall be calculated as follows:

$$\text{Percentage of potassium perchlorate} = \frac{159\ A}{W}$$

where:
A = weight of residue in crucible.
W = weight of moisture free sample.

4.5.2.3.3 Dextrin. - The percentage of dextrin in the sample shall be calculated by subtracting from 100 the combined percentage of red gum and potassium perchlorate.

*4.5.3 Protective coating of extension spring and bracket. - The adequacy of the protective coating shall be tested in accordance with the procedures specified in QQ-Z-325 or QQ-P-416 whichever is applicable. (Destructive tests)

*4.5.4 Embrittlement of extension spring. - The spring shall be stretched along its longitudinal axis until it no longer returns to its original position. When the spring no longer returns to its original length or profile it shall be considered permanently distorted. Any spring that breaks during the test shall be classed defective. Springs subjected to this test shall not be returned to the lot. (Destructive test)

*4.5.5 Length of trip wire. - The trip wire shall be unwound from the spool assembly and its length measured to



4577

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:14Z
Check the source to verify that this is the current version before use.

determine compliance with the specified requirement. (Destructive test)

*4.5.6 Functioning. - The following functioning test, in accordance with Acceptance Test Procedure, SIM-BTI (latest revision) shall be performed at a Government proving ground. (Destructive test)

4.5.6.1 Functioning. - The simulator assemblies shall be mounted in accordance with instructions on dwg. 8848620. The assemblies shall be ignited bycutting the trip wire. Burning time shall be determined using equipment in accordance with 4.4.4.

4.5.6.2 Test validity. - If for any reason the proving ground considers that the test conditions have detrimentally affected the test results, the test shall be declared invalid and a new test performed with additional samples.

*4.5.7 Quick leak test (Vacuum Differential Method). - The filled and sealed packages, after conditioning at ambient temperature (70 plus or minus 5 degrees F.) for at least four (4) hours, shall be tested for leakage by submerging in water contained in a vacuum vessel. A vacuum differential of 216mm ( 8 1/2 inches) of mercury from ambient conditions shall be drawn and held for 30 seconds (minimum) while observing for leakage of air. Repeat the test after inverting the sample. A steady stream or recurring succession of bubbles from any surface or seam shall be cause for rejection. Where there is no emission of bubbles observed, the package shall be dried, opened and inspected. Evidence of water within the barrier, or on the carton shall also be cause for rejection. (Destructive test)

## 5. PREPARATION FOR DELIVERY

### 5.1 Preservation and packaging.

5.1.1 Level A. - The simulators assemblies and accessories shall be preserved and packaged in accordance with dwg. 8799713.

5.1.2 Level A. - For Marine Corps. use, preservation and packaging shall be in accordance with dwg. 3139675.

### 5.2 Packing.



4577

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

5.2.1 Level A. - The cartons shall be packed in accordance with dwg. 8799712.

5.2.2 Level A. - For Marine Corps use, packing shall be in accordance with dwg. 2128176.

5.3 Marking.

5.3.1 The cartons and boxes shall be marked as specified on dwg. 8799712 and 8799713.

5.3.2 For Marine Corps use, marking shall be as specified on dwg. 2128176 and 3139675.

5.4 Inert Parts. - Simulator parts shall be packaged, packed and marked in accordance with MIL-STD-1169 requirements for Level C shipment.

*6. NOTES

*6.1 Intended Use. - The illuminating booby trap simulator M118 is designed to be used in training to simulate actual booby traps.

*6.2 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions for submission of first article samples. First article submission requirements should stipulate necessary conditions for the forwarding of samples to the proving grounds.

c. Provisions of MIL-A-48078..

d. For Marine Corps packing, packaging and marking see 5.1.2, 5.2.2 and 5.3.2.

*6.3 Submission of Inspection Equipment Designs for Approval. - (See MIL-A-48078). Submit equipment designs as required, to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T-T, Dover, New Jersey 07801.

*6.4 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:14Z
Check the source to verify that this is the current version before use.

6527

*6.5 Proving Ground Functioning Test Summary

| Test | Production Lots | | | Requirements |
|---|---|---|---|---|
| | First Article | First three Consecutive Acceptable | Remaining | |
| Functioning | 50 | 125 | 50 | see 3.5 and Table IV |

*6.6 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1370-A-045



4577

944

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:14Z
Check the source to verify that this is the current version before use.

6657

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-A
Dover, New Jersey 07801

FOLD

4577

8F9

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:14Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity.. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

**DD** FORM 1 JAN 72 **1426** PREVIOUS EDITIONS OBSOLETE AND MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:14Z
Check the source to verify that this is the current version before use.