INCH-POUND

MIL-T-10646D
30 September 1988
SUPERSEDING
MIL-T-10646C
5 November 1961

MILITARY SPECIFICATION

TELESCOPES, STRAIGHT: M90 SERIES & P/N 12599180

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers straight telescopes of two types, designated the M90 series and P/N 12599180. The differences are reticle pattern and reticle illumination.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitations for bids or requests for proposals, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-O-13830	Optical Components of Fire Control Instruments; General Specifications Governing the Manufacture, Assembly, and Inspection of
MIL-F-13926	Fire Control Materiel: General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel, Packaging of

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions, and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-01-17T14:18Z
Check the source to verify that this is the current version before use.

MIL-STD-129	Marking for Shipping and Storage
MIL-STD-130	Identification Marking of US Military property
DSAM 4145.8	Radioactive Quantities in the DOD Supply System

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

7680673	Fixture, Pressure Testing
7694010	Test Fixture for Telescope, M90 Series
8205096	Telescopes, Straight: M90C, M90D,and M90F
12599180	Telescope, Straight: P/N 12599180

PACKAGING DATA SHEETS

MIL-P-14232/P7648432	Packaging of Telescope, Straight: M90
MIL-P-14232/P5800885	Packaging of Telescope, Straight: M90 with Carrying Case

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

DEPARTMENT OF TRANSPORTATION, BUREAU OF HAZARDOUS MATERIAL

49 CFR 171-190	Interstate Commerce Commission and Department of Transportation and Regulations for the Transportation of Explosives and other Dangerous Articles.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington D.C. 20402.)

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:18Z
Check the source to verify that this is the currentversion before use.

3. REQUIREMENTS

3.1 Radiological requirements telescope: P/N 12599180.

3.1.1 Radioactive material. Prospective bidders should be cognizant of the need for a Nuclear Regulatory License governing the procurement, processing, handling and shipping of radioactive material.

3.1.2 Regulations pertaining to radioactive devices. Marking, identification, handling and shipping of Radioactive devices shall be in accordance with DSAM 4145.8 and MIL-STD-129 as applicable.

3.1.3 External tritium contamination. Tritium shall not be present on the external surfaces of the Telescope in excess of 1000 dpm/100 sq. cm.

3.2 Materials. Materials shall be in accordance with drawings, material specifications and general specifications forming a part of this specification.

3.3 Fabrication. The M90C, M90D and M90F telescopes shall be manufactured in accordance with Drawing 8205096 and drawings pertaining thereto. The P/N 12599180 telescope shall be manufactured in accordance with Drawing 12599180 and drawing pertaining thereto.

3.4 General specification. The contractor shall be responsible for the compliance with the requirements of specification MIL-F-13926 as they apply

3.5 Environmental.

3.5.1 Storage temperature. The telescope shall show no evidence of physical failure and shall meet all requirements of this specification at standard ambient temperature (+60 degrees to +90 degrees Fahrenheit) after having been thermally stabilized at ambient temperature of +160 degrees and -80 degrees Fahrenheit for a period of 6 hours at each temperature extreme.

3.5.2 Operating temperature. The telescope shall meet the applicable requirements of this specification while exposed and thermally stabilized at ambient temperature of +60 degrees Fahrenheit to +90 degrees Fahrenheit.

3.5.3 Vibration. The telescope shall be vibrated at a constant frequency of 30 $\pm$ 5 cycles per second with an amplitude of 1/16 inch (1/8 inch total excursion). Subsequent to vibration there shall be no evidence of damage or physical failure and the telescope shall meet the requirements of 3.6 to 3.9 inclusive.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:18Z
Check the source to verify that this is the current version before use.

3.5.4 Rain test. The Telescope shall meet the requirements of Procedure I of the rain test of MIL-F-13926.

3.6 Cleanliness. Subsequent to vibration the telescope shall meet the cleanliness requirements of MIL-O-13830. There shall be no more than 2 particles of dirt visible on the reticle. The size of each particle shall not exceed the aparrent width of a reticle line. There shall be no other dirt within the telscope which interferes with observation or adversely affects image quality.

3.7 Sealing.

3.7.1 Telescopes: M90C, M90D and M90F. The telescope shall show no evidence of leakage when subjected to an external pressure of 5 ± 0.10 pounds per square inch gauge pressure (psig).

3.7.2 Telescope: P/N 12599180. The P/N 12599180 telscope body shall be capable of sustaining an internal pressure of 5.0 ± 0.50 pounds per square inch gauge pressure (psig) for a period of 2 hours (minimum) without loss of pressure in excess of 0.5 psig.

3.8 Purging, telescope: P/N 12599180. The P/N 12599180 Telescope body shall be purged with dry nitrogen supplied at a pressure of 8 ± 0.50 psig until the dew point of the emergent gas is no higher than -25 degrees Fahrenheit. Purging apertures shall be quickly and positively closed to minimize intermingling of external atmosphere upon disconnecting of purging equipment.

3.9 Optical.

3.9.1 Collimation.

3.9.1.1 Open sight. The line of sight of the open sight shall be parallel with the optical axis of the telescope within one degree.

3.9.1.2 Telescope M90C. The line of sight thru the boresight point shall subtend an angle of 51.7 mils ± 0.5 mils with a line of sight established parallel to the bottom of the dovetail mounting surface.

3.9.1.3 Telescope: M90D. The line of sight thru the boresight point shall subtend an angle of 41.5 mils ± 0.5 mils with a line of sight established parallel to the bottom of the dovetail mounting surface.

3.9.1.4 Telescope: M90F. The line of sight thru the intersection of the cross lines shall be parallel to the bottom of the dovetail mounting surface within 0.5 mils.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:18Z
Check the source to verify that this is the current version before use.

3.9.1.5 Telescope: P/N 12599180. The line of sight thru the boresight point shall subtend an angle of 30.0 mils + 0.5 mils with a line of sight established parallel to the bottom of the dovetail mounting surface.

3.9.2 Image tilt. The image of a vertical target line shall be vertical within 1 degree of arc.

3.9.3 Parallelism of reticle and image.

3.9.3.1 Telescopes: M90C and M90D. With the flat of the dovetail horizontal, the horizontal reticle line through the geometric axis shall not deviate from the image of a horizontal target line by more than the angle subtended by a 3.0 mil block at one extremity of the horizontal reticle line when the other extremity of the reticle line is in coincidence with the horizontal target line.

3.9.3.2 Telescope: M90F. With the flat of the dovetail horizontal, the horizontal reticle line through the geometric axis shall not deviate from the image of the horizontal target line by more than the angle subtended by a 3.0 mil block at one extremity of the horizontal reticle line when the other extremity of the reticle line is on coincidence with the horizontal target line.

3.9.4 Reticle accuracy,telescopes: M90C, M90D and P/N 12599180. The total angular subtense of the reticle graduations between zero and maximum range shall be as follows:

Telescope	Range	Mils	Tolerance(Mils)
M90C	0-2700	111.6	+/-0.6
M90D	0-2700	120.3	+/-0.6
P/N 12599180	------	60.0	+/-0.6

3.9.5 Parallax. Parallax at the opticl axis shall not exceed 0.2 mil when viewing a target at a distance of between 200 yards and infinity.

3.9.6 Resolution. Resolving power on the optical axis shall be 10 seconds of arc or less.

3.9.7 Eyepiece focus. The eyepiece focus shall be fixed between -0.50 and -1.0 diopter.

3.9.8 Illumination. The telescope shall meet the "Illuminated reticles" requirement of MIL-O-13830. The reticle shall be clearly defined when in a darkened area.

3.10 Eyeshield. The rubber eyeshield shall show no evidence of deterioration, cuts, or tears and shall fit snugly on the telescope body.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:18Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisons. The component and subassembly inspection requirements of MIL-F-13926 form a part of the quality assurance provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article (Initial Production) approval. The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval test shall consist of three (3) telescopes plus three (3) each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.2.1 Government testing. When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.2.2 Contractor testing. When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection.

4.3 Inspection Provisions.

4.3.1 Submission of product. Unless otherwise specified by the contracting office, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" provision of MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202640-17T14:18Z
Check the source to verify that this is the currentversion before use.

4.3.2 Examination and Tests.

4.3.2.1 Components and subassemblies. All components and subassemblies shall be inspected in accordance with the inspection provisions contained in Supplementary Quality Assurance Provisions (SQAP) listed in the technical data package (TDP). In the absence of SQAP's the applicable Quality Assurance Provisions of MIL-F-13926 shall apply.

4.3.2.2 Final acceptance inspection. Subsequent to first article approval, examination and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Table I herein. Examination and tests for Packaging, Packing and Marking shall be in accordance with MIL-P-14232 and section 5 herein. The tabulated classification of defects in Table I and II shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Governement acceptance or rejection by item or lot.

TABLE I - CLASSIFICATION OF DEFECTS

NO	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
MAJOR:	100% INSPECTION		
101	Sealing (M90C, M90D, M90F)	3.7.1	4.6.5.1
102	Sealing (P/N 12599180)	3.7.2	4.6.5.2
103	Purging (P/N 12599180)	3.8	4.6.6
MAJOR:	AQL 0.65% DEFECTIVE		
104	Ext'l Tritium Contamination	3.1.3	4.6.1
105	Vibration	3.5.3	4.6.2.2
106	Cleanliness	3.6	4.6.4
107	Open Sight	3.9.1.1	4.6.6
108	Collimation(M90C)	3.9.1.2	4.6.6
109	Collimation(M90D)	3.9.1.3	4.6.6
110	Collimation(M90F)	3.9.1.4	4.6.6
111	"(P/N 12599180)	3.9.1.5	4.6.6
112	Image Tilt	3.9.2	4.6.7
113	Parallelism of Reticle & Image (M90C & M90D)	3.9.3.1	4.6.8
114	Parallelsim of Reticle & Image (M90F)	3.9.3.2	4.6.8
115	Reticle Accuracy (M90C,M90D,P/N 12599180)	3.9.4	4.6.9
116	Parallax	3.9.5	4.6.10
117	Resolution	3.9.6	4.6.11
118	Eyepiece Focus	3.9.7	4.6.12
119	Illumination	3.9.8	4.6.13
120	Eyeshield	3.10	4.7
MINOR:	NONE		

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:18Z
Check the source to verify that this is the current version before use.

NOTE: The tests of Table I shall be conducted at a temperature between +60 degrees and +90 degrees Fahrenheit.

4.3.3 Acceptance and rejection. Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.4 Special Sampling.

General. Three telescopes shall be selected at random as a special sampling from each 100 produced or one months production, whichever occurs first. The sample shall meet the requirements of Table II.

TABLE II

NO	CHARACTERISTIC	REQUIREMENT	TEST PROCEDURE
301	Fabrication	3.3	Applicable drawings-visual
302	General Specification	3.4	MIL-F-13926 & MIL-O-13830
303	Storage Temperature	3.5.1	4.6.2.1
304	Operating Temperature	3.5.2	4.6.2.1
305	Rain	3.5.4	4.6.2.3

4.4.2 Failure of sample. Should any one of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.3.3).

4.5 Test equipment.

4.5.1 Inspection equipment. Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

4.5.2 Government furnished inspection equipment. Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:18Z
Check the source to verify that this is the current version before use.

4.5.3 Contractor Furnished Inspection Equipment.

4.5.3.1 Government design. Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications or SQAP forming a part of the contract shall be supplied by the contractor in accordance with technical data listed in the list of inspection documents when provided with the Technical Data Package (TDP).

4.5.3.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the "Test Methods and Procedures" specified in this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerance limit used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptabiltiy of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when nonconforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.5.3.3 Inspection equipment design requirements.

4.5.3.3.1 Sealing, telescopes: M90C, M90D, & M90F. Special pressure testing equipment, as shown on Drawing 7680673, shall be capable of being rendered pressure-tight and of holding the required pressure for the specific period of time with a test specimen inserted in the chamber.

4.5.3.3.2 Performance. Special test equipment utilized to test the telescope shall conform to drawing 7694010, Test Fixture for Telescope, M90 Series. The test equipment shall permit inserting and securing the dovetail of the telescope in a horizontal plane within 10 seconds of arc. The fixture shall also consist of a target collimator containing a calibrated reticle to check collimation, parallax, and accuracy readings.

4.6 Test methods and procedures.

4.6.1 External tritium contamination. Contamination test shall be performed by wiping the telescope with filter paper moistened in distilled water. The wiping shall be performed with moderate finger pressure. The damp filter paper shall be placed in a container with the proper portion of scintillation liquid.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:18Z
Check the source to verify that this is the current version before use.

The read out shall be within 10% of the known standard value when counted to a total of 2000 disintergrations. The actual test for determining contamination is performed by placing the container into the scintillation system. The measured contamination shall be within the limits specified in 3.1.3.

4.6.2 Environmental.

4.6.2.1 Storage and operating temperatures. Test equipment utilized in this test shall be in accordance with the "Test Facilities" requirements of MIL-F-13926 and the conditions of 3.5.1. The telescope shall be exposed to and stabilized at the temperature extremes for a minimum of 6 hours. The temperatures shall be cycled to avoid subjecting the telescope to thermal shock. Subsequent to the temperature exposures, the telescope shall be stabilized in an ambient temperature between +60 and 90 F and subjected to the requirements of 3.5.2

4.6.2.2 Vibration. Standard vibrating equipment capable of providing the amplitude and frequency specified in 3.5.3 shall be utilized for the vibration test. Unless otherwise specified , the test equipment shall be in accordance with the "test facilities" requirements of MIL-F-13926. The telescope shall be mounted horizontally by means of a government approved adapter that is secured to the vibration fixture. This adapter shall contain the necessary dovetail slot capable of mounting and securing the dovetail of the telescope during the vibration test. Subsequent to the test the telescope shall be visually examined for damage. The telescope shall then meet the examinations and tests of this specification.

4.6.2.3 Rain. The rain test chamber shall be in accordance with the "Test Facilities" section of MIL-F-13926. The test shall be performed according to Procedure I of the rain test in MIL-F-13926. There shall be no degradation of the telescope and it shall meet the examinations and tests of this specification.

4.6.3 Cleanliness. The optical surfaces of the telescope shall be inspected for cleanliness in accordance with MIL-O-13830. The telescope shall conform to the requirement of 3.6.

4.6.4 Sealing.

4.6.4.1 Sealing, Telescopes: M90C, M90D & M90F. The external pressure testing of the telescope shall be performed with test equipment conforming to 4.5.3.3.1. The pressure shall be applied to the telescope by means of the adapter specified in the test equipment. Place the telescope in the adapter and pressurize with dry air.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:18Z
Check the source to verify that this is the current version before use.

Retain the applied pressure of 5 ± 0.10 pounds per square inch gage (psig) on the telescope for a period of 5 minutes ± 15 seconds. At the end of the time period there shall be no evidence of leakage as detected on the dial indicators of the testing equipment, in order to conform to the requirements of 3.7.1.

4.6.4.2 Sealing, telescope: P/N 12599180. The gage used in this test shall be capable of assuring conformance to the requirements of 3.7.2. The telescope shall be pressurized with dry nitrogen to a pressure of 5.0 +/- 0.5 pounds per square inch gage. The pressure shall be noted and subsequent to the 2 hour period checked for compliance with 3.7.2.

4.6.5 Purging, telescope: P/N 12599180. Connect the test equipment to the purging valve of the telescope. Adjust the dry nitrogen to the pressure specified in 3.8. The pressure is to remain constant until the dewpoint of the emergent gas is no higher than -25 degrees F.

4.6.6 Collimation. The collimation test shall be performed using the test equipment described in 4.5.3.3.2 or by using a government approved wall target. The wall target shall be placed at a distance and have target lines that shall represent the applicable requirements of 3.9.1. The test collimator or wall target must locate the line of sight parallel to the bottom of the dovetail to within 10 seconds. Once the bottom of the dovetail surface is located, sight through the telescope eyepiece to determine if the boresight point is in conformance with 3.9.1.

4.6.7 Image tilt. This test shall be performed with the aid of an auxiliary telescope containing a vertical and horizontal reticle line, and the test equipment in 4.5.3.3.2. The telescope shall be at least 3 power (3X). Plumb the vertical reticle line of the telescope to a plumb line and position the eyepiece of the telescope under test. View through the telescope and establish one extremity of the telescope vertical reticle line coincident to the respective target image line. The image of the target shall be parallel to the telescope's reticle line within the tolerance specified in 3.9.2 as measured on the target.

4.6.8 Parallelism of reticle and image. This test is made with one extremity of the horizontal reticle line of the auxiliary telescope in coincidence with the horizontal target line image. The reticle of the telescope under test shall be parallel to the target line within the tolerances specified in 3.9.3.1 and 3.9.3.2 as measured on the target.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:18Z
Check the source to verify that this is the current version before use.

4.6.9 Reticle accuracy, telescopes M90C, M90D & P/N12599180. Utilizing the equipment in 4.5.3.3.2 the horizontal cross line of the boresight line shall be coincident to a calibrated mark on the target reticle. A government approved wall target can also be used in place of the collimator target. The maximum range lines on the reticle shall meet the requirements and shall be within the tolerance specified in 3.9.4 as measured on the target image.

4.6.10 Parallax. This test shall be performed by observing through the telescope eyepiece. Parallax is recognized as displacement caused between the telescope reticle and the image of the target when the observer's head is moved from side to side or up and down. Such movement of the observer's head shall not cause displacement of the two images to exceed the tolerance specified in 3.9.5 at the distance indicated.

4.6.11 Resolution. A resolution target and an auxiliary telescope of at least 3 power (3X) shall be used for this test. The resolution target shall be either a wall target or reticle in a collimator. The target must represent the angular subtense for seconds of arc specified in 3.9.6. The target used shall either be as specified in MIL-O-13830 or the Air Force Resolution chart which forms a part of NBS circulars. It shall have the detectable line structure and proper line count in each meridian. The telescope shall resolve the target within the requirements of 3.9.6.

4.6.12 Eyepiece focus. This test shall be performed utilizing a dioptometer with at least a minus 1.0 diopter to a plus 1.0 diopter setting. The crossline reticle of the dioptometer shall be adjusted to the individual eye. Placing the dioptometer at the eyepiece of the telescope under test, observe the sharpness of the telescope reticle in comparision to the reticle in the dioptometer. Adjust the dioptometer until both reticle lines appear to be equal, then read the diopter scale of the dioptometer. The index shall be within the tolerance specified in 3.9.7.

4.6.13 Illumination. This is a visual check performed in a darkened area. The graduations shall appear to be evenly illuminated without flaring at the edge of the graduations or bright spots over the area as required by 3.9.8.

4.7 Eyeshield. The eyeshield shall be given a visual and tactile examination. The material shall show no physical damage or deterioration and it shall fit snug to the eyepiece end of the telescope as required by 3.10.

Source: https://assist.dla.mil -- Downloaded: 202610-17T14:18Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, Packing and Marking. Packaging, packing and marking shall be in accordance with MIL-P-14232, MIL-STD-129 and applicable packaging data sheets. The level of protection shall be specified in the procurement document.

6. NOTES

6.1 Intended use.

6.1.1 Telescope: M90C. This telescope is intended for use on the 105MM Recoilless Rifle: M27A1.

6.1.2 Telescope: M90D. This telescope is intended for use on the 75MM Recoilless Rifle: M20

6.1.3 Telescope: M90F. This telescope is intended for alignment of the Hawk missile launcher and utilizes a plain cross line reticle. It is also used in conjunction with Radar Chronograph: M36 for alignment purposes.

6.1.4 Telescope: P/N 12599180. This telescope is intended for use as the direct fire sight for the 105MM Light Howitzer: M119A1.

6.2 Ordering data. Procurement documents should specify:

a. Title, date, and number of this specification.

b. Serial number to be used for identification marking.

c. Applicable packaging data sheet number.

d. Selection of applicable levels of preservation and packaging

e. Requirements for first article testing.

f. Contract data requirements for submission of inspection equipment designs to Data Item Description DI-R-1714.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:18Z
Check the source to verify that this is the current version before use.

6.3 Submission of designs for approval. Contractor designs for final acceptance inspection shall be approved by the Government prior to fabrication or procuring the equipment. The contractor is referred to MIL-HDBK-204 for guidance. Submission of design concept on inspection equipment is permissible for tentative approval. The completion date for design review will be based on the date of the final submission of designs and the required delivery schedule is stipulated in the contract. Submit designs as required to: Commander, US Army Armament Research Development and Engineering Center, ATTN: AMSMC-QAF-I (D), Picatinny Arsenal, New Jersey 07806-5000. When the contractor submits inspection equipment designs to the government for approval, he shall give the following information in his letter of transmittal:

a. The contract number.

b. The contract item (name, model number, etc.).

c. The designs remaining to be submitted and the expected date of submittal.

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.5 Subject term (key word) listing.

Telescope
Optical
Fire Control
Radioactive
Tritium

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1240-A925)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:18Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-10646D	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 20260-17T14:18Z
Check the source to verify that this is the current version before use.