MILITARY SPECIFICATION
FUZE, MECHANICAL TIME, M543A1, ASSEMBLY

This amendment forms a part of Military Specification MIL-F-60204 (MU), 20 November 1964.

Paragraph 3.5: Delete and substitute:

"3.5 Dynamic regulation.- The movement subassembly shall have a timing accuracy of ± 0.07% from 10 to 95 seconds when regulated at the frequency specified on the applicable drawing and rotated at a spin of 6000 ± 25 r.p.m."

Table I: "Delete and substitute amended Table I as shown on page 2."

Paragraph 4.4.16: Delete and substitute:

"4.4.16 Dynamic regulation monitoring.- The following procedure shall be observed: The movement subassemblies shall be regulated, using the operational procedures furnished with the equipment. The movement subassembly shall be rotated in a clockwise direction when viewed from the bottom (No. 1 plate) at a constant speed of 6000 ± 25 r.p.m. Timekeeping and performance shall be checked over a period of not less than 95 seconds. No adjustment shall be made on the escapement during the 95 second check run. Inspection shall be performed on a monitoring basis only (paragraph 4.3.3.13)."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1390 - A441

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.

TABLE I

Weapon	Charge Zone	Set Time (Sec)		Limits for Individual Rounds (Sec)	Limits for Sample Mean Time (Sec) Sample Size 18	17	16	15	14
8" Howitzer	1	20	UL	21.029	20.628	20.630	20.632	20.634	20.637
			LL	19.799	20.200	20.198	20.196	20.194	20.191
8" Howitzer	7	55	UL	56.216	55.568	55.571	55.574	55.577	55.581
			LL	54.366	55.014	55.011	55.008	55.005	55.001

Weapon	Charge Zone	Set Time	Upper Limits for Sample Std. Dev. (Sec) Sample Size 18	17	16	15	14
8" Howitzer	1	20	.254	.257	.259	.261	.264
8" Howitzer	7	55	.411	.417	.420	.423	.428

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:17Z
Check the source to verify that this is the current version before use.