MILITARY SPECIFICATION

POWER SUPPLY PP-4763( )/GRC

This amendment forms a part of Military Specification MIL-P-55695(EL), dated 14 April 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 2

2.1 Add:

NN-P-71	Pallet, Materials handling, Wood (General Construction Requirements)
PPP-T-76	Tape, Pressure sensitive Adhesive paper, Water Resistant (For carton testing)

Delete:

QQ-P-416	Plating, Cadmium (Electrodeposited)
TT-E-529	Enamel, Alkyd, Semi-gloss
TT-P-636	Primer coating, Synthetic, Wood and Ferrous Metal
PPP-T-97	Tape Pressure sensitive Adhesive, Filament Reinforced

Page 15

4.8.5 Delete and substitute:

SALT FOG TEST (see 3.14.2.5) - After completion of the Salt Fog test in accordance with Method 509, Procedure 1 of MIL-STD-810, the Power Supply shall be examined visually with the aid of a 10-power magnifier. The Power Supply shall show no evidence of degradation such as flaking, pitting, blistering or loosening of finish on metal surfaces. Electrical operation is not required.

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:57Z
Check the source to verify that this is the current version before use.

Page 15

4.8.6 Add:

"Note: maximum frequency for all tests shall be 33 Hz"

Page 16

4.8.9 Delete and substitute:

FUNGUS TEST (see 3.7.2) - The Power Supply shall be subjected to 28 days of the fungus test specified in MIL STD 810, Method 508, Procedure 1. After completion of the test the power supply shall be inspected for evidence of damage and deterioration. Electrical operation is not required.

Page 17

4.12 - Change "Test Plan IVA" to "Test Plan XXV"

4.12.2 - Delete and substitute:

4.12.2 Equipment Quantity - A minimum of ten (10) equipments shall be selected from each production lot for each reliability acceptance test.

In no way may more than fifteen (15) equipments be used for a reliability acceptance test.

A production lot is defined as two months production, unless otherwise specified in the contract.

5 - Delete and substitute:

Source: https://assist.dla.mil -- Downloaded: 202640-22T23:57Z
Check the source to verify that this is the currentversion before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C, as specified (see 6.(2)(b).

5.1.1 Level A.

5.1.1.1 Cleaning. Power Supply PP-4763( )/GRC shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Power Supply PP-4763( )/GRC shall be dried in accordance with the applicable procedures of MIL-P-116.

5.1.1.3 Preservation application. None required.

5.1.1.4 Unit packaging. Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.4.1 Technical literature. Each technical literature shall be packaged method IC-1.

5.1.1.4.2 Power Supply PP-4763( )/GRC. Each power supply shall be packaged method III as follows: Wind the A.C. cable on the mounting bracket and secure the plug end to the bracket with twine. Cushion the power supply on all surfaces with cells or pads or both fabricated of fiberboard conforming to PPP-F-320, class weather-resistant, W5c, designed to protect all projections and absorb the shock of impact in handling and transit. Place the cushioned power supply within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Close the box in accordance with the appendix of the box specification.

5.1.2 Level C. Power Supply PP-4763( )/GRC. Each power supply shall be preserved and packaged in a manner that will afford adequate protection against physical and environmental damage during shipment, handling and limited intransit storage.

5.2 Packing. Packing shall be level A, B or C, as specified. Shipping containers for all levels shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents (see 6.(2)b).

5.2.1 Level A.

5.2.1.1 Palletized load. A quantity of Power Supply PP-4763( )/GRC, packaged as specified in 5.1, shall be placed on a pallet, load type I conforming to MIL-STD-147 except that the pallet shall be softwood conforming to NN-P-71, type IV, size 2. A fiberboard cap shall be employed over the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:57Z
Check the source to verify that this is the current version before use.

load having two sides extending down the stacked load at least 12 inches to accommodate marking requirements. The cap shall be fabricated of fiberboard conforming to PPP-F-320, class weather-resistant, W5s or V3c. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A or shrink film.

5.2.1.2 Less than palletized load. When quantities per destination are less than a pallet load, the item packaged as specified in 5.1, shall be waterproofed with tape conforming to PPP-T-76, in accordance with the taping requirements of the appendix of the box specification. A quantity of the waterproofed containers shall be packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2; or PPP-B-585, style 2 or 3, class 3. Skids, 3 x 4 inch, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, finish A.

5.2.2 Level B.

5.2.2.1 Palletized load. A quantity of Power Supply PP-4763( )/GRC, packaged as specified in 5.1, shall be palletized as specified in 5.2.1.1.

5.2.2.2 Less than palletized load. When quantities per destination are less than a pallet load, a quantity of Power Supply PP-4763( )/GRC, packaged as specified in 5.1, shall be packed within a close-fitting box conforming to PPP-B-601, domestic type; or PPP-B-621, style 4, class 1. Skids, 3 x 4 inch, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto.

5.2.3 Level C.

5.2.3.1 Palletized load. A quantity of Power Supply PP-4763( )/GRC, packaged as specified in 5.1, shall be palletized as specified in 5.2.1.1, except that the fiberboard caps shall be class domestic.

5.2.3.2 Less than palletized load. When quantities per destination are less than a pallet load, a quantity of Power Supply PP-4763( )/GRC, packaged as specified in 5.1, shall be packed as specified in 5.2.2.2.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:57Z
Check the source to verify that this is the current version before use.

Page 19

6.2(b) - delete "level B"

Page 20

6.2 - Add 6.2(j)

6.2(j) When rough handling is required

Custodian

ARMY - EL

Preparing Activity:

ARMY - EL

Project No. 5820-A-638

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:57Z
Check the source to verify that this is the current version before use.