INCH-POUND

MS3112H
w/AMENDMENT 1
05 March 2024
SUPERSEDING
MS3112H
1 March 2007

DETAIL SPECIFICATION SHEET

CONNECTORS, RECEPTACLE, ELECTRICAL, BOX MOUNTING, FLANGE, BAYONET COUPLING, SOLDER CONTACT, SERIES 1

Inactive for new design after 15 December 1998. For new design, use MS3470.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-26482.




FIGURE 1. Receptacle.

AMSC N/A

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.




FIGURE 1. Receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.




FIGURE 1. Receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.

Shell size	A max length	B (TP) ℄ – ℄ mounting holes	C + .031 - .016 OD	F + .031 - .000 mounting flange location	G ± .016 thick mounting flange	H ± .005 dia mounting holes
8	.828 (21.03)	.594 (15.09)	.438 (11.12)	.431 (10.95)	.062 (1.57)	.120 (3.05)
10	.954 (24.23)	.719 (18.26)	.562 (14.27)			
12	1.047 (26.59)	.812 (20.62)	.688 (17.48)			
14	1.141 (28.98)	.906 (23.01)	.812 (20.62)			
16	1.234 (31.34)	.969 (24.61)	.938 (23.83)			
18	1.328 (33.73)	1.062 (26.97)	1.062 (26.97)			
20	1.453 (36.91)	1.156 (29.36)	1.188 (30.18)	.556 (14.12)	.094 (2.39)	
22	1.578 (40.08)	1.250 (31.75)	1.312 (33.32)			
24	1.703 (43.26)	1.375 (34.93)	1.438 (36.53)	.589 (14.96)		.147 (3.73)

Shell size	J max	L max overall length	N UNEF-2A thread optional	P min edge distance	R max packing ring	S max
8	.354 (8.99)	.978 (24.84)	.4375-28	.035 (0.89)	.329 (8.36)	.087 (2.21)
10			.5625-24		.457 (11.61)	
12			.6875-24		.564 (14.33)	
14			.8125-20		.689 (17.50)	
16			.9375-20		.814 (20.68)	
18			1.0625-18		.907 (23.04)	
20	.417 (10.59)	1.196 (30.38)	1.1875-18	.050 (1.27)	1.039 (26.39)	.212 (5.38)
22			1.3125-18		1.164 (29.57)	
24	.445 (11.30)		1.4375-18		1.289 (32.74)	

FIGURE 1. Receptacle - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.005	0.13	.020	0.51
.010	0.25	.031	0.79
.015	0.38	.070	1.78
.016	0.41	.156	3.96


NOTES:
1. Dimensions are in inches. Metric equivalents are given for information only.
2. True position (TP) tolerances specified are in accordance with ASME Y14.5.

FIGURE 1. Receptacle - Continued.

REQUIREMENTS:

Dimensions and configurations: See figure 1.
Connector mating: This connector mates with MS3111, MS3116, MS3121 and MS3126.
For insert arrangement: See MIL-STD-1669.
Intermateability dimensions are in accordance with MIL-DTL-26482.

Part or Identifying Number (PIN) example:



Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-26482, this document references the following:

MS3111
MS3116
MS3121
MS3126
MS3470
MIL-STD-1669
ASME Y14.5

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – AS
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

(Project 5935-2024-081)

Review activities:
Army – AV
Navy – SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:58Z
Check the source to verify that this is the current version before use.