INCH-POUND
MIL-PRF-83504/9C
23 February 2001
SUPERSEDING
MIL-PRF-83504/9B
27 October 1993

PERFORMANCE SPECIFICATION SHEET

SWITCHES, DUAL IN-LINE PACKAGE (DIP), RECESSED ROCKER ACTUATOR, STANDARD PROFILE, DOUBLE POLE, DOUBLE THROW STATIONS, SEALED BASE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-PRF-83504.



FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.



Typical circuit diagram
(Viewed from top)

Inches	mm	Inches	mm
.003	0.08	.090	2.29
.005	0.13	.100	2.54
.010	0.25	.160	4.06
.012	0.30	.200	5.08
.015	0.38	.240	6.10
.020	0.51	.300	7.62
.021	0.53	.380	9.65
.030	0.76	.447	11.35
.040	1.02		

NOTES
1. Dimensions are in inches. Metric equivalents are given for information only.
2. Each switch position shall be numbered as shown.
3. Exact shape of switch is optional, provided outline dimensions are not exceeded.
4. Design of terminals and standoffs are optional

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS:

Material:

Body and actuator rocker: Molded plastic.

Terminals: The terminals shall be equivalent to or better than solder over nickel over copper over brass.

Terminal sealing and solderability: The terminal potting material meniscus may extend to .030 inch maximum beyond the solder standoff.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.

Dimensions and configuration: See figure 1 and table I.

Seal: Sealed base. No top seal.

Switch position and setting identification: See figure 1.

Orientation: See figure 1.

Tape top seal: Not provided

Operating force: 6-32 ounces.

Electrical ratings:

10 mA maximum at 50 mV, switching (resistive load)
100 mA maximum at 6 V dc, switching (resistive load)
25 mA maximum at 24 V dc, switching (resistive load).

Application note: In applications where the switch will mate with sockets or with panel boards, the user should consider the compatibility of the mating terminals with respect to finished and mechanical configurations.

Part or Identifying Number (PIN): M83504/09- (and dash number from table I).

TABLE I. Dash numbers and characteristics

Dash number	Number of stations	Dimension "A" inches (mm)	
021	2	.380	(9.65)
022	3	.580	(14.73)
023	4	.780	(19.81)

1/ PIN's M83504/09-002, -003, -004 (switches with gold finish terminals have been cancelled without replacement

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, AV, MI
Navy - AS
Air Force - 99

Preparing activity:
DLA - CC

(Project 5930-1128-08)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.