MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

INDUCTORS

TO ALL HOLDERS OF DOD-STD-35-37A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-37A(MI) HAVE BEEN RESISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	18 SEPTEMBER 1992	v	15 DECEMBER 1978
1	15 DECEMBER 1978 (Reprinted without change)		
2	18 SEPTEMBER 1992	2	15 DECEMBER 1978
3	18 SEPTEMBER 1992	3	15 DECEMBER 1978
4	18 SEPTEMBER 1992	4	15 DECEMBER 1978
57	15 DECEMBER 1978 (Reprinted without change)		
58	13 SEPTEMBER 1992	53	15 DECEMBER 1978
59	18 SEPTEMBER 1992	59	15 DECEMBER 1978
60	15 DECEMBER 1973 (Reprinted without change)		
65	15 DECEMBER 1978 (Reprinted without change)		
66	13 SEPTEMBER 1992	66	15 DECEMBER 1978
67	18 SEPTEMBER 1992	67	15 DECEMBER 1978
68	15 DECEMBER 1978 (Reprinted without change)		
73	15 DECEMBER 1978 (Reprinted without change)		
74	18 SEPTEMBER 1992	74	15 DECEMBER 1978
75	18 SEPTEMBER 1992	75	15 DECEMBER 1978
76	15 DECEMBER 1978 (Reprinted without change)		
81	15 DECEMBER 1978 (Reprinted without change)		
82	18 SEPTEMBER 1992	82	15 DECEMBER 1978
83	18 SEPTEMBER 1992	83	15 DECEMBER 1978
84	15 DECEMBER 1978 (Reprinted without change)		
87	15 DECEMBER 1978 (Reprinted without change)		
88	18 SEPTEMBER 1992	88	15 DECEMBER 1978
89	18 SEPTEMBER 1992	89	15 DECEMBER 1978
90	15 DECEMBER 1978 (Reprinted without change)		

AMSC N/A AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
93	15 DECEMBER 1978 (Reprinted without change)		
94	18 SEPTEMBER 1992	94	15 DECEMBER 1978
95	18 SEPTEMBER 1992	95	15 DECEMBER 1978
96	18 SEPTEMBER 1992	96	15 DECEMBER 1978
97	18 SEPTEMBER 1992	97	15 DECEMBER 1978
98	15 DECEMBER 1978 (Reprinted without change)		
119	15 DECEMBER 1978 (Reprinted without change)		
120	18 SEPTEMBER 1992	120	15 DECEMBER 1978
121	18 SEPTEMBER 1992	121	15 DECEMBER 1978
122	15 DECEMBER 1978 (Reprinted without change)		
135	15 DECEMBER 1978 (Reprinted without change)		
136	18 SEPTEMBER 1992	136	15 DECEMBER 1978
137	18 SEPTEMBER 1992	137	15 DECEMBER 1978
138	15 DECEMBER 1978 (Reprinted without change)		

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-37A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army - MI

Review activities:
Army - AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army – MI

(Project - EGDS-A415)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	APPLICABLE DOCUMENTS	4
	2.1	Government documents	4
	2.2	Other publications	5
	3.	DEFINITIONS	6
	4.	GENERAL REQUIREMENTS	7
	4.1	Introduction	7
	4.2	Specification Requirement Sheet (SRS)	7
	4.3	Configuration	7
	4.3.1	Dimensions	7
	4.3.2	Illustrations	7
	4.4	Units of measure	7
	5	DETAILED REQUIREMENTS	9
	5.1	Introduction	9
	5.2	MSE Formats	9
	5.3	Referenced documents	9
	5.4	Tabulation	9
	5.5	Keyword Code Index (KCI) and Standard Paragraphs	11
	5.5.1	Interrelationship of Codes	11
	5.5.2	Automatic MSE Data	11
	5.5.3	DOD-STD-35 Tables	11

TABLES

Table	I.	Title Index	2
	III.	Tabulation Candidates	10

APPENDICES

Appendix	A.	Illustrations	150
	B.	Characteristic Code Index	173
		Index	179

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Inductors.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. It is recommended that MIL-STD-1286, Selection and Use of Transformers, Inductors, and Coils be reviewed prior to using this dash-numbered part book.

The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code space on the SRS blank, and attach a request for th eassignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit doces listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the a part of the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with the title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found usefull in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIGG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying the identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	COVERAGE
INDUCTOR, POWER	020001	MIL-T-27	POWER, AUDIO FREQ, HIGH Q, VARIABLE, FIXED
		MS16465	POWER, TYPE TF4RX04FA207
		MS16469	POWER, TYPE TF4RX04KB211
		MS75001	POWER, TYPE TF4RX04MA010
		MS75002	POWER, TYPE TF4RX04NA012
		MS75003	POWER, TYPE TF4RX04YY013
		MS90013	POWER, TYPE TF4TX04HA005
INDUCTOR, REACTOR	020002	MIL-T-27 MIL-T-83720	NONXPL, OPEN COIL AND CORE CONSTRUCTION
INDUCTOR, DECADE	020003	MIL-T-27	
CHOKE	020004	MIL-C-60190	VOLTAGE RGLTR (10525930)
REACTOR, POWER	020006	MIL-T-27	
REACTOR, NETWORK	020007	MIL-T-27	
REACTOR, SWITCHING	020008	MIL-T-27	
INDUCTOR, TOROIDAL	020009	MIL-T-27	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	COVERAGE
INDUCTOR, CHIP, THICK FILM, FIXED	020010	MIL-C-83446	FOR MELEC CKT
INDUCTOR, CHIP, SHIELDED, THICK FILM, FIXED	0200111	MIL-C-83446	FOR MELEC CKT
INCUCTOR, CHIP, THICK FILM, VARIABLE	020012	MIL-C-83446	FOR MELEC CKT
INDUCTOR	020013	MIL-T-27 MIL-C-83446 MIL-T-83720	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those lised in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-I-l72l4	Indicator, Permeability; Low-Mu (Go-No-Go)
MIL-C-83446	Inductors, Chip, Thick or Thin Film, Fixed or Variable, General Specification For

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-8l0	Environmental Test Methods for Aerospace and Ground Equipment
MIL-STD-883	Test Methods and Procedures for Micro-electronics
MIL-STD-1285	Marking of Electrical and Electronic Parts

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4844	BETWEEN MUTUALLY INSULATED PARTS.
4845	BETWEEN ALL INSULATED PARTS AND GROUND.
4846	BETWEEN CURRENT CARRYING PARTS AND THE CASE .
4867	DURATION OF APPLICATION OF TEST VOLTAGE SHALL BE 4867. SECOND(S).
4869	REGULATION OF TEST VOLTAGE SHALL BE WITHIN 4869 PERCENT.
4870	THE KILOVOLTAMPERE RATING OF HIGH VOLTAGE SOURCE SHALL BE NOT LESS THAN 4870 KILOVOLTAMPERE(S).
4717	THE SURGE CURRENT SHALL BE NOT GREATER THAN 4717 AMPERE(S).
4897	THE SURGE CURRENT SHALL BE NOT GREATER THAN 4897 MILIAMPERE(S).
2371	EFFECTIVE PARALLEL RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACORDANCE WITH THE BASE DOCUMENT, EXCEPT 2371.
2372	EFFECTIVE PARALLEL RESISTANCE. THE EFFECTIVE PARRALLEL RESISTANCE SHALL BE 2372 KILOHM(S).
2375	EFFECTIVE PARALLEL RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE; WITH THE BASE DOCUMENT, EXCEPT 2375.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
EFFECTIVE PARALLEL RESISTANCE (CONT)	
TEST METHODS (CONT)	
PER MIL-C-83446.	2376
FREQUENCY (MEGAHERTZ)	2377
CAPACITANCE (PICOFARADS)	2378
EXPLOSION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1974
NO EVIDENCE OF EXPLOSION OR VIOLENT BURNING	1976
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1966
PER MIL-STD-202, METHOD 109.	1967
CHAMBER TEMPERATURE (DEGREES CELSIUS)	1968
ELECTRICAL LOAD (OHMS)	1970
FLAMMABILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _	1944

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2376	EFFECTIVE PARALLEL RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-83446.
2377	TEST FREQUENCY SHALL, BE 2377 MEGAHERTZ.
2378	THE CAPACITANCE SHALL BE 2378 PICOFARD(S).
1974	EXPLOSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1974.
1976	EXPLOSION. THERE SHALL BE NO EVIDENCE OF EXPLOSION OR VIOLENT BURNING.
1966	EXPLOSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1966.
1967	EXPLOSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 109 OF MIL-STD-202.
1968	THE CHAMBER TEMPERATURE SHALL BE 1968 DEGREES CELSIUS.
1970	THE ELECTRICAL LOAD SHALL BE 1970 OHM(S).
1944	FLAMMABILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1944.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FLAMMABILITY (CONT)	
REQUIREMENTS (CONT)	
AS FOLLOW:	
NO EXPLOSIVE FLAME.	1948
NO DRIPPING OF FLAMMABLE MATERIAL.	1952
MAXIMUM BURNING DURATION (SECONDS)	1946
MINIMUM INSULATION RESISTANCE (MEGOHMS)	1954
WINDINGS SHALL REMAIN ELECTRICALLY CONTINUOUS.	1950
ELECTRICAL CHARACTERISTICS SHALL NOT EXCEED THE VALUES SPECIFIED IN THE ELECTRICAL CHARACTERISTICS TABLE.	1956
MAXIMUM INDUCTANCE CHANGE (PERCENT)	1958
MAXIMUM DC RESISTANCE CHANGE (PERCENT)	1960
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1922
PER MIL-STD-202, METHOD III.	1923

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4761	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THE MANUFACTURER SHALL VERIFY BY CERTIFICATION THAT ALL EXTERMAL MATERIALS ARE FUNGUS RESISTANT OR SHALL PERFORM THE FUNGUS TEST. WHEN THE FUNGUS TEST IS PERFORMED, THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.
4762	FUNGUS. ALL EXTERNAL MATERIALS SHALL BE NONNUTRIENT TO FUNGUS GROWTH OR SHALL BE SUITABLY TREATED TO RETARD FUNGUS GROWTH. THERE SHALL BE NO EVIDENCE OF FUNGUS GROWTH ON THE EXTERNAL SURFACES.
4754	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4754.
4755	FUNGUS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 508 OF MIL-STD-810.
4756	TEST PERIOD SHALL BE 4756 DAY(S).
2400	HIGH TEMPERATURE EXPOSURE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2400.
2401	HIGH TEMPERATURE EXPOSURE. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
2404	HIGH TEMPERATURE EXPOSURE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2404.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

GHARACTERISTIC NAME	CHAR CODE
HIGH TEMPERATURE EXPOSURE (CONT)	
TEST METHODS (CONT)	
PER MIL-C-83446.	2405
HIGH TEMPERATURE (DEGREES CELSIUS)	2406
DURATION OF EXPOSURE (HOURS)	2407
TOLERANCE (HOURS)	2408
DURATION AT AMBIENT TEMPERATURE PRIOR TO MEASUREMENTS (HOURS)	2410
HUMIDITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT	4798
NO EVIDENCE OF CORROSION OR PHYSICAL, DAMAGE.	4799
NO DEGRADATION OF PERFORMANCE.	4815
NO EVIDENCE OF ARCING, FLASHOVER, OR INSULATION BREAKDOWN WHEN DWV APPLIED.	1477
MINIMUM INSULATION RESISTANCE AT HIGH HUMIDITY (MEGOHMS)	4795

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2405	HIGH TEMPERATURE EXPOSURE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-83446.
2406	THE HIGH TEMPERATURE SHALL BE 2406 DEGREES CELSIUS.
2407	DURATION OF EXPOSURE TO THE HIGH TEMPERATURES SHALL BE 2407 HOUR(S).
2408	DURATION OF EXPOSURE TOLERANCE SHALL BE 2408 HOUR(S).
2410	DURATION OF TEST AT AMBIENT TEMPERATURE PRIOR TO MEASUREMENT(S) SHALL BE 2410 HOUR(S).
4798	HUMIDITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4798.
4799	HUMIDITY. THERE SHALL BE NO EVIDENCE OF CORROSION OR PHYSICAL DAMAGE.
4815	THERE SHALL BE NO DEGRADATION OF PERFORMANCE.
1477	THERE SHALL BE NO EVIDENCE OF ARCING, FLASHOVER, OR INSULATION BREAKDOWN WHEN DIELECTRIC WITHSTANDING VOLTAGE IS PERFORMED.
4795	INSULATION RESISTANCE SHALL BE NOT LESS THAN 4795 MEGOH(S) AT HIGH HUMIDITY.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORK CODE INDEX (KWI)

CHARACTERISTIC NAME	CHAR CODE
HUMIDITY (CONT)	
NO EVIDENCE OF CORROSION OR PHYSICAL DANAGE. (CONT)	
MINIMUM INSULATION RESISTANCE AFTER DRYING (DEGOHMS)	4805
MAXIMUM LEAKAGE AT HIGH HUMIDITY (MILLIANPERES)	4813
MAXIMUM LEAKAGE AFTER DRYING (MILLIAMPERES)	4803
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4788
PER MIL-STD-202, METHOD 103.	4853
*TEST CONDITION (LETTER)	4890
POLARIZING VOLTAGE (VOLTS, DC)	4793
DURATION OF POLARIZING VOLTAGE APPLICATION (SELECT ONE)	
(HOURS)	4790
(MINUTES)	4794

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
4809	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4809.
4810	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 104 OF MIL-STD-202.
4811	TEST CONDITION LETTER 4811 SHALL APPLY.
4812	FINAL MEASUREMENT(S) SHALL BE MADE WITHIN 4812 HOUR(S) AFTER FINAL CYCLE.
4814	MEASUREMENTS SHALL BE NOT MADE UNTIL 4814 HOUR(S) AFTER THE FINAL CYCLE.
2415	INCREMENTAL CURRENT INDUCTANCE REDUCTION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2415.
2416	INCREMENTAL CURRENT INDUCTANCE REDUCTION. THE INCREMENTAL CURRENT INDUCTANCE REDUCTION VALUE SHALL REPRESENT A REDUCTION OF 2416 PERCENT.
2417	INCREMENTAL CURRENT INDUCTANCE REDUCTION. THE INCREMENTAL CURRENT INDUCTANCE REDUCTON VALUE SHALL BE LESS THAN THE INDUCTANCE MEASURED WITH ZERO DC CURRENT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
INCREMENTAL CURRENT INDUCTANCE REDUCTION (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2420
PER MIL-C-83446.	2421
TEST VOLTAGE (MILLIVOLTS)	2422
TEST FREQUENCY (KILOHERTZ)	2423
TEST CURRENT (AMPERES DC)	2424
INDUCED VOLTAGE , REDUCED BAROMETRIC PRESSURE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1724
AS FOLLOWS:	1726
NO EVIDENCE OF CONTINUOUS ARCHING OR BREAKDOWN IN INSULATION.	1727
MAXIMUM FLUCTUATION OF INPUT CURRENT (PERCENT)	1828
MAXIMUM CHANGE IN Q FACTOR (PERCENT)	1730

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2420	INCREMENTAL CURRENT INDUCTANCE REDUCTION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2420.
2421	INCREMENTAL CURRENT INDUCTANCE REDUCTION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-83446.
2422	THE TEST VOLTAGE SHALL BE 2422 MILLIVOLT(S) RMS.
2423	THE TEST FREQUENCY SHALL BE 2423 KILOHERTZ.
2424	THE TEST CURRENT SHALL BE 2424 AMPERE(S) DC.
1724	INDUCED VOLTAGE, REDUCED BAROMETRIC PRESSURE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1724.
1726	INDUCED VOLTAGE, REDUCED BAROMETRIC PRESSURE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1727	THERE SHALL BE NO EVIDENCE OF CONTINUOUS ARCING OR BREAKDOWN IN INSULATION.
1728	FLUCTUATION OF INPUT CURRENT SHALL BE NOT GREATER THAN 1728 PERCENT.
1730	CHANGE IN Q FACTOR SHALL BE NOT GREATER THAN 1730 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORK CODE INDEX (KCI)

(CHACTERISTIC NAME	CHAR CODE
INDUCED VOLTAGE , REDUCED BAROMETRIC PRESSURE (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT _____	1702
PER MIL-T-27.	1704
ALTITUDE PER MIL-STD-202, METHOD 105.	2428
TEST FREQUENCY (KILOHERTZ)	1708
MINIMUM DURATION OF APPLICATION (SECONDS)	1714
CYCLES (NUMBER)	1716
TEST VOLTAGE (VOLTS RMS)	2429
INDUCED PULSE WIDTH (MICROSECONDS)	2430
REPETITION RATE (PULSES PER SECOND)	2431
POINTS OF APPLICATION, TERMINALS (NAME)	2432
ELECTRICAL LOAD (OHMS)	2433
PROTECTIVE DEVICES PROVIDED (NAME)	1712
(WRITE-IN)	2434
INDUCED VOLTAGE, SEA LEVEL	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2440

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2456	THE POINTS OF APPLICATION SHALL BE TERMINAL(S) 2456.
2458	THE ELECTRICAL LOAD SHALL BE 2458 OHM(S).
2459	2459.
1748	INDUCTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1748.
2462	INDUCTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE VALUE(S) LISTED IN THE ELECTRICAL CHARACTERISTICS TABLE.
1742	INDUCTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1742.
1744	INDUCTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-T-27.
2464	THE TEST CURRENT SHAL BE 2464 AMPERE(S) DC.
2466	THE TEST FREQUENCY SHALL BE 2466 HERTZ.
2467	THE TEST FREQUENCY SHALL BE 2467 MEGAHERTZ.
2468	THE TEST VOLTAGE SHALL BE 2468 VOLT(S) RMS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
INDUCTANCE (CONT)	
PER MIL-T-27. (CONT)	
TERMINALS (NAME)	2469
(WRITE-IN)	2470
PER MIL-C-83446.	2471
TEST CURRENT (AMPERES DC)	2472
TEST FREQUENCY (SELECT ONE)	
(HERTZ)	2473
(MEGAHERTZ)	2474
TEST VOLTAGE (VOLTS RMS)	2475
TERMINALS (NAME)	2476
(WRITE-IN)	2477
INSULATION RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1380
AS FOLLOWS:	6359

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2469	THE TERMINAL(S) TO BE USED IN MEASURING INDUCTANCE SHALL BE 2469.
2470	2470.
2471	INDUCTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-83446.
2472	THE TEST CURRENT SHALL BE 2472 AMPERE(S).
2473	THE TEST FREQUENCY SHALL BE 2473 HERTZ.
2474	THE TEST FREQUENCY SHALLL BE 2474 MEGAHERTZ.
2475	THE TEST VOLTAGE SHALL BE 2475 VOLT(S) RMS.
2476	THE TERMINAL(S) TO BE USED IN MEASURING INDUCTANCE SHALL BE 2476.
2477	2477.
1380	INSULATION RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1380.
6359	INSULATION RESISTANCE. THE REQUIREMENT(S) SHALL BE AS FOLLOW:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
INSULATION RESISTANCE (CONT)	
AS FOLLOWS: (CONT)	
*MINIMUM INSULATION RESISTANCE (SELECT ONE)	
SINGLE TEST	
(MEGOHMS)	1386
MULTIPLE TEST	
*FIRST TEST (MEGOHMS)	1384
*SECOND TEST (MEGOHMS)	1387
REMAIN WITHIN SPECIFIED TOLERANCE.	1388
NO EVIDENCE OF PHYSICAL DAMAGE.	1407
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1371
PER MIL-STD-202, METHOD 302.	1511
*CONDITION (SELECT ONE)	
TEST CONDITION (LETTER)	1378
TEST VOLTAGE (VOLTS, DC)	1373
ELECTRIFICATION TIME (SECONDS)	1376

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1377	THE MEASUREMENT ERROR AT THE INSULATION RESISTANCE VALUE REQUIRED SHALL BE NOT GREATER THAN 1377 PERCENT.
	POINTS OF INSULATION RESISTANCE MEASUREMENT SHALL BE AS FOLLOWS:
1497	BETWEEN THE TERMINATIONS TIED TOGETHER AND THE MOUNTING HARDWARE.
1498	BETWEEN THE TERMINATIONS TIED TOGETHER AND THE CASE l
1522	BETWEEN MUTUALLY INSULATED PARTS.
1523	BETWEEN ALL INSULATED PARTS AND GROUND.
1524	BETWEEN CURRENT CARRYING PARTS AND THE CASE.
2480	LOW TEMPERATURE OPERATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANC WITH THE BASE DOCUMENT, EXCEPT 2480.
2481	LOW TEMPERATURE OPERATION. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARARACTERISTIC NAME	CHAR CODE
LOW TEMPERATURE OPERATION (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2483
PER MIL-C-83446.	2484
LOW TEMPERATURE (DEGREES CELSIUS)	2485
TOLERANCE (DEGREES CELSIUS)	2486
STABILIZATION TIME AT LOW TEMPERATURE (MINUTES)	2487
TOLERANCE (MINUTES)	2488
APPLY RATED CONTINUOUS DC CURRENT AT LOW TEMPERATURE.	2489
DURATION (MINUTES)	2490
DURATION AT AMBIENT TEMPERATURE PRIOR TO EXAMINATION (HOURS)	2491
MOISTURE RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1400

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2483	LOW TEMPERATURE OPERATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2483.
2484	LOW TEMPERATURE OPERATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-83446.
2485	THE LOW TEMPERATURE SHALL BE 2485 DEGREES CELSIUS.
2486	THE LOW TEMPERATURE TOLERANCE SHALL BE 2486 DEGREES CELSIUS.
2487	THE STABILIZATION TIME AT LOW TEMPERATURE SHALL BE 2487 MINUTE(S).
2488	THE STABILIZATION TOLERANCE AT LOW TEMPERATURE SHALL BE 2488 MINUTE(S).
2489	APPLY RATED CONTINUOUS DC CURRENT AT THE LOW TEMPERATURE.
2490	RATED CONTINUOUS DC CURRENT SHALL BE APPLIED AT THE LOW TEMPERATURE FOR 2490 MINUTE(S).
2491	THE INDUCTOR SHALL BE MAINTAINED AT AMBIENT TEMPERATURE FOR 2491 HOUR(S) PRIOR TO EXAMINATION.
1400	MOISTURE RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT , EXCEPT 1400.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
MOISTURE RESISTANCE (CONT)	
REQUIREMENTS (CONT)	
NO EVIDENCE OF CORROSION OR PHYSICAL DAMAGE.	1396
REMAIN WITHIN SPECIFIED TOLERANCE.	1398
NO EVIDENCE OF ARCING, FLASHOVER , OR INSULATION BREAKDOWN WHEN DWV APPLIED.	1394
MAXIMUM LEAKAGE AT HIGH HUMIDITY (MILLIAMPERES)	1429
MAXIMUM LEAKAGE AFTER DRYING (MILLIAMPERES)	1404
MINIMUM INSULATION RESISTANCE AT HIGH HUMIDITY (MEGOHMS)	1432
MINIMUM INSULATION RESISTANCE AFTER DRYING (MEGOHMS)	1406
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1921
PER MIL-STD-202, METHOD 106.	1397

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1395	Polarizing VOLTAGE SHALL BE 1395 VOLTS, DC.
4981	LOADING VOLTAGE SHALL BE 4981 VOLTS, DC.
4980	LOADING VOLTAGE SHALL BE 4980 VOLTS, AC.
4991	4991 PERCENT OF THE SAMPLE SHALL BE SUBJECTED TO THE POLARIZING VOLTAGE.
4985	STEP 7A OF METHOD 106 OF MIL-STD-202 IS NOT APPLICABLE.
4986	STEP 7B OF METHOD 106 OF MIL-STD-202 IS NOT APPLICABLE.
4983	PERFORM DIELECTRIC WITHSTANDING VOLTAGE TEST AT HIGH HUMIDITY.
4984	PERFORM DIELECTRIC WITHSTANDING VOLTAGE TEST AFTER DRYING.
1634	OVERLOAD. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1634.
1636	OVERLOAD. THE TOTAL SURFACE SHOWING EVIDENCE OF PHYSICAL DAMAGE SHALL BE NOT GREATER THAN 1636 PERCENT.
2493	OVERLOAD. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
OVERLOAD (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1612
PER MIL-T-27.	1614
AMBIENT TEMPERATURE (DEGREES CELSIUS)	1615
MAXIMUM TEMPERATURE RISE (DEGREES CELSIUS)	1618
TEST VOLTAGE (VOLTS RMS)	1620
DURATION OF APPLIED VOLTAGE (HOURS)	1622
TEST CURRENT (AMPERES)	2494
TEST FREQUENCY (HERTZ)	1624
PER MIL-C-83446.	2495
TEST CURRENT (AMPERES DC)	2496
DURATION OF APPLIED CURRENT (MINUTES)	2497
PERCENT COUPLING	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2500
COUPLING (PERCENT)	2501

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1612	OVERLOAD. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1612.
1614	OVERLOAD. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-T-27.
1616	THE AMBIENT TEMPERATURE SHALL BE 1616 DEGREES CELSIUS.
1618	THE TEMPERATURE RISE SHALL BE NOT GREATER THAN 1618 DEGREES CELSIUS.
1620	THE TEST VOLTAGE SHALL BE 1620 VOLT(S) RMS.
1622	DURATION OF APPLIED VOLTAGE SHALL BE 1622 HOUR(S).
2494	THE TEST CURRENT SHALL BE 2492 AMPERE(S).
1624	THE TEST FREQUENCY SHALL BE 1624 HERTZ.
2495	OVERLOAD. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-83446.
2496	THE TEST CURRENT SHALL BE 2496 AMPERE(S) DC.
2497	DURATION OF APPLIED CURRENT SHALL BE 2497 MINUTE(S).
2500	PERCENT COUPLING, THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2500.
2501	PERCENT COUPLING . PERCENT COUPLING SHALL BE 2501 PERCENT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
PERCENT COUPLING (CONT)	
COUPLING (CONT)	
COEFFICIENT OF MUTUAL INDUCTANCE (MICROHEMRIES)	2507
SERIES AIDING INDUCTANCE (MICROHENRIES)	2508
SERIES BUCKING INDUCTANCE (MICROHENRIES)	2509
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2504
PER MIL-C-83446.	2505
FREQUENCY (HERTZ)	2506
PERMEABILITY, MAGNETIC	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2515
MINIMUM PERMEABILITY (MU)	2516
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2519
TEST PER MIL-I-17214.	2520

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2507	COEFFICIENT OF MUTUAL INDUCTANCE SHALL BE ~~2507~~ MICROHENRY(S).
2508	SERIES AIDING INDUCTANCE SHALL BE 2508 MICROHENRY(S).
2509	SERIES BUCKING INDUCTANCE SHALL BE ~~2509~~ MICROHENRY(S).
2504	PERCENT COUPLING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2504.
2505	PERCENT COUPLING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-83446.
2506	THE FREQUENCY SHALL BE 2506 HERTZ.
2515	PERMEABILITY, MAGNETIC. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2515.
2516	PERMEABILITY MAGNETIC. THE INITIAL RELATIVE PERMEABILITY SHALL BE NOT GREATER 2516 MU WHEN COMPARED TO AIR WHICH EQUALS 1.0.
2519	PERMEABILITY, MAGNETIC. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT ~~2519~~.
2520	PERMEABILITY, MAGNETIC. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-I-17214.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
QUALITY FACTOR (Q)	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1788
P E R	1790
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1782
PER MIL-STD-202 , METHOD 306.	1784
*TEST FREQUENCY (HERTZ)	1785
RADIOGRAPHIC	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6291
NO INHOMOGENEITIES, FOREIGN PARTICLES, INCORRECT ALIGNMENT, DEFECTS.	6371

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6329	PROCEDURE NUMBER IV SHALL APPLY,
4751	CHAMBER PRESSURE SHALL BE 4751 TORR.
4735	CHAMBER PRESSURE SHALL BE 4735 KILOPASCALS.
4752	DURATION AT LOW PRESSURE SHALL BE 4752 MINUTE(S).
6330	GROSS LEAK TEST CONDITION LETTER 6330 SHALL APPLY.
6331	TEST CONDITION LETTER D SHALL APPLY.
4743	MOUNTING SHALL BE BY ANY SUITABLE METHOD.
6332	TEST CONDITION LETTER E SHALL APPLY.
6333	MOUNTING SHALL BE BY ANY SUITABLE METHOD.
2600	SELF-RESONANT FREQUENCY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2600.
2601	SELF-RESONANT FREQUENCY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SELF-RESONANT FREQUENCY (CONT)	
AS FOLLOWS: (CONT)	
MINIMUM SELF-RESONANT FREQUENCY (SELECT ONE)	
(HERTZ)	2602
(KILOHERTZ)	2603
(MEGAHERTZ)	2604
MAXIMUM SELF-RESONANT FREQUENCY (SELECT ONE)	
(HERTZ)	2605
(KILOHERTZ)	2609
(MEGAHERTZ)	2607
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2610
PER MIL-C-83446.	2611
AS FOLLOWS:	2612

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2602	SELF-RESONANT FREQUENCY SHALL BE NOT LESS THAN 2602 HERTZ.
2603	SELF-RESONANT FREQUENCY SHALL BE NOT LESS THAN 2603 KILOHERTZ.
2604	SELF-RESONANT FREQUENCY SHALL BE NOT LESS THAN 2604 MEGAHERTZ.
2605	SELF-RESONANT FREQUENCY SHALL BE NOT GREATER THAN 2605 HERTZ.
2609	SELF-RESONANT FREQUENCY SHALL BE NOT GREATER THAN 2609 KILOHERTZ.
2607	SELF-RESONANT FREQUENCY SHALL BE NOT GREATER THAN 2607 MEGAHERTZ.
2610	SELF-RESONANT FREQUENCY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2610.
2611	SELF-RESONANT FREQUENCY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-83446.
2612	SELF-RESONANT FREQUENCY. TESTING SHALL BE PERFORMED AS FOLLOWS:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SELF-RESONANT FREQUENCY (CONT)	
As FOLLOWS: (CONT)	
PRIMARY VOLTAGE (VOLTS RMS)	2618
LOAD IMPEDANCE (OHMS)	2614
MINIMUM SOURCE FREQUECY (HERTZ)	2615
MAXIMUM SOURCE FREQUENCY (HERTZ)	2616
(WRITE-IN)	2617
SHOCK, HIGH-IMPACT	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1494
NO EVIDENCE OF PHYSICAL DAMAGE.	1495
NO DISCONTINUITY DURING TEST.	1451
TEST METH0DS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1486
PER MIL-STD-202 , METHOD 207,	1482

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T20:56Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
1414	TEST SPECIMENS SHALL BE SUBJECTED TO TEST CONDITION.
1416	TEST SPECIMENS SHALL BE SUBJECTED TO TEST CONDITION E. THE TORQUE SHALL BE 1416 POUND(S).
1421	TEST SPECIMENS SHALL BE SUBJECTED TO TEST CONDITI0N E. THE TORQUE SHALL BE 1421 NEWTON METER(S).
4722	THERMAL SHOCK (TEMPERATURE CYCLING). THE REQUIREMENT(S) SHALL BE IN ACCORDANCE; WITH THE THE BASE DOCUMENT, EXCEPT 4722.
4723	THERMAL SHOCK (TEMPERATURE CYCLING). TESTING SHALL BE EVIDENCE OF PHYSICAL DAMAGE.
4726	ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE.
4713	THERMAL SHOCK (TEMPERATURE CYCLING). TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4713.
4714	THERMAL SHOCK (TEMPERATURE CYCLING). TESTING SHALL BE PERFORMED IN ACCORDANCE; WITH METHOD 107 OF MIL-STD-202.
4715	TEST CONDITION LETTER 4715 SHALL APPLY.
4719	MOUNTING SHALL BE IN ACCORDANCE WITH 4719.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T20:56Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TORQUE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2650
MAXIMUM TORQUE (OUNCE-INCHES)	2651
MAXIMUM TORQUE (NEWTON METERS)	2652
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2674
PER MIL-C-83446.	2656
VIBRATION, HIGH FREQUENCY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1455
NO EVIDENCE OF PHYSICAL DAMAGE.	1456
NO DISCONTINUITY DURING TEST.	1473
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1446

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2650	TORQUE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT , EXCEPT 2650.
2651	TORQUE. THE TORQUE SHALL BE NOT GREATER THAN 2651 OJNCE-INCH(S).
2652	TORQUE. THE TORQUE SHALL BE NOT GREATER THAN 2652 NEWTON METER(S).
2655	TORQUE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2655
2656	TORQUE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-C-83446.
1455	VIBRATION, HIGH FREQUENCY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1455.
1456	VIBRATION, HIGH FREQUENCY. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
1473	THERE SHALL BE NO DISCONTINUIY DURING TEST.
1446	VIBRATION, HIGH FREQUENCY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1446.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
VIBRATION, HIGH FREQUENCY (CONT)	
TEST METHODS (CONT)	
PER MIL-STD-202, METHOD 204.	1447
*TEST CONDITION (LETTER)	1448
PERCENT RATED LOAD APPLIED (PERCENT)	6200
METHOD OF MOUNTING (SELECT ONE)	
ANY SUITABLE MOUNTING METHOD.	4709
NORMAL MOUNTING MEANS.	4708
MOUNT PER DOCUMENT (DOC DES)	4707
METHOD OF DETERMINING MECHANICAL RESONANCE (SELECT ONE)	
VISUALLY BY MEANS OF A STROBOTAC.	1533
ELECTRICAL OUTPUT INDICATORS.	1534
VIBRATION, LOW FREQUENCY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1475
NO EVIDENCE OF PHYSICAL DAMAGE.	1476
NO DISCONTINUITY DURING TEST.	1490

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:56Z
Check the source to verify that this is the current version before use.