

FED. SUP CLASS
2350





MS PART NO.	ENGINEERING DRAWING NO.
MS52223-1	8736945

APPROVED 26 AUG 85 REVISED

P. A. ARMY-AT Other Cust	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
		TANK, COMBAT, FULL TRACKED 105 MM GUN, M60A3 PASSIVE	MS52223(AT)
PROCUREMENT SPECIFICATION M60PD-T-62221	SUPERSEDES:		SHEET 1 OF 2

DD FORM 1 MAY 73 672-1 LIMITED COORDINATION

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

This military standard is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:23Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
2350

VEHICLE CHARACTERISTICS

LIST OF EQUIPMENT:

BASIC ISSUE ITEMS	12270402
INTEGRAL COMPONENTS OF ITEMS	12270209
ADDITIONAL AUTHORIZED LIST	12270400
EXPENDABLE SUPPLIES AND MATERIALS LIST	12270211

VEHICLE INSTALLATION DRAWINGS:

CHASSIS ASSEMBLY	12270883
TURRET ASSEMBLY	9337883

SPECIFICATIONS:

VEHICLE SHIPMENT AND STORAGE SPEC	MIL-T-45309

REFERENCE DOCUMENTS:

CHART, PRODUCTION LUBRICATION	11674298
DIAGRAM, STRAP	11674297
CHART, TORQUE	10940607
TRANSPORTABILITY CLEARANCE DIAGRAM	12251869
M60A3 PASSIVE IDF CONFIGURATION	12271002

WEIGHT:

FULLY EQUIPPED APPROX	114,000 LBS

ENGINE: AVDS-1790-2CA

V-12, COMPRESSION IGNITION, AIR COOLED

GROSS HP	750 BHP @ 2400 RPM

TRANSMISSION: CD-850-6A

CROSS DRIVE

2 SPEEDS FORWARD, 1 REVERSE

VEHICLE ACCESSORY KITS:

KIT, WATER FORDING, ARMY	11655621
KIT, WATER FORDING, USMC	11655662
KIT, DOZER	8750001

PERFORMANCE:

MAX VEHICLE SPEED	30 MPH
CRUISING RANGE APPROX	300 MI
MAX GRADE ABILITY ASCENDING	60%
MAX GRADE ABILITY DECENDING	60%
MAX FORDING ABILITY WO/KIT	48 IN
VERTICAL OBSTACLE ABILITY	36 IN
MAX TRENCH WIDTH CROSSING	102 IN

ARMAMENT:

1 GUN, MACH, M240 TANK	7.62 MM
2 GUN, SUB MACH, M3A1 (US ARMY ONLY)	45 CAL
1 GUN, MACH M85 (CUPOLA TYPE)	50 CAL
1 GUN,	105 MM
1 RIFLE, M16A1 (USMC ONLY)	5.56 MM

AMMUNITION:

7.62 MM (MG)	5950 ROUNDS
CAL .45 (SMG)	360 ROUNDS
CAL 50 (MG)	940 ROUNDS
5.56 MM (RIFLE) (USMC ONLY)	ROUNDS
105 MM	63 ROUNDS
GRENADES	8

CREW:

COMMANDER, DRIVER,
GUNNER, LOADER

COMMUNICATION EQUIPMENT:

ARMY	
OPTIONAL RADIOS	AN/VRC-12
	AN/VRC-46
	AN/VRC-64
SUPPRESSOR INSTALLATION KIT	SM-D-627931
INTERCOM	AN/VIC-1
USMC	
RADIO	AN/VRC-44
SUPPRESSOR INSTALLATION KIT	SM-D-627931
INTERCOM	AN/VIC-1
VOICE SECURITY UNIT	TSEC/KY-38

NOTES:

1. DIMENSIONS ARE IN INCHES AND ARE SHOWN FOR ENGINEERING REFERENCE ONLY.
2. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.
3. THIS VEHICLE SHALL BE IN ACCORDANCE WITH REFERENCED ENGINEERING DRAWINGS, COPIES WHICH MAY BE OBTAINED FROM: US ARMY-AUTOMOTIVE COMMAND, WARREN, MICH. 48397-5000.

APPROVED 26 AUG 85 REVISED

MS PART NO.	ENGINEERING DRAWING NO.
MS52223-1	8736945

P. A. ARMY-AT	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust		TANK, COMBAT, FULL TRACKED 105 MM GUN, M60A3 PASSIVE	MS52223(AT)
PROCUREMENT SPECIFICATION M60PD-T-62221	SUPERSEDES:		SHEET 2 OF 2

DD FORM 1 MAY 73 672-1 LIMITED COORDINATION

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

This military standard is approved for use by the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:23Z
Check the source to verify that this is the current version before use.