FED. SUP CLASS
5306




TABLE I. DASH NUMBERS AND DIMENSIONS

DASH NO	L	K	APPROX WEIGHT LB/100
-04	.875	.113-.133	12.08
-05	.938	.113-.133	12.52
-06	1.000	.113-.133	12.96
-07	1.062	.113-.133	13.40
-08	1.125	.113-.133	13.81
-09	1.188	.113-.133	14.28
-10	1.250	.113-.133	14.72
-11	1.312	.113-.133	15.16
-12	1.375	.113-.133	15.61
-13	1.438	.113-.133	16.05
-14	1.500	.113-.133	16.49
-15	1.562	.128-.188	16.93
-16	1.625	.190-.250	17.27
-17	1.688	.252-.312	17.81
-18	1.750	.315-.375	18.25
-19	1.812	.378-.438	18.69
-20	1.875	.440-.500	19.13
-21	2.000	.565-.625	20.01
-22	2.125	.690-.750	20.89
-23	2.250	.815-.875	21.77
-24	2.375	.940-1.000	22.65
-25	2.500	1.065-1.125	23.53
-26	2.625	1.190-1.250	24.41
-27	2.750	1.315-1.375	25.29
-28	2.875	1.440-1.500	26.17

DASH NO	L	K	APPROX WEIGHT LB/100
-29	3.000	1.565-1.625	27.05
-30	3.125	1.690-1.750	27.93
-31	3.250	1.815-1.875	28.81
-32	3.375	1.940-2.000	29.69
-33	3.500	2.065-2.125	30.57
-34	3.625	2.190-2.250	31.45
-35	3.750	2.315-2.375	32.34
-36	3.875	2.440-2.500	33.22
-37	4.000	2.565-2.625	34.10
-38	4.125	2.690-2.750	34.98
-39	4.250	2.815-2.875	35.86
-40	4.375	2.940-3.000	36.74
-41	4.500	3.065-3.125	37.62
-42	4.625	3.190-3.250	38.50
-43	4.750	3.315-3.375	39.38
-44	4.875	3.440-3.500	40.26
-45	5.000	3.565-3.625	41.14
-46	5.125	3.690-3.750	42.02
-47	5.250	3.815-3.875	42.90
-48	5.375	3.940-4.000	43.78
-49	5.500	4.065-4.125	44.66
-50	5.625	4.190-4.250	45.54
-51	5.750	4.315-4.375	46.42
-52	5.875	4.440-4.500	47.30
-53	6.000	4.565-4.625	48.18
-54	1.938	.502-.562	19.57

Ⓓ ENTIRE STANDARD REVISED

APPROVED 5 MAY 1965 REVISED Ⓓ 30 SEPT 87

USER ACTIVITIES:

REVIEWER ACTIVITIES:
AIR FORCE-82
ARMY-MI
DLA-IS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

AMSC N/A

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
NAVY-AS Other Cust AIR FORCE-99		BOLT, MACHINE-HEXAGON HEAD, DRILLED, 6 HOLES, FULL SHANK, .5625-18 UNJF-3A	MS9589
PROCUREMENT SPECIFICATION AMS7477	SUPERSEDES:		PAGE 1 OF 2

DD FORM 1 MAY 73 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5306-1184

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:20Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. MATERIAL: CORROSION AND HEAT RESISTANT STEEL IN ACCORDANCE WITH AMS 5731 (UNS S66286).
2. THREADS: THREADS IN ACCORDANCE WITH MIL-S-8879. INCOMPLETE THREADS NOT TO ENTER FILLET.
3. FLUORESCENT PENETRANT INSPECTION: FLUORESCENT PENETRANT INSPECTION SHALL BE IN ACCORDANCE WITH AMS 2645.
4. SURFACE TEXTURE: SURFACE TEXTURE IN ACCORDANCE WITH ANSI B46.1. UNLESS OTHERWISE SPECIFIED, SURFACE TO BE 125 MICROINCHES EXCEPT UPSET HEAD.
5. MARKING: MARK PART NUMBER AND MANUFACTURER'S IDENTIFICATION IN ACCORDANCE WITH AS 478 CLASS A.
6. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
7. TOLERANCES: UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE FOR LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.
8. EDGES: BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
9. PART NUMBER: THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS9589-04



MS9588-04 INDICATES - BOLT, MACHINE-HEXAGON HEAD, DRILLED, 6 HOLES, FULL SHANK AMS 5731, .5625-18 UNJF-3A x .875 LONG

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. DO NOT USE UNASSIGNED PART NUMBERS.
3. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DoDISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.
5. THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE SAE AEROSPACE PROPULSION DIVISION.
6. AS AND AMS ARE SAE PUBLICATIONS.

APPROVED 5 MAY 1965 REVISED (D) FOR CHANGES SEE PAGES 1 AND 2

USER ACTIVITIES:
REVIEWER ACTIVITIES:
AIR FORCE-82
ARMY-MI
DLA-IS
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
NAVY - AS Other Cust AIR FORCE-99		BOLT, MACHINE-HEXAGON HEAD, DRILLED, 6 HOLES, FULL SHANK, .5625-18 UNJF-3A	MS9589
PROCUREMENT SPECIFICATION AMS7477	SUPERSEDES:		PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:20Z
Check the source to verify that this is the current version before use.