
MS9802

FED. SUP CLASS 5306



PART NUMBER	L	K	APPROX WEIGHT LB/100
MS9802-18	2.000	.190- .250	35.64
MS9802-19	2.125	.315- .375	37.19
MS9802-20	2.250	.440- .500	38.73
MS9802-21	2.375	.565- .625	40.28
MS9802-22	2.500	.690- .750	41.82
MS9802-23	2.625	.815- .875	43.37
MS9802-24	2.750	.940-1.000	45.00
MS9802-25	2.875	1.065-1.125	46.45
MS9802-26	3.000	1.190-1.250	47.99
MS9802-27	3.125	1.315-1.375	49.64
MS9802-28	3.250	1.440-1.500	51.07
MS9802-29	3.375	1.565-1.625	52.61
MS9802-30	3.500	1.690-1.750	54.16
MS9802-31	3.625	1.815-1.875	55.70
MS9802-32	3.750	1.940-2.000	57.25
MS9802-33	3.875	2.065-2.125	58.79
MS9802-34	4.000	2.190-2.250	60.33
MS9802-35	4.125	2.315-2.375	61.87
MS9802-36	4.250	2.440-2.500	63.42
MS9802-37	4.375	2.565-2.625	64.96
MS9802-38	4.500	2.690-2.750	66.51
MS9802-39	4.625	2.815-2.875	68.04
MS9802-40	4.750	2.940-3.000	69.59
MS9802-41	4.875	3.065-3.125	71.13
MS9802-42	5.000	3.190-3.250	72.68
MS9802-43	5.125	3.315-3.375	74.22
MS9802-44	5.250	3.440-3.500	75.76
MS9802-45	5.375	3.565-3.625	77.30
MS9802-46	5.500	3.690-3.750	78.85
MS9802-47	5.625	3.815-3.875	80.39
MS9802-48	5.750	3.940-4.000	81.93
MS9802-49	5.875	4.065-4.125	83.47
MS9802-50	6.000	4.190-4.250	85.01

1. SHANK SHALL BE STRAIGHT WITHIN .002 TOTAL PER INCH OF BOLT LENGTH.
2. THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.
3. THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .032 FIR.
4. INCOMPLETE THREADS NOT TO ENTER FILLET.
5. MATERIAL: CORROSION RESISTANT STEEL AMS 5643.
6. HARDNESS: ROCKWELL C32-38.
7. MANUFACTURING SPECIFICATION: AMS 7474.
8. FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
9. SURFACE TEXTURE: USAS B46.1-1962. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES EXCEPT UPSET HEAD.
10. BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
11. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.
12. DO NOT USE UNASSIGNED PART NUMBERS.

Ⓑ REINSTATED 15 AUG 84

AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIV.

APPROVED 11 MAR 70 REVISED Ⓐ 21 DEC 83 Ⓑ 15 AUG 84

Review activities: AIR FORCE - 82 Ⓑ DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. AS	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust. Ⓤ AV 99	Ⓑ	BOLT, MACHINE - HEXAGON HEAD, DRILLED, 1 HOLE, FULL SHANK, AMS 5643, .750-16 UNJF-3A	MS9802
PROCUREMENT SPECIFICATION NONE		SUPERSEDES:	PAGE 1 OF 1

DD FORM 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5306-0856

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:25Z
Check the source to verify that this is the current version before use.