INCH-POUND
MIL-PRF-22097K
SUPPLEMENT 1
20 September 2022

PERFORMANCE SPECIFICATION

RESISTOR, VARIABLE, NONWIREWOUND (ADJUSTMENT TYPE), GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-22097K
dated 20 September 2022.

ASSOCIATED SPECIFICATIONS

MIL-PRF-22097/1	-	Resistor, Variable, Nonwirewound, Adjustment Type, Lead Screw Actuated, Style RJ11 INACTIVE FOR NEW DESIGN
MIL-PRF-22097/2	-	Resistor, Variable, Nonwirewound, Adjustment Type, Lead Screw Actuated, Style RJ12
MIL-PRF-22097/3	-	Resistor, Variable, Nonwirewound, Adjustment Type, Lead Screw Actuated, Style RJ22 INACTIVE FOR NEW DESIGN
MIL-PRF-22097/4	-	Resistor, Variable, Nonwirewound, Adjustment Type, Lead Screw Actuated, Style RJ24 INACTIVE FOR NEW DESIGN EXCEPT FOR TERMINAL TYPE - L
MIL-PRF-22097/5	-	Resistor, Variable, Nonwirewound, Adjustment Type, Lead Screw Actuated, Style RJ26 INACTIVE FOR NEW DESIGN
MIL-PRF-22097/6	-	Resistor, Variable, Nonwirewound, Adjustment Type, Lead Screw Actuated, Style RJ50 INACTIVE FOR NEW DESIGN

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Review activities
Army - AR, AT, AV, CR4, MI
Navy - AS, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
FSC 5905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:06Z
Check the source to verify that this is the current version before use.