MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, MODULAR, TYPE IV, CONNECTOR, 40 PIN, OFFSET, CONTACT TAILS ON .050 CENTERS (MODIFIED FRAME, CERAMIC COMPATIBLE)

This specification is approved for use by all Departments and Agencies of the Department of Defense

The complete requirements for acquiring the connector described herein shall consist of this specification and the latest issue of MIL-C-28754






FIGURE 1 Dimensions and configurations

FSC 5935


Source: https://assist.dla.mil -- Downloaded: 202610-20T14:48Z
Check the source to verify that this is the current version before use.



VIEW A-A



DETAIL A
40 X




DETAIL B

DETAIL B
CONFIGURATION 1

FIGURE 1 Dimensions and configurations - continued

Source: https://assist.dla.mil -- Downloaded: 202610-20T14:48Z
Check the source to verify that this is the current version before use.



SECTION A-A

INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
001	03	015	38	070	1 77	150	3 81	280	7 11
002	05	016	41	080	2 03	160	4 06	750	19 05
003	08	020	51	100	2 54	.170	4.31	1.680	42.67
004	10	030	76	120	3 05	190	4.83	1 960	49 78
005	13	040	1 02	130	3 30	225	5.72	2.200	55.88
007	18	050	1 27	140	3 56	230	5.84	2 440	61 98
010	25	060	1 52	145	3 68	270	6 86		

FIGURE 1 Dimensions and configurations - continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:48Z
Check the source to verify that this is the current version before use.

NOTES

1 Dimensions are in inches.

2 Metric equivalents are given for general information only and are based upon 1 00 inch = 25 4 mm

3 Unless otherwise specified, tolerances are ± 005 (13 mm) inch for three place decimals, ± 01 (3 mm) inch for two place decimals and ±2° for angles

4 Flash around blade contacts not to exceed .010 (.25 mm) inch from the surface of the insulator and shall be firmly attached.

5 Pin shield shall be marked with contact numbers 1, 20, 21 and 40 in contrasting color ink 06 (1.5 mm) inch high.

6 The carrier strip shall remain attached to the contact tails to facilitate shipping and may be tinned. It shall be scored at the point indicated to facilitate removal at final assembly The carrier strip is not required to be continuous.

7. Single or multiple piece construction is optional provided that the end requirements of the drawing are met. It is permissible for the connector body to be installed in either an aluminum or thermoplastic shell which provides the pin shield and key pin hole features The thermoplastic shall be Type GLT-30F

8. Dimension prior to solder coating.

9 Dimensions apply after plating

10 See Table I for key pin hole size and body material

11 Contact engagement length

12 Shaded area shall be solder coated

13 Connector shall be marked in approximate location shown with part number, manufacturer's number and date code with contrasting ink in characters 06 (1 5 mm) inch high

14 Plating defects on the carrier strip above the score line are acceptable

FIGURE 1 Dimensions and configurations - continued

Source: https://assist.dla.mil -- Downloaded: 202610-20T14:48Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration See Figure 1

Materials Contacts shall be either copper alloy sheet or strip, UNS Number C72500, temper 1/4 hard minimum in accordance with ANSI/ASTM B 122 or brass, QQ-B-613, alloy 260, temper 1/2 hard

Connector body shall be either polyetherimide, Type GLT-20F or GLT-30F, molded thermoplastic in accordance with MIL-M-24519 or molding plastic, diallyl phthalate resin, GL filler, MIL-M-14, Type GDI-30F or Type SDG-F

The pin shield shall be aluminum alloy 5052, QQ-A-250/8, H34, or glass-epoxy, GF-0160-00/00-0-1-X, MIL-P-13949 or polyetherimide, Type GLT-20F or GLT-30F, molded thermoplastic in accordance with MIL-M-24519. Pin shield thickness for molded thermoplastic shall be 0 020 (51 mm) inch minimum

Plating Contacts shall be finished on all exposed surfaces The contact engagement length indicated shall be finished with gold plate, MIL-G-45204, Type II, Grade C, Class 1, 0 000050 (0 00013 mm) inch minimum thickness over nickel plating, QQ-N-290, Class 1, 0 000050 (0 00013 mm) inch minimum thickness

Plating requirements for connector solder tails shall be as follows

Steps 1, 2, 4, 5, 7 - Clean prior to plating per MIL-P-81728. MIL-P-81728 states cleanliness requirements prior to plating

Step 3 - Cu plate per MIL-C-14550 Class 4 to a thickness of 0 0001 (0 0025 mm) inch

Step 6 - Plate per MIL-P-81728 to a thickness of 0 0003 - 0 0005 (0 0076 - 0 0127 mm) inch Alloy 90% SN-10 Pb

Step 8 - Bake as per Section 3 3 4 of MIL-P-81728

Step 9 - Form

Step 10 - Fuse/reflow with peanut oil as suggested Quality assurance of MIL-P-81728 shall apply No sign of dewet or poor solderability will be accepted

Step 11 - Avoid chlorinated solvents in rinse

Step 12 - Selectively solder coat the leads as shown in the shaded area with QQ-S-571, SN60 or SN63 to a thickness of 0.0005 - 0 003 (0 0005 - 0 0800 mm) inch using flux, MIL-F-14256, Type RMA

All aluminum alloy parts shall be anodic coated in accordance with MIL-A-8625, Type III, Class 2, black.

Key pin holes For M28754/64-02 material, 095 ± 001 (2 41 ± 03 mm) inch diameter x 150 (3 81 mm) inch deep

For M28754/64-01 material, 098 ± 01 (2 48 ± 03 mm) inch diameter x 150 (3.81 mm) inch deep

Electrical requirements

Dielectric withstanding voltage The connector shall meet the requirements of MIL-STD-1344, Method 3001 for 600 VAC (RMS) 60 Hz, or 850 VDC The point of measurement shall be between adjacent contacts

Low level (dry circuit) Voltage drop shall not exceed 36 millivolts Wire size is not applicable

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:48Z
Check the source to verify that this is the current version before use.

Contact resistance Voltage drop shall not exceed 36 millivolts Current Rating, 3 Amp

Temperature rating -55°C to +125°C

Voltage rating 300 Volts, AC (RMS), at sea level

Durability In accordance with MIL-C-28754 and shall not exceed 36 millivolts

Solderability In accordance with MIL-C-28754

Military part number M28754/64- (Dash Number from Table I)

TABLE I

DASH NUMBER	KEY PIN HOLE SIZE INCH (MM)	SHELL MATERIAL
01	098 ± 001 (2 49 ± 03)	Aluminum Alloy
02	.095 ± 001 (2.41 ± .03)	Type GLT-20F or GLT-30F
CONFIGURATION 1		
03	.098 ± 001 (2 49 ± 03)	Aluminum Alloy
04	095 ± 001 (2 41 ± .03)	Type GLT-20F or GLT-30F

Warning The GLT-20F or GLT-30F may be susceptible to stress cracking when exposed to certain cleaning solvents

Qualification information The connector shall meet the qualification test of MIL-C-28754 Table IV, Type IV, except for Subgroup IV, Method Paragraph 4.7.18, 4.7 19 and 4 7 20 All testing, except Visual and Mechanical, shall be done with the connector attached to a ceramic substrate as described in Figure

Number of units to be inspected Twelve (12) of each dash number to be qualified shall be inspected.

Supersession data Supersedes Naval Electronic Systems Command Drawing Number 0102-718-2 and -4, Code Identification Number 28687

Custodians
Navy - EC

User Activities
Navy - AS

Agent
DLA - ES

Preparing Activity
Navy - EC

(Project 5935-N252-11)

U S GOVERNMENT PRINTING OFFICE 1985 — 505 038/22480

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:48Z
Check the source to verify that this is the current version before use.