MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, MODULAR, TYPE IV, CONNECTOR,
100 PIN, OFFSET CONTACT TAILS ON .050 CENTERS (CERAMIC COMPATIBLE)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the connector described herein shall consist of this specification and the latest issue of MIL-C-28754.






FIGURE 1 Dimensions and configurations

FSC 5935


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:46Z
Check the source to verify that this is the current version before use.



DETAIL A
100 X




DETAIL B



DETAIL B
CONFIGURATION 1

FIGURE 1 Dimensions and configurations - continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:46Z
Check the source to verify that this is the current version before use.



SECTION A-A

INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.001	.03	015	38	080	2 03	170	4 31	750	19 05
.002	.05	.016	.40	.100	2.54	.190	4.83	4 960	125 98
.003	.08	.020	51	120	3 05	225	5 72	5 200	132 08
.004	.10	.040	1 02	130	3.30	230	5.84	5.440	138 18
.005	13	.050	1.27	.145	3.68	250	6 35		
.007	.18	060	1.52	.150	3.81	.270	6.86		
.010	.25	.070	1.77	160	4 06	.280	7 11		

FIGURE 1 Dimensions and configurations - continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:46Z
Check the source to verify that this is the current version before use.

NOTES:

1 Dimensions are in inches.

2 Metric equivalents are given for general information only and are based upon 1 00 inch = 25 4 mm

3 Unless otherwise specified, tolerances are ± 005 (13 mm) inch for three place decimals, ± 01 (3 mm) inch for two place decimals and ±2° for angles

4 Flash around blade contacts not to exceed .010 (.25 mm) inch from the surface of the insulator and shall be firmly attached

5 Pin shield shall be marked with contact numbers 1, 50, 51 and 100 in contrasting color ink .06 (1 5 mm) inch high

6. The carrier strip shall remain attached to the contact tails to facilitate shipping and may be tinned It shall be scored at the point indicated to facilitate removal at final assembly. The carrier strip is not required to be continuous

7 Single or multiple piece construction is optional provided that the end requirements of the drawing are met

8. Dimension prior to solder coating.

9 Dimensions apply after plating

10. See Table I for key pin hole size and body material

11. Contact engagement length

12. Shaded area shall be solder coated.

13. Connector shall be marked in approximate location shown with part number, manufacturer's number and date code with contrasting ink in characters 06 (1 5 mm) inch high

14 Plating defects on the carrier strip above the score line are acceptable.

FIGURE 1. Dimensions and configuration - continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:46Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configuration: See Figure 1 and Table I

Materials: Contacts shall be either copper alloy sheet or strip, UNS Number C72500, temper 1/4 hard minimum, in accordance with ANSI/ASTM B 122 or brass, QQ-B-613, alloy 260, temper 1/2 hard.

Connector body shall be either polyetherimide, Type GLT-20F or GLT-30F, molded thermoplastic in accordance with MIL-M-24519 or molding plastic, diallyl phthalate resin, GL filler, MIL-M-14, Type GDI-30F or Type SDG-F

The pin shield shall be aluminum alloy 5052, QQ-A-250/8, H34, or glass-epoxy, GF-0160-00/00-0-1-X, MIL-P-13949 or polyetherimide, Type GLT-20F or GLT-30F, molded thermoplastic in accordance with MIL-M-24519 Pin shield thickness for molded thermoplastic shall be 0 020 (51 mm) inch minimum

Plating Contacts shall be finished on all exposed surfaces The contact engagement length indicated shall be finished with gold plate, MIL-G-45204, Type II, Grade C, Class 1, 0.000050 (0 00013 mm) inch minimum thickness over nickel plating, QQ-N-290, Class 1, 0 000050 (0 00013 mm) inch minimum thickness

Plating requirements for connector solder tails shall be as follows

Steps 1, 2, 4, 5, 7 - Clean prior to plating per MIL-P-81728 MIL-P-81728 states cleanliness requirements prior to plating

Step 3 - Cu plate per MIL-C-14550 Class 4 to a thickness of 0 0001 (0 0025 mm) inch

Step 6 - Plate per MIL-P-81728 to a thickness of 0 0003 - 0 0005 (0.0076 - 0 0127 mm) inch Alloy 90% SN-10% Pb

Step 8 - Bake as per Section 3.3 4 of MIL-P-81728

Step 9 - Form

Step 10 - Fuse/reflow with peanut oil as suggested Quality assurance of MIL-P-81728 shall apply No sign of dewet or poor solderability will be accepted

Step 11 - Avoid chlorinated solvents in rinse

Step 12 - Selectively solder coat the leads as shown in the shaded area with QQ-S-571, SN60 or SN63 to a thickness of 0.0005 - 0 003 (0.0005 - 0 0800 mm) inch using flux, MIL-F-14256, Type RMA

All aluminum alloy parts shall be anodic coated in accordance with MIL-A-8625, Type III, Class 2, black

Key pin holes: For M28754/56-02 material, .095 ± 001 (2.41 ± 03 mm) inch diameter x 150 (3 81 mm) inch deep.

For M28754/56-01 material, .114 $^{+.000}_{-.005}$ (2.90 $^{+.00}_{-.13}$ mm) inch diameter x 150 (3 81 mm) inch deep

C'bore .134 $^{+\ 005}_{-\ 000}$ (3 40 $^{+.13}_{-.00}$ mm) inch dia x .020 $^{+.005}_{-.000}$ (.51 $^{+\ 13}_{-.00}$ mm) inch deep

Three equally spaced 0.010 (.25 mm) inch rad beads x .150 (3.81 mm) inch deep around the periphery of the .114 (2.90 mm) inch diameter shall be utilized.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:46Z
Check the source to verify that this is the current version before use.

Electrical requirements:

Dielectric withstanding voltage. The connector shall meet the requirements of MIL-STD-1344, Method 3001 for 600 VAC (RMS) 60 Hz, or 850 VDC The point of measurement shall be between adjacent contacts

Low level (dry circuit) Voltage drop shall not exceed 36 millivolts Wire size is not applicable

Contact resistance Voltage drop shall not exceed 36 millivolts Current Rating, 3 Amp

Temperature rating -55°C to +125°C

Voltage rating 300 Volts, AC (RMS), at sea level

Durability In accordance with MIL-C-28754 and shall not exceed 36 millivolts

Solderability In accordance with MIL-C-28754

Military part number M28754/56- (Dash Number from Table I)

TABLE I

DASH NUMBER	KEY PIN HOLE SIZE INCH (MM)	BODY MATERIAL
01	114^{+000}_{-005} ($2\ 90^{+00}_{-13}$)	Type GDI-30F or SDG-F
02	095 · 001 (2 41 · 03)	Type GLT-20F or GLT-30F
CONFIGURATION 1		
03	114^{+000}_{-005} ($2\ 90^{+00}_{-13}$)	Type GDI-30F or SDG-F
04	095 · 001 (2 41 · 03)	Type GLT-20F or GLT-30F

Warning The GLT-20F or GLT-30F may be susceptible to stress cracking when exposed to certain cleaning solvents

Qualification information The connector shall meet the qualification test of MIL-C-28754 Table IV, Type IV, except for Subgroup IV, Method Paragraph 4 7 18, 4 7 19 and 4 7 20

Number of units to be inspected Twelve (12) of each dash number to be qualified shall be inspected

Supersession data Supersedes Naval Electronic Systems Command Drawing Number 0102-691-1 and -5, Code Identification Number 28687

Custodians
Navy - EC

User Activities
Navy - AS

Preparing Activity:
Navy - EC

(Project 5935-N252-03)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:46Z
Check the source to verify that this is the current version before use.