[Metric]
A-A-1021C
March 08, 1996
Superseding
A-A-1021B
December 9, 1994

COMMERCIAL ITEM DESCRIPTION
PERFORATOR, PAPER, THREE HOLE, DESK

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. Scope: This commercial item description covers perforators which are used for punching three or more holes simultaneously in paper.

2. Salient Characteristics:

2.1 Perforators shall have a base, punches, dies and plates, handle, punch operating shaft and springs made of a commercially acceptable metal. Perforators shall also have an adjustable extension guide, adjustable paper stop, locking devices and receptacle.

2.2 The punch heads shall be removable and adjustable from 34.9 mm (1.4") between the centers of two holes to not less than 20.8 cm (8.1") between the centers of the two outermost holes. A permanent marking shall indicate the center of the punch of each head. Perforators shall have a spring loaded handle and punches. The handles shall be connected directly to the punches.

2.3 The base shall provide a stable platform for punching operations and be designed to prevent marring of the surface on which it rests. A mark indicating the midpoint between the two outermost punch locations and a scale which spans not less than 20.3 cm (8"), shall appear on the base. A removable receptacle shall be attached to the base for collecting punched paper waste and be finished in beige, black or gray color, as specified in the contract or ordering document.

2.4 Perforators shall have a paper guide which locks into place for common paper sizes, including, but not limited to 20.3 cm (8"), 20.8 cm, (8.1"), 26.7 cm (10.5"), and 27.9 cm (11.1").

2.5 Perforators shall be permanently marked with the manufacturer's name or trademark. Placement of these permanent markings shall be at the option of the manufacturer, provided they are prominently displayed.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

2.6 All metal parts shall be corrosion resistant. Individual parts shall be either corrosion resistant stainless steel or anodized, plated, finished with baked enamel, epoxy powder coated, subjected to a bluing process, or what ever is commercially appropriate for the specific function of the part.

2.7 Perforators shall meet test requirements as specified in paragraph 4.3. Handles and punches shall automatically return to the upward position after each punching operation under normal use. When the handle does not automatically return to the upright position, it can be retracted from the dies by pulling up on the handle. The contractor shall provide a manufacturer's certification of corrosion resistance upon request by the Government.

2.8 Dimensions. Hole punches shall have 6.7 mm (.263") ± .79 mm (.003") or 10.32 mm (0.406") ± .79 mm (.003") diameters, as specified. The distance from the edge of the material being punched to the center of the hole shall be not less than the diameter of the hole.

2.9 Workmanship. Except for the cutting edge of the punch, the perforator shall be free of sharp edges. The perforator shall be free of superfluous coating of any kind, burrs, scratches, cracks, discoloration, loosened parts, warping, or visible stress marks. The handle shall bind in use. The perforator shall not exhibit any evidence of deformity and shall be free of any defects which affect appearance or impairs serviceability.

3. **Regulatory Requirements:** The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with Paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Certification: The contractor shall certify that if polystyrene is used in the manufacture of the item, it shall contain a minimum of 25 percent Postconsumer Recovered Materials in accordance with the 40 Code of Federal Regulations Part 247, Comprehensive Guideline for Procurement of Products Containing Recovered Materials, final rule. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

4. **Quality Assurance Provisions:**

4.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and therefore as may be otherwise provided for under the provisions of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

4.2 Examination and Testing

4.2.1 Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3 / American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein.

4.2.2 End item inspection/testing may be used by the offeror or the Government representative, as a means to determine the effectiveness of the in process quality controls. While in process controls shall not be substituted for end item performance testing they may be substituted for visual and dimensional inspections/testing.

4.2.3 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection/test shall be required. The sample unit shall be one perforator. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society for Quality Control (ASQC) Z1.4, Sampling Procedures and Tables for Inspection by Attributes.

4.2.4 An inspection lot shall consist of all like items submitted for inspection at one time. The inspection level for visual and dimensional examination shall be S-3 with an AQL of 4.0 percent defective. The inspection level for performance testing shall be S-1 with an AQL of 4.0 percent defective. The supplier must provide objective evidence (tests and inspection records) that the presented material meets the requirements of the sampling plan as indicated above.

4.3 Performance Test: Each operation shall be performed 100 times. All 100 operations shall leave holes entirely punched out, without torn or ragged edges.

4.3.1 Durability Test. The perforator shall be tested using Kraft or Manila paperboard - Basis Weight 66.7 kg (147 lb.), 60.96 cm(24") x 91.44 cm (36") - 500 sheets, 11 pt. The perforator shall be capable of consistently perforating 10 paperboard sheets at one time.

4.3.2 Normal Use Test. The perforator shall be tested using bond paper - Basis Weight 7.26 kg (16 lb.), 43.18 cm (17") x 55.88 cm(22") - 500 sheets. The perforator shall be capable of consistently perforating 16 sheets bond paper at one time.

5. Packaging:

5.1 Preservation, Packing and marking shall be specified in the contract or order

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.

6. **Notes:**

6. 1 Referenced Documents: The issue of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this Commercial Item Description.

6.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington. DC 20402.

6.1.2 Application for copies of (ANSI) Z1.1, Z1.2 and Z1.3 and (ASQC) B.1, B.2 and B.3 may be obtained from the American Society for Quality Control, PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

6.2 National Stock Number Listing (NSNs. The following is a list of NSNs assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID

7520-00-139-3942
7520-00-163-2563

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice

Preparing Activity

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:11Z
Check the source to verify that this is the current version before use.