[INCH-POUND]
A-A-3148
January 13, 1998
SUPERSEDING
DDD-P-56G
June 7, 1994

COMMERCIAL ITEM DESCRIPTION

PAD, MATTRESS, POLYESTER BATTING, QUILTED, FLAT OR FITTED

The General Services Administration has authorized the use of this commercial item description as a replacement for Federal Specification DDD-P-56G, which is canceled.

1. SCOPE.

1.1 Scope. This commercial item description covers flat and fitted mattress pads intended for protection of mattresses.

2. CLASSIFICATION.

2.1 Classification. The mattress pad shall be in the following type and size, as specified (see 7.3).

Type I - Flat: quilted pad to cover mattress top; with bound edges.

Size 1 - 36 inches by 75 inches (91.4 cm by 190.5 cm).
Size 2 - 52 inches by 75 inches (132.1 cm by 190.5 cm)

Type II - Fitted: quilted pad to cover mattress top and cloth skirt with elasticized edge to cover mattress sides; for mattress depths from 6.5 inches (16.5 cm) to 10 inches (25.4 cm).

Size 1 - 29 inches by 76 inches (73.7 cm by 193.0 cm).
Size 2 - 36 inches by 75 inches (91.4 cm by 190.5 cm)
Size 3 - 36 inches by 78 inches (91.4 cm by 198.1 cm).
Size 4 - 36 inches by 84 inches (91.4 cm by 213.4 cm)
Size 5 - 38 inches by 75 inches (96.5 cm by 190.5 cm)
Size 6 - 39 inches by 78 inches (99.1 cm by 198.1 cm)
Size 7 - 63 inches by 75 inches (160.0 cm by 190.5 cm).
Size 8 - 36 inches by 80 inches (91.4 cm by 203.2 cm).
Size 9 - 38 inches by 80 inches (96.5 cm by 203.2 cm).
Size 10 - 53 inches by 75 inches (134.6 cm by 190.5 cm)
Size 11 - 53 inches by 80 inches (134.6 cm by 203.2 cm).
Size 12 - 60 inches by 80 inches (152.4 cm by 203.2 cm).
Size 13 - 76 inches by 80 inches (193.0 cm by 203.2 cm).

Tolerance, types I and II: Width -0, +0.5 inch; length -0, +1.0 inch; (width -0, +1.3 cm; length -0, +2.5 cm).

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Branch (7FXEE), 819 Taylor Street, Fort Worth, TX 76102-6114.

FSC 7210

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS.

3.1 Performance. The finished mattress pad shall be durable in appearance and function to repeated use and laundering. The type II mattress pad skirt shall be sized to fit, at a minimum, mattress depths ranging from 6.5 to 10 inches (16.5 to 25.4 cm) and shall hold the mattress pad firmly in place, covering the mattress sides and ends, on an appropriately sized mattress. Batting fiber shall not migrate to the outside of the mattress pad.

3.2 Construction. The mattress pad shall have a layered construction consisting of a top cloth, fiber batting, and a backing cloth quilted together in a pattern designed to stabilize the batting, maintain batting loft, and prevent shifting of the batting during use and laundering. The type II mattress pad shall have a fitted skirt, finished with elastic webbing on the free edge, attached around the entire perimeter of the pad. Edges of the cloth components shall be cut parallel to the grain of the cloth. The batting shall extend to the cut edges of the top and backing fabrics. Mattress pad edges shall be completely enclosed with binding for type I mattress pads and with binding or overedge stitching for type II mattress pads. Skirt seam edges shall be enclosed in overedge stitching or binding. Seams shall be straight and uniform. Stitching shall be evenly spaced and uniformly distributed. Ends of seams and stitching, when not caught in other seams and stitching, shall be secured to prevent unraveling. Thread breaks shall be backstitched or overstitched to prevent unraveling.

3.3 Components.

3.3.1 Cloth. Cloth for top and backing layers of the mattress pad and for the type II skirt shall be bleached white 65/35 or 50/50 polyester/cotton blend muslin or percale sheeting meeting the requirements for woven non-flannel sheeting defined in Table I of ASTM D 5431, Standard Performance Specification for Woven and Knitted Sheeting Products for Institutional and Household Use, except that requirements for laundered appearance, colorfastness and crocking may be omitted. The requirements for dimensional change and flammability shall apply to the finished mattress pad (end item) only. The definitions of muslin and percale in ASTM D 5431, Section 3, Terminology, shall apply.

3.3.2 Cloth binding. Edges of the flat (type I) mattress pad shall be bound with the same kind of cloth used for the mattress pad top and described in 3.3.1.

3.3.3 Elastic webbing. Elastic webbing for the skirt edge shall be one piece, white, flat, heat-resistant, launderable, non-staining, treated rubber which has been compounded of natural rubber, synthetic rubber, or a mixture of natural and synthetic rubber. The elastic webbing shall be a type suitable for and typically used as skirt edging on mattress pads in the commercial market and shall be durable in appearance and function to the care method appropriate for the finished mattress pad.

3.3.4 Batting. The batting shall be made of polyester fiber and shall be a high loft type suitable for mattress pads and typically used in mattress pads in the commercial market. The batting shall be non-allergenic, non-toxic, noise free, odor free, and uniform in thickness. Any bonding agents used shall be evenly applied, non-allergenic, non-toxic, and durable to the care method appropriate for the finished mattress pad and shall not exceed 18.0 percent by weight of the finished batting.

3.3.5 Thread. Spun or multi-filament thread of a type appropriate for mattress pad production and the type of cloth and batting specified (see 7.3) shall be used. Thread color shall match the fabric color. The thread shall be durable in appearance and function to the care method appropriate for the finished mattress pad.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

3.4 Labeling. Each mattress pad shall have a permanent label with the following information and, where applicable, shall have a state label conforming to the legal requirements of the state in which the mattress pad is manufactured. When permitted by law, and at the manufacturer's option, the following information may be printed on the state label in lieu of on a separate label. The label(s) shall be permanently attached at one end of the pad.

a) National Stock Number (NSN), product name, size and contract number.
b) Fiber content in accordance with the Rules and Regulations Under the Textile Fiber Products Identification Act.
c) Care instructions appropriate for the mattress pad.
d) Manufacturer's name or trademark.

All information required on the label(s) shall be completely visible after the label(s) is (are) attached. The marking shall be well defined, clearly legible and readable for the life of the mattress pad. The label material and the marking shall be durable to the care method appropriate for the mattress pad.

3.5 Flammability. Mattress pads supplied under this commercial item description shall comply with and be labeled in accordance with the provisions of CFR Part 1602-1632, Subchapter D - Flammable Fabrics Act Regulations, Standard for the Flammability of Mattresses and Mattress Pads (FF 4-72, amended).

3.6 Workmanship. The finished mattress pad shall conform to the quality of product established by this commercial item description and shall function as a comfortable, durable mattress pad suitable for protecting mattress surfaces. The mattress pad shall be clean and free from soil, dirt, spots, stains, cuts, tears, mends, burns, thread pulls and other fabric defects. The mattress pad shall be free of objectionable odor, and free of objectionable sound and crackling noise when flexed, folded, or rested on. The skirt of a type II mattress pad shall fit smoothly over an appropriately sized mattress up to 10 inches (25.4 cm) deep and tuck readily under the mattress without pulling so tightly that the fabric shows evidence of strain or that the stitching breaks or pulls loose. The finished mattress pad shall be free of needle chews; puckers, twists, or pleats; uneven seams; corners not uniform; parts not aligned; raw edges of any length; loose stitch tension resulting in a loose seam; or tight stitch tension (breaks when normal strain applied). Stitches shall be secure and uniform. The mattress pad shall be free of pieces of batting material on the outside of the finished mattress pad. No component shall be omitted. No defects affecting function, appearance, or serviceability shall be permitted.

3.7 Measurement system. The values stated in inch-pound units are to be regarded as the standard. The metric values stated in parenthesis are for information purposes only.

3.8 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

4. REGULATORY REQUIREMENTS.

4.1 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

6. PACKAGING.

6.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or purchase order.

7. NOTES.

7.1 Part Identification Number (PIN). Mattress pads conforming with this commercial item description are identified by a part number configuration consisting of a portion of the CID number, type and size. An example of a part number configuration is shown below. This part numbering system is intended for identification and cross-indexing of the item within the federal cataloging system. The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

AA3148A1 EXAMPLE: AA3148-A1 = 29 by 76 in (73.7 x 193.0 cm) fitted mattress pad.

| | |
| | |____ Size (1 through 13)
| |_____ Type (I = A, II = B)
|_____ Commercial item description number

7.2 Referenced documents. The documents referenced in this commercial item description shall be the issues in effect on the date of issuance of the invitation for bids or request for proposals unless otherwise specified. These documents form a part of this commercial item description to the extent specified. In the event of a conflict between this commercial item description and a document referenced herein, this commercial item description shall take precedence.

Copies of the Code of Federal Regulations are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC, 20402 (Internet - http://www.access.gpo.gov).

Copies of Rules and Regulations Under the Textile Fiber Products Identification Act are available from the Federal Trade Commission, Washington, DC 20580.

Copies of ASTM standards are available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

7.3 Ordering data. Purchaser should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a) Title, number, and date of this commercial item description.
b) Type and size (See 2.1).
c) Preservation, packing, and marking desired.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

7.4 National stock numbers (NSNs). The following NSNs correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

National Stock Number	Type	Size	PIN
7210-00-227-1526	I	1	AA3148A1
7210-00-753-3042	I	2	AA3148A2
7210-01-306-3243	II	1	AA3148B1
7210-01-306-3244	II	2	AA3148B2
7210-01-306-3245	II	3	AA3148B3
7210-01-306-3246	II	4	AA3148B4
7210-01-306-3247	II	5	AA3148B5
7210-01-306-3248	II	6	AA3148B6
7210-01-306-3249	II	7	AA3148B7
7210-01-306-3250	II	8	AA3148B8
7210-01-306-3251	II	9	AA3148B9
7210-01-417-5531	II	10	AA3148B10
7210-01-417-5530	II	11	AA3148B11
7210-01-417-5532	II	12	AA3148B12

7.5 Supersession data. This commercial item description supersedes DDD-P-56G, dated June 7, 1994, with the following adjustment in sizes.

DDD-P-56G	A-A-3148
Type II - Fitted, quilted pad with elastic edged skirt. Size 7 - 36 by 80 in (91.4 x 203.2 cm). Size 8 - 38 by 80 in (96.5 x 203.2 cm).	Type II - Fitted, quilted pad with elastic edged skirt. Size 7 - 63 by 75 in (160.0 x 190.5 cm). Size 8 - 36 by 80 in (91.4 x 203.2 cm).

MILITARY INTERESTS:

Military Coordinating Activity:

Custodians:
Air Force Code 99

Review Activities:
Air Force Codes 99, 45, 03

User Activities:

CIVIL AGENCY COORDINATING ACTIVITIES:

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.